



Component - Plastics

File Number: E244324

TEIJIN CHEMICALS PLASTIC COMPOUNDS SHANGHAI LTD

WAIGAOQIAO FREE TRADE ZONE

310 HUAJING RD

SHANGHAI, . 200131 China



Panlite: ML-7500Z(#)(f1)

Polycarbonate (PC), pellets

(#) - Suffix optional

(f1) - Suitable for outdoor use with respect to exposure to Ultraviolet Light, Water Exposure and Immersion in accordance with UL 746C.

Flammability	Value	Test Method
Flame Rating		UL 94
1.0 mm, ALL	V-0	IEC 60695-11-10, -20
1.5 mm, ALL	V-0	
2.0 mm, ALL	V-0	
3.0 mm, ALL	V-0	
Glow Wire Flammability Index		IEC 60695-2-12
1.0 mm	930 °C	
3.0 mm	960 °C	
Glow Wire Ignition Temperature		IEC 60695-2-13
1.0 mm	850 °C	
3.0 mm	850 °C	
Electrical	Value	Test Method
Hot-wire Ignition (HWI)		UL 746A
1.0 mm	PLC 3	
1.5 mm	PLC 3	
2.0 mm	PLC 2	
3.0 mm	PLC 2	
High Amp Arc Ignition (HAI)		UL 746A
1.0 mm	PLC 0	
1.5 mm	PLC 0	
2.0 mm	PLC 0	
3.0 mm	PLC 0	
Comparative Tracking Index (CTI)	PLC 2	UL 746A
Thermal	Value	Test Method
RTI Elec		UL 746B
1.0 mm	130 °C	
1.5 mm	130 °C	
2.0 mm	130 °C	
3.0 mm	130 °C	
RTI Imp		UL 746B
1.0 mm	125 °C	
1.5 mm	125 °C	
2.0 mm	125 °C	
3.0 mm	125 °C	



Component - Plastics

File Number: E244324

Thermal	Value	Test Method
RTI Str		UL 746B
1.0 mm	130 °C	
1.5 mm	130 °C	
2.0 mm	130 °C	
3.0 mm	130 °C	
Ball Pressure Test (125°C)	Pass	IEC 60695-10-2
Physical	Value	Test Method
Outdoor Suitability	f1	UL 746C