

**HYTREL HTR8068 NAT (TA)**

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: -           |
| 1.0     | 02-03-2025     | 300010001898 | Date of first issue: 02-03-2025 |

---

**SECTION 1. IDENTIFICATION**

Product name : HYTREL HTR8068 NAT (TA)

Product code : 000000000021056918

**Manufacturer or supplier's details**

Company : Celanese Sales U.S. Ltd.

Address : 222 West Las Colinas Boulevard Suite 900N  
Irving TX TX 75039

Telephone : '+1 972-443-4000

Emergency telephone number : DOMESTIC NORTH AMERICA: 800-424-9300  
INTERNATIONAL, CALL +1 703-527-3887 (collect calls accepted)

**Recommended use of the chemical and restrictions on use**

Recommended use : Polymer

Restrictions on use : For manufacturing and research use only

---

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)**

Combustible dust

**GHS label elements**

Signal word : Warning

Hazard statements : If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.

**Other hazards**

None known.

---

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

**Components**

This product does not contain any components that require disclosure according to OSHA Hazard Communication Standard 2012.

---

**SECTION 4. FIRST AID MEASURES**

If inhaled : Move to fresh air in case of accidental inhalation of fumes

---

**HYTREL HTR8068 NAT (TA)**

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: -           |
| 1.0     | 02-03-2025     | 300010001898 | Date of first issue: 02-03-2025 |

---

- from overheating or combustion.  
If not breathing, give artificial respiration.  
If breathing is difficult, give oxygen.  
Call a physician.
- In case of skin contact : The material is not likely to be hazardous by skin contact, but cleaning the skin after use is advisable.  
Cool skin rapidly with cold water after contact with molten material.  
Do not peel polymer from the skin.  
Obtain medical treatment for thermal burn.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.  
Call a physician.
- If swallowed : No specific intervention is indicated.  
Consult a physician if necessary.
- Most important symptoms and effects, both acute and delayed : None known.
- Notes to physician : Treat symptomatically.
- 

**SECTION 5. FIREFIGHTING MEASURES**

- Suitable extinguishing media : Water  
Foam  
Dry chemical  
Carbon dioxide (CO<sub>2</sub>)
- Specific hazards during fire-fighting : Combustible  
Large molten masses may ignite spontaneously in air.  
Water quenching is good practice.  
Minimize the generation and accumulation of dust.  
Material in pellet form may accumulate static charge when poured from one container to another.  
Failure or malfunction of temperature control systems on processing equipment, such as extruders, may create explosion hazards.
- Hazardous combustion products : Hazardous combustion products may include:  
Carbon monoxide  
carbon dioxide  
(see also section 10)
- Further information : Evacuate personnel and keep upwind of fire.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus and protective suit.
- 

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Spilled material is a slipping hazard.
- Environmental precautions : Do not discharge to streams, ponds, lakes or sewers.

## HYTREL HTR8068 NAT (TA)

Version 1.0      Revision Date: 02-03-2025      SDS Number: 300010001898      Date of last issue: -  
Date of first issue: 02-03-2025

Methods and materials for containment and cleaning up : Spills of fine material should be cleaned using gentle sweeping or vacuuming. Cleaning methods (e.g. compressed air) which can generate potentially combustible dust clouds should not be used.  
Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration.  
Use only non-sparking tools.

## SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Open container only in well-ventilated area.  
Wash hands thoroughly after handling.  
Provide appropriate exhaust ventilation at dryers, machinery and at places where dust or volatiles can be generated.  
Do not breathe dust.  
Pneumatic conveying and other mechanical handling operations can generate combustible dust.  
Minimize the generation and accumulation of dust.  
Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces.

Conditions for safe storage : Store in a cool, dry place.  
Keep container closed to prevent contamination.  
Keep in an area equipped with sprinklers.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Components with workplace control parameters

| Components                               | CAS-No.      | Value type (Form of exposure)       | Control parameters / Permissible concentration | Basis    |
|------------------------------------------|--------------|-------------------------------------|------------------------------------------------|----------|
| Dust (inhalable and respirable fraction) | Not Assigned | TWA (total dust)                    | 50 Million particles per cubic foot            | OSHA Z-3 |
|                                          |              | TWA (total dust)                    | 15 mg/m3                                       | OSHA Z-3 |
|                                          |              | TWA (respirable fraction)           | 5 mg/m3                                        | OSHA Z-3 |
|                                          |              | TWA (respirable fraction)           | 15 Million particles per cubic foot            | OSHA Z-3 |
|                                          |              | TWA (Respirable particulate matter) | 3 mg/m3                                        | ACGIH    |
|                                          |              | TWA (Inhalable particulate matter)  | 10 mg/m3                                       | ACGIH    |

This product does not contain any exposure limits that require disclosure according to OSHA Hazard Communication Standard 2012.

Engineering measures : General mechanical ventilation is normally adequate but use local exhaust where necessary to maintain exposures below acceptable limits.  
Use local exhaust to completely remove vapors and fumes liberated during hot processing from the work area.

## HYTREL HTR8068 NAT (TA)

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: -           |
| 1.0     | 02-03-2025     | 300010001898 | Date of first issue: 02-03-2025 |

**Personal protective equipment**

- Respiratory protection : Additives in this product do not present a respiration hazard unless the product is ground to a powder of respirable size and the dust is inhaled. All dusts are potentially injurious to the respiratory tract if respirable particles are generated and inhaled.  
A respiratory protection program that meets country requirements must be followed whenever workplace conditions warrant respirator use.  
Consult the respirator manufacturer to determine the appropriate type of equipment for a given application. Observe respirator use limitations specified by the manufacturer.  
Use a positive pressure air supplied respirator if exposure levels are not known or there are any other circumstances where air purifying respirators may not provide adequate protection.  
Consult the OSHA respiratory protection information located at 29CFR 1910.134.
- Hand protection
- Remarks : Wear leather or cotton gloves when grinding, sawing, routing, drilling or sanding. When handling hot material, use heat resistant gloves.
- Eye protection : Wear safety glasses with side shields.  
Wear tightly fitting chemical splash goggles and face shield when possibility exists for eye and face contact due to spattering or splashing of molten material.  
A full-face mask respirator provides protection from eye irritation.
- Skin and body protection : If there is a potential for contact with hot/molten material wear heat resistant clothing and footwear.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

- Appearance : pellets
- Colour : natural color
- Odour : none
- Odour Threshold : Not applicable
- pH : Substance/mixture is non-soluble (in water).
- Melting point/ range : > 266 °F / > 130 °C
- Boiling point/boiling range : Not applicable
- Flash point : Not applicable
- Evaporation rate : Not applicable
- Flammability (solid, gas) : May form combustible dust concentrations in air during processing, handling or other means.
- Self-ignition : Not applicable

**HYTREL HTR8068 NAT (TA)**

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: -           |
| 1.0     | 02-03-2025     | 300010001898 | Date of first issue: 02-03-2025 |

---

|                                                  |   |                                                                                                                                                                                                                                                                          |
|--------------------------------------------------|---|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Upper explosion limit / Upper flammability limit | : | Not applicable                                                                                                                                                                                                                                                           |
| Lower explosion limit / Lower flammability limit | : | Not applicable                                                                                                                                                                                                                                                           |
| Vapour pressure                                  | : | Not applicable                                                                                                                                                                                                                                                           |
| Relative vapour density                          | : | Not applicable                                                                                                                                                                                                                                                           |
| Relative density                                 | : | > 1                                                                                                                                                                                                                                                                      |
| Solubility(ies)                                  |   |                                                                                                                                                                                                                                                                          |
| Water solubility                                 | : | insoluble                                                                                                                                                                                                                                                                |
| Decomposition temperature                        | : | > 527 °F / 275 °C<br>Thermal decomposition of the resin accelerates above temperature listed.<br>Decomposition can occur below the recommended processing temperature limit.<br>Decomposition is a function of both processing temperature and time at that temperature. |
| Viscosity                                        |   |                                                                                                                                                                                                                                                                          |
| Viscosity, dynamic                               | : | Not applicable                                                                                                                                                                                                                                                           |
| Viscosity, kinematic                             | : | Not applicable                                                                                                                                                                                                                                                           |

---

**SECTION 10. STABILITY AND REACTIVITY**

|                                    |   |                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|------------------------------------|---|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Reactivity                         | : | Stable at normal ambient temperature and pressure.                                                                                                                                                                                                                                                                                                                                                                                        |
| Chemical stability                 | : | Stable at normal ambient temperature and pressure.                                                                                                                                                                                                                                                                                                                                                                                        |
| Possibility of hazardous reactions | : | Polymerization will not occur.                                                                                                                                                                                                                                                                                                                                                                                                            |
| Conditions to avoid                | : | Temperature > 275 °C<br>Abnormally long processing time or high temperatures can produce irritating and toxic fumes.<br>Decomposes on heating.<br>At temperatures above the "conditions to avoid" temperature, thermal decomposition of the resin accelerates.<br>Decomposition can occur below the recommended processing temperature limit.<br>Decomposition is a function of both processing temperature and time at that temperature. |
| Incompatible materials             | : | Strong acids<br>Strong bases<br>Strong oxidizing agents                                                                                                                                                                                                                                                                                                                                                                                   |
| Hazardous decomposition products   | : | Hazardous thermal decomposition products may include:<br><br>Carbon monoxide<br>carbon dioxide<br>acetic acid<br>Tetrahydrofuran                                                                                                                                                                                                                                                                                                          |

## HYTREL HTR8068 NAT (TA)

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: -           |
| 1.0     | 02-03-2025     | 300010001898 | Date of first issue: 02-03-2025 |

2-Methylpropene  
acetaldehydes  
formic acid  
Acrolein  
Propionaldehyde  
hydrogen bromide  
Hydrogen cyanide (hydrocyanic acid)  
Nitrogen oxides (NOx)

**SECTION 11. TOXICOLOGICAL INFORMATION****Acute toxicity**

Not classified due to lack of data.

**Skin corrosion/irritation**

Not classified due to lack of data.

**Serious eye damage/eye irritation**

Not classified due to lack of data.

**Respiratory or skin sensitisation****Skin sensitisation**

Not classified based on available information.

**Respiratory sensitisation**

Not classified due to lack of data.

**Germ cell mutagenicity**

Not classified due to lack of data.

**Carcinogenicity**

Not classified based on available information.

**Product:**

Remarks : This product does not contain any reportable carcinogens according to OSHA Hazard Communication Standard 2012.

**Reproductive toxicity**

Not classified due to lack of data.

**STOT - single exposure**

Not classified due to lack of data.

**STOT - repeated exposure**

Not classified due to lack of data.

**Aspiration toxicity**

Not classified due to lack of data.

**Further information****Product:**

Remarks : No data is available on the product itself.  
For additional toxicity data, write to the company address or call the non-emergency number shown in Section 1.

**HYTREL HTR8068 NAT (TA)**

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: -           |
| 1.0     | 02-03-2025     | 300010001898 | Date of first issue: 02-03-2025 |

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity**

No data available

**Persistence and degradability**

No data available

**Bioaccumulative potential**

No data available

**Mobility in soil**

No data available

**Other adverse effects****Product:**

Additional ecological information : No data is available on the product itself.  
Toxicity is expected to be low based on insolubility in water.

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues : Preferred options for disposal are recycling or incineration with energy recovery.  
The high fuel value of this product makes incineration very desirable for material that cannot be recycled.  
Incinerator must be capable of scrubbing out acidic combustion products.  
Treatment, storage, transportation, and disposal must be in accordance with applicable federal, state/provincial, and local regulations.

Contaminated packaging : Dispose of in accordance with local regulations.

**SECTION 14. TRANSPORT INFORMATION****International Regulations****UNRTDG**

Not regulated as a dangerous good

**IATA-DGR**

Not regulated as a dangerous good

**IMDG-Code**

Not regulated as a dangerous good

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**National Regulations****49 CFR**

Not regulated as a dangerous good

**HYTREL HTR8068 NAT (TA)**

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: -           |
| 1.0     | 02-03-2025     | 300010001898 | Date of first issue: 02-03-2025 |

**Special precautions for user**

Not applicable

**SECTION 15. REGULATORY INFORMATION****SARA 302 Extremely Hazardous Substances Threshold Planning Quantity**

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : Combustible dust**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

Antimony trioxide 1309-64-4 &gt;= 5 - &lt; 10 %

**California Prop. 65**

WARNING: This product can expose you to chemicals including Antimony trioxide, which is/are known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**TSCA list**

No substances are subject to a Significant New Use Rule.

In compliance with TSCA-active Inventory requirements for commercial purposes.

No substances are subject to TSCA 12(b) export notification requirements.

**SECTION 16. OTHER INFORMATION****Full text of other abbreviations**

|                |   |                                                                    |
|----------------|---|--------------------------------------------------------------------|
| ACGIH          | : | USA. ACGIH Threshold Limit Values (TLV)                            |
| OSHA Z-3       | : | USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts |
| ACGIH / TWA    | : | 8-hour, time-weighted average                                      |
| OSHA Z-3 / TWA | : | 8-hour time weighted average                                       |

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -

## HYTREL HTR8068 NAT (TA)

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: -           |
| 1.0     | 02-03-2025     | 300010001898 | Date of first issue: 02-03-2025 |

---

Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 02-03-2025

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN

## Warning

**Hazard Statements:** If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.

Refer to Safety Data Sheet (SDS) for further information.

Celanese Sales U.S. Ltd.  
222 West Las Colinas Boulevard Suite 900N  
IrvingTX  
TX 75039

**Product Information:** '+1 972-443-4000

**Transport:** DOMESTIC NORTH AMERICA: 800-424-9300 INTERNATIONAL,  
CALL +1 703-527-3887 (collect calls accepted): DOMESTIC NORTH AMERICA:  
800-424-9300 INTERNATIONAL, CALL +1 703-527-3887 (collect calls accepted)

Version 1.0  
Revision Date 02-03-2025  
Issue Date 02-05-2025  
Ref. 300010001898