

# SAFETY DATA SHEET

# ExxonMobil

NEODECANOIC ACID, TECHNICAL

## Section 1. Identification

**Product name** : NEODECANOIC ACID, TECHNICAL  
**Regulatory reference** : Not available.  
**Product description** : carboxylic acid

### Identification data of the safety data sheet

**OKPD 2** : Not available.  
**TN VED** : Not available.

### Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** : Chemical Intermediate  
**Uses advised against** : This product is not recommended for any industrial, professional or consumer use other than the Identified Uses above.

**Supplier** : ExxonMobil Chemical Asia Pacific (Regn. No. 52893724C)  
(A Division Of ExxonMobil Asia Pacific Pte Ltd - Regn. No. 196800312N)  
1 HarbourFront Place  
#06-00 HarbourFront Tower One 098633 Singapore

**24 Hour Emergency Telephone** : +44 20 3885 0382 / +1-703-527-3887 (CHEMTREC)

**Supplier General Contact** : +65 6885 8000

**SDS Internet Address** : [www.sds.exxonmobil.com](http://www.sds.exxonmobil.com)

## Section 2. Hazards identification

**Classification of the substance or mixture according to GOST 32419-2022 and GOST 32423/24/25-2013**

**Classification of the substance or mixture** : ACUTE TOXICITY (oral) - Category 4

### GHS label elements

**Hazard pictograms** :



**Signal word** : Warning

**Hazard statements** : H302 - Harmful if swallowed.

### Precautionary statements

**Prevention** : P264 - Wash thoroughly after handling.  
P270 - Do not eat, drink or smoke when using this product.

**Response** : P301 + P330, P312 - IF SWALLOWED: Rinse mouth. Call a POISON CENTER or doctor if you feel unwell.

**Disposal** : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Contains** : neodecanoic acid

**Other hazards which do not result in classification** : None known.

**Nota** : This material should not be used for any other purpose than the intended use in Section 1 without expert advice. Health studies have shown that chemical exposure may cause potential human health risks which may vary from person to person.

**Date of issue/Date of revision**

: 9 October 2024

**Date of previous issue**

: 4 August 2024

**Version** : 1.02

1/10

## Section 2. Hazards identification

## Section 3. Composition/information on ingredients

**Substance/mixture** : Substance  
**Chemical name** : neodecanoic acid  
**General description of the composition/Method of production** : Not available.

Ingredient name	%	Identifiers	Exposure limits	Type
neodecanoic acid	100	CAS: 26896-20-8 EC: 248-093-9	<b>ExxonMobil (COMPANY)</b> TWA 8 hours: 5 mg/m <sup>3</sup> . Form: Stable Aerosol.. TWA 8 hours: 25 mg/m <sup>3</sup> . Form: Vapour..	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

### Type

[1] Constituent

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First-aid measures

### Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.  
**Inhalation** : No known significant effects or critical hazards.  
**Skin contact** : No known significant effects or critical hazards.  
**Ingestion** : Harmful if swallowed.

#### Over-exposure signs/symptoms

- Eye contact** : No specific data.

## Section 4. First-aid measures

- Inhalation** : No specific data.  
**Skin contact** : No specific data.  
**Ingestion** : No specific data.

### Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.  
**Specific treatments** : No specific treatment.  
**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

## Section 5. Firefighting measures

**General characteristics of fire and explosion hazards** : In a fire or if heated, a pressure increase will occur and the container may burst.

### Indicators of fire and explosion hazard of chemical products

- Flash point** : Closed cup: >100°C (>212°F) [ASTM D-93]  
**Ignition temperature** : Not available.  
**Auto-ignition temperature** : >300°C (>572°F) [In-house method]  
**Lower and upper explosion limit/flammability limit** : Lower: 1.4% [In-house method]  
 Upper: 12.4%

### Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, alcohol-resistant foam or water spray (fog).  
**Unsuitable extinguishing media** : Do not use water jet.

**Specific hazards arising from the chemical** : In a fire or if heated, a pressure increase will occur and the container may burst.

**Hazardous combustion products** : Incomplete combustion products, Oxides of carbon, Smoke, Fume

**Special protective actions for fire-fighters** : Use standard firefighting procedures and consider the hazards of other involved materials. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. Assure an extended cooling down period to prevent re-ignition. Prevent run-off from fire control or dilution from entering streams, sewers or drinking water supply. No action shall be taken involving any personal risk or without suitable training.

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

### NOTIFICATION PROCEDURES

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

### Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate.

## Section 6. Accidental release measures

**For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and material for containment and cleaning up

**Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

**Large spill** : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Confine the spill immediately with booms. Remove from the surface by skimming or with suitable absorbents. Seek the advice of a specialist before using dispersants. Warn other shipping. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Water spill and land spill recommendations are based on the most likely spill scenario for this material; however, geographic conditions, wind, temperature, (and in the case of a water spill) wave and current direction and speed may greatly influence the appropriate action to be taken. For this reason, local experts should be consulted. Note: Local regulations may prescribe or limit action to be taken.

## Section 7. Handling and storage

### Precautions for safe handling

**Protective measures** : Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

**Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

**Static Accumulator** : This material is not a static accumulator.

**Loading/Unloading** : Ambient

**Temperature**

**Transport Temperature** : Ambient

**Transport Pressure** : Ambient

**Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

**Storage Temperature** : Ambient

**Storage Pressure** : Ambient

## Section 7. Handling and storage

**Suitable Materials and Coatings** : Phenolic Coatings, polyethylene, polypropylene, aluminium, Stainless Steel

**Unsuitable Materials and Coatings** : copper, Inorganic Zinc, Amine Epoxy, Polyamide, Epoxies

## Section 8. Exposure controls/personal protection

### Control parameters

#### Occupational exposure limits

Ingredient name	Exposure limits
neodecanoic acid	<b>ExxonMobil (COMPANY)</b> TWA 8 hours: 5 mg/m <sup>3</sup> . Form: Stable Aerosol.. TWA 8 hours: 25 mg/m <sup>3</sup> . Form: Vapour..

**Appropriate engineering controls** : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

### Skin protection

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. < 1 hour (breakthrough time): Nitrile, minimum 0.38 mm thickness or comparable protective barrier material

**Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: organic vapour filter (Type A)

## Section 9. Physical and chemical properties and safety characteristics

**Note: Physical and chemical properties are provided for safety, health and environmental considerations only and may not fully represent product specifications. Contact the Supplier for additional information.**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### Appearance

<b>Physical state</b>	: Liquid. [Clear]
<b>Colour</b>	: Colourless
<b>Odour</b>	: Mild
<b>Odour threshold</b>	: Not available.
<b>pH</b>	: Not applicable.
<b>Melting point/freezing point</b>	: -39°C (-38.2°F)
<b>Boiling point or initial boiling point and boiling range</b>	: 245 to 265°C (473 to 509°F) [ASTM D1078]
<b>Flash point</b>	: Closed cup: >100°C (>212°F) [ASTM D-93]
<b>Evaporation rate</b>	: <1 (butyl acetate = 1) [In-house method]
<b>Flammability</b>	: Ignitable
<b>Lower and upper explosion limit/flammability limit</b>	: Lower: 1.4% [In-house method] Upper: 12.4%
<b>Vapour pressure</b>	: 0.09 mm Hg [50 °C] [In-house method]
<b>Relative vapour density</b>	: >1 [Air = 1] [Calculated]
<b>Relative density</b>	: 0.913 [Calculated]
<b>Density</b>	: 0.911 g/cm <sup>3</sup> [20°C (68°F)] [ASTM D4052]
<b>Solubility in water</b>	: Negligible
<b>Partition coefficient: n-octanol/water</b>	: 3.83 [OECD 117]
<b>Auto-ignition temperature</b>	: >300°C (>572°F) [In-house method]
<b>Decomposition temperature</b>	: Not available.
<b>Viscosity</b>	: 40 cSt [20 °C] [ASTM D7042]
<b>Molecular weight</b>	: 172
<b>Particle characteristics</b>	
<b>Median particle size</b>	: Not applicable.
<b>Pour point</b>	: <-40°C [ASTM D5950]
<b>Hygroscopic</b>	: No
<b>Coefficient of Thermal Expansion</b>	: 0.0004 per Deg C

## Section 10. Stability and reactivity

<b>Reactivity</b>	: No specific test data related to reactivity available for this product or its ingredients.
<b>Chemical stability</b>	: The product is stable.
<b>Possibility of hazardous reactions</b>	: Under normal conditions of storage and use, hazardous reactions will not occur.
<b>Conditions to avoid</b>	: High energy sources of ignition. Excessive heat.
<b>Incompatible materials</b>	: Ammonia, Inorganic acids, Caustics, amines, Alkanolamines, Aldehydes, Monomers, Polymerisable esters, Strong oxidisers, Alkylene Oxides, Cyanohydrins, Nitriles

## Section 10. Stability and reactivity

**Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Test	Species	Result	Duration
neodecanoic acid	LC50 Inhalation Vapour	Rat	>3 mg/l	6 hours
	LD50 Dermal	Rabbit	>3640 mg/kg	-
neodecanoic acid	LD50 Oral	Rat	1000 mg/kg	-

#### Conclusion/Summary

- Inhalation** : Minimally Toxic. Data available. Based on test data for the material. Test(s) equivalent or similar to OECD Guideline 403
- Dermal** : Minimally Toxic. Data available. Based on test data for the material. Test(s) equivalent or similar to OECD Guideline 402
- Oral** : Slightly toxic. Data available. Based on test data for the material. Test(s) equivalent or similar to OECD Guideline 423

#### Irritation/Corrosion

##### Conclusion/Summary

- Skin** : Negligible irritation to skin at ambient temperatures. Data available. Based on test data for the material. Test(s) equivalent or similar to OECD Guideline 404
- Eyes** : May cause mild, short-lasting discomfort to eyes. Data available. Based on test data for the material. Test(s) equivalent or similar to OECD Guideline 405
- Respiratory** : Negligible hazard at ambient/normal handling temperatures. Data available. Elevated temperatures or mechanical action may form vapours, mist, or fumes which may be irritating to the eyes, nose, throat, or lungs.

#### Respiratory or skin sensitization

##### Conclusion/Summary

- Skin** : Not expected to be a skin sensitizer. Data available. Based on test data for the material. Test(s) equivalent or similar to OECD Guideline 406
- Respiratory** : Not expected to be a respiratory sensitizer. No end point data for material.

#### Mutagenicity

##### Conclusion/Summary

- : Not expected to be a germ cell mutagen. Data available. Based on test data for the material. Test(s) equivalent or similar to OECD Guideline 471 473

#### Carcinogenicity

##### Conclusion/Summary

- : Not expected to cause cancer. No end point data for material.

#### Reproductive toxicity

##### Conclusion/Summary

- : Not expected to be a reproductive toxicant. Data available. Based on test data for the material. Test(s) equivalent or similar to OECD Guideline 414 416

#### Specific target organ toxicity (single exposure)

##### Conclusion/Summary

- : Not expected to cause organ damage from a single exposure. No end point data for material.

#### Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Target organs
neodecanoic acid	Not applicable.	-

##### Conclusion/Summary

- : Not expected to cause organ damage from a single exposure. No end point data for material.

#### Aspiration hazard

##### Conclusion/Summary

- : Not expected to be an aspiration hazard. Based on physico-chemical properties of the material. Data available.

## Section 11. Toxicological information

## Section 12. Ecological information

The information given is based on data for the material, components of the material, or for similar materials, through the application of bridging principals.

**General characteristics of the impact on environmental objects** : No known significant effects or critical hazards.

**Ways of affecting the environment** : Violation of storage and transport regulations, incorrect placement and incineration of waste, discharge into bodies of water or the ground, accidents and emergencies.

### Toxicity

Product/ingredient name	Duration	Species	Result
neodecanoic acid	72 hours	Algae - <i>Pseudokirchneriella subcapitata</i>	Acute EL50 >100 mg/l
	48 hours	daphnia - <i>Daphnia magna</i>	Acute EL50 >1000 mg/l
	96 hours	Fish - <i>Oncorhynchus mykiss</i>	Acute LL50 100 to 300 mg/l
	21 days	daphnia - <i>Daphnia magna</i>	Chronic LOEC 10.1 mg/l
	14 days	Fish - <i>Oncorhynchus mykiss</i>	Chronic NOEC >2.22 mg/l
	21 days	daphnia - <i>Daphnia magna</i>	Chronic NOEC 4.78 mg/l

### Conclusion/Summary

**Acute toxicity** : Not expected to be harmful to aquatic organisms.

**Chronic toxicity** : Not expected to demonstrate chronic toxicity to aquatic organisms

### Persistence and degradability

Product/ingredient name	Test	Result	Qualifier	Media
neodecanoic acid	Ready Biodegradability	11 % - 28 days	-	water

**Photolysis** : 0.58 day(s)

**Biodegradability** : Material -- Expected to biodegrade slowly.

**Hydrolysis** : Material -- Transformation due to hydrolysis not expected to be significant.

**Photolysis** : Material -- Transformation due to photolysis not expected to be significant.

**Atmospheric Oxidation** : Material -- Expected to degrade rapidly in air

### Bioaccumulative potential

**Bioconcentration factor (BCF)** : <225 14day(s)

**Conclusion/Summary** : Material -- Potential to bioaccumulate is low.

### Environmental limits

Not available.

### Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** : 2.08 Media:Sediment

**Mobility** : Material -- Expected to partition to water. Some partitioning to sediment and wastewater solids. Minimally volatile.

### Other ecological information

## Section 12. Ecological information

**Other adverse effects** : No known significant effects or critical hazards.

## Section 13. Disposal considerations

**Disposal methods** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Empty Container Warning (where applicable): Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Empty drums should be completely drained and safely stored until appropriately reconditioned or disposed. Empty containers should be taken for recycling, recovery, or disposal through suitably qualified or licensed contractor and in accordance with governmental regulations. **DO NOT PRESSURISE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.**

## Section 14. Transport information

	ADR	IMDG	IATA
<b>UN number</b>	Not regulated.	Not regulated.	Not regulated.
<b>UN proper shipping name</b>	-	-	-
<b>Transport hazard class(es)</b>	-	-	-
<b>Packing group</b>	-	-	-
<b>Environmental hazards</b>	No.	No.	No.

**Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**Transport in bulk according to IMO instruments**      **Proper shipping name** : neodecanoic acid  
**Remarks** : **Liquid bulk cargoes:**  
 Ship type: 2  
 Pollution category: Y

## Section 15. Regulatory information

### Inventory list

**Australia inventory (AIC)** : All components are listed or exempted.  
**Canada inventory (DSL-NDSL)** : All components are listed or exempted.  
**China inventory (IECSC)** : All components are listed or exempted.  
**Japan inventory (CSCL)** : All components are listed or exempted.  
**Japan inventory (Industrial Safety and Health Act)** : All components are listed or exempted.

## Section 15. Regulatory information

<b>New Zealand Inventory of Chemicals (NZIoC)</b>	: All components are listed or exempted.
<b>Philippines inventory (PICCS)</b>	: All components are listed or exempted.
<b>Korea inventory (KECI)</b>	: All components are listed or exempted.
<b>Taiwan Chemical Substances Inventory (TCSI)</b>	: All components are listed or exempted.
<b>United States inventory (TSCA 8b)</b>	: All components are active or exempted.

## Section 16. Other information

### History

**Date of issue/Date of revision** : 9 October 2024

**Date of previous issue** : 4 August 2024

**Version** : 1.02

**Key to abbreviations** :

- ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
- ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
- ATE = Acute Toxicity Estimate
- BCF = Bioconcentration Factor
- GHS = Globally Harmonized System of Classification and Labelling of Chemicals
- GOST = Gosudarstvennyy standart
- IATA = International Air Transport Association
- IBC = Intermediate Bulk Container
- IMDG = International Maritime Dangerous Goods
- LogPow = logarithm of the octanol/water partition coefficient
- MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
- N/A = Not available
- RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
- SGG = Segregation Group
- UN = United Nations

### Procedure used to derive the classification

Classification	Justification
ACUTE TOXICITY (oral) - Category 4	Calculation method

**References** : Not available.

✔ Indicates information that has changed from previously issued version.

**Product code** : 1161336\_13632380

### Notice to reader

"The information and recommendations contained herein are, to the best of ExxonMobil's knowledge and belief, accurate and reliable as of the date issued. You can contact ExxonMobil to insure that this document is the most current available from ExxonMobil. The information and recommendations are offered for the user's consideration and examination. It is the user's responsibility to satisfy itself that the product is suitable for the intended use. If buyer repackages this product, it is the user's responsibility to insure proper health, safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, re-publication or retransmission of this document, in whole or in part, is not permitted. The term, ""ExxonMobil"" is used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliates in which they directly or indirectly hold any interest."