

STANDARD TYPES OF TOYOLAC

TYPES		PROCESSING	FEATURES
GENERAL PURPOSE ABS	100 322	Injection and Extrusion	High Impact Strength
	100 X01	Injection and Extrusion	Super High Impact Strength
	250 X10	Injection	High Flow
	500 322	Injection	High Rigidity
	700 314	Injection	Medium Impact Strength
	700 X01	Injection	High Flow Medium Impact
GLASS FIBRE REINFORCED ABS (ABSG)	100G-10	Injection	10% Glass Fibre Reinforced ABS
	100G-20	Injection	20% Glass Fibre Reinforced ABS
	100G-30	Injection	30% Glass Fibre Reinforced ABS
GLASS FIBRE REINFORCED AS (ASG)	ASG-10	Injection	10% Glass Fibre Reinforced AS
	ASG-20	Injection	20% Glass Fibre Reinforced AS
	ASG-30	Injection	30% Glass Fibre Reinforced AS
HIGH HEAT ABS	440Y MH1	Injection	DTL 92 °C (ISO 75)
	440Y MH5	Injection	DTL 92 °C (ISO 75)
	450Y MH1	Injection	DTL 98 °C (ISO 75)
	450Y MH5	Injection	DTL 98 °C (ISO 75)
	450Y X10	Injection	DTL 95 °C (ISO 75)
	470Y MH1	Injection	DTL 104 °C (ISO 75)
FLAME RETARDANT ABS	884 X01	Injection	0.75mm V-2, 1.5mm V-0, 2.5mm 5VA
	824V X01	Injection	0.75mm V-2, Light Resistant
	834V X01	Injection	2.0mm V-0, 3.0 mm 5VA, Light Resistant
	844V X05	Injection	1.5mm V-0, 2.5 mm 5VA, 2.0mm 5VB, Light Resistant
CHEMICAL RESISTANT ABS	AX05 X03	Injection	Chemical Resistant
PAINTING ABS	100 MPF	Injection	Paintable
	100 MPM	Injection	Paintable
PLATING ABS	325	Injection	Plating
TRANSPARENT ABS	920 555	Injection	Transparent ABS
	910 X01	Injection	Transparent ABS
	912 X01	Injection	Transparent ABS

Toray Plastics Malaysia Sdn Bhd. (Head Office)
 2628, MK1 SPT, Lorong Perusahaan 4 FIZ, Prai, 13600, Penang, Malaysia
 Tel: 604-3988088 Fax: 604-3908975
 Email : sales.tpm@toray.com.my
www.torayplastics.com