



组件 - 塑料

UL 档案号: E41797

TORAY INDUSTRIES INC
NIHONBASHI-MITSUI TOWER
1-1 NIHONBASHI-MUROMACHI 2-CHOME
CHUO-KU, TOKYO 103-8666 Japan



UTN320, U320

Polyamide 66 (PA66), pellets

NOTE - Polyamide (nylon) grades may be prefixed with the letters CM and may employ hyphens in various locations. The designations of ECODEAR products may employ hyphens and/or spaces in various locations. All grades that include ABS, SAN, and/or PC (designations of TOYOLAC or TOYOLACPAREL or TORAYCA products) may employ hyphens and/or spaces and may be suffixed with 3 or 4 digits of letters and/or numbers.

可燃性	值	测试方法
UL 阻燃等级		
1.5 mm, ALL	HB	UL 94
3.0 mm, ALL	HB	UL 94
3.0 mm, ALL	HB40	IEC 60695-11-10, -20
1.5 mm, ALL	HB75	IEC 60695-11-10, -20
热性能	值	测试方法
RTI Elec		UL 746
1.5 mm	65.0 °C	
3.0 mm	65.0 °C	
RTI Imp		UL 746
1.5 mm	65.0 °C	
3.0 mm	65.0 °C	
RTI		UL 746
1.5 mm	65.0 °C	
3.0 mm	65.0 °C	