



组件 - 塑料
UL 档案号: E59481

CHANG CHUN PLASTICS CO LTD
NO 8 HUAXI RD
DALIAO DISTRICT
KAOHSIUNG CITY, 83164 Taiwan



LONGLITE: 56(\$)F

Polybutylene Terephthalate (PBT), pellets, glass reinforced

(\$) - Maybe 00~30 indicating the content of glass fiber from 0% to 30%(exclude 0 % and 30%).

可燃性	值	测试方法
UL 阻燃等级		UL 94
0.40 mm, ALL	V-0	IEC 60695-11-10, -20
0.8 mm, ALL	V-0	
3.0 mm, ALL	V-0	
灼热丝易燃指数		IEC 60695-2-12
0.40 mm	960 °C	
0.8 mm	960 °C	
3.0 mm	960 °C	
热灯丝点火温度		IEC 60695-2-13
0.40 mm	725 °C	
0.8 mm	725 °C	
3.0 mm	750 °C	
电气性能	值	测试方法
热丝引燃 (HWI)		UL 746A
0.40 mm	PLC 4	
0.8 mm	PLC 4	
3.0 mm	PLC 2	
高电弧燃烧指数(HAI)		UL 746A
0.40 mm	PLC 0	
0.8 mm	PLC 0	
3.0 mm	PLC 0	
相比耐漏电起痕指数(CTI)	PLC 0	UL 746A
高电压电弧起痕速率 (HVTR)	PLC 4	UL 746A
耐电弧性	PLC 6	ASTM D495
热性能	值	测试方法
RTI Elec		UL 746B
0.40 mm	75.0 °C	
0.8 mm	130 °C	
3.0 mm	130 °C	
RTI Imp		UL 746B
0.40 mm	75.0 °C	
0.8 mm	130 °C	
3.0 mm	130 °C	
RTI		UL 746B
0.40 mm	75.0 °C	
0.8 mm	130 °C	
3.0 mm	130 °C	