



TECHNICAL DATA SHEET

Product	AM 189/A
Gruppo✓ Group	Plastificati Medicali Flexible Medical
Categoria✓ Categorie	Estrusione Extrusion
Emissione: 1 del 10/2009 Revisione: 1 del 01/2010	

TECHNICAL INFORMATION	TESTING METHOD	UNIT OF MEASURE	VALUE
Peso Specifico Specific Weight	ISO 1183	g/cm ³	1,250
Durezza Hardness	ISO 868	Shore A	91
Carico di Rottura Tensile Strength	ISO 527	N/mm ²	24,5
Allungamento a Rottura Elongation at Break	ISO 527	%	340
Caratter. Alimentari Foodstuff Properties	2002/72/CE - ITA 21/3/73 and updating (Aqueous, acid and alcoholic foodstuff products)		OK
Caratter. Farmacopea Pharmacopoeia Properties	EUROPEAN PHARM. VII Ed. (Par. 3.1.1.2.)		NO
Caratter. Farmacopea U.S.A. U.S. Pharmacopoeia Properties	U.S.P. XXVIII Ed. Class VI		OK
Applicazioni	Compound per estrusione tubi, esente da ftalati. Plasticizzazione: Di-2-etilesil-adipato DOA Stabilizzazione: Ca/Zn Sterilizzazione suggerita: Eto Lista Reach-SVHC: conforme		
Note	Le caratteristiche tecniche sopra riportate derivano da nostre analisi di laboratorio su campioni rappresentativi e sono da considerarsi valori medi tipici misurati sul prodotto e non possono essere usati come valori di specifica. Analisi eseguite su prodotto naturale non colorato.		
Applications	PVC for tubes extrusion, phthalates free. Plasticization: Bis-2-ethylhexyl-adipate DOA Stabilization: Ca/Zn Suggested sterilization: Eto Reach-SVHC list: in compliance		
Notes	The above mentioned technical characteristics come from our laboratory tests done on representative samples. They have to be considered as average typical values measured on the product and can not be used as technical specification values. Analyses referred to natural material without pigments.		