



DAI-EL_{TM} G-101

DAI-EL G-101 is a fluoroelastomer which is liquid at room temperature and used for applications to improve the processability and reduce the hardness of solid fluoroelastomer.

1. Properties of the product

Items	Data	Test method
Color	Milky white or light yellow	Visual observation
Specific gravity (23°C)	1.76	JIS K 6268
Viscosity (P)	3300	JIS K 6893-1 B type viscometer No. 4 0.6rpm 45 min.)
Solubility	Soluble in low molecular weight ketones and esters	—

2. Handling method/Safety information

Be sure to read the notes stated in MSDS and labels before use.

This product is supplied for general industry and therefore its adequacy and safety for medical applications cannot be guaranteed.

3. Packing specification 15kg

DAIKIN INDUSTRIES, LTD.
Chemical Division
Umeda Center Bldg.,
2-4-12, Nakazaki-Nishi, Kita-ku,
Osaka 530-8323, Japan
Phone: +81-6-6373-4342
Facsimile: +81-6-6373-4390
<http://www.daikin.com/chm>

DAIKIN AMERICA, INC.
20 Olympic Drive,
Orangeburg, NY 10962, USA
Phone: +1-845-365-9500
Toll-Free: +1-800-365-9570
Facsimile: +1-845-365-9598
<http://www.daikin-america.com>

DAIKIN CHEMICAL EUROPE
GmbH
Immermannstr. 65D,
40210 Dusseldorf, Germany
Phone: +49-211-179225-0
Facsimile: +49-211-1640732
<http://www.daikinchem.de>