



Elvaloy® 4924

DuPont Packaging & Industrial Polymers - Thermoplastic

Wednesday, November 6, 2019

General Information

Product Description

DuPont™ Elvaloy® 4924 is an ethylene/vinyl acetate/carbon monoxide (E/V/A/CO) copolymer.

Elvaloy® 741 is a high molecular weight copolymer often used as a non-migrating, permanent PVC plastizer in roofing, geo-membranes, and other applications needing flexible pvc.

General

Material Status	• Commercial: Active		
Availability	• Africa & Middle East	• Europe	• North America
	• Asia Pacific	• Latin America	
Features	• Good Flexibility	• Good Toughness	
Uses	• Plastics Modification		
Agency Ratings	• FDA 21 CFR 175.105		
Forms	• Pellets		

ASTM & ISO Properties ¹

Physical	Nominal Value	Unit	Test Method
Density / Specific Gravity	1.00		ASTM D792
Density	1.00	g/cm ³	ISO 1183
Melt Mass-Flow Rate (190°C/2.16 kg)	15	g/10 min	ASTM D1238
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	15	g/10 min	ISO 1133
Molecular Weight Distribution	Normal		ASTM D3593
Mechanical	Nominal Value	Unit	Test Method
Tensile Elongation (Break)	740	%	ASTM D638
Thermal	Nominal Value	Unit	Test Method
Glass Transition Temperature	-32.8	°F	ASTM D3418
Peak Melting Temperature	158	°F	ASTM D3418
Melting Temperature (DSC)	158	°F	ISO 3146

Processing Information

Injection	Nominal Value	Unit
Processing (Melt) Temp	< 464	°F

Notes

¹ Typical properties: these are not to be construed as specifications.