



Lusin® Clean 1500

Chem-Trend L.P. - Thermoplastic

Wednesday, November 6, 2019

General Information

Product Description

Ready-to-use Purging Compound for Screw, Barrel, Nozzle and Hot-runner of Injection Moulding Machines Processing Polycarbonates

Benefits

- Especially dedicated for the cleaning of injection moulding machines processing polycarbonates
- Economical due to low consumption
- No smell during application
- No contamination of the following parts
- Removes residues and encrustations
- Suitable for use on hot-runner systems
- No generation of milky traces

Description

Lusin® Clean 1500 is a highly concentrated purging compound that is specially developed for the processing of polycarbonate. The purging compound consists of high quality thermoplastic resins as well as highly efficient cleaning additives and does not contain abrasives. The product is completely miscible with polycarbonates and does not generate any milky traces.

Lusin® Clean 1500 is suitable for colour and material change as well as for removal of black spot contaminations and carbon residues especially on transparent parts and can be used at processing temperatures up to 350°C (662°F).

Typical Properties

Appearance yellowish granules

General

Material Status	• Commercial: Active		
Availability	• Asia Pacific	• Latin America	• Europe
Additive	• Unspecified Additive		
Uses	• Purging Compound		
Appearance	• Yellow		
Forms	• Granules		