



Lusin® Clean G 301

Chem-Trend L.P. - Thermoplastic

Wednesday, November 6, 2019

General Information

Product Description

Ready-to-use Purging Compound for Blow Moulding Machines and Extruders

Benefits

- Suitable for processing temperatures up to 300°C/572°F
- Economical due to low consumption
- No smell during application
- Rapid cleaning effect
- Helps to prevent carbonization
- NSF registered, conforms to H2 listing requirements

Description

Lusin® Clean G 301 is a ready to use granular purging compound for screw, barrel and heads of blow moulding machines and extruders.

The purging compound consists of high quality thermoplastic resins as well as highly efficient cleaning additives and does not contain abrasives. Lusin® Clean G 301 helps prevent carbon build-up, when used as a preventive maintenance product.

Typical Properties

Appearance : Grey to white granules

General

Material Status	• Commercial: Active	
Availability	• Asia Pacific	• Latin America
	• Europe	• North America
Additive	• Unspecified Additive	
Uses	• Purging Compound	
Agency Ratings	• NSF Unspecified Rating	
Appearance	• Grey	• White
Forms	• Granules	

UL and the UL logo are trademarks of UL LLC © 2019. All Rights Reserved.

The information presented here was acquired by UL from the producer of the product or material or original information provider. However, UL assumes no responsibility or liability for the accuracy of the information contained on this website and strongly encourages that upon final product or material selection information is validated with the manufacturer. This website provides links to other websites owned by third parties. The content of such third party sites is not within our control, and we cannot and will not take responsibility for the information or content.