

POLYFLON™ M-15HS

聚四氟乙烯

DAIKIN AMERICA, INC.

PROSPECTOR®

www.ulprospector.com

Technical Data

产品说明

Daikin-Polyflon M-15HS is a polytetrafluoroethylene virgin granular fine cut resin. This general purpose molding powder has been specifically designed for use as a feedstock for filled compound production. M-15HS is particularly well suited for compounds requiring a higher shrinkage than attainable with M-15X or a typical fine cut molding resin.

总体

材料状态	• 已商用：当前有效
资料 ¹	• Technical Datasheet (English)
搜索 UL 黄卡	• DAIKIN AMERICA, INC. • POLYFLON™
供货地区	• 北美洲
用途	• 通用
外观	• 白色
形式	• 粉状
加工方法	• 注射成型

物理性能	额定值	单位制	测试方法
比重	2.15	g/cm³	ASTM D792
表观密度	0.28	g/cm³	ASTM D1895
机械性能	额定值	单位制	测试方法
抗张强度 (屈服)	35.0	MPa	ASTM D638
伸长率 (断裂)	350	%	ASTM D638

补充信息

All of the above properties were tested in accordance with ASTM D4894
Shrinkage, DAIKIN qac206fp: 6.0-8.0%

备注

- ¹ 通过这些链接您能够访问供应商资料。我们尽量保证及时更新资料；不过您可以从供应商处了解最新资料。
- ² 一般属性：这些不能被视为规格。



POLYFLON™ M-15HS

聚四氟乙烯

DAIKIN AMERICA, INC.

PROSPECTOR®

www.ulprospector.com

购买地点

供应商

DAIKIN AMERICA, INC.
Orangeburg, NY USA
电话: 800-365-9570
Web: <http://www.daikin-america.com/>

分销商

请联系供应商以便为 POLYFLON™ M-15HS 查找分销商

