

1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- **Trade name:** POLYFLON PTFE EK-1209BKER
- **Article number:** EK1209BKER
- **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Coating compound/ Surface coating/ paint
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
DAIKIN INDUSTRIES, LTD. CHEMICALS DIVISION:
Umeda Center Bldg., 4-12, Nakazaki-Nishi2-chome, Kita-Ku, Osaka, JAPAN
Phone: (+81) 6-6373-4345 Fax: (+81) 6-6373-4281
- **Further information obtainable from:** <http://www.daikin.com/>
- **Emergency telephone number:**
+81-6-6349-7521, +1-256-306-5000, +86-512-5-232-0949, +82-2-568-1722, +49-211-179 225-0

2 Hazard identification

- **Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



Repr. 1B H360D May damage the unborn child.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H335 May cause respiratory irritation.

- **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

- **Signal word** Danger

- **Precautionary statements**

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P321 Specific treatment (see on this label).

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

- **Chemical characterization: Substances**

9002-84-0 Polytetrafluoroethylene	10-20%
Binders	1-10%
Acute Tox. 4, H302	
Polyoxyethylene glycol alkyl ether	<5%
Acute Tox. 4, H302	
Poly(oxyethylene) nonylphenyl ether	<5%
Xi R36; N R50	
Aquatic Acute 1, H400; Eye Irrit. 2, H319	

Safety data sheet

Printing date 17.04.2014

Revision: 17.04.2014

Trade name: POLYFLON PTFE EK-1209BKER

1333-86-4 Carbon black substance with a Community workplace exposure limit	<5%
872-50-4 N-methyl-2-pyrrolidone T Repr. Cat. 2 R61; Xi R36/37/38 Repr. 1B, H360D; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	15-25%
7732-18-5 Water	40-50%
Others	5-15%
<ul style="list-style-type: none"> · Chemical characterization: Mixtures · SVHC 	
872-50-4 N-methyl-2-pyrrolidone	
· Additional information: For the wording of the listed risk phrases refer to section 16.	

4 First aid measures

- **Description of first aid measures**
- **General information:** Seek immediate medical advice.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.
Remove contaminated clothes immediately.
- **After eye contact:**
Immediately rinse with a lot of water for several minutes. Remove contact lenses if possible. Continue rinsing.
- **After swallowing:** Rinse mouth with water. Do not induce vomiting.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.
- **Special hazards arising from the substance or mixture**
Formation of toxic gases is possible during heating or in case of fire.
- **Advice for firefighters**
- **Protective equipment:**
Inhalation respiratory device.
Do not inhale explosion gases or combustion gases.
Wear fully protective suit.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Ensure adequate ventilation before entering the area.
Keep out unauthorized persons.
Wear appropriate protective devices (See Section 8 Exposure Controls/ Personal Protection). Avoid contact with eyes and skin.
Do not swallow/ inhale the product.
- **Environmental precautions:** Prevent seepage into sewage system, workpits and cellars.
- **Methods and material for containment and cleaning up:**
For a small amount of leakage: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust) or collect in an empty container that can be sealed tightly.
For a large amount of leakage: Enclose with banks to avoid outflow. Lead the leakage to a safe place and collect.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

Safety data sheet

Printing date 17.04.2014

Revision: 17.04.2014

Trade name: POLYFLON PTFE EK-1209BKER

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
 - Ensure good ventilation/exhaustion at the workplace.
 - Do not handle until all safety precautions have been read and understood.
 - Install extractors.
- **Information about fire - and explosion protection:** Keep ignition sources away - Do not smoke.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
 - **Requirements to be met by storerooms and receptacles:** Store in a cool and dry location.
 - **Information about storage in one common storage facility:**
 - See section 10 for information on incompatible materials.
 - **Further information about storage conditions:**
 - Store in cool, dry conditions in well sealed receptacles.
 - Protect from heat and direct sunlight.
 - Store receptacle in a well ventilated area.
 - Store locked up.
 - **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**

872-50-4 N-methyl-2-pyrrolidone

OEL (Japan) Long-term value: 4 mg/m³, 1 ppm
 WEEL (USA) Long-term value: 10 ppm
 Skin

1333-86-4 Carbon black

PEL (USA) Long-term value: 3,5 mg/m³
 REL (USA) Long-term value: 3,5* mg/m³
 *0,1 in presence of PAHs; See Pocket Guide Apps.A+C
 TLV (USA) Long-term value: 3* mg/m³
 *inhalable fraction

- **Ingredients with biological limit values:**

872-50-4 N-methyl-2-pyrrolidone

BEI (USA) 100 mg/L
 Medium: urine
 Time: end of shift
 Parameter: 5-Hydroxy-N-methyl-2-pyrrolidone

- **Additional information:** The lists valid during the making were used as basis.

- **Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Wash hands before breaks and at the end of work.

Do not eat or drink while working.

Keep away from tobacco products.

- **Respiratory protection:**

Use respiratory protective device with filters for organic and acid gas (or airline respirators in some cases) if formation of toxic gases is possible while the product is heated.

Use respiratory protective device with organic gas cartridge.

Safety data sheet

Printing date 17.04.2014

Revision: 17.04.2014

Trade name: POLYFLON PTFE EK-1209BKER

- Protection of hands:



Protective gloves

- Eye protection: Safety glasses
- Body protection: Protective work clothing

9 Physical and chemical properties

- Information on basic physical and chemical properties

- General Information

- Appearance:

Form:	Liquid
Colour:	Black
· Odour:	Odourless
· Odour threshold:	Not determined.

· pH-value:	5-8
-------------	-----

- Change in condition

Melting point/Melting range: No further information available.

Boiling point/Boiling range: ca.100 °C

No further information available.

· Flash point:	Not applicable.
----------------	-----------------

· Danger of explosion:	Product does not present an explosion hazard.
------------------------	---

· Lower:	No further information available.
----------	-----------------------------------

· Upper:	No further information available.
----------	-----------------------------------

· Vapour pressure:	No further information available.
--------------------	-----------------------------------

· Density:	No further information available.
------------	-----------------------------------

· Solubility in / Miscibility with water:	Fully miscible.
---	-----------------

· Partition coefficient (n-octanol/water):	No further information available.
--	-----------------------------------

· Other information	No further relevant information available.
---------------------	--

10 Stability and reactivity

- Reactivity

- Chemical stability

· Thermal decomposition / conditions to be avoided: To avoid thermal decomposition do not overheat.

· Possibility of hazardous reactions No dangerous reactions known under normal conditions of use.

· Conditions to avoid Keep away from heat, sparks, flame, high temperature.

· Incompatible materials: No further relevant information available.

- Hazardous decomposition products:

As for decomposition products, particulate matters and extremely toxic/ corrosive fumes may be generated (HF, carbonyl fluoride, monomer, perfluoroisobutylene).

Decomposition products differ depending on the temperature and conditions.

11 Toxicological information

- Information on toxicological effects

- Acute toxicity:

- LD/LC50 values relevant for classification:

872-50-4 N-methyl-2-pyrrolidone

Oral LD50 3914 mg/kg (rat)

Dermal LD50 8000 mg/kg (rabbit)

- Primary irritant effect:

· on the skin: Irritant to skin and mucous membranes.

Safety data sheet

Printing date 17.04.2014

Revision: 17.04.2014

Trade name: POLYFLON PTFE EK-1209BKER

- **on the eye:** Irritating effect.

Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

General effects:

Fumes generated during burning may cause "polymer fume fever" (flu-like symptoms such as fever, chill, cough). This may last for a whole day and night.

Fumes are not absorbed in skin. No sensitizing effect known.

Effects of hydrogen fluoride:

Low concentration of hydrogen fluoride may cause feeling of dyspnea, cough, irritation in eyes, nose, throat, fever, chill for 1-2 days.

After that, dyspnea, cyanosis and pulmonary edema may be seen.

High concentration of hydrogen fluoride damages liver and kidney.

Effects of carbonyl fluoride:

Skin: Irritation or eruption

Eye: Ulcer in cornea, conjunctiva

Respiratory system : Irritation

Lung: Temporary symptoms such as cough, pain, dyspnea

Persons who have experienced lung diseases are vulnerable to toxicity caused by excessive exposure to pyrolysis products

· CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Repr. 1B

12 Ecological information

· Toxicity

· Aquatic toxicity: No further relevant information available.

· Persistence and degradability No further relevant information available.

· Behaviour in environmental systems:

· Bioaccumulative potential No further relevant information available.

· Mobility in soil No further relevant information available.

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

· Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation: Disposal must be made according to official regulations.

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

14 Transport information

· UN-Number

· ADR, ADN, IMDG, IATA Not applicable

· UN proper shipping name

· ADR, ADN, IMDG, IATA Not applicable

· Transport hazard class(es)

· ADR, ADN, IMDG, IATA

· Class Not applicable

· Packing group

· ADR, IMDG, IATA Not applicable

· Environmental hazards:

· Marine pollutant: No

· Special precautions for user Not applicable.

Safety data sheet

Printing date 17.04.2014

Revision: 17.04.2014

Trade name: POLYFLON PTFE EK-1209BKER

- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** *Not applicable.*
- **Transport/Additional information:** *Avoid direct sunlight. Make sure of no damage, corrosion, leaks on the receptacles.*
Take necessary measures for preventing cargo shift.
- **UN "Model Regulation":** *-*

15 Regulatory information

- **National regulations:**
- **Other regulations, limitations and prohibitive regulations**
- **Substances of very high concern (SVHC) according to REACH, Article 57**

872-50-4 N-methyl-2-pyrrolidone

16 Other information

The product is for the industrial use only. We do not guarantee the safety in case the product is used for the other purposes. When using the product for health-care application or food/feed application, consult us in advance. This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS: EHS Department**

- **Contact:** <http://www.daikin.com/>

- **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent