

Printing date 24.03.2015

Version number 1

Revision: 24.03.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: DAI-EL LATEX GLP-104QR

Article number: GLP104QR

1.2 Relevant identified uses of the substance or mixture and uses advised against:

No further relevant information available.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

DAIKIN INDUSTRIES, LTD. CHEMICALS DIVISION:

Umeda Center Bldg., 4-12, Nakazaki-Nishi 2-chome, Kita-Ku, Osaka, JAPAN

Phone: (+81) 6-6373-4345 Fax: (+81) 6-6373-4281

Further information obtainable from: <http://www.daikin.com/>

1.4 Emergency telephone number:

+81-6-6349-7521, +86-512-5-232-0949, +86-21-34151689,

+82-2-568-1722, +1-256-306-5000, +49-211-179 225-0

SECTION 2: Hazard identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 2 H225 Highly flammable liquid and vapour.



Repr. 2 H361d Suspected of damaging the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



Eye Dam. 1 H318 Causes serious eye damage.



Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008:

The product is classified and labelled according to the CLP regulation.

Signal word: Danger

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

Safety data sheet

Printing date 24.03.2015

Version number 1

Revision: 24.03.2015

Trade name: DAI-EL LATEX GLP-104QR

P501 *Dispose of contents/container in accordance with local/regional/national/international regulations.*

SECTION 3: Composition/information on ingredients

Information on ingredients:

Silicon	10-20%
108-88-3 Toluene	55-65%
Xn R48/20-63-65; Xi R38; F R11	
R67	
Repr. Cat. 3	
Flam. Liq. 2, H225; Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304; Skin Irrit. 2, H315; STOT SE 3, H336	
71-36-3 n-Butanol	15-25%
Xn R22; Xi R37/38-41	
R10-67	
Flam. Liq. 3, H226; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	

Description: Mixture of substances listed below with nonhazardous additions.

Additional information: For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: Seek medical treatment.

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact:

Remove contaminated clothes immediately.

Immediately wash with water and soap and rinse thoroughly.

Consult a doctor in case of complaints.

After eye contact:

Immediately rinse with a lot of water for several minutes. Remove contact lenses if possible. Continue rinsing.

Consult an ophthalmologist in case of complaints.

After swallowing:

Rinse mouth with water. Do not induce vomiting.

Consult a doctor in case of complaints.

4.2 Most important symptoms and effects, both acute and chronic: No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed:

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

Foam

Fire-extinguishing powder

CO2

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture:

Formation of toxic gases is possible during heating or in case of fire.

Receptacle may explode when heated.

Extremely flammable; can ignite easily with heat, sparks, fire.

5.3 Advice for firefighters:

The flash point is extremely low; water spray can be used for a large fire only if other extinguishing means have no effect.

Remove receptacles from area of fire if possible.

Protective equipment:

Wear self-contained breathing apparatus and protective suit.

Safety data sheet

Printing date 24.03.2015

Version number 1

Revision: 24.03.2015

Trade name: DAI-EL LATEX GLP-104QR*Do not inhale explosion gases or combustion gases.*

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

*Ensure adequate ventilation before entering the area.**Stay on the windward side.**Keep out unauthorized persons.**Wear appropriate protective devices (See Section 8 Exposure Controls/ Personal Protection). Avoid contact with eyes and skin.**Do not swallow the product.***6.2 Environmental precautions:** *Prevent seepage into sewage system, workpits and cellars.*

6.3 Methods and material for containment and cleaning up:

*Do not flush with water or aqueous cleansing agents**For a small amount of leakage: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders) or collect in an empty container that can be sealed tightly.**For a small amount of leakage: Use clean anti-static tools when absorbing the product.**For a large amount of leakage: Enclose with banks to avoid outflow. Lead the leakage to a safe place and collect.**Remove ignition sources immediately.**Ground all equipment when the product leaks.**There is a danger of explosion. Prepare fire extinguisher in case of emergency.*

6.4 Reference to other sections:

*See Section 8 for information on personal protection equipment.**See Section 13 for disposal information.*

SECTION 7: Handling and storage

7.1 Precautions for safe handling:

*Open and handle receptacle with care.**Ensure good ventilation/exhaustion at the workplace.**Handle with care. Avoid jolting, friction and impact.**Do not handle until all safety precautions have been read and understood.*

Information about fire - and explosion protection:

*Keep ignition sources away - Do not smoke.**Protect against electrostatic charges.**Use flame proof electric/ lighting devices and ventilation equipment.**Ground/Bond container and receiving equipment.*

7.2 Conditions for safe storage, including any incompatibilities:

Storage

Requirements to be met by storerooms and receptacles:

*Store in a cool and dry location.**Provide solvent resistant, sealed floor.**Keep receptacle tightly sealed.*

Information about storage in one common storage facility:

See section 10 for information on incompatible materials.

Further information about storage conditions:

*Protect from heat and direct sunlight.**Store receptacle in a well ventilated area.**Store locked up.***7.3 Specific end use(s):** *No further relevant information available.*

SECTION 8: Exposure controls/personal protection

Additional information about design of technical facilities: *No further data; see item 7.***8.1 Control parameters** *No further information available.*

Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

Safety data sheet

Printing date 24.03.2015

Version number 1

Revision: 24.03.2015

Trade name: DAI-EL LATEX GLP-104QR**8.2 Exposure controls****Personal protective equipment****General protective and hygienic measures:**

Wash hands before breaks and at the end of work.

Do not eat or drink while working.

Keep away from tobacco products.

Respiratory protection:

Use respiratory protective device with filters for organic and acid gas (or airline respirators in some cases) if formation of toxic gases is possible while the product is heated.

Use respiratory protective device with organic gas cartridge.

Protection of hands:

Protective gloves

Material of gloves: Rubber**Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:

Safety glasses

Body protection: Protective work clothing

SECTION 9: Physical and chemical properties
--

9.1 Information on basic physical and chemical properties**General Information****Appearance****Form:** Liquid**Colour:** Light yellow**Odour:** Alcohol-like**Odour threshold:** Not determined.**pH-value:** No further information available.**Melting point/Melting range:** No further information available.**Boiling point/Boiling range:** ca. 100 °C

No further information available.

Flash point: 5 °C (SCC)**Flammability (solid, gaseous):** Not applicable.**Ignition temperature:** >300 °C**Decomposition temperature:** No further information available.**Self-igniting:** Product is not selfigniting.**Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.**Lower explosive limit:** 1,2 Vol %**Upper explosive limit:** 9,4 Vol %**Vapour pressure:** No further information available.**Density at 25 °C:** 0,89 g/cm³

No further information available.

Solubility in / Miscibility with water:

No further information available.

Safety data sheet

Printing date 24.03.2015

Version number 1

Revision: 24.03.2015

Trade name: DAI-EL LATEX GLP-104QR**Partition coefficient (n-octanol/water):** No further information available.**9.2 Other information:** No further relevant information available.

SECTION 10: Stability and reactivity

10.1 Reactivity**10.2 Chemical stability****Thermal decomposition / conditions to be avoided:** To avoid thermal decomposition do not overheat.**10.3 Possibility of hazardous reactions:**

No dangerous reactions known under normal conditions of use.

Reacts with water and acids.

Reacts with alkalis.

10.4 Conditions to avoid: Keep away from heat, sparks, flame, high temperature.**10.5 Incompatible materials:** Oxidizing agents**10.6 Hazardous decomposition products:** Methanol

SECTION 11: Toxicological information

11.1 Information on toxicological effects**Acute toxicity****LD/LC50 values relevant for classification:****108-88-3 Toluene**

Oral LD50 5000 mg/kg (Rat)

Dermal LD50 12124 mg/kg (Rabbit)

Inhalative LC50/4 h 5320 ppm (Mouse)

71-36-3 n-Butanol

Oral LD50 790 mg/kg (Rat)

Dermal LD50 3400 mg/kg (Rabbit)

Inhalative LC50/4 h 8000 ppm (Rat)

Primary irritant effect**on the skin:** Irritant to skin and mucous membranes.**on the eye:** Strongly irritant with the danger of severe eye injury.**Sensitisation:** No sensitising effects known.**Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant**General effects:**

Fumes generated during burning may cause "polymer fume fever" (flu-like symptoms such as fever, chill, cough).

This may last for a whole day and night.

Fumes are not absorbed in skin. No sensitizing effect known.

Effects of hydrogen fluoride:

Low concentration of hydrogen fluoride may cause feeling of dyspnea, cough, irritation in eyes, nose, throat, fever, chill for 1-2 days.

After that, dyspnea, cyanosis and pulmonary edema may be seen.

High concentration of hydrogen fluoride damages liver and kidney.

Effects of carbonyl fluoride:

Skin: Irritation or eruption

Eye: Ulcer in cornea, conjunctiva

Respiratory system : Irritation

Lung: Temporary symptoms such as cough, pain, dyspnea

Persons who have experienced lung diseases are vulnerable to toxicity caused by excessive exposure to pyrolysis products

Safety data sheet

Printing date 24.03.2015

Version number 1

Revision: 24.03.2015

Trade name: DAI-EL LATEX GLP-104QR**CMR effects**

Repr. 2

Germ cell mutagenicity: No further information available.**Carcinogenicity:** No further information available.**Reproductive toxicity:** No further information available.**Aspiration hazard:** No further information available.**Specific target organ toxicity - single exposure:** No further information available.**Specific target organ toxicity - repeated exposure:** No further information available.

SECTION 12: Ecological information

12.1 Toxicity**Aquatic toxicity:** No further relevant information available.**12.2 Persistence and degradability:** No further relevant information available.**12.3 Bioaccumulative potential:** No further relevant information available.**12.4 Mobility in soil:** No further relevant information available.**Ecotoxicological effects:** no data**12.5 Results of PBT and vPvB assessment****PBT:** No further relevant information available.**vPvB:** No further relevant information available.**12.6 Other adverse effects:** No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods**Recommendation:** Disposal must be made according to official regulations.**Uncleaned packaging****Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN-Number:**ADR, IMDG, IATA**

UN1263

14.2 UN proper shipping name:**ADR:**

1263 PAINT

IMDG, IATA

PAINT

14.3 Transport hazard class(es):**ADR, IMDG, IATA****Class:**

3 Flammable liquids.

Label:

3

14.4 Packing group:**ADR, IMDG, IATA**

II

14.5 Environmental hazards:**Marine pollutant:**

No

14.6 Special precautions for user:

Warning: Flammable liquids.

Danger code (Kemler):

33

EMS Number:

F-E, S-E

14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:

Not applicable.

Transport/Additional information:

Avoid direct sunlight. Make sure of no damage, corrosion, leaks on the receptacles.

Take necessary measures for preventing cargo shift.

Safety data sheet

Printing date 24.03.2015

Version number 1

Revision: 24.03.2015

Trade name: DAI-EL LATEX GLP-104QR**ADR****Limited quantities (LQ):**

5L

Excepted quantities (EQ)

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

Transport category:

2

Tunnel restriction code:

D/E

IMDG**Limited quantities (LQ)**

5L

Excepted quantities (EQ)

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

UN "Model Regulation":

UN1263, PAINT, 3, II

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

No further relevant information available.

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms

GHS02

GHS05

GHS07

GHS08

Signal word Danger**Hazard-determining components of labelling:**

n-Butanol

Toluene

Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H361d Suspected of damaging the unborn child.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

National regulations No further information available.**Other regulations, limitations and prohibitive regulations:** No further information available.

SECTION 16: Other information

The product is for the industrial use only. We do not guarantee the safety in case the product is used for the other purposes. When using the product for health-care application or food/feed application, consult us in advance.

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Safety data sheet

Printing date 24.03.2015

Version number 1

Revision: 24.03.2015

Trade name: DAI-EL LATEX GLP-104QR

Department issuing SDS: EHS Department

Contact: <http://www.daikin.com/>

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

Repr. 2: Reproductive toxicity, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

Asp. Tox. 1: Aspiration hazard, Hazard Category 1