

SAFETY DATA SHEET



1. Identification

Covestro LLC
1 Covestro Circle
Pittsburgh, PA 15205
USA

TRANSPORTATION EMERGENCY

CALL CHEMTREC: (800) 424-9300
INTERNATIONAL: (703) 527-3887

NON-TRANSPORTATION

Emergency Phone: Call Chemtrec
Information Phone: (844) 646-0545

Product Name: BAYBLEND T85 XF 900047 BBS910
Material Number: 86561689
Chemical Family: Thermoplastic Polymer
Use: Production of molded plastic articles

2. Hazards Identification

GHS Classification

This product is not hazardous in the form in which it is shipped by the manufacturer.

GHS Label Elements

Signal word: Warning

Hazard statements: If fine particles are generated during further processing, handling or by other means, product may form combustible dust concentrations in air.

3. Composition/Information on Ingredients

Hazardous Components

The following potentially hazardous ingredient(s) are used to formulate this product. As supplied, the ingredient(s) are bound in the polymer matrix. Because they are bound in the matrix, they are not expected to create any unusual hazards when handled and processed according to good manufacturing and industrial hygiene practices and the guidelines provided in this SDS.

Concentration	Components	CAS-No.
0.1 - 1%	Carbon Black	1333-86-4

The specific chemical identity and/or exact percentage of component(s) have been withheld as a trade

Material Name: BAYBLEND T85 XF 900047 BBS910

Material Number: 86561689

secret.

4. First Aid Measures

Most Important Symptom(s)/Effect(s)

Acute: Contact with heated material can cause thermal burns., Gases and fumes evolved during the thermal processing or decomposition of this material may irritate the eyes, skin or respiratory tract.

Eye Contact

In case of contact, flush eyes with plenty of lukewarm water.

Skin Contact

Cool melted product on skin with plenty of water. Do not remove solidified product. Get medical attention if thermal burn occurs.

Inhalation

Move to fresh air in case of accidental inhalation of dust or fumes from overheating or combustion.

Ingestion

Get medical attention.

5. Firefighting Measures

Suitable Extinguishing Media: Water fog, Dry chemical, Carbon dioxide (CO₂), Foam

Unsuitable Extinguishing Media: High Pressure Water Streams

Fire Fighting Procedure

Firefighters should be equipped with self-contained breathing apparatus to protect against potentially toxic and irritating fumes.

Hazardous Decomposition Products

By Fire and Thermal Decomposition: PhenolStyreneAcrylonitrile Carbon oxides, Hazardous decomposition products due to incomplete combustion

Unusual Fire/Explosion Hazards

Toxic and irritating gases/fumes may be given off during burning or thermal decomposition. Avoid generating dust: fine dust dispersed in air in sufficient concentrations and in the presence of an ignition source is a potential dust explosion hazard.

6. Accidental Release Measures

Spill and Leak Procedures

If molten, allow material to cool and place into an appropriate marked container for disposal. Sweep up and shovel into suitable containers for disposal. Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture as they are released into the atmosphere in sufficient concentrations. Avoid dispersal of dust in the air (e.g., cleaning dust from surfaces with compressed air).

7. Handling and Storage

Handling/Storage Precautions

Handle in accordance with good industrial hygiene and safety practices. Wash thoroughly after handling. Minimize dust generation and accumulation. Routine housekeeping should be instituted to ensure that dust does not accumulate on surfaces. Solid particulate can generate electrical charging during operations such as unloading from containers and pneumatic transfer. Provide adequate precautions, such as electrical grounding and bonding, where conductive equipment is involved.

Storage Period:

None.

Storage Temperature

Maximum: 49 °C (120.2 °F)

Storage Conditions

Containers should be tightly closed to prevent contamination with foreign materials and moisture.

Substances to Avoid

None known.

8. Exposure Controls/Personal Protection

The recommendations in this section should not be a substitute for a personal protective equipment (PPE) assessment performed by the employer as required by 29 CFR 1910 Subpart I.

Exposure Limits

Carbon Black (1333-86-4)

US. ACGIH Threshold Limit Values, as amended

Time weighted average 3 mg/m³ (Inhalable fraction.)

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended

Permissible exposure limit 3.5 mg/m³

US. ACGIH Threshold Limit Values, as amended

Hazard Designation: Group A3 Confirmed animal carcinogen with unknown relevance to humans.

Any component which is listed in section 3 and is not listed in this section does not have a known ACGIH TLV, OSHA PEL or supplier recommended occupational exposure limit.

Industrial Hygiene/Ventilation Measures

General dilution and local exhaust as necessary to control airborne vapors, mists, dusts and thermal decomposition products below appropriate airborne concentration standards/guidelines, especially during cutting, grinding and high heat operations.

Respiratory Protection

Although no exposure limit has been established for this product, the OSHA PEL for Particulates Not Otherwise Regulated (PNOR) of 15 mg/m³ - total dust, 5 mg/m³ - respirable fraction is recommended. In addition, the ACGIH recommends 3 mg/m³ - respirable particles and 10 mg/m³ - inhalable particles for Particles (insoluble or poorly soluble) Not Otherwise Specified (PNOS). In the event that these limits are exceeded, an air purifying respirator (APR) equipped with particulate (P100) cartridges is recommended.

Hand Protection

Ensure gloves remain in good condition during use and replace if any deterioration is observed.
Wear heat resistant gloves when handling molten material.

Eye Protection

Safety glasses with side-shields

Skin Protection

No special skin protection requirements during normal handling and use.

Additional Protective Measures

Employees should wash their hands and face before eating, drinking, or using tobacco products. Educate and train employees in the safe use and handling of this product. Purgings should be collected as small flat thin shapes or thin strands to allow for rapid cooling.

9. Physical and Chemical Properties

Physical state:	solid
Appearance:	pellets
Color:	Black
Odor:	Odorless
Odor Threshold:	No Data Available
pH:	not applicable
Melting Point:	220 °C (428 °F)
Boiling Point:	No Data Available
Flash Point:	Not applicable.
Evaporation Rate:	No Data Available
Flammability:	No Data Available
Lower Explosion Limit:	not applicable
Upper Explosion Limit:	not applicable
Vapor Pressure:	No Data Available
Vapor Density:	No Data Available
Density:	ca. 1.1 - 1.2 g/cm ³ (DIN 53479)
Relative Vapor Density:	No Data Available
Specific Gravity:	No Data Available
Solubility in Water:	practically insoluble
Partition Coefficient: n-octanol/water:	No Data Available
Auto-ignition Temperature:	> 390 °C (> 734 °F)
Decomposition Temperature:	>= 380 °C (716 °F)
Unblocking Temperature:	No Data Available
Softening point:	100 - 200 °C (212 - 392 °F)
Dynamic Viscosity:	not applicable
Kinematic Viscosity:	No Data Available
Bulk Density:	600 - 700 kg/m ³
Molecular Weight:	No Data Available
Particle characteristics:	No Data Available

10. Stability and Reactivity**Hazardous Reactions**

Material Name: BAYBLEND T85 XF 900047 BBS910

Material Number: 86561689

Hazardous polymerisation does not occur.

Stability

Stable

Materials to Avoid

None known.

Conditions to Avoid

Generation of dust clouds.

Hazardous Decomposition Products

By Fire and Thermal Decomposition: Phenol; Styrene; Acrylonitrile; Carbon oxides, Hazardous decomposition products due to incomplete combustion

11. Toxicological Information

Likely Routes of Exposure:

Inhalation
Skin Contact
Eye Contact

Health Effects and Symptoms

Acute: Contact with heated material can cause thermal burns., Gases and fumes evolved during the thermal processing or decomposition of this material may irritate the eyes, skin or respiratory tract.

Toxicity Data for: BAYBLEND T85 XF 900047 BBS910

No data available for this product.

Toxicity Data for: Carbon Black

Acute Oral Toxicity

LD50: > 8,000 mg/kg (rat, male/female) (OECD Test Guideline 401)

Acute Dermal Toxicity

LD50: > 3,000 mg/kg (rabbit)

Skin Irritation

rabbit, Non-irritating

Eye Irritation

Human, non-irritant

Sensitization

Buehler Test: negative (Guinea pig, OECD Test Guideline 406)

Skin sensitization (local lymph node assay (LLNA)):: negative (Mouse, OECD Test Guideline 429)

Repeated Dose Toxicity

13 weeks, Inhalative: NOAEL: 0.0011 mg/kg, (rat,)

Mutagenicity

Genetic Toxicity in Vitro:

Salmonella/microsome test (Ames test): negative

Material Name: BAYBLEND T85 XF 900047 BBS910

Material Number: 86561689

Mammalian cell - gene mutation assay: positive (other mammalian cell line, Metabolic Activation: without)
Micronucleus test: positive (other human cell line, Metabolic Activation: without)

Genetic Toxicity in Vivo:

Other assay: negative (Mouse, male, intraperitoneal)

negative

Carcinogenicity

Several inhalation studies involving carbon black in female rats have shown increases in benign and malignant lung tumors. Although a large body of data on possible mechanisms of carcinogenicity in rats was considered by the IARC Working Group, it was not possible to state with confidence that the mechanisms of carcinogenicity in rats correlate to exposure in humans. Tumors have not been observed in other animal species (i.e., mouse and hamster) under similar circumstances and study conditions.

Developmental Toxicity/Teratogenicity

rat, female, Inhalative, 10 days, daily,

Other Relevant Toxicity Information

May cause irritation of respiratory tract.

Carcinogenicity:

Carbon Black

IARC - Overall evaluation: 2B Possibly carcinogenic to humans.

12. Ecological Information

Ecological Data for: BAYBLEND T85 XF 900047 BBS910

No data available for this product.

Ecological Data for Carbon Black

Acute and Prolonged Toxicity to Fish

LC0: > 1,000 mg/l (Danio rerio (zebra fish), 96 h)

Acute Toxicity to Aquatic Invertebrates

EC50: > 5,600 mg/l (Water flea (Daphnia magna), 24 h)

Toxicity to Microorganisms

EC0: 100 - 800 mg/l, (Activated sludge microorganisms, 3 h)

13. Disposal Considerations

Waste Disposal Method

Waste disposal should be in accordance with existing federal, state and local environmental control laws.

14. Transportation Information

Land transport (DOT)

Non-Regulated

Sea transport (IMDG)

Non-Regulated

Material Name: BAYBLEND T85 XF 900047 BBS910

Material Number: 86561689

Air transport (ICAO/IATA)
Non-Regulated

15. Regulatory Information

United States Federal Regulations

US. Toxic Substances Control Act: Listed on the Active Portion of the TSCA Inventory.

SNUR Components

No substances are subject to Section 5 Significant New Use Rule (SNUR) requirements.

Section 6 Risk Management Components:

No substances are subject to Section 6 Risk Management rule requirement.

Section 12b Components:

No substances are subject to TSCA 12(b) export notification requirements.

Section 4 Test Order/Rule Components:

No substances are subject to Section 4 Final Test Orders or Rules.

Consent Order:

No substances are subject to Section 5 Consent Order requirements.

US. EPA CERCLA Hazardous Substances (40 CFR 302.4) Components:

None

SARA Section 311/312 Hazard Categories:

Refer to hazard classification information in Section 2.

**US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III
Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A) Components:**

None

**US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III
Section 313 Toxic Chemicals (40 CFR 372.65) - Supplier Notification Required Components:**

None

**US. EPA Resource Conservation and Recovery Act (RCRA) Composite List of Hazardous Wastes
and Appendix VIII Hazardous Constituents (40 CFR 261):**

Under RCRA, it is the responsibility of the person who generates a solid waste, as defined in 40 CFR 261.2, to determine if that waste is a hazardous waste.

State Right-To-Know Information

The following chemicals are specifically listed by individual states; other product specific health and safety data in other sections of the SDS may also be applicable for state requirements. For details on your regulatory requirements you should contact the appropriate agency in your state.

The concentrations reported below in units of parts per million (ppm) or parts per billion (ppb) are maximum values.

Massachusetts, New Jersey or Pennsylvania Right to Know Substance Lists:

Concentration

Components

CAS-No.

Material Name: BAYBLEND T85 XF 900047 BBS910

Material Number: 86561689

>=1%	Bisphenol A Polycarbonate	CAS# is a trade secret
>=1%	Polymer	CAS# is a trade secret
>=1%	Polymer	CAS# is a trade secret
>=1%	Polymer	CAS# is a trade secret
>=1%	Bisphenol A Polycarbonate	CAS# is a trade secret
0.1 - 1%	Carbon Black	1333-86-4

New Jersey Environmental Hazardous Substances List and/or New Jersey RTK Special Hazardous Substances Lists:

<u>Concentration</u>	<u>Components</u>	<u>CAS-No.</u>
>=1%	Polymer	CAS# is a trade secret
0.1 - 1%	Carbon Black	1333-86-4
0.1 - 1%	C.I. Pigment Brown 24	68186-90-3

Massachusetts Right to Know Extraordinarily Hazardous Substance List:

<u>Concentration</u>	<u>Components</u>	<u>CAS-No.</u>
<0.1%	Styrene	100-42-5
<=100 ppm	Acrylonitrile	107-13-1
<=3 ppm	Methylene Chloride	75-09-2
<100 ppm	1,3-Butadiene	106-99-0

California Proposition 65 List:

<u>Concentration</u>	<u>Components</u>	<u>CAS-No.</u>
<0.1%	Styrene	100-42-5
<=100 ppm	Acrylonitrile	107-13-1
<1 ppt	Cobalt and cobalt compounds	7440-48-4
<=3 ppm	Methylene Chloride	75-09-2
Trace element	Bisphenol A	80-05-7
<100 ppm	1,3-Butadiene	106-99-0
<100 ppm	4-Vinylcyclohexene (4-VCH)	100-40-3
<1 ppm	Arsenic	7440-38-2
<1 ppm	Nickel (Ni)	7440-02-0
<100 ppm	Ethyl Benzene	100-41-4
<100 ppm	Cumene	98-82-8

CFATS (Chemical Facility Anti-Terrorism Standards) Chemicals

This product contains the following Appendix A Chemicals of Interest (COI), at or above the Screening Threshold Quantity (STQ), as defined by the Department of Homeland Security (DHS) Chemical Facility Anti-terrorism Standard (CFATS, 6 CFR Part 27)

Components	# CAS	%
Aluminum	7429-90-5	5.8

Based on information provided by our suppliers, this product is considered "DRC Conflict Free" as defined by the SEC Conflict Minerals Final Rule (Release No. 34-67716; File No. S7-40-10; Date: 2012-08-22).

16. Other Information

Contact: Product Safety Department
Telephone: (412) 413-2835
Version Date: 10/31/2025
SDS Version: 1.3

Material Name: BAYBLEND T85 XF 900047 BBS910

Material Number: 86561689

Information contained in this Safety Data Sheet (SDS) is believed to be accurate but is furnished without warranty, express or implied, including warranties of merchantability or fitness for a particular purpose. The information relates only to the specific material designated herein. Covestro LLC assumes no legal responsibility for use of or reliance upon the information in this SDS and such information shall in no case be considered a part of our terms and conditions of sale. The user is responsible for determining whether the Covestro product is suitable for user's method of use or application. Covestro is not liable for any failure to observe the precautionary measures described in this SDS or for any misuse of the product.