



SAFETY DATA SHEET

DATE ISSUED: 2004.11.03

DATE REVISED: 2019.05.01

REV. No.: 008

1. COMPANY IDENTIFICATION

PRODUCT NAME : 1000、1000T、1000D、1003、1250、3000、3000D、3100、3100M、
 3000P、5000、5000S、5002、6000、6000P、5000W、5000M、5000F、
 3100R

SUPPLIER : TAITA CHEMICAL CO. LTD., / KAOHSIUNG BRANCH

COMPANY ADDRESS: No.5, Industrial 1st Rd., Lin-Yuan, Kaohsiung, Taiwan

TELEPHONE: 886-7-7040988 EXT 1355

FACSIMILE: 886-7-6414544 EXT 1355

2. HAZARD IDENTIFICATION :

GHS classification:

This product is not hazardous under United Nations GHS Parts 2,3 and 4.

Most Important Hazards	None
Adverse Human Health Effects	None
Environmental Effects	None
Physical and Chemical Hazards	None

3. COMPOSITION / INFORMATION ON INGREDIENTS

PRODUCT DESCRIPTION : Acrylonitrile-Butadiene-Styrene copolymer

PRODUCT IDENTIFIER : TAITALAC ABS

Content : 100%

Formula : (C₃H₃N)_x - (C₄H₆)_y - (C₈H₈)_z

CAS No. : 9003-56-9

4. FIRST AID MEASURES

Eye Contact : In case of pellets or powder, flush with plenty of water for at least 15 minutes.

Seek medical advice if any dust particles still remain. In case of gases evolving from melted resin of high temperature, flush with plenty of water for at least 15 minutes.

Seek medical advice if necessary.

Skin Contact : Wash skin thoroughly with soap and water. Seek medical attention if rash or burn



Ingestion : Induce vomiting. Rinse mouth with water. Seek medical advice if necessary.

Inhalation : In case of gases evolving from melted resin, move subject to fresh air. Treat symptomatically.

5. FIRE FIGHTING MEASURES

Extinguishing Measures : At the time of fire, high heat as well as gases containing dense black smoke, carbon dioxide, carbon monoxide, nitrogen oxides, etc. are generated. At the time of fire-fighting, wear proper protective clothing and respirators.

Extinguishing Media : Water, water spray, and various kinds of fire-extinguishers may be used.

Special Fire-Fighting Procedure : Self contained breathing apparatus.

Fire and Explosion Hazards : None

6. ACCIDENTAL RELEASE MEASURES

Environmental Precautions : In case it is spilled on the road or floor, there is danger of slipping and falling. Thus, collect the spilled pellets and dispose of them. If it is accidentally released, it may cause environmental contamination, so immediately collect all that have been released.

Methods for Cleaning up : Recovery if not contaminated or Disposal

7. HANDLING AND STORAGE

Handling : Gases and fumes in the drying and molding process may cause irritation to the skin and respiratory tract. Prevent contact with skin and eyes. Use industrial hygiene practices. Provide adequate ventilation. Secondary operation such as grinding, sanding or sawing may produce a dust explosion hazard. Use aggressive housekeeping activities to prevent dust accumulation; employ bonding, grounding, venting and explosion relief provisions in accordance with accepted engineering practices.

Storage : Store in a dry place away from moisture, excessive heat and sources of ignition. Avoid direct sunlight. To avoid risk of collapse, do not stack unsupported boxes too high.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Threshold Limit Value : Not determined

Ventilation : Necessary to exclude dust, fumes and gases.



PERSONAL PROTECTION :

Eye : Wear safety glasses for general purpose. Wear chemical goggles for cleaning molding machines.

Skin : When handling pellets avoid prolonged or repeated contact with skin , there is no special need of gloves, But when handing molten resins, wear gloves having good Thermal insulation. Ordinary work clothing will do , but in case of handling molten resins, wear work clothing having long sleeves.

Respiratory : Wear masks for cleaning molding machines.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Milky off-white Solids
Melting Point	: Softening above 100 °C
Vapor Pressure (mmHg)	: None
Specific Gravity	: 1.03-1.08
Solubility	: Insoluble in water
Volatility	: None

10. STABILITY AND REACTIVITY

Flashing Point	:400°C
Auto Ignition Point	: 466°C.
Upper Explosion Limit	: None
Lower Explosion Limit	: None
Stability	: Stable under recommended conditions of storage and handling
Reactivity with Water	: No :Yes
Flammability	: Explosive
Dust Explosiveness	: CO, HCN, AN, SM and NO
Thermal Decomposition Gases	

11. TOXICOLOGICAL INFORMATION

Irritation : Fumes or vapors generated from decomposing resin may be irritant to eyes.

Acute Toxicity (Includes 50% Lethal Dose) : Oral LD₅₀ (Rat) > 5g/kg (Assumed Value)

Sub-Acute Toxicity : No Information

Mutagenicity : Not determined.



12. ECOLOGICAL INFORMATION

To avoid being taken by ocean species or birds, disposal of the waste to the ocean and water sources is inhibited.

13. DISPOSAL INFORMATION

It shall be handled in accordance with the laws, rules, and ordinances related to the disposal of waste matters.

14. TRANSPORTATION INFORMATION :

Not classified.

15. REGULATORY INFORMATION :

Not available.

16. OTHER INFORMATION :

Pre-Registration Number of REACH:

EC Number	Tonnage Band	Submission Number	Pre-registration Number	Deadline
202-851-5	100~1000	LV488022-13	05-2117246118-46-0000	5/31/2013
203-466-5	10~100	ZZ488326-77	05-2117247483-42-0000	11/30/2010
203-450-8	10~100	YB488397-17	05-2117247976-27-0000	11/30/2010
203-755-6	1~10	HW488480-05	05-2117248420-53-0000	5/31/2018

Taita Chemical Company, Limited / Kaohsiung Branch



No.5, Industrial 1st Rd., Lin-Yuan, Kaohsiung, Taiwan

TEL : 886-7-641-3201

FAX : 886-7-641-4544

MSDS-ABS

Ver. : 7.0

TAITALAC

ABS Resin