



TORAY INDUSTRIES INC
NIHONBASHI-MITSUI TOWER
1-1 NIHONBASHI-MUROMACHI 2-CHOME
CHUO-KU, TOKYO 103-8666 Japan



Toyolac: 950-X02 1A003

Acrylic/Acrylonitrile Butadiene Styrene (Acrylic/ABS), pellets

NOTE - Polyamide (nylon) grades may be prefixed with the letters CM and may employ hyphens in various locations. The designations of ECODEAR products may employ hyphens and/or spaces in various locations. All grades that include ABS, SAN, and/or PC (designations of TOYOLAC or TOYOLACPAREL or TORAYCA products) may employ hyphens and/or spaces and may be suffixed with 3 or 4 digits of letters and/or numbers.

可燃性	值	测试方法
UL 阻燃等级		
1.5 mm, ALL	HB	UL 94
3.0 mm, ALL	HB	UL 94
3.0 mm, ALL	HB40	IEC 60695-11-10, -20
1.5 mm, ALL	HB75	IEC 60695-11-10, -20
电气性能	值	测试方法
相比耐漏电起痕指数(CTI)	PLC 0	UL 746
介电强度	48 kV/mm	ASTM D149
体积电阻率	1.0E+16 ohms-cm	ASTM D257 IEC 60093
热性能	值	测试方法
RTI Elec		UL 746
1.5 mm	60.0 °C	
3.0 mm	60.0 °C	
RTI Imp		UL 746
1.5 mm	60.0 °C	
3.0 mm	60.0 °C	
RTI		UL 746
1.5 mm	60.0 °C	
3.0 mm	60.0 °C	

