



组件 - 塑料
UL 档案号: E135809

SK GLOBAL CHEMICAL CO LTD
110 KOSA-DONG NAM-GU
ULSAN, 680-130 Korea, Republic of



BX3500

Polypropylene (PP), pellets

| 可燃性 | 值 | 测试方法 |
|--------------|--------|----------------------|
| UL 阻燃等级 | | |
| 1.5 mm, ALL | HB | UL 94 |
| 3.0 mm, ALL | HB | UL 94 |
| 3.0 mm, ALL | HB40 | IEC 60695-11-10, -20 |
| 1.5 mm, ALL | HB75 | IEC 60695-11-10, -20 |
| 电气性能 | 值 | 测试方法 |
| 热丝引燃 (HWI) | | UL 746 |
| 1.5 mm | PLC 4 | |
| 3.0 mm | PLC 2 | |
| 高电弧燃烧指数(HAI) | | UL 746 |
| 1.5 mm | PLC 0 | |
| 3.0 mm | PLC 0 | |
| 热性能 | 值 | 测试方法 |
| RTI Elec | | UL 746 |
| 1.5 mm | 125 °C | |
| 3.0 mm | 125 °C | |
| RTI Imp | | UL 746 |
| 1.5 mm | 125 °C | |
| 3.0 mm | 125 °C | |
| RTI | | UL 746 |
| 1.5 mm | 125 °C | |
| 3.0 mm | 125 °C | |

