

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Trade name: Terluran® ABS Granulate, Color  
This safety data sheet pertains to the following products:  
Terluran® GP-35 White

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

General use: Polymer  
For industrial processing only

### 1.3 Details of the supplier of the safety data sheet

Company name: INEOS Styrolution Group GmbH  
Street/POB-No.: Mainzer Landstraße 50  
Postal Code, city: 60325 Frankfurt  
Germany  
WWW: www.styrolution.com  
Dept. responsible for information:  
Infopoint, Telephone: +49 (0) 2133 - 51- 4007  
E-mail: infopoint.emea@styrolution.com

### 1.4 Emergency telephone number

Telephone: +44 (0) 1235 239 670

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

#### Classification according to EC regulation 1272/2008 (CLP)

This mixture is classified as not hazardous.

### 2.2 Label elements

#### Labelling (CLP)

Hazard statements: not applicable

Precautionary statements: not applicable

### 2.3 Other hazards

Dust: Can cause skin, eye and respiratory tract irritation.  
In case of dust formation (Fine dust): May form explosible dust-air mixture if dispersed.  
The melted product can cause severe burns.  
Swallowing may cause gastrointestinal irritation and pain of guts.

Results of PBT and vPvB assessment:

This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

## SECTION 3: Composition / information on ingredients

3.1 Substances: not applicable

### 3.2 Mixtures

Chemical characterisation: Polymer mixture:

CAS No. 9003-56-9: Styrene-acrylonitrile-butadiene copolymer

CAS No. 13463-67-7: Titanium dioxide

Additional information: Preparation does not contain dangerous substances above limits that need to be mentioned in this section according to applicable legislation.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

General information: Immediately remove any contaminated clothing, shoes or stockings.

In case of inhalation: Provide fresh air. Put victim at rest and keep warm. Seek medical attention

Following skin contact: The melted product can cause severe burns.  
Do not attempt to remove molten product, or molten product that has cooled, from skin without medical assistance.  
After contact with molten product, cool skin area rapidly with cold water. Consult physician.

After eye contact: Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing.  
Consult an eye specialist in the event of irritation.

After swallowing: Rinse mouth with water. Drink one or two glasses of water.  
Never give an unconscious person anything through the mouth. Seek medical attention

### 4.2 Most important symptoms and effects, both acute and delayed

Dust: Skin irritation, eye irritations and redness

### 4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.  
Decontamination, vital functions

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media:

Water fog, foam, extinguishing powder, carbon dioxide.

Extinguishing media which must not be used for safety reasons:

High power water jet

### 5.2 Special hazards arising from the substance or mixture

In case of fire may be liberated: Hydrogen cyanide, carbon monoxide and carbon dioxide (CO<sub>2</sub>).

In case of dust formation (Fine dust): May form explosible dust-air mixture if dispersed.

### 5.3 Advice for firefighters

Special protective equipment for firefighters:

Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information: Hazchem-Code: -  
Do not allow fire water to penetrate into surface or ground water. Fire residuals and contaminated extinguishing water must be disposed of in accordance with the regulations of the local authorities.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation.  
Wear personal protection equipment. Do not breathe dust.

### 6.2 Environmental precautions

Do not allow to penetrate into soil, waterbodies or drains.

### 6.3 Methods and material for containment and cleaning up

Avoid generation of dust. Remove all sources of ignition.  
Take up mechanically. Collect in closed containers for disposal.

Additional information: Special danger of slipping by leaking/spilling product.

### 6.4 Reference to other sections

Refer additionally to section 8 and 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advices on safe handling: Provide adequate ventilation, and local exhaust as needed. Do not breathe dust.  
In the case of the formation of dust: Withdraw by suction.  
Molten material: Avoid contact with the substance.

Precautions against fire and explosion:

Take precautionary measures against static discharges. Keep away from sources of ignition. Use grounding equipment. Use explosion-proof equipment and non-sparking tools/utensils. Avoid open flames.  
In case of dust formation (Fine dust): May form explosible dust-air mixture if dispersed.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storerooms and containers:

Store in a well-ventilated place. Keep container tightly closed.  
Protect against heat /sun rays. Protect from moisture contamination.

### 7.3 Specific end use(s)

No information available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Occupational exposure limit values:

CAS No.	Designation	Type	Limit value
	Terluran® ABS Granulate, Color	Great Britain: WEL-TWA	10 mg/m <sup>3</sup>
		Great Britain: WEL-TWA	4 mg/m <sup>3</sup>
		Ireland: 8 hours	10 mg/m <sup>3</sup>
	Styrene	Ireland: 8 hours	4 mg/m <sup>3</sup>
100-42-5		Great Britain: WEL-STEL	1080 mg/m <sup>3</sup> ; 250 ppm
		Great Britain: WEL-TWA	430 mg/m <sup>3</sup> ; 100 ppm
	Ireland: 15 minutes	170 mg/m <sup>3</sup> ; 40 ppm	
	Acrylonitrile	Ireland: 8 hours	85 mg/m <sup>3</sup> ; 20 ppm
107-13-1		Great Britain: WEL-TWA	4.4 mg/m <sup>3</sup> ; 2 ppm
		Ireland: 8 hours	4.5 mg/m <sup>3</sup> ; 2 ppm
	106-99-0	Great Britain: WEL-TWA	22 mg/m <sup>3</sup> ; 10 ppm
Ireland: 8 hours		2.2 mg/m <sup>3</sup> ; 1 ppm	
13463-67-7		Titanium dioxide	Great Britain: WEL-TWA
	Great Britain: WEL-TWA		4 mg/m <sup>3</sup>
	Ireland: 8 hours		10 mg/m <sup>3</sup>
	Ireland: 8 hours		4 mg/m <sup>3</sup>

Additional information: The product contains very low levels of residual monomers and process chemicals (styrene, ethylbenzene, acrylonitrile and butadiene) that may be evolved during thermal processing, along with possible decomposition products. As the identity and levels of these impurities evolved will depend upon the processing conditions (temperature etc.) it is the responsibility of the user to determine the adequacy of any protection or safety measures.

### 8.2 Exposure controls

Provide good ventilation and/or an exhaust system in the work area.

### Personal protection equipment

#### Occupational exposure controls

Respiratory protection: Respiratory protection must be worn whenever the WEL levels have been exceeded. Use filter type A-P2 according to EN 14387.

Hand protection: Protective gloves according to EN 374.  
Protective gloves made of fabric or leather.  
Observe glove manufacturer's instructions concerning penetrability and breakthrough time.  
In case of melting: Impervious heat protective gloves according to EN 407.  
Glove material: Leather  
Observe glove manufacturer's instructions concerning penetrability and breakthrough time.

Eye protection: Tightly sealed goggles according to EN 166.

Body protection: Wear suitable protective clothing. Boots or Wear protective shoes.

General protection and hygiene measures:

Molten material: Avoid contact with skin.  
Avoid breathing dust and vapours. Keep away from sources of ignition.  
Wash hands before breaks and after work.

In case of dust formation: Particular danger of slipping on spilled product on the ground.

Protective gloves made of fabric or leather

**Environmental exposure controls**

Do not allow to penetrate into soil, waterbodies or drains.

**SECTION 9: Physical and chemical properties**

**9.1 Information on basic physical and chemical properties**

Appearance:	Form: granulate (solid) Colour: varying, depends on colouring
Odour:	weak, characteristic
Odour threshold:	No data available
pH value:	No data available
Melting point/freezing point:	> 100 °C (DIN EN ISO 306)
Initial boiling point and boiling range:	No data available
Flash point/flash point range:	No data available
Evaporation rate:	No data available
Flammability:	Not highly flammable.
Explosion limits:	No data available
Vapour pressure:	No data available
Vapour density:	No data available
Density:	at 20 °C: approx. 1.04 g/cm <sup>3</sup> (DIN 53479)
Water solubility:	insoluble
Partition coefficient: n-octanol/water:	No data available
Auto-ignition temperature:	not self-igniting
Decomposition temperature:	approx. 300 °C To avoid thermal decomposition, do not overheat.
Viscosity, kinematic:	No data available
Explosive properties:	In case of dust formation (Fine dust): May form explosible dust-air mixture if dispersed.
Oxidizing characteristics:	Not oxidising

**9.2 Other information**

Bulk density: at 20 °C: approx. 600 kg/m<sup>3</sup> (DIN 53466)

**SECTION 10: Stability and reactivity**

**10.1 Reactivity**

refer to 10.3

## 10.2 Chemical stability

Stable under recommended storage conditions.

## 10.3 Possibility of hazardous reactions

In case of dust formation (Fine dust): May form explosible dust-air mixture if dispersed.

## 10.4 Conditions to avoid

Protect from excessive heat. Keep away from sources of ignition and heat.  
Avoid dust formation.

## 10.5 Incompatible materials

Strong oxidizing agents

## 10.6 Hazardous decomposition products

When greatly overheated, material may release hazardous decomposition products:  
Hydrogen cyanide, monomers, hydrocarbons, gases/vapours, cyclic low molecular weight oligomers, carbon monoxide and carbon dioxide.

Thermal decomposition: approx. 300 °C

To avoid thermal decomposition, do not overheat.

# SECTION 11: Toxicological information

## 11.1 Information on toxicological effects

Toxicological effects: The statements are derived from the properties of the single components. No toxicological data is available for the product as such.

Acute toxicity (oral): Lack of data.

Acute toxicity (dermal): Lack of data.

Acute toxicity (inhalative): Lack of data.

Skin corrosion/irritation: Lack of data. May cause irritations.

Eye damage/irritation: Lack of data. May cause irritations.

Sensitisation to the respiratory tract: Lack of data. Not to be expected

Skin sensitisation: Lack of data. Not to be expected

Germ cell mutagenicity/Genotoxicity: Lack of data. Not to be expected

Carcinogenicity: Lack of data. Not to be expected

Reproductive toxicity: Lack of data. Not to be expected

Effects on or via lactation: Lack of data.

Specific target organ toxicity (single exposure): Lack of data.

Dusts: Irritating to eyes, respiratory system and skin.

Specific target organ toxicity (repeated exposure): Lack of data.

Aspiration hazard: Lack of data.

Other information: When handled appropriately, even after long years of experience with this product, no adverse health effects are known.

**Symptoms**

Dust: Can cause skin, eye and respiratory tract irritation.  
The melted product can cause severe burns.  
Thermal treatment, Processing: Irritating to eyes, respiratory system and skin.  
In case of ingestion: Swallowing may cause gastrointestinal irritation and pain of guts.

**SECTION 12: Ecological information**

**12.1 Toxicity**

Aquatic toxicity: no evidence of aquatic toxicity

**12.2. Persistence and degradability**

Further details: Biodegradation: Product is not readily biodegradable.  
The product is likely to persist in the environment.

Effects in sewage plants: In sewage treatment plants it may be separated mechanically.

**12.3 Bioaccumulative potential**

To avoid bioaccumulation plastics should not be disposed in the sea or in other water environments.

Partition coefficient: n-octanol/water:  
No data available

**12.4 Mobility in soil**

No data available

**12.5 Results of PBT and vPvB assessment**

This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

**12.6 Other adverse effects**

General information: Do not allow to enter into ground-water, surface water or drains.

**SECTION 13: Disposal considerations**

**13.1 Waste treatment methods**

**Product**

Waste key number: 07 02 99 = wastes from the MFSU of plastics, synthetic rubber and man-made fibres  
MFSU = manufacture, formulation, supply and use

Recommendation: With due observance of the regulations laid down by the local authorities, this must be brought to a suitable incineration plant/waste disposal site.

**Contaminated packaging**

Recommendation: Dispose of waste according to applicable legislation.  
Non-contaminated packages may be recycled.

## SECTION 14: Transport information

### 14.1 UN number

ADR/RID, IMDG, IATA-DGR:

not applicable

### 14.2 UN proper shipping name

ADR/RID, IMDG, IATA-DGR:

Not restricted

### 14.3 Transport hazard class(es)

ADR/RID, IMDG, IATA-DGR:

not applicable

### 14.4 Packing group

ADR/RID, IMDG, IATA-DGR:

not applicable

### 14.5 Environmental hazards

Marine pollutant:

no

### 14.6 Special precautions for user

No dangerous good in sense of these transport regulations.

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

No data available

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### National regulations - Great Britain

Hazchem-Code:

-

No data available

### 15.2 Chemical Safety Assessment

For this substance a chemical safety assessment is not required.

## SECTION 16: Other information

### Further information

Reason of change: Changes in section 1: Changes of product list NAFTA  
Changes in section 9: General revision  
Changes in section 3: Change of composition

Date of first version: 28/2/2013

### Department issuing data sheet

Contact person: see section 1: Dept. responsible for information



## SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)  
and Regulation (EU) No 2015/830

Revision date: 21/9/2016

Version: 12

Language: en-GB,IE

Date of print: 15/11/2016

### Terluran® ABS Granulate, Color

Material number TER005

Page: 9 of 9

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.