



PREWHITE PE 13-60

0611

PREWHITE PE 13-60 is a PE-LD based white masterbatch, developed especially for medical packages made by injection or blow moulding of PE-LD, PE-LLD or PE-HD.

Due to the good dispersion PREWHITE PE 13-60 is well suited for very thin products.

According to FDA and BgVV regulations PREWHITE PE 13-60 is approved for use in contact with foodstuffs without limitations and also fulfils the requirements mentioned in U.S.P. XXII pages 1497-1500, 1572-1573. PREWHITE PE 13-60 carries the DMF number of 10333, Type III of FDA.

Appearance	Granule
Carrier	PE-LD
Pigmentation	TiO ₂ (rutile), 60 %
Density	1.7 g/cm ³
Light fastness	8, very good
Temperature stability	< 260 °C
Dosing	0.5 - 30 % depending on desired opacity
Moisture content	Max. 0.15% when produced
Packaging	1250 kg in 25 kg PE valve bags on a one-way stretch wrapped pallet, or 1250 kg in octabins
Storage	Can be stored for one year in its original package. Packages should be stored indoors.

The information in this data sheet represents typical values obtained by us and should not be regarded as a specification.

We condition that the product will be inspected and qualified by the customer for his process to meet the specific requirements set by application, processing equipment and end product.