

Technical Data Sheet

Hostacom DYS707N NATRL

Polypropylene Compounds

Product Description

Hostacom DYS707N NATRL high melt flow, 1000 MPa flexural modulus, high impact, natural thermoplastic elastomeric olefin (TEO) resin has an excellent combination of stiffness, impact resistance and processability. It is typically used for automotive interior trim applications that demand balanced performance characteristics.

Regulatory Status

For regulatory compliance information, see Hostacom DYS707N NATRL [Product Stewardship Bulletin \(PSB\) and Safety Data Sheet \(SDS\)](#).

Status	Commercial: Active
Availability	North America
Application	Interior Automotive Applications
Market	Automotive
Processing Method	Injection Molding
Attribute	Good Colorability; Good Moldability; High Flow; High Impact Resistance; Low Temperature Toughness; Medium Rigidity

Typical Properties	Nominal Value	Units	Test Method
Physical			
Melt Flow Rate, (230 °C/2.16 kg)	23	g/10 min	ISO 1133-1
Density, (23 °C)	0.90	g/cm ³	ISO 1183-1
Mechanical			
Flexural Modulus	1000	MPa	ISO 178
Tensile Stress at Yield	17	MPa	ISO 527-1, -2
Impact			
Charpy Impact Strength - Notched, (23 °C)	60	kJ/m ²	ISO 179
Additional Information			
Mold Shrinkage			ISO 294-4
Please contact LyondellBasell for shrinkage recommendations.			

Notes

These are typical property values not to be construed as specification limits.