



Moplen HP528N

Polypropylene, Homopolymer

Product Description

Moplen HP528N is a polypropylene homopolymer. With its high clarity, high slip and anti-blocking properties, it is especially suitable for water-quenched tubular film (IPP). Potential end use applications include packaging for hosiery, shirts, other textiles and food.

Product Characteristics

Status	Commercial: Active
Test Method used	ASTM
Availability	Asia-Pacific, Australia/NZ, Africa-Middle East
Processing Methods	Blown Film, Injection Molding
Features	Unspecified Antiblocking , High Clarity, Homopolymer, Good Processability, High Slip, Good Stiffness
Typical Customer Applications	Food Packaging Film, Textile Packaging Film

Typical Properties	Method	Value	Unit
Physical			
Density -Specific Gravity	ASTM D 792	0.90	g/cm ³
Melt Flow Rate (230°C/2.16kg)	ASTM D 1238	11	g/10 min
Mechanical			
Flexural Modulus	ASTM D 790	1500	MPa
Tensile Strength @ Yield	ASTM D 638	34	MPa
Tensile Elongation @ Yield	ASTM D 638	10	%
Impact			
Notched Izod Impact (23 °C)	ASTM D 256	23	J/m
Thermal			
DTUL @66psi - Unannealed	ASTM D 648	97	°C

Notes

Typical properties; not to be construed as specifications