

# 2041 MICROMAX™ RESISTOR PASTE

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04-12-2024

 8.1
 06-18-2025
 300000000135
 Date of first issue: 01-29-2024

#### **SECTION 1. IDENTIFICATION**

Product name : 2041 MICROMAX™ RESISTOR PASTE

Product code : 00000000027046095

Manufacturer or supplier's details

Company name of supplier : Celanese Ltd. Irving Texas

Address : 222 West Las Colinas Boulevard Suite 900N

Irving TX 75039

Telephone : '+1 972-443-4000

Emergency telephone num: DOMESTIC NORTH AMERICA: 800-424-9300

per INTERNATIONAL, CALL +1 703-527-3887 (collect calls ac-

cepted)

Recommended use of the chemical and restrictions on use

Recommended use : For industrial use only.

Paste for electronic industry

#### **SECTION 2. HAZARDS IDENTIFICATION**

# GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin irritation : Category 2

Eye irritation : Category 2A

Germ cell mutagenicity : Category 2

Carcinogenicity : Category 1A

Reproductive toxicity : Category 1A

Specific target organ toxicity

- repeated exposure (Oral)

Category 1 (Blood)

#### Other hazards

None known.

**GHS** label elements

Hazard pictograms





Signal word : Danger

Hazard statements : H315 Causes skin irritation.

H319 Causes serious eye irritation.

H341 Suspected of causing genetic defects.

H350 May cause cancer.

H360 May damage fertility or the unborn child.

H372 Causes damage to organs (Blood) through prolonged or

repeated exposure if swallowed.



# 2041 MICROMAX™ RESISTOR PASTE

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04-12-2024

 8.1
 06-18-2025
 300000000135
 Date of first issue: 01-29-2024

Precautionary statements

### Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe mist or vapours.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product. P280 Wear protective gloves/ eye protection/ face protection. P280 Wear protective gloves, protective clothing, eye protection and face protection.

#### Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P332 + P313 If skin irritation occurs: Get medical advice/ attention

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

#### Storage:

P405 Store locked up.

# Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

# Components

Chemical name	CAS-No.	Concentration (% w/w)
Terpineol	8000-41-7	>= 10 - < 20
Bis(2-butoxyethyl) ether	112-73-2	>= 10 - < 20
Ruthenium (IV) oxide	12036-10-1	>= 10 - < 20
Polyethylene oxide, mo- no(nonylphenyl) ether, branched, phosphate	68412-53-3	>= 1 - < 10
Quartz	14808-60-7	>= 0.1 - < 1

Glass or Ceramic ingredient(s)		50 - 60%
Lead, Silicon, Ruthenium, Aluminum	1	

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.



# 2041 MICROMAX™ RESISTOR PASTE

Version **Revision Date:** SDS Number: Date of last issue: 04-12-2024 06-18-2025 30000000135 Date of first issue: 01-29-2024 8.1

#### **SECTION 4. FIRST AID MEASURES**

If inhaled If inhaled, remove to fresh air.

> If breathing is difficult, give oxygen. If not breathing, give artificial respiration.

Get medical attention.

In case of skin contact Wash off with soap and water.

Get medical attention if irritation develops and persists.

Wash contaminated clothing before re-use.

In case of eye contact Immediately flush eyes for at least 15 minutes. Get medical

attention.

If swallowed If swallowed

Rinse mouth with water.

Call a physician or poison control centre immediately.

DO NOT induce vomiting unless directed to do so by a physi-

cian or poison control center.

Most important symptoms

and effects, both acute and

delayed

Causes skin irritation.

Causes serious eye irritation.

Suspected of causing genetic defects.

May cause cancer.

May damage fertility or the unborn child.

Causes damage to organs through prolonged or repeated

exposure if swallowed.

#### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Dry sand Dry chemical

Alcohol-resistant foam

Specific hazards during fire-

fighting

Hazardous decomposition products formed under fire condi-

tions.

(see also section 10)

Avoid breathing decomposition products.

Further information Evacuate personnel to safe areas.

Stop spill/release if it can be done with minimal risk.

Do not allow run-off from fire fighting to enter drains or water

courses.

Special protective equipment :

for firefighters

Exposure to decomposition products may be a hazard to

health

Wear self-contained breathing apparatus for firefighting if nec-

essary.



# 2041 MICROMAX™ RESISTOR PASTE

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04-12-2024

 8.1
 06-18-2025
 300000000135
 Date of first issue: 01-29-2024

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protec- :

tive equipment and emer-

gency procedures

Avoid contact with skin, eyes and clothing.

Ensure adequate ventilation.

Wear suitable protective equipment.

Dispose of in accordance with local regulations.

Environmental precautions : Prevent further leakage or spillage if safe to do so.

Prevent product from entering drains.

Clean contaminated floors and objects thoroughly while ob-

serving environmental regulations.

Methods and materials for

containment and cleaning up

Contain spill.

Soak up with inert absorbent material.

Collect and contain contaminated absorbent and dike material

for disposal.

Keep in suitable, closed containers for disposal.

Ventilate the area.

Clean contaminated surface thoroughly.

#### **SECTION 7. HANDLING AND STORAGE**

Advice on protection against

fire and explosion

Avoid formation of dust and aerosols.

Keep away from heat and sources of ignition.

Advice on safe handling : Avoid inhalation, ingestion and contact with skin and eyes.

Use only with adequate ventilation/personal protection.

Keep container closed when not in use.

Take care to avoid waste and spillage when weighing, loading

and mixing the product.

Conditions for safe storage

Store in original container.

Keep containers tightly closed in a dry, cool and well-

ventilated place.

Keep away from sources of ignition - No smoking. Do not store or consume food, drink or tobacco in areas where they may become contaminated with this material.

Keep container closed when not in use.

Do not reuse empty container.

Further information on stor-

age stability

Stable under normal conditions.

#### **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Lead	7439-92-1	TWA	0.05 mg/m3 (Lead)	ACGIH
		PEL	0.05 mg/m3 (Lead)	OSHA CARC
		TWA	0.05 mg/m3 (Lead)	NIOSH REL



# 2041 MICROMAX™ RESISTOR PASTE

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04-12-2024

 8.1
 06-18-2025
 300000000135
 Date of first issue: 01-29-2024

Silicon	7440-21-3	TWA (Respirable)	5 mg/m3	NIOSH REL
		TWA (total)	10 mg/m3	NIOSH REL
		TWA (total	15 mg/m3	OSHA Z-1
		dust) `		
		TWÁ (respir-	5 mg/m3	OSHA Z-1
		able fraction)		
		TWA (Total	10 mg/m3	OSHA P0
		dust)		
		TWA (respir-	5 mg/m3	OSHA P0
		able dust		
		fraction)		
Aluminum	7429-90-5	TWA (Res-	5 mg/m3	NIOSH REL
		pirable)		
		TWA (total)	10 mg/m3	NIOSH REL
		TWA (total	15 mg/m3	OSHA Z-1
		dust)	(Aluminium)	
		TWA (respir-	5 mg/m3	OSHA Z-1
		able fraction)	(Aluminium)	
		TWA (Total	15 mg/m3	OSHA P0
		dust)	(Aluminium)	
		TWA (respir-	5 mg/m3	OSHA P0
		able dust	(Aluminium)	
		fraction)		
Quartz	14808-60-7	TWA (Res-	0.05 mg/m3	OSHA Z-1
		pirable dust)		
		TWA (respir-	10 mg/m3 /	OSHA Z-3
		able)	%SiO2+2	
		TWA (respir-	250 mppcf /	OSHA Z-3
		able)	%SiO2+5	
		TWA (respir-	0.1 mg/m3	OSHA P0
		able dust	_	
		fraction)		
		TWA (Res-	0.025 mg/m3	ACGIH
		pirable par-	(Silica)	
		ticulate mat-		
		ter)		
		TWA (Res-	0.05 mg/m3	NIOSH REL
		pirable dust)	(Silica)	
		PEL (respir-	0.05 mg/m3	OSHA CARC
		able)		

### **Biological occupational exposure limits**

Components	CAS-No.	Control parameters	Biological specimen	Sam- pling time	Permissible concentration	Basis
Lead	7439-92-1	Lead (Lead)	In blood	Not criti- cal	200 μg/l	ACGIH BEI

**Engineering measures** : Local exhaust or a laboratory hood should be used when

handling the materials.

Maintain air concentrations below occupational exposure

standards.

# Personal protective equipment

Respiratory protection : Provide adequate ventilation.



# 2041 MICROMAX™ RESISTOR PASTE

Version Revision Date: SDS Number: Date of last issue: 04-12-2024 06-18-2025 30000000135 Date of first issue: 01-29-2024 8.1

> No personal respiratory protective equipment normally reauired.

Where there is potential for airborne exposures in excess of applicable limits, wear approved respiratory protection with

dust/mist cartridge.

When workers are facing concentrations above the exposure

limit they must use appropriate certified respirators.

Consult the respirator manufacturer to determine the appropriate type of equipment for a given application. Observe respirator use limitations specified by the manufacturer. Persons performing maintenance or repairs on exhaust system equipment (e.g. ducts) may need to use respirators and protective clothing to prevent exposure to any accumulated

residues.

Hand protection

Material Impervious gloves

Remarks Gloves must be inspected prior to use. Gloves should be

> discarded and replaced if there is any indication of degradation or chemical breakthrough. The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of

cuts, abrasion, and the contact time. Wear safety glasses with side shields.

Eye protection

Skin and body protection Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Lightweight protective clothing

Safety shoes

Handle in accordance with good industrial hygiene and safety Hygiene measures

Avoid contact with skin, eyes and clothing.

Contaminated work clothing should not be allowed out of the

workplace.

Remove contaminated clothing and protective equipment

before entering eating areas.

Remove and wash contaminated clothing before re-use.

### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

viscous liquid Appearance

Colour black

Odour pine

Substance/mixture is non-polar/aprotic. рΗ

Flash point 210 °F / 99 °C



# 2041 MICROMAX™ RESISTOR PASTE

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04-12-2024

 8.1
 06-18-2025
 300000000135
 Date of first issue: 01-29-2024

Method: closed cup

Density : 2.16 g/cm³ (68 °F / 20 °C)

Solubility(ies)

Water solubility : slightly soluble (68 °F / 20 °C)

Viscosity

Viscosity, dynamic : > 100 Pa.s (77 °F / 25 °C)

Viscosity, kinematic : > 20.5 mm2/s (104 °F / 40 °C)

estimated

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Not classified due to data which are conclusive although insuf-

ficient for classification.

#### **SECTION 10. STABILITY AND REACTIVITY**

Possibility of hazardous reac- :

tions

Polymerization will not occur.

Stable at normal temperatures and storage conditions.

Conditions to avoid : None reasonably foreseeable.

Incompatible materials

Hazardous decomposition

products

Acids

No decomposition if stored and applied as directed.

Under fire conditions:

Carbon monoxide, carbon dioxide and unburned hydrocar-

bons (smoke). Metal oxides

### **SECTION 11. TOXICOLOGICAL INFORMATION**

# **Acute toxicity**

Not classified due to lack of data.

**Product:** 

Acute oral toxicity : Acute toxicity estimate: 4,776 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 20.25 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

Components:

Lead:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401



# 2041 MICROMAX™ RESISTOR PASTE

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04-12-2024

 8.1
 06-18-2025
 300000000135
 Date of first issue: 01-29-2024

Remarks: Information given is based on data obtained from

similar substances.

Acute inhalation toxicity : LC50 (Rat): > 5.05 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Remarks: Information given is based on data obtained from

similar substances.

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 402

Remarks: Information given is based on data obtained from

similar substances.

Terpineol:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 401

Assessment: The substance or mixture has no acute oral tox-

icity

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Silicon:

Acute oral toxicity : LD50 (Rat): 3,160 mg/kg

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : Remarks: No data available

Barium:

Acute oral toxicity : LD50 (Rat): 132 mg/kg

Target Organs: Cardio-vascular system Symptoms: Cardiovascular system effects

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : Remarks: No data available

Polyethylene oxide, mono(nonylphenyl) ether, branched, phosphate:

Acute oral toxicity : LD50 (Rat): 4,450 mg/kg

Aluminum:

Acute oral toxicity : Remarks: No data available

Acute inhalation toxicity : Remarks: Effects of breathing high concentration of respirable

particles may include: Respiratory tract damage

una domogo

Lung damage



# 2041 MICROMAX™ RESISTOR PASTE

Version Revision Date: SDS Number: Date of last issue: 04-12-2024 8.1 06-18-2025 300000000135 Date of first issue: 01-29-2024

Acute dermal toxicity : Remarks: No data available

Quartz:

Acute oral toxicity : LD50 (Rat): > 11,000 mg/kg

Assessment: The substance or mixture has no acute oral tox-

icity

Skin corrosion/irritation

Causes skin irritation.

**Components:** 

Lead:

Species : Rabbit

Assessment : Not classified as irritant
Method : OECD Test Guideline 404

Result : No skin irritation

Remarks : Information given is based on data obtained from similar sub-

stances.

Terpineol:

Species : Rabbit

Assessment : Irritating to skin.

Method : OECD Test Guideline 404

Result : Skin irritation

Silicon:

Remarks : No data available

Barium:

Species : animals (unspecified species)

Result : Mild skin irritation

Remarks : Irritant

Polyethylene oxide, mono(nonylphenyl) ether, branched, phosphate:

Species : Rabbit

Assessment : Irritating to skin.
Result : Severe skin irritation

Remarks : Information given is based on data obtained from similar sub-

stances.

Aluminum:

Remarks : No data available

Quartz:

Species : Rabbit

Assessment : No skin irritation Result : No skin irritation



# 2041 MICROMAX™ RESISTOR PASTE

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04-12-2024

 8.1
 06-18-2025
 300000000135
 Date of first issue: 01-29-2024

#### Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

Lead:

Species : Rabbit

Result : No eye irritation

Assessment : Not classified as irritant
Method : OECD Test Guideline 405

Remarks : Information given is based on data obtained from similar sub-

stances.

Terpineol:

Species : animals (unspecified species)

Result : Eye irritation
Assessment : Irritating to eyes.

Method : OECD Test Guideline 405

Silicon:

Species : Rabbit

Remarks : slight irritation

Barium:

Species : Rabbit

Result : Severe eye irritation

Remarks : Irritant

Polyethylene oxide, mono(nonylphenyl) ether, branched, phosphate:

Species : Rabbit

Result : Risk of serious damage to eyes. Assessment : Risk of serious damage to eyes.

Remarks : Information given is based on data obtained from similar sub-

stances.

**Aluminum:** 

Remarks : No data available

Quartz:

Species : Rabbit

Result : Slight or no eye irritation

Assessment : No eye irritation

Remarks : Minimal effects that do not meet the threshold for classifica-

tion.

Respiratory or skin sensitisation

Skin sensitisation

Not classified due to lack of data.



# 2041 MICROMAX™ RESISTOR PASTE

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04-12-2024

 8.1
 06-18-2025
 300000000135
 Date of first issue: 01-29-2024

### Respiratory sensitisation

Not classified due to lack of data.

Components:

Lead:

Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

Result : Does not cause skin sensitisation.

Remarks : Information given is based on data obtained from similar sub-

stances.

Terpineol:

Test Type : Maximisation Test Species : Guinea pig

Assessment : Not a skin sensitizer.

Method : OECD Test Guideline 406

Result : Did not cause sensitisation on laboratory animals.

Silicon:

Remarks : No data available

Barium:

Remarks : No data available

Polyethylene oxide, mono(nonylphenyl) ether, branched, phosphate:

Species : Human

Assessment : Does not cause skin sensitisation.
Result : Does not cause skin sensitisation.

Remarks : Information given is based on data obtained from similar sub-

stances.

**Aluminum:** 

Remarks : No data available

Quartz:

Species : Guinea pig

Assessment : Does not cause skin sensitisation.
Result : Does not cause skin sensitisation.

Germ cell mutagenicity

Suspected of causing genetic defects.

Components:

Lead:

Germ cell mutagenicity -

Assessment

In vitro tests showed mutagenic effects, Genetic damage in cultured mammalian cells was observed in some laboratory

tests but not in others.



# 2041 MICROMAX™ RESISTOR PASTE

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04-12-2024

 8.1
 06-18-2025
 300000000135
 Date of first issue: 01-29-2024

**Terpineol:** 

Germ cell mutagenicity -

Assessment

: Tests on bacterial or mammalian cell cultures did not show mutagenic effects., Evidence suggests this substance does

not cause genetic damage in animals.

Quartz:

Germ cell mutagenicity -

Assessment

: Genetic damage in cultured mammalian cells was observed in some laboratory tests but not in others., Genetic damage in animals was observed in some laboratory tests but not in oth-

ers.

Carcinogenicity

May cause cancer.

**Components:** 

Lead:

Carcinogenicity - Assess-

ment

Suspected human carcinogens, An increased incidence of tumours was observed in laboratory animals., Information

given is based on data obtained from similar substances.

Terpineol:

Carcinogenicity - Assess-

ment

Not classifiable as a human carcinogen., Overall weight of evidence indicates that the substance is not carcinogenic.

Quartz:

Carcinogenicity - Assess-

ment

Human carcinogen., An increased risk of cancer in humans

has been shown in workplace-based studies.

IARC Group 1: Carcinogenic to humans

Quartz 14808-60-7

(Silica dust, crystalline)

Group 2B: Possibly carcinogenic to humans

Lead 7439-92-1

OSHA specifically regulated carcinogen

Lead 7439-92-1

(Lead and inorganic lead compounds)

OSHA specifically regulated carcinogen

Quartz 14808-60-7

(crystalline silica)

NTP Reasonably anticipated to be a human carcinogen

Lead 7439-92-1

Known to be human carcinogen

Quartz 14808-60-7

(Silica, Crystalline (Respirable Size))

Reproductive toxicity

May damage fertility or the unborn child.



# 2041 MICROMAX™ RESISTOR PASTE

Version Revision Date: SDS Number: Date of last issue: 04-12-2024 8.1 06-18-2025 300000000135 Date of first issue: 01-29-2024

#### **Components:**

Lead:

Reproductive toxicity - As-

sessment

Known human reproductive toxicant, Reduced fertility, Information given is based on data obtained from similar sub-

stances.

Delayed foetal development (variations), Information given is

based on data obtained from similar substances.

**Terpineol:** 

Reproductive toxicity - As-

sessment

Animal testing showed effects on reproduction at levels equal

to or above those causing parental toxicity.

STOT - single exposure

Not classified due to lack of data.

**Components:** 

Lead:

Assessment : The substance or mixture is not classified as specific target

organ toxicant, single exposure.

Terpineol:

Assessment : The substance or mixture is not classified as specific target

organ toxicant, single exposure.

STOT - repeated exposure

Causes damage to organs (Blood) through prolonged or repeated exposure if swallowed.

**Components:** 

**Terpineol:** 

Assessment : The substance or mixture is not classified as specific target

organ toxicant, repeated exposure.

Quartz:

Target Organs : Lungs

Assessment : The substance or mixture is classified as specific target organ

toxicant, repeated exposure, category 1.

Repeated dose toxicity

Components:

Lead:

Species : Rat LOAEL : 200 Application Route : Oral Target Organs : Blood

Assessment : The substance or mixture is classified as specific target organ

toxicant, repeated exposure, category 1.

Remarks : altered blood chemistry

Information given is based on data obtained from similar sub-



# 2041 MICROMAX™ RESISTOR PASTE

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04-12-2024

 8.1
 06-18-2025
 300000000135
 Date of first issue: 01-29-2024

stances.

Terpineol:

Species : Rat Application Route : Oral

Remarks : No toxicologically significant effects were found.

Silicon:

Remarks : No data available

Barium:

Species : multiple species

Application Route : Oral

Remarks : kidney effects

**Aluminum:** 

Species : Human Application Route : Inhalation

Remarks : Respiratory tract damage

Lung damage

Quartz:

Species : multiple species
Application Route : Inhalation
Test atmosphere : dust/mist
Target Organs : Lungs

# **Aspiration toxicity**

Not classified due to lack of data.

#### Components:

#### Lead:

No aspiration toxicity classification

# Polyethylene oxide, mono(nonylphenyl) ether, branched, phosphate:

No aspiration toxicity classification

### Quartz:

No aspiration toxicity classification

#### **SECTION 12. ECOLOGICAL INFORMATION**

#### **Ecotoxicity**

### **Components:**

Lead:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0.107 mg/l



# 2041 MICROMAX™ RESISTOR PASTE

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04-12-2024

 8.1
 06-18-2025
 300000000135
 Date of first issue: 01-29-2024

Exposure time: 96 h

Remarks: Information given is based on data obtained from

similar substances.

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Ceriodaphnia dubia (water flea)): 0.597 mg/l

Exposure time: 48 h

Remarks: Information given is based on data obtained from

similar substances.

Toxicity to algae/aquatic

plants

NOEC (algae): 0.0227 mg/l

Exposure time: 96 h

Remarks: Information given is based on data obtained from

similar substances.

Toxicity to fish (Chronic tox-

icity)

NOEC (Pimephales promelas (fathead minnow)): 0.02 mg/l

Exposure time: 30 d

Remarks: Information given is based on data obtained from

similar substances.

**Ecotoxicology Assessment** 

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

Terpineol:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 62 - 80 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

LC50 (Daphnia magna (Water flea)): 73 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

ErC50 (Pseudokirchneriella subcapitata (green algae)): 68

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

EbC50 (Pseudokirchneriella subcapitata (green algae)): 17

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Silicon:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other :

aquatic invertebrates

ıotio

Remarks: No data available

Toxicity to algae/aquatic

plants

Remarks: No data available

Barium:

Toxicity to fish : Remarks: No data available



# 2041 MICROMAX™ RESISTOR PASTE

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04-12-2024

 8.1
 06-18-2025
 300000000135
 Date of first issue: 01-29-2024

Toxicity to daphnia and other :

aquatic invertebrates

Toxicity to algae/aquatic

plants

Remarks: No data available

Remarks: No data available

Polyethylene oxide, mono(nonylphenyl) ether, branched, phosphate:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 81 mg/l

Exposure time: 96 h

**Ecotoxicology Assessment** 

Acute aquatic toxicity : Harmful to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Aluminum:

Toxicity to fish : NOEC (Salmo trutta (brown trout)): > 100 mg/l

Exposure time: 96 h
Test Type: semi-static test

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

NOEC (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

NOEC (Scenedesmus capricornutum (fresh water algae)): >

100 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Quartz:

**Ecotoxicology Assessment** 

Acute aquatic toxicity : Toxic effects cannot be excluded

Persistence and degradability

**Components:** 

Terpineol:

Biodegradability : Biodegradation: 80 %

Exposure time: 28 d

Method: OECD Test Guideline 301 Remarks: Readily biodegradable.

Quartz:

Biodegradability : Result: Not biodegradable

Remarks: Not applicable

**Bioaccumulative potential** 

**Components:** 

Terpineol:



# 2041 MICROMAX™ RESISTOR PASTE

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04-12-2024

 8.1
 06-18-2025
 300000000135
 Date of first issue: 01-29-2024

Bioaccumulation : Bioconcentration factor (BCF): 24.13

Remarks: Bioaccumulation is unlikely.

Quartz:

Bioaccumulation : Remarks: Not applicable

**Mobility in soil** No data available

Other adverse effects

**Product:** 

Additional ecological infor-

mation

: No data is available on the product itself.

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

Disposal methods

Waste from residues : If recycling is not practicable, dispose of in compliance with

local regulations.

Do not reuse empty container. Never place unused product

down any indoor or out door drain.

Contaminated/not cleaned containers should be treated/handled like product waste.Dispose of container properly.Refer to applicable Local, State/Provincial, and Federal

Regulations, as well as industry Standards.

#### **SECTION 14. TRANSPORT INFORMATION**

# **International Regulations**

**UNRTDG** 

UN number : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(Silver oxide, Glass frits)

Class : 9
Packing group : III
Labels : 9
Environmentally hazardous : no

**IATA-DGR** 

UN/ID No. : UN 3082

Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.

(Silver oxide, Glass frits)

Class : 9 Packing group : III

Labels : Miscellaneous

Packing instruction (cargo : 964

aircraft)

Packing instruction (passen-

964

ger aircraft)

**IMDG-Code** 

UN number : UN 3082



# 2041 MICROMAX™ RESISTOR PASTE

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04-12-2024

 8.1
 06-18-2025
 300000000135
 Date of first issue: 01-29-2024

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(Silver oxide, Glass frits)

Class : 9
Packing group : III
Labels : 9
EmS Code : F-A

EmS Code : F-A, S-F Marine pollutant : no

### Transport in bulk according to IMO instruments

Not applicable for product as supplied.

### **National Regulations**

#### **49 CFR**

Not regulated as a dangerous good

#### Special precautions for user

Remarks : Marine Pollutants assigned UN number 3077 and 3082 in

single or combination packaging containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 KG or less for solids may be transported as non-dangerous goods as provided in section 2.10.2.7 of IMDG code, IATA special provi-

sion A197, and ADR/RID special provision 375.

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

# **SECTION 15. REGULATORY INFORMATION**

#### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Germ cell mutagenicity

Carcinogenicity
Reproductive toxicity

Specific target organ toxicity (single or repeated exposure)

Skin corrosion or irritation

Serious eye damage or eye irritation

SARA 313 : The following components are subject to reporting levels es-

tablished by SARA Title III, Section 313:

Lead 7439-92-1

Barium 7440-39-3

### California Prop. 65

WARNING: This product can expose you to chemicals including Lead, Quartz, 1,4-Dioxane, Acetaldehyde, which is/are known to the State of California to cause cancer, and

Lead, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.



# 2041 MICROMAX™ RESISTOR PASTE

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04-12-2024

 8.1
 06-18-2025
 300000000135
 Date of first issue: 01-29-2024

#### California Regulated Carcinogens

Lead 7439-92-1 Quartz 14808-60-7

#### **TSCA list**

In compliance with TSCA-active Inventory requirements for commercial purposes.

The following substance(s) is/are subject to a Significant New Use Rule:

Bis(2-butoxyethyl) ether 112-73-2 See 40 CFR § 721.10229; Final

Rule

See 40 CFR § 721.10229; Proposed

Rule

The following substance(s) is/are subject to TSCA 12(b) export notification requirements:

 Bis(2-butoxyethyl) ether
 112-73-2

 Lead
 7439-92-1

 Zinc
 7440-66-6

#### **SECTION 16. OTHER INFORMATION**

#### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA CARC : OSHA Specifically Regulated Chemicals/Carcinogens

OSHA PO : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated

values)

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Min-

eral Dusts

ACGIH / TWA : 8-hour, time-weighted average

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

OSHA CARC / PEL : Permissible exposure limit (PEL)
OSHA P0 / TWA : 8-hour time weighted average
OSHA Z-1 / TWA : 8-hour time weighted average
OSHA Z-3 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - In-



# 2041 MICROMAX™ RESISTOR PASTE

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04-12-2024

 8.1
 06-18-2025
 300000000135
 Date of first issue: 01-29-2024

ternational Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ -Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Celanese®, registered C-ball design and all other trademarks identified herein with ®, TM, SM, unless otherwise noted, are trademark

Revision Date : 06-18-2025

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN

