according to GB/T 16483 and GB/T 17519



5091D MICROMAX™ RESISTOR PASTE

Version Revision Date: SDS Number: Date of last issue: 2024/04/12 7.1 2025/07/22 300000000203 Date of first issue: 2024/01/29

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : 5091D MICROMAX™ RESISTOR PASTE

Product code : 00000000027046186

Manufacturer or supplier's details

Company : Celanese (Shanghai) International Trading Co., Ltd

Address : 4560 Jinke Road, Zhangjiang, Pudong

Shanghai, China 201210

Telephone : 86-21-38619288

Emergency telephone number: +1-703-527 3887,

+86 532 8388-9090 (China, 24h)

E-mail address : HazCom@celanese.com

Recommended use of the chemical and restrictions on use

Recommended use : For industrial use only.

Paste for electronic industry

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance : viscous liquid

Colour: blackOdour: pine

Combustible liquid. Causes skin irritation. Causes serious eye damage. Suspected of causing genetic defects. May cause cancer. May damage fertility or the unborn child. Causes damage to organs (Blood) through prolonged or repeated exposure if swallowed. Very toxic to aquatic life with long lasting effects.

GHS Classification

Flammable liquids : Category 4

Skin corrosion/irritation : Category 2

Serious eye damage/eye

irritation

Category 1

Germ cell mutagenicity : Category 2

Carcinogenicity : Category 1A

Reproductive toxicity : Category 1A

Specific target organ toxicity - : Category 1 (Blood)

according to GB/T 16483 and GB/T 17519



5091D MICROMAX™ RESISTOR PASTE

Revision Date: SDS Number: Date of last issue: 2024/04/12 Version 2025/07/22 300000000203 Date of first issue: 2024/01/29 7.1

repeated exposure (Oral)

Short-term (acute) aquatic

hazard

Category 1

Long-term (chronic) aquatic

hazard

Category 1

GHS label elements

Hazard pictograms







Signal word Danger

H227 Combustible liquid. Hazard statements

H315 Causes skin irritation.

H318 Causes serious eye damage.

H341 Suspected of causing genetic defects.

H350 May cause cancer.

H360 May damage fertility or the unborn child.

H372 Causes damage to organs (Blood) through prolonged or

repeated exposure if swallowed.

H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking. P260 Do not breathe mist or vapours. P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.

P308 + P313 IF exposed or concerned: Get medical advice/

attention.

P332 + P313 If skin irritation occurs: Get medical advice/

attention.

P362 + P364 Take off contaminated clothing and wash it before

P370 + P378 In case of fire: Use dry sand, dry chemical or

according to GB/T 16483 and GB/T 17519



5091D MICROMAX™ RESISTOR PASTE

Version Revision Date: SDS Number: Date of last issue: 2024/04/12 7.1 2025/07/22 300000000203 Date of first issue: 2024/01/29

alcohol-resistant foam to extinguish.

P391 Collect spillage.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Physical and chemical hazards

Combustible liquid.

Health hazards

Causes skin irritation. Causes serious eye damage. Suspected of causing genetic defects. May cause cancer. May damage fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure if swallowed.

Environmental hazards

Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects.

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Terpineol	8000-41-7	>= 10 -< 20
Bis(2-butoxyethyl) ether	112-73-2	>= 10 -< 20
Silica, vitreous	60676-86-0	>= 1 -< 10
Dicopper oxide	1317-39-1	>= 1 -< 10
Ethyl cellulose	9004-57-3	>= 1 -< 10
Quartz	14808-60-7	>= 0.1 -< 1

Glass or Ceramic ingredient(s) Lead, Bismuth, Silicon, Barium, Copper, Gadolinium		40 - 50%
Contains:	Lead Bismuth Silicon Barium Copper Gadolinium	10 - 20 % 1 - 10 % 1 - 10 % 1 - 10 % <0.1 % 1 - 10 %

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

according to GB/T 16483 and GB/T 17519



5091D MICROMAX™ RESISTOR PASTE

Version Revision Date: SDS Number: Date of last issue: 2024/04/12 7.1 2025/07/22 300000000203 Date of first issue: 2024/01/29

4. FIRST AID MEASURES

If inhaled : If inhaled, remove to fresh air.

If breathing is difficult, give oxygen.
If not breathing, give artificial respiration.

Get medical attention.

In case of skin contact : Wash off with soap and water.

Get medical attention if irritation develops and persists.

Wash contaminated clothing before re-use.

In case of eye contact : Immediately flush eyes for at least 15 minutes. Get medical

attention.

If swallowed : If swallowed

Rinse mouth with water.

Call a physician or poison control centre immediately. DO NOT induce vomiting unless directed to do so by a

physician or poison control center.

Most important symptoms

and effects, both acute and

delayed

Causes skin irritation.

Causes serious eye damage.

Suspected of causing genetic defects.

May cause cancer.

May damage fertility or the unborn child.

Causes damage to organs through prolonged or repeated

exposure if swallowed.

5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Dry sand Dry chemical

Alcohol-resistant foam

Specific hazards during

firefighting

Hazardous decomposition products formed under fire

conditions.

(see also section 10)

Avoid breathing decomposition products.

Specific extinguishing

methods

: Evacuate personnel to safe areas.

Stop spill/release if it can be done with minimal risk.

Do not allow run-off from fire fighting to enter drains or water

courses.

according to GB/T 16483 and GB/T 17519



5091D MICROMAX™ RESISTOR PASTE

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2024/04/12

 7.1
 2025/07/22
 300000000203
 Date of first issue: 2024/01/29

Special protective equipment :

for firefighters

Exposure to decomposition products may be a hazard to

health.

Wear self-contained breathing apparatus for firefighting if

necessary.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures Avoid contact with skin, eyes and clothing.

Ensure adequate ventilation.

Wear suitable protective equipment.

Environmental precautions : Prevent further leakage or spillage if safe to do so.

Prevent product from entering drains.

Clean contaminated floors and objects thoroughly while

observing environmental regulations.

Methods and materials for containment and cleaning up

Contain spill.

Soak up with inert absorbent material.

Collect and contain contaminated absorbent and dike material

for disposal.

Keep in suitable, closed containers for disposal.

Ventilate the area.

Clean contaminated surface thoroughly.

Prevention of secondary

hazards

Dispose of in accordance with local regulations.

7. HANDLING AND STORAGE

Handling

Advice on protection against

fire and explosion

Avoid formation of dust and aerosols.

Keep away from heat and sources of ignition.

Advice on safe handling : Avoid inhalation, ingestion and contact with skin and eyes.

Use only with adequate ventilation/personal protection.

Keep container closed when not in use.

Take care to avoid waste and spillage when weighing, loading

and mixing the product.

Avoidance of contact : Acids

Storage

Conditions for safe storage : Store in original container.

Keep containers tightly closed in a dry, cool and well-

ventilated place.

Keep away from sources of ignition - No smoking. Do not store or consume food, drink or tobacco in areas where they may become contaminated with this material.

according to GB/T 16483 and GB/T 17519



5091D MICROMAX™ RESISTOR PASTE

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2024/04/12

 7.1
 2025/07/22
 300000000203
 Date of first issue: 2024/01/29

Keep container closed when not in use.

Do not reuse empty container.

Further information on storage stability

: Stable under normal conditions.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis		
Lead	7439-92-1	PC-TWA (Dust)	0.05 mg/m3	CN OEL		
	Further inform		ssibly carcinogenic t			
		PC-TWA (Fumes)	0.03 mg/m3	CN OEL		
	Further inform	Further information: G2B - Possibly carcinogenic to humans				
		TWA	0.05 mg/m3 (Lead)	ACGIH		
Gadolinium	7440-54-2	PC-TWA (Total dust)	2.5 mg/m3	CN OEL		
Quartz	14808-60-7	PC-TWA (Total dust)	0.5 mg/m3	CN OEL		
	Further inform		inogenic to humans			
		PC-TWA (Respirable dust)	0.2 mg/m3	CN OEL		
	Further inform	nation: G1 - Card	inogenic to humans	<u> </u>		
		PC-TWA (Total dust)	0.7 mg/m3	CN OEL		
	Further inform	nation: G1 - Card	inogenic to humans			
		PC-TWA (Respirable dust)	0.3 mg/m3	CN OEL		
	Further inform	Further information: G1 - Carcinogenic to humans				
		PC-TWA (Total dust)	1 mg/m3	CN OEL		
	Further inform	Further information: G1 - Carcinogenic to humans				
		PC-TWA (Respirable dust)	0.7 mg/m3	CN OEL		
	Further inform	Further information: G1 - Carcinogenic to humans				
		TWA (Respirable particulate matter)	0.025 mg/m3 (Silica)	ACGIH		
Copper	7440-50-8	PC-TWA (Dust)	1 mg/m3 (Copper)	CN OEL		
		PC-TWA	0.2 mg/m3	CN OEL		

according to GB/T 16483 and GB/T 17519



5091D MICROMAX™ RESISTOR PASTE

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2024/04/12

 7.1
 2025/07/22
 300000000203
 Date of first issue: 2024/01/29

(Fumes)	(Copper)	
TWA (Dust	1 mg/m3	ACGIH
and mist)	(Copper)	
TWA	0.2 mg/m3	ACGIH
(Fumes)	(Copper)	

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Samplin g time	Permissible concentratio n	Basis
Lead	7439-92-1	Lead (Lead)	Blood	Any time after three weeks of exposure	2 micromol per litre	CN BEI
		Lead (Lead)	Blood	Any time after three weeks of exposure	400 μg/l	CN BEI
		Lead (Lead)	In blood	Not critical	200 μg/l	ACGIH BEI

Engineering measures

Local exhaust or a laboratory hood should be used when

handling the materials.

Maintain air concentrations below occupational exposure

standards.

Personal protective equipment

Respiratory protection

Provide adequate ventilation.

No personal respiratory protective equipment normally

required.

Where there is potential for airborne exposures in excess of applicable limits, wear approved respiratory protection with

dust/mist cartridge.

When workers are facing concentrations above the exposure

limit they must use appropriate certified respirators. Consult the respirator manufacturer to determine the appropriate type of equipment for a given application. Observe respirator use limitations specified by the

manufacturer.

Persons performing maintenance or repairs on exhaust system equipment (e.g. ducts) may need to use respirators

and protective clothing to prevent exposure to any

accumulated residues.

Eye/face protection : Wear safety glasses with side shields.

Skin and body protection : Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to

the specific work-place.

Lightweight protective clothing

Safety shoes

according to GB/T 16483 and GB/T 17519



5091D MICROMAX™ RESISTOR PASTE

Version Revision Date: SDS Number: Date of last issue: 2024/04/12 7.1 2025/07/22 300000000203 Date of first issue: 2024/01/29

Hand protection

Material : Impervious gloves

Remarks : Gloves must be inspected prior to use. Gloves should be

discarded and replaced if there is any indication of degradation or chemical breakthrough. The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

Avoid contact with skin, eyes and clothing.

Contaminated work clothing should not be allowed out of the

workplace.

Remove contaminated clothing and protective equipment

before entering eating areas.

Remove and wash contaminated clothing before re-use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : viscous liquid

Colour : black

Odour : pine

pH : No data available Substance/mixture is non-polar/aprotic.

Flash point : 88 °C

Method: closed cup

Density : 2.1 g/cm³ (20 °C)

Solubility(ies)

Water solubility : slightly soluble (20 °C)

Viscosity

Viscosity, dynamic : > 100 Pa.s (25 °C)

Viscosity, kinematic : > 20.5 mm2/s (40 °C)

estimated

according to GB/T 16483 and GB/T 17519



5091D MICROMAX™ RESISTOR PASTE

Version Revision Date: SDS Number: Date of last issue: 2024/04/12 7.1 2025/07/22 300000000203 Date of first issue: 2024/01/29

10. STABILITY AND REACTIVITY

Possibility of hazardous

reactions

: Polymerization will not occur.

Stable at normal temperatures and storage conditions.

Conditions to avoid : None reasonably foreseeable.

Incompatible materials : Acids

Hazardous decomposition

products

No decomposition if stored and applied as directed.

Under fire conditions:

Carbon monoxide, carbon dioxide and unburned

hydrocarbons (smoke).

Metal oxides

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified due to lack of data.

Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 10 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Calculation method

Components:

Lead:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Remarks: Information given is based on data obtained from

similar substances.

Acute inhalation toxicity : LC50 (Rat): > 5.05 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Remarks: Information given is based on data obtained from

similar substances.

Terpineol:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 401

according to GB/T 16483 and GB/T 17519



5091D MICROMAX™ RESISTOR PASTE

Version Revision Date: SDS Number: Date of last issue: 2024/04/12 7.1 2025/07/22 300000000203 Date of first issue: 2024/01/29

Assessment: The substance or mixture has no acute oral

toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Silica, vitreous:

Acute oral toxicity : LD50 (Rat): > 7,500 mg/kg

Dicopper oxide:

Acute oral toxicity : LD50 (Rat): 1,340 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 3.34 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Bismuth:

Acute oral toxicity : LD50 (Rat): 5,000 mg/kg

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : Remarks: No data available

Gadolinium:

Acute oral toxicity : Remarks: No data available

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : Remarks: No data available

Silicon:

Acute oral toxicity : LD50 (Rat): 3,160 mg/kg

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : Remarks: No data available

Barium:

Acute oral toxicity : LD50 (Rat): 132 mg/kg

Target Organs: Cardio-vascular system

according to GB/T 16483 and GB/T 17519



5091D MICROMAX™ RESISTOR PASTE

Version Revision Date: SDS Number: Date of last issue: 2024/04/12 7.1 2025/07/22 300000000203 Date of first issue: 2024/01/29

Symptoms: Cardiovascular system effects

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : Remarks: No data available

Quartz:

Acute oral toxicity : LD50 (Rat): > 11,000 mg/kg

Assessment: The substance or mixture has no acute oral

toxicity

Copper:

Acute oral toxicity : LD50 (Rat): > 17,000 mg/kg

Acute inhalation toxicity : (animals (unspecified species)): 0.1 mg/l

Acute dermal toxicity : Remarks: No data available

Skin corrosion/irritation

Causes skin irritation.

Components:

Lead:

Species : Rabbit

Assessment : Not classified as irritant
Method : OECD Test Guideline 404

Result : No skin irritation

Remarks : Information given is based on data obtained from similar

substances.

Terpineol:

Species : Rabbit

Assessment : Irritating to skin.

Method : OECD Test Guideline 404

Result : Skin irritation

Bis(2-butoxyethyl) ether:

Species : Rabbit

Assessment : Not classified as irritant
Method : OECD Test Guideline 404

Result : No skin irritation

Silica, vitreous:

Species : Guinea pig
Assessment : Irritating to skin.
Result : Severe skin irritation

Dicopper oxide:

according to GB/T 16483 and GB/T 17519



5091D MICROMAX™ RESISTOR PASTE

Version Revision Date: SDS Number: Date of last issue: 2024/04/12 7.1 2025/07/22 300000000203 Date of first issue: 2024/01/29

Species : Rabbit

Assessment : No skin irritation

Method : OECD Test Guideline 404

Result : No skin irritation

Bismuth:

Remarks : No data available

Gadolinium:

Remarks : No data available

Silicon:

Remarks : No data available

Barium:

Species : animals (unspecified species)

Result : Mild skin irritation

Remarks : Irritant

Quartz:

Species : Rabbit

Assessment : No skin irritation Result : No skin irritation

Copper:

Remarks : No data available

Serious eye damage/eye irritation

Causes serious eye damage.

Components:

Lead:

Species : Rabbit

Result : No eye irritation

Assessment : Not classified as irritant
Method : OECD Test Guideline 405

Remarks : Information given is based on data obtained from similar

substances.

Terpineol:

Species : animals (unspecified species)

Result : Eye irritation
Assessment : Irritating to eyes.

Method : OECD Test Guideline 405

Bis(2-butoxyethyl) ether:

Species : Rabbit

according to GB/T 16483 and GB/T 17519



5091D MICROMAX™ RESISTOR PASTE

Version Revision Date: SDS Number: Date of last issue: 2024/04/12 7.1 2025/07/22 300000000203 Date of first issue: 2024/01/29

Result : No eye irritation

Assessment : Not classified as irritant
Method : OECD Test Guideline 405

Silica, vitreous:

Species : Rabbit
Result : Eye irritation
Assessment : Irritating to eyes.

Dicopper oxide:

Species : Rabbit

Result : Irreversible effects on the eye
Assessment : Risk of serious damage to eyes.
Method : OECD Test Guideline 405

Bismuth:

Remarks : No data available

Gadolinium:

Remarks : No data available

Silicon:

Species : Rabbit

Remarks : slight irritation

Barium:

Species : Rabbit

Result : Severe eye irritation

Remarks : Irritant

Quartz:

Species : Rabbit

Result : Slight or no eye irritation

Assessment : No eye irritation

Remarks : Minimal effects that do not meet the threshold for

classification.

Copper:

Species : animals (unspecified species)

Remarks : Irritant

Respiratory or skin sensitisation

Skin sensitisation

Not classified due to lack of data.

Respiratory sensitisation

Not classified due to lack of data.

according to GB/T 16483 and GB/T 17519



5091D MICROMAX™ RESISTOR PASTE

Version Revision Date: SDS Number: Date of last issue: 2024/04/12 7.1 2025/07/22 300000000203 Date of first issue: 2024/01/29

Components:

Lead:

Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

Result : Does not cause skin sensitisation.

Remarks : Information given is based on data obtained from similar

substances.

Terpineol:

Test Type : Maximisation Test Species : Guinea pig

Assessment : Not a skin sensitizer.

Method : OECD Test Guideline 406

Result : Did not cause sensitisation on laboratory animals.

Bis(2-butoxyethyl) ether:

Species : Human

Assessment : Does not cause skin sensitisation.
Result : Does not cause skin sensitisation.

Remarks : Information given is based on data obtained from similar

substances.

Silica, vitreous:

Species : Human

Assessment : Does not cause skin sensitisation. Result : Does not cause skin sensitisation.

Dicopper oxide:

Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

Result : Does not cause skin sensitisation.

Bismuth:

Remarks : No data available

Gadolinium:

Remarks : No data available

Silicon:

Remarks : No data available

Barium:

Remarks : No data available

according to GB/T 16483 and GB/T 17519



5091D MICROMAX™ RESISTOR PASTE

Version Revision Date: SDS Number: Date of last issue: 2024/04/12 7.1 2025/07/22 300000000203 Date of first issue: 2024/01/29

Quartz:

Species : Guinea pig

Assessment : Does not cause skin sensitisation.
Result : Does not cause skin sensitisation.

Copper:

Species : Human

Remarks : May cause sensitisation of susceptible persons by skin

contact.

Germ cell mutagenicity

Suspected of causing genetic defects.

Components:

Lead:

Germ cell mutagenicity -

Assessment

In vitro tests showed mutagenic effects, Genetic damage in cultured mammalian cells was observed in some laboratory

tests but not in others.

Terpineol:

Germ cell mutagenicity -

Assessment

 Tests on bacterial or mammalian cell cultures did not show mutagenic effects., Evidence suggests this substance does

not cause genetic damage in animals.

Bis(2-butoxyethyl) ether:

Germ cell mutagenicity -

Assessment

: Tests on bacterial or mammalian cell cultures did not show

mutagenic effects., Did not cause genetic damage in cultured mammalian cells., Did not cause genetic damage in cultured

bacterial cells.

Dicopper oxide:

Germ cell mutagenicity -

Assessment

: Animal testing did not show any mutagenic effects., Did not

cause genetic damage in cultured bacterial cells., Information given is based on data obtained from similar substances.

Ethyl cellulose:

Germ cell mutagenicity -

Assessment

: Tests on bacterial or mammalian cell cultures did not show

mutagenic effects., Did not cause genetic damage in cultured bacterial cells., Did not cause genetic damage in cultured mammalian cells., Animal testing did not show any mutagenic effects., Information given is based on data obtained from

similar substances.

Quartz:

Germ cell mutagenicity -

Assessment

: Genetic damage in cultured mammalian cells was observed in

some laboratory tests but not in others., Genetic damage in animals was observed in some laboratory tests but not in

others.

according to GB/T 16483 and GB/T 17519



5091D MICROMAX™ RESISTOR PASTE

Version Revision Date: SDS Number: Date of last issue: 2024/04/12 7.1 2025/07/22 300000000203 Date of first issue: 2024/01/29

Carcinogenicity

May cause cancer.

Components:

Lead:

Carcinogenicity - Assessment

Suspected human carcinogens, An increased incidence of tumours was observed in laboratory animals., Information given is based on data obtained from similar substances.

Terpineol:

Carcinogenicity - Assessment

Not classifiable as a human carcinogen., Overall weight of evidence indicates that the substance is not carcinogenic.

Silica, vitreous:

Carcinogenicity - Assessment Not classifiable as a human carcinogen., Overall weight of evidence indicates that the substance is not carcinogenic.

Quartz:

Carcinogenicity - Assessment Human carcinogen., An increased risk of cancer in humans

has been shown in workplace-based studies.

Reproductive toxicity

May damage fertility or the unborn child.

Components:

Lead:

Reproductive toxicity -

Assessment

Known human reproductive toxicant, Reduced fertility, Information given is based on data obtained from similar

substances.

Delayed foetal development (variations), Information given is

based on data obtained from similar substances.

Terpineol:

Reproductive toxicity -

Assessment

Animal testing showed effects on reproduction at levels equal

to or above those causing parental toxicity.

Bis(2-butoxyethyl) ether:

Reproductive toxicity -

Assessment

No toxicity to reproduction, Animal testing showed no

reproductive toxicity.

Animal testing showed no developmental toxicity.

Silica, vitreous:

Reproductive toxicity -

Assessment

Animal testing showed no reproductive toxicity., Information given is based on data obtained from similar substances.

according to GB/T 16483 and GB/T 17519



5091D MICROMAX™ RESISTOR PASTE

Version Revision Date: SDS Number: Date of last issue: 2024/04/12 7.1 2025/07/22 300000000203 Date of first issue: 2024/01/29

Dicopper oxide:

Reproductive toxicity - : Weight of evidence does not support classification for

Assessment reproductive toxicity, Animal testing showed no reproductive

toxicity., Information given is based on data obtained from

similar substances.

Animal testing showed effects on embryo-fetal development at levels equal to or above those causing maternal toxicity.,

Information given is based on data obtained from similar

substances.

STOT - single exposure

Not classified due to lack of data.

Components:

Lead:

Assessment : The substance or mixture is not classified as specific target

organ toxicant, single exposure.

Terpineol:

Assessment : The substance or mixture is not classified as specific target

organ toxicant, single exposure.

Dicopper oxide:

Assessment : The substance or mixture is not classified as specific target

organ toxicant, single exposure.

STOT - repeated exposure

Causes damage to organs (Blood) through prolonged or repeated exposure if swallowed.

Components:

Terpineol:

Assessment : The substance or mixture is not classified as specific target

organ toxicant, repeated exposure.

Bis(2-butoxyethyl) ether:

Exposure routes : Ingestion

Assessment : The substance or mixture is not classified as specific target

organ toxicant, repeated exposure.

Dicopper oxide:

Assessment : The substance or mixture is not classified as specific target

organ toxicant, repeated exposure.

Quartz:

Target Organs : Lungs

Assessment : The substance or mixture is classified as specific target organ

toxicant, repeated exposure, category 1.

according to GB/T 16483 and GB/T 17519



5091D MICROMAX™ RESISTOR PASTE

Version Revision Date: SDS Number: Date of last issue: 2024/04/12 7.1 2025/07/22 300000000203 Date of first issue: 2024/01/29

Repeated dose toxicity

Components:

Lead:

Species : Rat LOAEL : 200 Application Route : Oral Target Organs : Blood

Assessment : The substance or mixture is classified as specific target organ

toxicant, repeated exposure, category 1.

Remarks : altered blood chemistry

Information given is based on data obtained from similar

substances.

Terpineol:

Species : Rat Application Route : Oral

Remarks : No toxicologically significant effects were found.

Bis(2-butoxyethyl) ether:

Species : Rat
NOAEL : 100 mg/kg
Application Route : Ingestion

Method : see user defined free text

Silica, vitreous:

Species : Rat
Application Route : Inhalation
Test atmosphere : dust/mist
Exposure time : 12 Months

Target Organs : Respiratory system

Assessment : The substance or mixture is classified as specific target organ

toxicant, repeated exposure, category 2.

Remarks : Respiratory effects

Dicopper oxide:

Species : Rat
NOAEL : 1000
LOAEL : 2000
Application Route : Ingestion
Exposure time : 92 d

Method : Regulation (EC) No. 440/2008, Annex, B.26

Remarks : No toxicological effects warranting significant target organ

toxicity classification were seen below the recommended

guidance values for classification.

Information given is based on data obtained from similar

substances.

Species : Rat

according to GB/T 16483 and GB/T 17519



5091D MICROMAX™ RESISTOR PASTE

Version Revision Date: SDS Number: Date of last issue: 2024/04/12 7.1 2025/07/22 300000000203 Date of first issue: 2024/01/29

NOAEL : 2 LOAEL : 0.2 Application Route : Inhalation Exposure time : 28 d

Method : OECD Test Guideline 412

Remarks : No toxicological effects warranting significant target organ

toxicity classification were seen below the recommended

guidance values for classification.

Information given is based on data obtained from similar

substances.

Bismuth:

Application Route : Intratracheal instillation

Remarks : lung effects

Gadolinium:

Remarks : No data available

Silicon:

Remarks : No data available

Barium:

Species : multiple species

Application Route : Oral

Remarks : kidney effects

Quartz:

Species : multiple species
Application Route : Inhalation
Test atmosphere : dust/mist

Copper:

Application Route : Inhalation

Remarks : Inhalation fume fever

Respiratory irritation immune system effects

Liver effects

Aspiration toxicity

Not classified due to lack of data.

Components:

Lead:

No aspiration toxicity classification

Silica, vitreous:

No aspiration toxicity classification

according to GB/T 16483 and GB/T 17519



5091D MICROMAX™ RESISTOR PASTE

Version Revision Date: SDS Number: Date of last issue: 2024/04/12 7.1 2025/07/22 300000000203 Date of first issue: 2024/01/29

Dicopper oxide:

No aspiration toxicity classification

Ethyl cellulose:

No aspiration toxicity classification

Quartz:

No aspiration toxicity classification

12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Lead:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0.107 mg/l

Exposure time: 96 h

Remarks: Information given is based on data obtained from

similar substances.

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Ceriodaphnia dubia (water flea)): 0.597 mg/l

Exposure time: 48 h

Remarks: Information given is based on data obtained from

similar substances.

Toxicity to algae/aquatic

plants

NOEC (algae): 0.0227 mg/l

Exposure time: 96 h

Remarks: Information given is based on data obtained from

similar substances.

M-Factor (Acute aquatic

toxicity)

: 1

Toxicity to fish (Chronic

toxicity)

NOEC (Pimephales promelas (fathead minnow)): 0.02 mg/l

Exposure time: 30 d

Remarks: Information given is based on data obtained from

similar substances.

M-Factor (Chronic aquatic

toxicity)

1

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

Terpineol:

according to GB/T 16483 and GB/T 17519



5091D MICROMAX™ RESISTOR PASTE

Version Revision Date: SDS Number: Date of last issue: 2024/04/12 7.1 2025/07/22 300000000203 Date of first issue: 2024/01/29

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 62 - 80 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

LC50 (Daphnia magna (Water flea)): 73 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

: ErC50 (Pseudokirchneriella subcapitata (green algae)): 68

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

EbC50 (Pseudokirchneriella subcapitata (green algae)): 17

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Bis(2-butoxyethyl) ether:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 210 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Remarks: Information given is based on data obtained from

similar substances.

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 42.5 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 (Desmodesmus subspicatus (green algae)): 41.3 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Ecotoxicology Assessment

Acute aquatic toxicity : Harmful to aquatic life.

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

Dicopper oxide:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0.0028 mg/l

Exposure time: 96 h

Remarks: Information given is based on data obtained from

similar substances.

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 0.026 mg/l

Exposure time: 48 h

Remarks: Information given is based on data obtained from

similar substances.

Toxicity to algae/aquatic

plants

: EC50 (Chlamydomonas reinhardtii (green algae)): 0.047 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

according to GB/T 16483 and GB/T 17519



5091D MICROMAX™ RESISTOR PASTE

Version Revision Date: SDS Number: Date of last issue: 2024/04/12 7.1 2025/07/22 300000000203 Date of first issue: 2024/01/29

Remarks: Information given is based on data obtained from

similar substances.

NOEC (Chlamydomonas reinhardtii (green algae)): 0.022 mg/l

Exposure time: 10 d

Method: OECD Test Guideline 201

Remarks: Information given is based on data obtained from

similar substances.

M-Factor (Acute aquatic

toxicity)

100

Toxicity to fish (Chronic

toxicity)

NOEC (Oncorhynchus mykiss (rainbow trout)): 0.0022 mg/l

Exposure time: 60 d

Method: OECD Test Guideline 204

Remarks: Information given is based on data obtained from

similar substances.

Toxicity to daphnia and other :

aquatic invertebrates (Chronic toxicity)

NOEC (Daphnia magna (Water flea)): 0.0126 mg/l

Exposure time: 21 d

Remarks: Information given is based on data obtained from

similar substances.

M-Factor (Chronic aquatic

toxicity)

10

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

Bismuth:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other :

aquatic invertebrates

Remarks: No data available

Toxicity to algae/aquatic

plants

Remarks: No data available

Gadolinium:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other :

aquatic invertebrates

Remarks: No data available

Toxicity to algae/aquatic

plants

Remarks: No data available

Silicon:

Toxicity to fish : Remarks: No data available

according to GB/T 16483 and GB/T 17519



5091D MICROMAX™ RESISTOR PASTE

Version Revision Date: SDS Number: Date of last issue: 2024/04/12 7.1 2025/07/22 300000000203 Date of first issue: 2024/01/29

Toxicity to daphnia and other :

aquatic invertebrates

Remarks: No data available

Toxicity to algae/aquatic

plants

Remarks: No data available

Barium:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other :

aquatic invertebrates

Remarks: No data available

Toxicity to algae/aquatic

plants

Remarks: No data available

Quartz:

Ecotoxicology Assessment

Acute aquatic toxicity : Toxic effects cannot be excluded

Copper:

Toxicity to algae/aquatic

plants

EC50 (algae): 0.0127 mg/l

Exposure time: 72 h

M-Factor (Acute aquatic

toxicity)

10

M-Factor (Chronic aquatic

toxicity)

10

Persistence and degradability

Components:

Terpineol:

Biodegradability : Biodegradation: 80 %

Exposure time: 28 d

Method: OECD Test Guideline 301 Remarks: Readily biodegradable.

Bis(2-butoxyethyl) ether:

Biodegradability : Result: rapidly biodegradable

Remarks: Information given is based on data obtained from

similar substances.

Quartz:

Biodegradability : Result: Not biodegradable

Remarks: Not applicable

according to GB/T 16483 and GB/T 17519



5091D MICROMAX™ RESISTOR PASTE

Version Revision Date: SDS Number: Date of last issue: 2024/04/12 2025/07/22 300000000203 Date of first issue: 2024/01/29 7.1

Bioaccumulative potential

Components:

Terpineol:

Bioaccumulation Bioconcentration factor (BCF): 24.13

Remarks: Bioaccumulation is unlikely.

Bis(2-butoxyethyl) ether:

Partition coefficient: n-

octanol/water

log Pow: 1.92

Dicopper oxide:

Bioaccumulation Remarks: Bioaccumulation is unlikely.

Ethyl cellulose:

Partition coefficient: n-

octanol/water

log Pow: 5.5

Quartz:

Bioaccumulation Remarks: Not applicable

Mobility in soil No data available

Other adverse effects

No data available

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues If recycling is not practicable, dispose of in compliance with

local regulations.

Do not reuse empty container. Never place unused product

down any indoor or out door drain.

Contaminated/not cleaned containers should be treated/handled like product waste. Dispose of container properly.Refer to applicable Local, State/Provincial, and Federal Regulations, as well as industry Standards.

14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN 3082 **UN** number

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, Proper shipping name

N.O.S.

(Ceramic, Dicopper oxide)

Class

according to GB/T 16483 and GB/T 17519



5091D MICROMAX™ RESISTOR PASTE

Version Revision Date: SDS Number: Date of last issue: 2024/04/12 7.1 2025/07/22 300000000203 Date of first issue: 2024/01/29

Packing group : III Labels : 9 Environmentally hazardous : no

IATA-DGR

UN/ID No. : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(Ceramic, Dicopper oxide)

Class : 9 Packing group : III

Labels : Miscellaneous

Packing instruction (cargo : 964

aircraft)

Packing instruction : 964

(passenger aircraft)

IMDG-Code

UN number : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(Ceramic, Dicopper oxide)

Class : 9
Packing group : III
Labels : 9
EmS Code : F-A, S-F
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

GB 6944/12268

UN number : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(Ceramic, Dicopper oxide)

Class : 9
Packing group : III
Labels : 9
Marine pollutant : no

JT/T 617

UN number : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

Class : 9
Packing group : III
Labels : 9
Environmentally hazardous : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

according to GB/T 16483 and GB/T 17519



5091D MICROMAX™ RESISTOR PASTE

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2024/04/12

 7.1
 2025/07/22
 300000000203
 Date of first issue: 2024/01/29

15. REGULATORY INFORMATION

National regulatory information

Law on the Prevention and Control of Occupational Diseases

Regulations on Safety Management of Hazardous Chemicals

Catalogue of Hazardous Chemicals : This product is not listed in the

catalogue of hazardous chemicals, but it meets the definition of hazardous chemicals and its principles of determination.

Identification of Major Hazard Installations for Hazardous Chemicals (GB : Not listed

18218)

Hazardous Chemicals for Priority Management under : Not listed

SAWS

Catalogue of Specially Controlled Hazardous : Not listed

Chemicals

List of Explosive Precursors : Listed

Regulations on Labour Protection in Workplaces where Toxic Substances are Used

Catalogue of Highly Toxic Chemicals : Listed

Regulation of Environmental Management on the First Import of Chemicals and the Import and Export of Toxic Chemicals

China Severely Restricted Toxic Chemicals for Import : Not listed

and Export

Regulation on the Administration of Precursor Chemicals

Catalogue and Classification of Precursor Chemicals : Not listed

Regulations on the Administration of Controlled Chemicals

List of Controlled Chemicals : Not listed

Regulations of Ozone Depleting Substances Management

List of Controlled Ozone Depleting Substances : Not listed

List of Controlled Ozone Depleting Substances Import : Not listed

and Export

Environmental Protection Law

List of Priority Controlled Chemicals : Listed

List of Key Controlled New Pollutants : Not listed

according to GB/T 16483 and GB/T 17519



5091D MICROMAX™ RESISTOR PASTE

Version Revision Date: SDS Number: Date of last issue: 2024/04/12 7.1 2025/07/22 300000000203 Date of first issue: 2024/01/29

16. OTHER INFORMATION

Revision Date : 2025/07/22

Date format : yyyy/mm/dd

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)
CN BEI : China. Biological Occupational Exposure Indices

CN OEL : Occupational exposure limits for hazardous agents in the

workplace - Chemical hazardous agents.

ACGIH / TWA : 8-hour, time-weighted average

CN OEL / PC-TWA : Permissible concentration - time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

according to GB/T 16483 and GB/T 17519



5091D MICROMAX™ RESISTOR PASTE

Version Revision Date: SDS Number: Date of last issue: 2024/04/12 7.1 2025/07/22 300000000203 Date of first issue: 2024/01/29

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CN / EN