according to GB/T 16483 and GB/T 17519



5421E MICROMAX™ CONDUCTOR PASTE

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2024/04/12

 8.1
 2025/07/31
 300000002443
 Date of first issue: 2024/01/29

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : 5421E MICROMAX™ CONDUCTOR PASTE

Product code : 00000000027046924

Manufacturer or supplier's details

Company : Celanese (Shanghai) International Trading Co., Ltd

Address : 4560 Jinke Road, Zhangjiang, Pudong

Shanghai, China 201210

Telephone : 86-21-38619288

Emergency telephone number: CHEMTREC International phone number: +1-703-527 3887,

+86 532 8388-9090 (China, 24h)

E-mail address : HazCom@celanese.com

Recommended use of the chemical and restrictions on use

Recommended use : For industrial use only.

Paste for electronic industry

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance: viscous liquidColour: dark greyOdour: pine

Combustible liquid. Causes skin irritation. Causes serious eye irritation. May cause damage to organs (Central nervous system) through prolonged or repeated exposure. Very toxic to aquatic life with long lasting effects.

GHS Classification

Flammable liquids : Category 4

Skin corrosion/irritation : Category 2

Serious eye damage/eye

irritation

Category 2A

Specific target organ toxicity - :

repeated exposure

Category 2 (Central nervous system)

Short-term (acute) aquatic

hazard

Category 1

Long-term (chronic) aquatic

hazard

Category 1

according to GB/T 16483 and GB/T 17519



5421E MICROMAX™ CONDUCTOR PASTE

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2024/04/12

 8.1
 2025/07/31
 300000002443
 Date of first issue: 2024/01/29

GHS label elements

Hazard pictograms







Signal word : Warning

Hazard statements : H227 Combustible liquid.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H373 May cause damage to organs (Central nervous system)

through prolonged or repeated exposure.

H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements :

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking. P260 Do not breathe mist or vapours. P264 Wash skin thoroughly after handling. P273 Avoid release to the environment.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P314 Get medical advice/ attention if you feel unwell. P332 + P313 If skin irritation occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/attention.

P362 + P364 Take off contaminated clothing and wash it before

P370 + P378 In case of fire: Use dry sand, dry chemical or

alcohol-resistant foam to extinguish.

P391 Collect spillage.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Physical and chemical hazards

Combustible liquid.

according to GB/T 16483 and GB/T 17519



5421E MICROMAX™ CONDUCTOR PASTE

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2024/04/12

 8.1
 2025/07/31
 300000002443
 Date of first issue: 2024/01/29

Health hazards

Causes skin irritation. Causes serious eye irritation. May cause damage to organs through prolonged or repeated exposure.

Environmental hazards

Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects.

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Silver Powder (particle diameter >100 nm	7440-22-4	60 -< 70
<1mm)		
Terpineol	8000-41-7	1 -< 10
Bis(2-butoxyethyl) ether	112-73-2	1 -< 10
Ethyl cellulose	9004-57-3	1 -< 10
2-(2-Butoxyethoxy)ethanol	112-34-5	1 -< 10
Stoddard solvent (< 0.1% benzene)	8052-41-3	1 -< 10
Palladium	7440-05-3	0.1 -< 1

Glass or Ceramic ingredient(s) Barium, Bismuth, Copper, Ruthenium		1 - 10%
Contains:	Barium Bismuth Copper Ruthenium	1 - 10 % 1 - 10 % 0.1 - 1 % 0.1 - 1 %

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

If inhaled : If inhaled, remove to fresh air.

If breathing is difficult, give oxygen.
If not breathing, give artificial respiration.

Get medical attention.

In case of skin contact : Wash off with soap and water.

Get medical attention if irritation develops and persists.

Wash contaminated clothing before re-use.

In case of eye contact : Immediately flush eyes for at least 15 minutes. Get medical

attention.

If swallowed : If swallowed

Rinse mouth with water.

according to GB/T 16483 and GB/T 17519



5421E MICROMAX™ CONDUCTOR PASTE

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2024/04/12

 8.1
 2025/07/31
 300000002443
 Date of first issue: 2024/01/29

Call a physician or poison control centre immediately. DO NOT induce vomiting unless directed to do so by a

physician or poison control center.

Most important symptoms and effects, both acute and delayed

Causes skin irritation.

Causes serious eye irritation.

May cause damage to organs through prolonged or repeated

exposure.

5. FIREFIGHTING MEASURES

Suitable extinguishing media : Dry sand

Dry chemical

Alcohol-resistant foam

Specific hazards during

firefighting

Hazardous decomposition products formed under fire

conditions.

(see also section 10)

Avoid breathing decomposition products.

Specific extinguishing

methods

Evacuate personnel to safe areas.

Stop spill/release if it can be done with minimal risk.

Do not allow run-off from fire fighting to enter drains or water

courses.

Special protective equipment:

for firefighters

Exposure to decomposition products may be a hazard to

health.

Wear self-contained breathing apparatus for firefighting if

necessary.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Avoid contact with skin, eyes and clothing.

Ensure adequate ventilation.

Wear suitable protective equipment.

Environmental precautions : Prevent further leakage or spillage if safe to do so.

Prevent product from entering drains.

Clean contaminated floors and objects thoroughly while

observing environmental regulations.

Methods and materials for containment and cleaning up

Contain spill.

Soak up with inert absorbent material.

Collect and contain contaminated absorbent and dike material

for disposal.

Keep in suitable, closed containers for disposal.

Ventilate the area.

Clean contaminated surface thoroughly.

according to GB/T 16483 and GB/T 17519



5421E MICROMAX™ CONDUCTOR PASTE

Version Revision Date: SDS Number: Date of last issue: 2024/04/12 8.1 2025/07/31 300000002443 Date of first issue: 2024/01/29

Prevention of secondary

hazards

Dispose of in accordance with local regulations.

7. HANDLING AND STORAGE

Handling

Advice on protection against

fire and explosion

Avoid formation of dust and aerosols.

Keep away from heat and sources of ignition.

Advice on safe handling : Avoid inhalation, ingestion and contact with skin and eyes.

Use only with adequate ventilation/personal protection.

Keep container closed when not in use.

Take care to avoid waste and spillage when weighing, loading

and mixing the product.

Avoidance of contact : Acids

Storage

Conditions for safe storage :

Store in original container.

Keep containers tightly closed in a dry, cool and well-

ventilated place.

Keep away from sources of ignition - No smoking. Do not store or consume food, drink or tobacco in areas where they may become contaminated with this material.

Keep container closed when not in use.

Do not reuse empty container.

Further information on

storage stability

Stable under normal conditions.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Silver Powder (particle diameter >100 nm <1mm)	7440-22-4	TWA (Dust and fume)	0.1 mg/m3	ACGIH
2-(2-Butoxyethoxy)ethanol	112-34-5	TWA (Inhalable fraction and vapor)	10 ppm	ACGIH
Stoddard solvent (< 0.1% benzene)	8052-41-3	TWA	100 ppm	ACGIH
Copper	7440-50-8	PC-TWA (Dust)	1 mg/m3 (Copper)	CN OEL
		PC-TWA (Fumes)	0.2 mg/m3 (Copper)	CN OEL
		TWA (Dust	1 mg/m3	ACGIH

according to GB/T 16483 and GB/T 17519



5421E MICROMAX™ CONDUCTOR PASTE

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2024/04/12

 8.1
 2025/07/31
 300000002443
 Date of first issue: 2024/01/29

and mist)	(Copper)	
TWA	0.2 mg/m3	ACGIH
(Fumes)	(Copper)	

Engineering measures : Local exhaust or a laboratory hood should be used when

handling the materials.

Maintain air concentrations below occupational exposure

standards.

Personal protective equipment

Respiratory protection : Provide adequate ventilation.

No personal respiratory protective equipment normally

required.

Where there is potential for airborne exposures in excess of applicable limits, wear approved respiratory protection with

dust/mist cartridge.

When workers are facing concentrations above the exposure

limit they must use appropriate certified respirators. Consult the respirator manufacturer to determine the appropriate type of equipment for a given application. Observe respirator use limitations specified by the

manufacturer.

Persons performing maintenance or repairs on exhaust system equipment (e.g. ducts) may need to use respirators

and protective clothing to prevent exposure to any

accumulated residues.

Eye/face protection : Wear safety glasses with side shields.

Skin and body protection : Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to

the specific work-place.

Lightweight protective clothing

Safety shoes

Hand protection

Material : Impervious gloves

Remarks : Gloves must be inspected prior to use. Gloves should be

discarded and replaced if there is any indication of degradation or chemical breakthrough. The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

according to GB/T 16483 and GB/T 17519



5421E MICROMAX™ CONDUCTOR PASTE

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2024/04/12

 8.1
 2025/07/31
 300000002443
 Date of first issue: 2024/01/29

Avoid contact with skin, eyes and clothing.

Contaminated work clothing should not be allowed out of the

workplace.

Remove contaminated clothing and protective equipment

before entering eating areas.

Remove and wash contaminated clothing before re-use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : viscous liquid

Colour : dark grey

Odour : pine

pH : No data available Substance/mixture is non-polar/aprotic.

Flash point : 81 °C

Method: closed cup

Density : 2.8 g/cm³ (20 °C)

Solubility(ies)

Water solubility : slightly soluble (20 °C)

Viscosity

Viscosity, dynamic : > 100 Pa.s (25 °C)

Viscosity, kinematic : > 20.5 mm2/s (40 °C)

estimated

10. STABILITY AND REACTIVITY

Possibility of hazardous

reactions

Polymerization will not occur.

Stable at normal temperatures and storage conditions.

Conditions to avoid : None reasonably foreseeable.

Incompatible materials : Acids

Hazardous decomposition

products

No decomposition if stored and applied as directed.

Under fire conditions:

Carbon monoxide, carbon dioxide and unburned

hydrocarbons (smoke).

Metal oxides

according to GB/T 16483 and GB/T 17519



5421E MICROMAX™ CONDUCTOR PASTE

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2024/04/12

 8.1
 2025/07/31
 300000002443
 Date of first issue: 2024/01/29

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified due to lack of data.

Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

Components:

Silver Powder (particle diameter >100 nm <1mm):

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 401

Assessment: The substance or mixture has no acute oral

toxicity

Acute inhalation toxicity : LC50 (Rat): > 5.16 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 436

Assessment: The substance or mixture has no acute

inhalation toxicity

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Terpineol:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 401

Assessment: The substance or mixture has no acute oral

toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

2-(2-Butoxyethoxy)ethanol:

Acute oral toxicity : LD50 (Mouse): 2,410 mg/kg

Method: OECD Test Guideline 401 Target Organs: Central nervous system

Remarks: narcosis

Acute inhalation toxicity : Remarks: An LC50/inhalation/4h/rat could not be determined

according to GB/T 16483 and GB/T 17519



5421E MICROMAX™ CONDUCTOR PASTE

Version Revision Date: SDS Number: Date of last issue: 2024/04/12 8.1 2025/07/31 300000002443 Date of first issue: 2024/01/29

because no mortality of rats was observed at the maximum

achievable concentration.

Acute dermal toxicity : LD50 (Rabbit): 2,764 mg/kg

Method: OECD Test Guideline 402

Stoddard solvent (< 0.1% benzene):

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Assessment: The substance or mixture has no acute oral

toxicity

Acute inhalation toxicity : Assessment: The substance or mixture has no acute

inhalation toxicity

Remarks: An LC50/inhalation/4h/rat could not be determined because no mortality of rats was observed at the maximum

achievable concentration.

Acute dermal toxicity : LD50 (Rabbit): > 3,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Barium:

Acute oral toxicity : LD50 (Rat): 132 mg/kg

Target Organs: Cardio-vascular system Symptoms: Cardiovascular system effects

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : Remarks: No data available

Bismuth:

Acute oral toxicity : LD50 (Rat): 5,000 mg/kg

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : Remarks: No data available

Copper:

Acute oral toxicity : LD50 (Rat): > 17,000 mg/kg

Acute inhalation toxicity : (animals (unspecified species)): 0.1 mg/l

Acute dermal toxicity : Remarks: No data available

Skin corrosion/irritation

Causes skin irritation.

according to GB/T 16483 and GB/T 17519



5421E MICROMAX™ CONDUCTOR PASTE

Version Revision Date: SDS Number: Date of last issue: 2024/04/12 8.1 2025/07/31 300000002443 Date of first issue: 2024/01/29

Components:

Silver Powder (particle diameter >100 nm <1mm):

Species : Rabbit

Assessment : No skin irritation

Method : OECD Test Guideline 404
Result : Slight or no skin irritation

Remarks : Minimal effects that do not meet the threshold for

classification.

Terpineol:

Species : Rabbit

Assessment : Irritating to skin.

Method : OECD Test Guideline 404

Result : Skin irritation

Bis(2-butoxyethyl) ether:

Species : Rabbit

Assessment : Not classified as irritant
Method : OECD Test Guideline 404

Result : No skin irritation

2-(2-Butoxyethoxy)ethanol:

Species : Rabbit

Assessment : Not classified as irritant
Method : OECD Test Guideline 404

Result : No skin irritation

Stoddard solvent (< 0.1% benzene):

Species : Rabbit

Assessment : Irritating to skin.

Method : OECD Test Guideline 404
Result : Severe skin irritation

Barium:

Species : animals (unspecified species)

Result : Mild skin irritation

Remarks : Irritant

Bismuth:

Remarks : No data available

Copper:

Remarks : No data available

Serious eye damage/eye irritation

Causes serious eye irritation.

according to GB/T 16483 and GB/T 17519



5421E MICROMAX™ CONDUCTOR PASTE

Version Revision Date: SDS Number: Date of last issue: 2024/04/12 8.1 2025/07/31 300000002443 Date of first issue: 2024/01/29

Components:

Silver Powder (particle diameter >100 nm <1mm):

Species : Rabbit

Result : No eye irritation
Assessment : No eye irritation

Method : OECD Test Guideline 405

Terpineol:

Species : animals (unspecified species)

Result : Eye irritation
Assessment : Irritating to eyes.

Method : OECD Test Guideline 405

Bis(2-butoxyethyl) ether:

Species : Rabbit

Result : No eye irritation

Assessment : Not classified as irritant
Method : OECD Test Guideline 405

2-(2-Butoxyethoxy)ethanol:

Species : Rabbit
Result : Eye irritation
Assessment : Irritating to eyes.

Method : OECD Test Guideline 405

Stoddard solvent (< 0.1% benzene):

Species : Rabbit

Result : Slight or no eye irritation

Assessment : No eye irritation

Method : OECD Test Guideline 405

Remarks : Minimal effects that do not meet the threshold for

classification.

Barium:

Species : Rabbit

Result : Severe eye irritation

Remarks : Irritant

Bismuth:

Remarks : No data available

Copper:

Species : animals (unspecified species)

Remarks : Irritant

according to GB/T 16483 and GB/T 17519



5421E MICROMAX™ CONDUCTOR PASTE

Version Revision Date: SDS Number: Date of last issue: 2024/04/12 8.1 2025/07/31 300000002443 Date of first issue: 2024/01/29

Respiratory or skin sensitisation

Skin sensitisation

Not classified due to lack of data.

Respiratory sensitisation

Not classified due to lack of data.

Components:

Silver Powder (particle diameter >100 nm <1mm):

Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : US EPA Test Guideline OPPTS 870.2600

Result : Does not cause skin sensitisation.

Remarks : Information given is based on data obtained from similar

substances.

Terpineol:

Test Type : Maximisation Test

Species : Guinea pig

Assessment : Not a skin sensitizer.

Method : OECD Test Guideline 406

Result : Did not cause sensitisation on laboratory animals.

Bis(2-butoxyethyl) ether:

Species : Human

Assessment : Does not cause skin sensitisation.
Result : Does not cause skin sensitisation.

Remarks : Information given is based on data obtained from similar

substances.

2-(2-Butoxyethoxy)ethanol:

Species : Mouse

Assessment : Does not cause respiratory sensitisation.
Result : Does not cause respiratory sensitisation.

Test Type : Maximisation Test

Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

Result : Does not cause skin sensitisation.

Stoddard solvent (< 0.1% benzene):

Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

Result : Does not cause skin sensitisation.

Species : Mouse

Assessment : Does not cause respiratory sensitisation. Result : Does not cause respiratory sensitisation.

according to GB/T 16483 and GB/T 17519



5421E MICROMAX™ CONDUCTOR PASTE

Version Revision Date: SDS Number: Date of last issue: 2024/04/12 8.1 2025/07/31 300000002443 Date of first issue: 2024/01/29

Barium:

Remarks : No data available

Bismuth:

Remarks : No data available

Copper:

Species : Human

Remarks : May cause sensitisation of susceptible persons by skin

contact.

Germ cell mutagenicity

Not classified due to lack of data.

Components:

Terpineol:

Germ cell mutagenicity -

Assessment

Tests on bacterial or mammalian cell cultures did not show mutagenic effects., Evidence suggests this substance does

not cause genetic damage in animals.

Bis(2-butoxyethyl) ether:

Germ cell mutagenicity -

Assessment

Tests on bacterial or mammalian cell cultures did not show mutagenic effects., Did not cause genetic damage in cultured mammalian cells., Did not cause genetic damage in cultured

bacterial cells.

Ethyl cellulose:

Germ cell mutagenicity -

Assessment

: Tests on bacterial or mammalian cell cultures did not show mutagenic effects., Did not cause genetic damage in cultured

bacterial cells., Did not cause genetic damage in cultured mammalian cells., Animal testing did not show any mutagenic effects., Information given is based on data obtained from

similar substances.

2-(2-Butoxyethoxy)ethanol:

Germ cell mutagenicity -

Assessment

: Tests on bacterial or mammalian cell cultures did not show mutagenic effects., Animal testing did not show any mutagenic

effects.

Stoddard solvent (< 0.1% benzene):

Germ cell mutagenicity -

Assessment

Animal testing did not show any mutagenic effects., Tests on bacterial or mammalian cell cultures did not show mutagenic

effects.

Carcinogenicity

Not classified due to lack of data.

according to GB/T 16483 and GB/T 17519



5421E MICROMAX™ CONDUCTOR PASTE

Version Revision Date: SDS Number: Date of last issue: 2024/04/12 8.1 2025/07/31 300000002443 Date of first issue: 2024/01/29

Components:

Terpineol:

Carcinogenicity - Assessment

Not classifiable as a human carcinogen., Overall weight of evidence indicates that the substance is not carcinogenic.

2-(2-Butoxyethoxy)ethanol:

Carcinogenicity -Assessment

Not classifiable as a human carcinogen.

Reproductive toxicity

Not classified due to lack of data.

Components:

Terpineol:

Reproductive toxicity - Assessment

Animal testing showed effects on reproduction at levels equal

to or above those causing parental toxicity.

Bis(2-butoxyethyl) ether:

Reproductive toxicity -

Assessment

No toxicity to reproduction, Animal testing showed no

reproductive toxicity.

Animal testing showed no developmental toxicity.

2-(2-Butoxyethoxy)ethanol:

Reproductive toxicity -

Assessment

No toxicity to reproduction, Animal testing showed no

reproductive toxicity.

Animal testing showed no developmental toxicity.

Stoddard solvent (< 0.1% benzene):

Reproductive toxicity -

Assessment

No toxicity to reproduction, Animal testing showed no reproductive toxicity., Information given is based on data

obtained from similar substances.

Animal testing showed no developmental toxicity.

STOT - single exposure

Not classified due to lack of data.

Components:

Terpineol:

Assessment : The substance or mixture is not classified as specific target

organ toxicant, single exposure.

2-(2-Butoxyethoxy)ethanol:

Target Organs : Central nervous system

Assessment : The substance or mixture is classified as specific target organ

toxicant, single exposure, category 3 with narcotic effects.

according to GB/T 16483 and GB/T 17519



5421E MICROMAX™ CONDUCTOR PASTE

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2024/04/12

 8.1
 2025/07/31
 300000002443
 Date of first issue: 2024/01/29

Stoddard solvent (< 0.1% benzene):

Target Organs : Respiratory system

Assessment : The substance or mixture is classified as specific target organ

toxicant, single exposure, category 3 with respiratory tract

irritation.

STOT - repeated exposure

May cause damage to organs (Central nervous system) through prolonged or repeated exposure.

Components:

Terpineol:

Assessment : The substance or mixture is not classified as specific target

organ toxicant, repeated exposure.

Bis(2-butoxyethyl) ether:

Exposure routes : Ingestion

Assessment : The substance or mixture is not classified as specific target

organ toxicant, repeated exposure.

2-(2-Butoxyethoxy)ethanol:

Assessment : The substance or mixture is not classified as specific target

organ toxicant, repeated exposure.

Stoddard solvent (< 0.1% benzene):

Target Organs : Central nervous system

Assessment : The substance or mixture is classified as specific target organ

toxicant, repeated exposure, category 1.

Repeated dose toxicity

Components:

Terpineol:

Species : Rat Application Route : Oral

Remarks : No toxicologically significant effects were found.

Bis(2-butoxyethyl) ether:

Species : Rat

NOAEL : 100 mg/kg Application Route : Ingestion

Method : see user defined free text

2-(2-Butoxyethoxy)ethanol:

Species : Rat
Application Route : Dermal
Remarks : Skin irritation

according to GB/T 16483 and GB/T 17519



5421E MICROMAX™ CONDUCTOR PASTE

Version Revision Date: SDS Number: Date of last issue: 2024/04/12 8.1 2025/07/31 300000002443 Date of first issue: 2024/01/29

Species : Rat Application Route : Oral

Remarks : Spleen effects

Organ weight changes

Liver effects kidney effects

Species : Rat
Application Route : Inhalation
Remarks : Liver effects
lung effects

Stoddard solvent (< 0.1% benzene):

Species : Human
Application Route : Inhalation
Test atmosphere : vapour
Exposure time : 12 Months

Species : Rat

NOAEL : 1,056 mg/kg
Application Route : Ingestion
Exposure time : 28 d

Method : OECD Test Guideline 407

Remarks : No toxicological effects warranting significant target organ

toxicity classification were seen below the recommended

guidance values for classification.

Information given is based on data obtained from similar

substances.

Species : Rabbit
NOAEL : 2,000 mg/kg
Application Route : Skin contact

Exposure time : 28 d

Method : OECD Test Guideline 410

Remarks : No toxicologically significant effects were found.

Barium:

Species : multiple species

Application Route : Oral

Remarks : kidney effects

Bismuth:

Application Route : Intratracheal instillation

Remarks : lung effects

Copper:

Application Route : Inhalation

Remarks : Inhalation fume fever

Respiratory irritation immune system effects

Liver effects

according to GB/T 16483 and GB/T 17519



5421E MICROMAX™ CONDUCTOR PASTE

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2024/04/12

 8.1
 2025/07/31
 300000002443
 Date of first issue: 2024/01/29

Aspiration toxicity

Not classified due to lack of data.

Components:

Silver Powder (particle diameter >100 nm <1mm):

No aspiration toxicity classification

Ethyl cellulose:

No aspiration toxicity classification

2-(2-Butoxyethoxy)ethanol:

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

Stoddard solvent (< 0.1% benzene):

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Silver Powder (particle diameter >100 nm <1mm):

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 0.016 mg/l

Exposure time: 96 h

Remarks: Information given is based on data obtained from

similar substances.

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 0.0125 mg/l

Exposure time: 48 h

Remarks: Information given is based on data obtained from

similar substances.

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 0.19

mg/l

Exposure time: 96 h

Remarks: Information given is based on data obtained from

similar substances.

EC10 (Pseudokirchneriella subcapitata (green algae)):

0.03462 mg/l

Exposure time: 72 h

Remarks: Information given is based on data obtained from

similar substances.

Toxicity to fish (Chronic : NOEC (Oncorhynchus mykiss (rainbow trout)): 0.0012 mg/l

according to GB/T 16483 and GB/T 17519



5421E MICROMAX™ CONDUCTOR PASTE

Version Revision Date: SDS Number: Date of last issue: 2024/04/12 8.1 2025/07/31 300000002443 Date of first issue: 2024/01/29

toxicity) Exposure time: 32 d

Remarks: Information given is based on data obtained from

similar substances.

Toxicity to daphnia and other :

aquatic invertebrates (Chronic toxicity)

NOEC (Daphnia magna (Water flea)): 0.00327 mg/l Exposure time: 21 d

Remarks: Information given is based on data obtained from

similar substances.

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

Terpineol:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 62 - 80 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

LC50 (Daphnia magna (Water flea)): 73 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

ErC50 (Pseudokirchneriella subcapitata (green algae)): 68

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

EbC50 (Pseudokirchneriella subcapitata (green algae)): 17

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Bis(2-butoxyethyl) ether:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 210 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Remarks: Information given is based on data obtained from

similar substances.

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 42.5 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 (Desmodesmus subspicatus (green algae)): 41.3 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Ecotoxicology Assessment

Acute aquatic toxicity : Harmful to aquatic life.

according to GB/T 16483 and GB/T 17519



5421E MICROMAX™ CONDUCTOR PASTE

Version Revision Date: SDS Number: Date of last issue: 2024/04/12 8.1 2025/07/31 300000002443 Date of first issue: 2024/01/29

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

2-(2-Butoxyethoxy)ethanol:

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 1,300 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Method: Directive 67/548/EEC, Annex V, C.2.

Toxicity to algae/aquatic

plants

ErC50 (Desmodesmus subspicatus (green algae)): > 100 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 201

NOEC (Desmodesmus subspicatus (green algae)): > 100 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 201

Stoddard solvent (< 0.1% benzene):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2.5 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Remarks: Information given is based on data obtained from

similar substances.

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 3 mg/l

Exposure time: 48 h

Remarks: Information given is based on data obtained from

similar substances.

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 1.2

mg/l

Exposure time: 96 h

Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 0.16

mg/l

Exposure time: 96 h

Method: OECD Test Guideline 201

Toxicity to daphnia and other :

aquatic invertebrates (Chronic toxicity)

NOEC (Daphnia magna (Water flea)): 0.1 mg/l

Exposure time: 21 d

Method: OECD Test Guideline 211

Ecotoxicology Assessment

Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Barium:

according to GB/T 16483 and GB/T 17519



5421E MICROMAX™ CONDUCTOR PASTE

Version Revision Date: SDS Number: Date of last issue: 2024/04/12 8.1 2025/07/31 300000002443 Date of first issue: 2024/01/29

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other :

aquatic invertebrates

Remarks: No data available

Toxicity to algae/aquatic

plants

Remarks: No data available

Bismuth:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other :

aquatic invertebrates

Remarks: No data available

Toxicity to algae/aquatic

plants

Remarks: No data available

Copper:

Toxicity to algae/aquatic

plants

EC50 (algae): 0.0127 mg/l Exposure time: 72 h

M-Factor (Acute aquatic

toxicity)

10

M-Factor (Chronic aquatic

toxicity)

10

Persistence and degradability

Components:

Terpineol:

Biodegradability : Biodegradation: 80 %

Exposure time: 28 d

Method: OECD Test Guideline 301 Remarks: Readily biodegradable.

Bis(2-butoxyethyl) ether:

Biodegradability : Result: rapidly biodegradable

Remarks: Information given is based on data obtained from

similar substances.

2-(2-Butoxyethoxy)ethanol:

Biodegradability : Biodegradation: 85 %

Exposure time: 28 d

Method: OECD Test Guideline 301C Remarks: Readily biodegradable.

Stoddard solvent (< 0.1% benzene):

Biodegradability : Result: Biodegradable

according to GB/T 16483 and GB/T 17519



5421E MICROMAX™ CONDUCTOR PASTE

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2024/04/12

 8.1
 2025/07/31
 300000002443
 Date of first issue: 2024/01/29

Method: OECD Test Guideline 301

Bioaccumulative potential

Components:

Silver Powder (particle diameter >100 nm <1mm):

Bioaccumulation : Remarks: Bioaccumulation is unlikely.

Information given is based on data obtained from similar

substances.

Partition coefficient: n-

octanol/water

Remarks: Not applicable

Terpineol:

Bioaccumulation : Bioconcentration factor (BCF): 24.13

Remarks: Bioaccumulation is unlikely.

Bis(2-butoxyethyl) ether:

Partition coefficient: n-

octanol/water

log Pow: 1.92

Ethyl cellulose:

Partition coefficient: n-

octanol/water

log Pow: 5.5

2-(2-Butoxyethoxy)ethanol:

Bioaccumulation : Remarks: Bioaccumulation is unlikely.

Partition coefficient: n-

log Pow: 1 (20 °C)

octanol/water

r pH: 7

Stoddard solvent (< 0.1% benzene):

Bioaccumulation : Remarks: The substance has the potential to bioaccumulate.

Partition coefficient: n-

octanol/water

log Pow: 3.5 - 6.4 (20 °C)

Mobility in soil

No data available

Other adverse effects

No data available

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : If recycling is not practicable, dispose of in compliance with

local regulations.

according to GB/T 16483 and GB/T 17519



5421E MICROMAX™ CONDUCTOR PASTE

Revision Date: SDS Number: Date of last issue: 2024/04/12 Version 2025/07/31 300000002443 Date of first issue: 2024/01/29 8.1

Do not reuse empty container. Never place unused product

down any indoor or out door drain.

Contaminated/not cleaned containers should be treated/handled like product waste. Dispose of container properly. Refer to applicable Local, State/Provincial, and Federal Regulations, as well as industry Standards.

14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number UN 3082

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, Proper shipping name

N.O.S.

(Silver)

Class 9 Packing group Ш 9 Labels Environmentally hazardous no

IATA-DGR

UN/ID No. UN 3082

Proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(Silver)

964

9 Class Packing group Ш

Miscellaneous Labels

Packing instruction (cargo

aircraft)

Packing instruction 964

(passenger aircraft)

IMDG-Code

UN number UN 3082

Proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(Silver)

Class 9 Ш Packing group Labels 9 EmS Code F-A, S-F Marine pollutant

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

GB 6944/12268

UN number UN 3082

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, Proper shipping name

N.O.S.

(Silver)

Class 9

according to GB/T 16483 and GB/T 17519



5421E MICROMAX™ CONDUCTOR PASTE

Version Revision Date: SDS Number: Date of last issue: 2024/04/12 8.1 2025/07/31 300000002443 Date of first issue: 2024/01/29

Packing group : III Labels : 9 Marine pollutant : no

JT/T 617

UN number : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

Class : 9
Packing group : III
Labels : 9
Environmentally hazardous : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

15. REGULATORY INFORMATION

National regulatory information

Law on the Prevention and Control of Occupational Diseases

Regulations on Safety Management of Hazardous Chemicals

Catalogue of Hazardous Chemicals : This product is not listed in the

catalogue of hazardous chemicals and it does not meet the definition of

hazardous chemicals and its principles of determination.

Identification of Major Hazard Installations for Hazardous Chemicals (GB : Not listed

18218)

Hazardous Chemicals for Priority Management under : Listed

SAWS

Catalogue of Specially Controlled Hazardous : Not listed

Chemicals

List of Explosive Precursors : Listed

Regulations on Labour Protection in Workplaces where Toxic Substances are Used

Catalogue of Highly Toxic Chemicals : Not listed

Regulation of Environmental Management on the First Import of Chemicals and the Import and Export of Toxic Chemicals

China Severely Restricted Toxic Chemicals for Import : Not listed

and Export

Regulation on the Administration of Precursor Chemicals

Catalogue and Classification of Precursor Chemicals : Not listed

according to GB/T 16483 and GB/T 17519



5421E MICROMAX™ CONDUCTOR PASTE

Version Revision Date: SDS Number: Date of last issue: 2024/04/12 8.1 2025/07/31 300000002443 Date of first issue: 2024/01/29

Regulations on the Administration of Controlled Chemicals

List of Controlled Chemicals : Not listed

Regulations of Ozone Depleting Substances Management

List of Controlled Ozone Depleting Substances : Not listed

List of Controlled Ozone Depleting Substances Import : Not listed

and Export

Environmental Protection Law

List of Priority Controlled Chemicals : Listed

List of Key Controlled New Pollutants : Not listed

16. OTHER INFORMATION

Revision Date : 2025/07/31

Date format : yyyy/mm/dd

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

CN OEL : Occupational exposure limits for hazardous agents in the

workplace - Chemical hazardous agents.

ACGIH / TWA : 8-hour, time-weighted average

CN OEL / PC-TWA : Permissible concentration - time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National

according to GB/T 16483 and GB/T 17519



5421E MICROMAX™ CONDUCTOR PASTE

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2024/04/12

 8.1
 2025/07/31
 300000002443
 Date of first issue: 2024/01/29

Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CN / EN