

8455 MICROMAX™ CONDUCTOR PASTE

Version Revision Date: SDS Number: Date of last issue: 09-25-2024 12.0 07-24-2025 300000002347 Date of first issue: 01-29-2024

SECTION 1. IDENTIFICATION

Product name : 8455 MICROMAX™ CONDUCTOR PASTE

Product code : 00000000027046805

Manufacturer or supplier's details

Company name of supplier : Celanese Ltd. Irving Texas

Address : 222 West Las Colinas Boulevard Suite 900N

Irving TX 75039

Telephone : '+1 972-443-4000

Emergency telephone : DOMESTIC NORTH AMERICA: 800-424-9300

number INTERNATIONAL, CALL +1 703-527-3887 (collect calls

accepted)

Recommended use of the chemical and restrictions on use

Recommended use : For industrial use only.

Paste for electronic industry

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids : Category 4

- single exposure (Oral)

Specific target organ toxicity : Category 1 (Eyes, Central nervous system)

Other hazards

None known.

GHS label elements

Hazard pictograms :

Signal word : Danger

Hazard statements : H227 Combustible liquid.

H370 Causes damage to organs (Eyes, Central nervous

system) if swallowed.

Precautionary statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking. P260 Do not breathe mist or vapours. P264 Wash skin thoroughly after handling.



8455 MICROMAX™ CONDUCTOR PASTE

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09-25-2024

 12.0
 07-24-2025
 300000002347
 Date of first issue: 01-29-2024

P270 Do not eat, drink or smoke when using this product.
P280 Wear protective gloves/ protective clothing/ eye protection/

face protection/ hearing protection.

Response:

P370 + P378 In case of fire: Use dry sand, dry chemical or

alcohol-resistant foam to extinguish.

Storage:

P403 Store in a well-ventilated place.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

| Chemical name | CAS-No. | Concentration (% w/w) |
|---------------------------------------|------------|-----------------------|
| Silver Powder (particle diameter >100 | 7440-22-4 | >= 60 - < 70 |
| nm <1mm) | | |
| (2-Methoxymethylethoxy)propanol | 34590-94-8 | >= 10 - < 20 |
| 2-(2-Butoxyethoxy)ethanol | 112-34-5 | >= 1 - < 10 |
| 2-(2-Ethoxyethoxy)ethyl acetate | 112-15-2 | >= 1 - < 10 |
| Methanol | 67-56-1 | >= 1 - < 10 |

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4. FIRST AID MEASURES

If inhaled : If inhaled, remove to fresh air.

If breathing is difficult, give oxygen.
If not breathing, give artificial respiration.

Get medical attention.

In case of skin contact : Wash off with soap and water.

Get medical attention if irritation develops and persists.

Wash contaminated clothing before re-use.

In case of eye contact : Immediately flush eyes for at least 15 minutes. Get medical

attention.



8455 MICROMAX™ CONDUCTOR PASTE

Version Revision Date: SDS Number: Date of last issue: 09-25-2024
12.0 07-24-2025 300000002347 Date of first issue: 01-29-2024

If swallowed : If swallowed

Rinse mouth with water.

Call a physician or poison control centre immediately.

DO NOT induce vomiting unless directed to do so by a

physician or poison control center.

Most important symptoms and effects, both acute and

delayed

Causes damage to organs if swallowed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Dry sand Dry chemical

Alcohol-resistant foam

Specific hazards during

firefighting

Hazardous decomposition products formed under fire

conditions.

(see also section 10)

Avoid breathing decomposition products.

Further information : Evacuate personnel to safe areas.

Stop spill/release if it can be done with minimal risk.

Do not allow run-off from fire fighting to enter drains or water

courses.

Special protective equipment:

for firefighters

Exposure to decomposition products may be a hazard to

health.

Wear self-contained breathing apparatus for firefighting if

necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures Avoid contact with skin, eyes and clothing.

Ensure adequate ventilation.

Wear suitable protective equipment.

Dispose of in accordance with local regulations.

Environmental precautions : Prevent further leakage or spillage if safe to do so.

Prevent product from entering drains.

Clean contaminated floors and objects thoroughly while

observing environmental regulations.

Methods and materials for

containment and cleaning up

Contain spill.

Soak up with inert absorbent material.



8455 MICROMAX™ CONDUCTOR PASTE

Version Revision Date: SDS Number: Date of last issue: 09-25-2024
12.0 07-24-2025 300000002347 Date of first issue: 01-29-2024

Collect and contain contaminated absorbent and dike material

for disposal.

Keep in suitable, closed containers for disposal.

Ventilate the area.

Clean contaminated surface thoroughly.

SECTION 7. HANDLING AND STORAGE

Advice on protection against :

fire and explosion

Avoid formation of dust and aerosols.

Keep away from heat and sources of ignition.

Advice on safe handling : Avoid inhalation, ingestion and contact with skin and eyes.

Do not use in areas without adequate ventilation.

Keep container closed when not in use.

Take care to avoid waste and spillage when weighing, loading

and mixing the product.

Conditions for safe storage : Store in original container.

Keep containers tightly closed in a dry, cool and well-

ventilated place.

Keep away from sources of ignition - No smoking. Do not store or consume food, drink or tobacco in areas where they may become contaminated with this material.

Keep container closed when not in use.

Do not reuse empty container.

Further information on

storage stability

Stable under normal conditions.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible | Basis |
|--|------------|-------------------------------------|----------------------------------|-----------|
| Cilver Douder (partials | 7440-22-4 | TWA (Dust | concentration | ACGIH |
| Silver Powder (particle diameter >100 nm <1mm) | 7440-22-4 | and fume) | 0.1 mg/m3 | ACGIH |
| | | TWA (Dust) | 0.01 mg/m3 | NIOSH REL |
| | | TWA | 0.01 mg/m3 | OSHA P0 |
| (2- Methoxymethylethoxy)propano | 34590-94-8 | TWA | 100 ppm 600 mg/m3 | NIOSH REL |
| | | ST | 150 ppm 900 mg/m3 | NIOSH REL |
| | | TWA | 100 ppm 600 mg/m3 | OSHA Z-1 |
| | | TWA | 100 ppm 600 mg/m3 | OSHA P0 |
| | | STEL | 150 ppm 900 mg/m3 | OSHA P0 |
| | | TWA | 50 ppm | ACGIH |
| 2-(2-Butoxyethoxy)ethanol | 112-34-5 | TWA | 10 ppm | ACGIH |



8455 MICROMAX™ CONDUCTOR PASTE

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09-25-2024

 12.0
 07-24-2025
 300000002347
 Date of first issue: 01-29-2024

| | | (Inhalable fraction and vapor) | | |
|----------|---------|--------------------------------|----------------------|-----------|
| Methanol | 67-56-1 | TWA | 200 ppm | ACGIH |
| | | STEL | 250 ppm | ACGIH |
| | | TWA | 200 ppm 260 mg/m3 | NIOSH REL |
| | | ST | 250 ppm 325 mg/m3 | NIOSH REL |
| | | TWA | 200 ppm 260 mg/m3 | OSHA Z-1 |
| | | STEL | 250 ppm 325 mg/m3 | OSHA P0 |
| | | TWA | 200 ppm 260 mg/m3 | OSHA P0 |

Engineering measures

Local exhaust or a laboratory hood should be used when

handling the materials.

Maintain air concentrations below occupational exposure

standards.

Personal protective equipment

Respiratory protection

Provide adequate ventilation.

No personal respiratory protective equipment normally

required.

Where there is potential for airborne exposures in excess of applicable limits, wear approved respiratory protection with

dust/mist cartridge.

When workers are facing concentrations above the exposure

limit they must use appropriate certified respirators. Consult the respirator manufacturer to determine the appropriate type of equipment for a given application. Observe respirator use limitations specified by the

manufacturer.

Persons performing maintenance or repairs on exhaust system equipment (e.g. ducts) may need to use respirators

and protective clothing to prevent exposure to any

accumulated residues.

Hand protection

Material : Impervious gloves

Remarks : Gloves must be inspected prior to use. Gloves should be

discarded and replaced if there is any indication of degradation or chemical breakthrough. The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.



8455 MICROMAX™ CONDUCTOR PASTE

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09-25-2024

 12.0
 07-24-2025
 300000002347
 Date of first issue: 01-29-2024

Eye protection : Wear safety glasses with side shields.

Skin and body protection : Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to

the specific work-place.

Lightweight protective clothing

Safety shoes

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

Avoid contact with skin, eyes and clothing.

Contaminated work clothing should not be allowed out of the

workplace.

Remove contaminated clothing and protective equipment

before entering eating areas.

Remove and wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : viscous liquid

Colour : silver

Odour : solvent-like

pH : Substance/mixture is non-polar/aprotic.

Flash point : $154 \,^{\circ}\text{F} / 68 \,^{\circ}\text{C}$

Method: closed cup

Density : 2.56 g/cm³ (68 °F / 20 °C)

Solubility(ies)

Water solubility : slightly soluble (68 °F / 20 °C)

Viscosity

Viscosity, dynamic : 10 - 100 Pa.s (77 °F / 25 °C)

Viscosity, kinematic : > 20.5 mm2/s (104 °F / 40 °C)

estimated

SECTION 10. STABILITY AND REACTIVITY

Possibility of hazardous : Polymerization will not occur.

reactions Stable at normal temperatures and storage conditions.

Stable at normal temperatures and storage conditions.

Conditions to avoid : None reasonably foreseeable.



8455 MICROMAX™ CONDUCTOR PASTE

Version Revision Date: SDS Number: Date of last issue: 09-25-2024 12.0 07-24-2025 300000002347 Date of first issue: 01-29-2024

Incompatible materials : Acids

Hazardous decomposition

products

No decomposition if stored and applied as directed.

Under fire conditions:

Carbon monoxide, carbon dioxide and unburned

hydrocarbons (smoke).

Metal oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified due to lack of data.

Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 200 mg/l

Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

Components:

Silver Powder (particle diameter >100 nm <1mm):

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 401

Assessment: The substance or mixture has no acute oral

toxicity

Acute inhalation toxicity : LC50 (Rat): > 5.16 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 436

Assessment: The substance or mixture has no acute

inhalation toxicity

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

(2-Methoxymethylethoxy)propanol:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Assessment: The substance or mixture has no acute oral

toxicity



8455 MICROMAX™ CONDUCTOR PASTE

Version Revision Date: SDS Number: Date of last issue: 09-25-2024
12.0 07-24-2025 300000002347 Date of first issue: 01-29-2024

Acute inhalation toxicity : Assessment: The substance or mixture has no acute

inhalation toxicity

Remarks: An LC50/inhalation/4h/rat could not be determined because no mortality of rats was observed at the maximum

achievable concentration.

Acute dermal toxicity : LD50 (Rabbit): 9,510 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: Skin effects

2-(2-Butoxyethoxy)ethanol:

Acute oral toxicity : LD50 (Mouse): 2,410 mg/kg

Method: OECD Test Guideline 401 Target Organs: Central nervous system

Remarks: narcosis

Acute inhalation toxicity : Remarks: An LC50/inhalation/4h/rat could not be determined

because no mortality of rats was observed at the maximum

achievable concentration.

Acute dermal toxicity : LD50 (Rabbit): 2,764 mg/kg

Method: OECD Test Guideline 402

2-(2-Ethoxyethoxy)ethyl acetate:

Acute oral toxicity : LD50 (Rat): 11,000 mg/kg

Assessment: The substance or mixture has no acute oral

toxicity

Acute inhalation toxicity : Assessment: The substance or mixture has no acute

inhalation toxicity

Remarks: An LC50/inhalation/4h/rat could not be determined because no mortality of rats was observed at the maximum

achievable concentration.

Acute dermal toxicity : LD50 (Rabbit): 15,300 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Methanol:

Acute oral toxicity : Acute toxicity estimate: 100 mg/kg

Assessment: The component/mixture is toxic after single

ingestion.

Remarks: central nervous system effects

narcosis eye effects

Acute inhalation toxicity : Acute toxicity estimate: 3 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Assessment: The component/mixture is toxic after short term

inhalation.

Remarks: central nervous system effects



8455 MICROMAX™ CONDUCTOR PASTE

Version Revision Date: SDS Number: Date of last issue: 09-25-2024 12.0 07-24-2025 300000002347 Date of first issue: 01-29-2024

> narcosis eye effects

Acute dermal toxicity : Acute toxicity estimate: 300 mg/kg

Assessment: The component/mixture is toxic after single

contact with skin.

Remarks: central nervous system effects

narcosis eye effects

Skin corrosion/irritation

Not classified due to lack of data.

Components:

Silver Powder (particle diameter >100 nm <1mm):

Species : Rabbit

Assessment : No skin irritation

Method : OECD Test Guideline 404
Result : Slight or no skin irritation

Remarks : Minimal effects that do not meet the threshold for

classification.

(2-Methoxymethylethoxy)propanol:

Species : Rabbit

Assessment : No skin irritation

Method : OECD Test Guideline 404

Result : No skin irritation

2-(2-Butoxyethoxy)ethanol:

Species : Rabbit

Assessment : Not classified as irritant
Method : OECD Test Guideline 404

Result : No skin irritation

2-(2-Ethoxyethoxy)ethyl acetate:

Species : Rabbit

Assessment : No skin irritation

Method : OECD Test Guideline 404

Result : No skin irritation

Remarks : Minimal effects that do not meet the threshold for

classification.

Methanol:

Species : Rabbit

Assessment : No skin irritation Result : No skin irritation

Serious eye damage/eye irritation

Not classified due to lack of data.



8455 MICROMAX™ CONDUCTOR PASTE

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09-25-2024

 12.0
 07-24-2025
 300000002347
 Date of first issue: 01-29-2024

Components:

Silver Powder (particle diameter >100 nm <1mm):

Species : Rabbit

Result : No eye irritation
Assessment : No eye irritation

Method : OECD Test Guideline 405

(2-Methoxymethylethoxy)propanol:

Species : Human

Result : Slight or no eye irritation

Assessment : No eye irritation

Remarks : Minimal effects that do not meet the threshold for

classification.

2-(2-Butoxyethoxy)ethanol:

Species : Rabbit
Result : Eye irritation
Assessment : Irritating to eyes.

Method : OECD Test Guideline 405

2-(2-Ethoxyethoxy)ethyl acetate:

Species : Rabbit

Result : Irritation to eyes, reversing within 7 days

Assessment : Mild eye irritation

Methanol:

Species : Rabbit

Result : Slight or no eye irritation

Assessment : No eye irritation

Remarks : Slight irritation observed but insufficient to warrant

classification

Respiratory or skin sensitisation

Skin sensitisation

Not classified due to lack of data.

Respiratory sensitisation

Not classified due to lack of data.

Components:

Silver Powder (particle diameter >100 nm <1mm):

Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : US EPA Test Guideline OPPTS 870.2600

Result : Does not cause skin sensitisation.

Remarks : Information given is based on data obtained from similar

substances.



8455 MICROMAX™ CONDUCTOR PASTE

Version Revision Date: SDS Number: Date of last issue: 09-25-2024
12.0 07-24-2025 300000002347 Date of first issue: 01-29-2024

(2-Methoxymethylethoxy)propanol:

Species : Human

Assessment : Does not cause skin sensitisation.
Result : Does not cause skin sensitisation.

2-(2-Butoxyethoxy)ethanol:

Species : Mouse

Assessment : Does not cause respiratory sensitisation.
Result : Does not cause respiratory sensitisation.

Test Type : Maximisation Test

Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

Result : Does not cause skin sensitisation.

2-(2-Ethoxyethoxy)ethyl acetate:

Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

Result : Does not cause skin sensitisation.

Methanol:

Test Type : Maximisation Test

Species : Guinea pig

Assessment : Does not cause skin sensitisation.
Result : Does not cause skin sensitisation.

Germ cell mutagenicity

Not classified due to lack of data.

Components:

(2-Methoxymethylethoxy)propanol:

Germ cell mutagenicity -

Assessment

Tests on bacterial or mammalian cell cultures did not show

mutagenic effects., Animal testing did not show any mutagenic

effects.

2-(2-Butoxyethoxy)ethanol:

Germ cell mutagenicity -

Assessment

Tests on bacterial or mammalian cell cultures did not show

mutagenic effects., Animal testing did not show any mutagenic

effects.

2-(2-Ethoxyethoxy)ethyl acetate:

Germ cell mutagenicity -

Assessment

Animal testing did not show any mutagenic effects., Tests on bacterial or mammalian cell cultures did not show mutagenic

effects.

Methanol:

Germ cell mutagenicity -

Assessment

Weight of evidence does not support classification as a germ

cell mutagen., Animal testing did not show any mutagenic



8455 MICROMAX™ CONDUCTOR PASTE

Version **Revision Date:** SDS Number: Date of last issue: 09-25-2024 07-24-2025 300000002347 Date of first issue: 01-29-2024 12.0

> effects., Genetic damage in cultured mammalian cells was observed in some laboratory tests but not in others., Did not cause genetic damage in cultured mammalian cells.

Carcinogenicity

Not classified due to lack of data.

Components:

(2-Methoxymethylethoxy)propanol:

Carcinogenicity -Animal testing did not show any carcinogenic effects... Assessment Information given is based on data obtained from similar

substances.

2-(2-Butoxyethoxy)ethanol:

Carcinogenicity -Not classifiable as a human carcinogen.

Assessment

Methanol:

Carcinogenicity -Not classifiable as a human carcinogen., Overall weight of Assessment evidence indicates that the substance is not carcinogenic.

IARC No component of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified due to lack of data.

Components:

(2-Methoxymethylethoxy)propanol:

Reproductive toxicity -No toxicity to reproduction, Animal testing showed no Assessment

reproductive toxicity., No effects on or via lactation, Information given is based on data obtained from similar

substances.

Animal testing showed no developmental toxicity.

2-(2-Butoxyethoxy)ethanol:

No toxicity to reproduction, Animal testing showed no Reproductive toxicity -

Assessment reproductive toxicity.

Animal testing showed no developmental toxicity.

2-(2-Ethoxyethoxy)ethyl acetate:

Reproductive toxicity -No toxicity to reproduction, Animal testing showed no

Assessment reproductive toxicity., No effects on or via lactation,

Information given is based on data obtained from similar



8455 MICROMAX™ CONDUCTOR PASTE

Version Revision Date: SDS Number: Date of last issue: 09-25-2024 12.0 07-24-2025 300000002347 Date of first issue: 01-29-2024

substances.

Animal testing showed no developmental toxicity., Information given is based on data obtained from similar substances.

Methanol:

Reproductive toxicity -

Assessment

No toxicity to reproduction, Evidence suggests the substance

is not a reproductive toxin in animals.

Evidence suggests the substance is not a developmental toxin

in animals.

STOT - single exposure

Causes damage to organs (Eyes, Central nervous system) if swallowed.

Components:

(2-Methoxymethylethoxy)propanol:

Assessment : The substance or mixture is not classified as specific target

organ toxicant, single exposure.

2-(2-Butoxyethoxy)ethanol:

Target Organs : Central nervous system

Assessment : The substance or mixture is classified as specific target organ

toxicant, single exposure, category 3 with narcotic effects.

2-(2-Ethoxyethoxy)ethyl acetate:

Assessment : The substance or mixture is not classified as specific target

organ toxicant, single exposure.

Methanol:

Exposure routes : Oral

Target Organs : Eyes, Central nervous system

Assessment : The substance or mixture is classified as specific target organ

toxicant, single exposure, category 1.

STOT - repeated exposure

Not classified due to lack of data.

Components:

(2-Methoxymethylethoxy)propanol:

Assessment : The substance or mixture is not classified as specific target

organ toxicant, repeated exposure.

2-(2-Butoxyethoxy)ethanol:

Assessment : The substance or mixture is not classified as specific target

organ toxicant, repeated exposure.

2-(2-Ethoxyethoxy)ethyl acetate:

Assessment : The substance or mixture is not classified as specific target

organ toxicant, repeated exposure.



8455 MICROMAX™ CONDUCTOR PASTE

Version Revision Date: SDS Number: Date of last issue: 09-25-2024 12.0 07-24-2025 300000002347 Date of first issue: 01-29-2024

Methanol:

Assessment : The substance or mixture is not classified as specific target

organ toxicant, repeated exposure.

Repeated dose toxicity

Components:

(2-Methoxymethylethoxy)propanol:

Species : Rat

NOAEL : 1,000 mg/kg
Application Route : Ingestion
Exposure time : 28 d

Remarks : No toxicologically significant effects were found.

Species : Rat
Application Route : Inhalation
Test atmosphere : vapour
Exposure time : 90 d

Method : OECD Test Guideline 413

Remarks : No toxicologically significant effects were found.

Species : Rabbit
NOAEL : 2,850 mg/kg
Application Route : Skin contact

Exposure time : 90 d

Method : OECD Test Guideline 411

Remarks : No toxicologically significant effects were found.

2-(2-Butoxyethoxy)ethanol:

Species : Rat
Application Route : Dermal
Remarks : Skin irritation

Species : Rat Application Route : Oral

Remarks : Spleen effects

Organ weight changes

Liver effects kidney effects

Species : Rat
Application Route : Inhalation
Remarks : Liver effects

lung effects

2-(2-Ethoxyethoxy)ethyl acetate:

Species : Rat
NOAEL : 250 mg/kg
Application Route : Ingestion
Exposure time : 90 d

Method : OECD Test Guideline 408

Remarks : No toxicologically significant effects were found.

Information given is based on data obtained from similar



8455 MICROMAX™ CONDUCTOR PASTE

Version Revision Date: SDS Number: Date of last issue: 09-25-2024 12.0 07-24-2025 300000002347 Date of first issue: 01-29-2024

substances.

Species : Rat
Application Route : Inhalation
Test atmosphere : dust/mist
Exposure time : 28 d

Remarks : No toxicologically significant effects were found.

Information given is based on data obtained from similar

substances.

Methanol:

Species : Monkey
Application Route : Inhalation
Test atmosphere : vapour
Exposure time : 29 Months

Remarks : No toxicological effects warranting significant target organ

toxicity classification were seen below the recommended

guidance values for classification.

Aspiration toxicity

Not classified due to lack of data.

Components:

Silver Powder (particle diameter >100 nm <1mm):

No aspiration toxicity classification

(2-Methoxymethylethoxy)propanol:

No aspiration toxicity classification

2-(2-Butoxyethoxy)ethanol:

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

2-(2-Ethoxyethoxy)ethyl acetate:

No aspiration toxicity classification

Methanol:

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Silver Powder (particle diameter >100 nm <1mm):

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 0.016 mg/l

Exposure time: 96 h

Remarks: Information given is based on data obtained from



8455 MICROMAX™ CONDUCTOR PASTE

Version Revision Date: SDS Number: Date of last issue: 09-25-2024 12.0 07-24-2025 300000002347 Date of first issue: 01-29-2024

similar substances.

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 0.0125 mg/l

Exposure time: 48 h

Remarks: Information given is based on data obtained from

similar substances.

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 0.19

mg/l

Exposure time: 96 h

Remarks: Information given is based on data obtained from

similar substances.

EC10 (Pseudokirchneriella subcapitata (green algae)):

0.03462 mg/l

Exposure time: 72 h

Remarks: Information given is based on data obtained from

similar substances.

Toxicity to fish (Chronic

toxicity)

NOEC (Oncorhynchus mykiss (rainbow trout)): 0.0012 mg/l

Exposure time: 32 d

Remarks: Information given is based on data obtained from

similar substances.

Toxicity to daphnia and other :

aquatic invertebrates (Chronic toxicity)

NOEC (Daphnia magna (Water flea)): 0.00327 mg/l

Exposure time: 21 d

Remarks: Information given is based on data obtained from

similar substances.

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

(2-Methoxymethylethoxy)propanol:

Toxicity to fish : LC50 (Poecilia reticulata (guppy)): > 1,000 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): Exposure time: 48 h

Method: OECD Test Guideline 202

Remarks: Aquatic toxicity is unlikely due to low solubility.

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): > 969

mg/l

Exposure time: 96 h

Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 969

mg/l

Exposure time: 96 h

Method: OECD Test Guideline 201



8455 MICROMAX™ CONDUCTOR PASTE

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09-25-2024

 12.0
 07-24-2025
 300000002347
 Date of first issue: 01-29-2024

Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

2-(2-Butoxyethoxy)ethanol:

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 1,300 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Method: Directive 67/548/EEC, Annex V, C.2.

Toxicity to algae/aquatic

plants

ErC50 (Desmodesmus subspicatus (green algae)): > 100 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 201

NOEC (Desmodesmus subspicatus (green algae)): > 100 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 201

2-(2-Ethoxyethoxy)ethyl acetate:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 100 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

LC50 (Daphnia magna (Water flea)): 143 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

EC50 (algae): 110.2 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 300

mg/l

Exposure time: 72 h Method: ISO 8692

Remarks: Information given is based on data obtained from

similar substances.

Toxicity to fish (Chronic

toxicity)

NOEC (Fish (unspecified species)): 28.64 mg/l

Exposure time: 28 d

Toxicity to daphnia and other :

aquatic invertebrates (Chronic toxicity)

NOEC (Daphnia magna (Water flea)): 102 mg/l

Exposure time: 21 d

Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : This product has no known ecotoxicological effects.



8455 MICROMAX™ CONDUCTOR PASTE

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09-25-2024

 12.0
 07-24-2025
 300000002347
 Date of first issue: 01-29-2024

Methanol:

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 15,400 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia (water flea)): 18,260 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

LC50 (Selenastrum capricornutum (green algae)): 22,000 mg/l

Exposure time: 96 h

Toxicity to fish (Chronic

toxicity)

NOEC (Pimephales promelas (fathead minnow)): 446 mg/l

Exposure time: 28 d

Toxicity to daphnia and other : aquatic invertebrates

(Chronic toxicity)

NOEC (Daphnia magna (Water flea)): 208 mg/l

Exposure time: 21 d

Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

Persistence and degradability

Components:

(2-Methoxymethylethoxy)propanol:

Biodegradability : Result: Biodegradable

Method: OECD Test Guideline 301 Remarks: Readily biodegradable.

2-(2-Butoxyethoxy)ethanol:

Biodegradability : Biodegradation: 85 %

Exposure time: 28 d

Method: OECD Test Guideline 301C Remarks: Readily biodegradable.

2-(2-Ethoxyethoxy)ethyl acetate:

Biodegradability : Result: Biodegradable

Methanol:

Biodegradability : Result: Biodegradable

Remarks: Readily biodegradable.

Bioaccumulative potential

Components:

Silver Powder (particle diameter >100 nm <1mm):

Bioaccumulation : Remarks: Bioaccumulation is unlikely.

Information given is based on data obtained from similar

substances.



8455 MICROMAX™ CONDUCTOR PASTE

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09-25-2024

 12.0
 07-24-2025
 300000002347
 Date of first issue: 01-29-2024

Partition coefficient: n-

octanol/water

Remarks: Not applicable

(2-Methoxymethylethoxy)propanol:

Partition coefficient: n- : log Pow: 0.004 (77 °F / 25 °C)

octanol/water pH: 7.5 - 7.7

2-(2-Butoxyethoxy)ethanol:

Bioaccumulation : Remarks: Bioaccumulation is unlikely.

Partition coefficient: n- : log Pow: 1 (68 °F / 20 °C)

octanol/water pH: 7

2-(2-Ethoxyethoxy)ethyl acetate:

Bioaccumulation : Remarks: Bioaccumulation is unlikely.

Partition coefficient: n- : log Pow: 0.74 (104 °F / 40 °C)

octanol/water pH: 8.3

Methanol:

Bioaccumulation : Remarks: Bioaccumulation is unlikely.

Partition coefficient: n-

octanol/water

log Pow: -0.77 (68 °F / 20 °C)

Mobility in soil
No data available

Other adverse effects

Product:

Additional ecological

information

No data is available on the product itself.

Components:

Methanol:

Results of PBT and vPvB

assessment

The substance does not meet the criteria for PBT / vPvB

according to REACH, Annex XIII

Endocrine disrupting

potential

Substance does not have endocrine disrupting properties.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : If recycling is not practicable, dispose of in compliance with

local regulations.

Do not reuse empty container. Never place unused product



8455 MICROMAX™ CONDUCTOR PASTE

Version Revision Date: SDS Number: Date of last issue: 09-25-2024
12.0 07-24-2025 300000002347 Date of first issue: 01-29-2024

down any indoor or out door drain.

Contaminated/not cleaned containers should be treated/handled like product waste. Dispose of container properly. Refer to applicable Local, State/Provincial, and Federal Regulations, as well as industry Standards.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(Silver)

Class : 9
Packing group : III
Labels : 9
Environmentally hazardous : no

IATA-DGR

UN/ID No. : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(Silver)

Class : 9 Packing group : III

Labels : Miscellaneous

Packing instruction (cargo : 964

aircraft)

Packing instruction : 964

(passenger aircraft)

IMDG-Code

UN number : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(Silver)

Class : 9
Packing group : III
Labels : 9
EmS Code : F-A, S-F
Marine pollutant : no

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

National Regulations

49 CFR

Not regulated as a dangerous good

Special precautions for user

Remarks : Regulated by DOT/49CFR as Combustible Liquid when

transported in a bulk package (>=119 gallons(450 litres))., Not

regulated by DOT in non-bulk package.

Marine Pollutants assigned UN number 3077 and 3082 in single or combination packaging containing a net quantity per



8455 MICROMAX™ CONDUCTOR PASTE

Version Revision Date: SDS Number: Date of last issue: 09-25-2024 12.0 07-24-2025 300000002347 Date of first issue: 01-29-2024

single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 KG or less for solids may be transported as non-dangerous goods as provided in section 2.10.2.7 of IMDG code, IATA special provision A197, and ADR/RID special provision 375.

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)

Specific target organ toxicity (single or repeated exposure)

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

Silver Powder 7440-22-4

(particle diameter >100 nm <1mm)

2-(2- 112-34-5

Butoxyethoxy)eth

anol

2-(2- 112-15-2

Ethoxyethoxy)eth

yl acetate

Methanol 67-56-1

California Prop. 65

WARNING: This product can expose you to chemicals including Formaldehyde, which is/are known to the State of California to cause cancer, and

Methanol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

TSCA list

In compliance with TSCA-active Inventory requirements for commercial purposes.

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations



8455 MICROMAX™ CONDUCTOR PASTE

Version Revision Date: SDS Number: Date of last issue: 09-25-2024
12.0 07-24-2025 300000002347 Date of first issue: 01-29-2024

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA PO : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated

values)

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1

Limits for Air Contaminants

ACGIH / TWA : 8-hour, time-weighted average ACGIH / STEL : Short-term exposure limit

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded

at any time during a workday

OSHA P0 / TWA : 8-hour time weighted average OSHA P0 / STEL : Short-term exposure limit OSHA Z-1 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials: bw - Body weight: CERCLA - Comprehensive Environmental Response. Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL -Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS -Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS -Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration: NO(A)EL - No Observed (Adverse) Effect Level: NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 07-24-2025

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a



8455 MICROMAX™ CONDUCTOR PASTE

Version Revision Date: SDS Number: Date of last issue: 09-25-2024 12.0 07-24-2025 300000002347 Date of first issue: 01-29-2024

guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN

