

Product Name: SANTOPRENE™ TPV DEVELOPMENTAL GRADE (RESIN CURED)

Revision Date: 13 Oct 2021

Page 1 of 12

## SAFETY DATA SHEET

### SECTION 1 PRODUCT AND COMPANY IDENTIFICATION

#### PRODUCT

**Product Name:** SANTOPRENE™ TPV DEVELOPMENTAL GRADE (RESIN CURED)

**Product Description:** Elastomer

**Intended Use:** Automotive Application

#### COMPANY IDENTIFICATION

**Supplier:** Celanese Sales U.S Ltd.  
222 West Las Colinas Boulevard Suite 900N  
TX 75039 Irving

**Email Address of the person responsible  
for the SDS:**

HazCom@celanese.com

**Telephone number:**

+1 972-443-4000

**Emergency Telephone number**

Domestic North America: 800-424-9300 International Call  
+1 703-527-3887 (Collect calls accepted)

### SECTION 2 HAZARDS IDENTIFICATION

This material is hazardous according to regulatory guidelines (see (M)SDS Section 15).

#### CLASSIFICATION:

Combustible Dust

#### LABEL:

**Pictogram:** No Pictogram

**Signal Word:** Warning

#### Hazard Statements:

May form combustible dust concentrations in air.

#### Other hazard information:

**HAZARD NOT OTHERWISE CLASSIFIED (HNOC):** None as defined under 29 CFR 1910.1200.

#### PHYSICAL / CHEMICAL HAZARDS

WARNING: May form combustible dust concentrations in air (during processing/handling). Thermal burn hazard - contact with hot material may cause thermal burns. Spilled pellets present a slipping hazard on hard

Product Name: SANTOPRENE™ TPV DEVELOPMENTAL GRADE (RESIN CURED)

Revision Date: 13 Oct 2021

Page 2 of 12

surfaces.

#### HEALTH HAZARDS

If dust is generated, it could scratch the eyes and cause minor irritation to the respiratory tract. When heated, the vapors/fumes given off may cause respiratory tract irritation.

#### ENVIRONMENTAL HAZARDS

No significant hazards.

|                        |           |                 |               |
|------------------------|-----------|-----------------|---------------|
| <b>NFPA Hazard ID:</b> | Health: 1 | Flammability: 1 | Reactivity: 0 |
| <b>HMIS Hazard ID:</b> | Health: 1 | Flammability: 1 | Reactivity: 0 |

### SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

This material is defined as a mixture.

#### Hazardous Substance(s) or Complex Substance(s) required for disclosure

| Name           | CAS#      | Concentration* | GHS Hazard Codes                                                     |
|----------------|-----------|----------------|----------------------------------------------------------------------|
| CARBON BLACK   | 1333-86-4 | 0 - 4%         | None                                                                 |
| TIN DICHLORIDE | 7772-99-8 | 0 - 0.5%       | H290, H302, H317, H332, H335, H314(1B), H373, H400(M factor 1), H412 |
| ZINC OXIDE     | 1314-13-2 | 0.1 - < 1%     | H400(M factor 1), H410(M factor 1)                                   |

\* All concentrations are percent by weight unless material is a gas. Gas concentrations are in percent by volume.

NOTE: The product may contain varying levels of additives such as slip and antiblocking agents, antioxidants and stabilizers. This material is supplied for limited use only for purposes of experimental research and development. It should not be used for commercial purposes or be made available except in small quantities. The material must be used by or under the supervision of a technically qualified person. The toxicological properties of this product may not have been fully investigated. The substances in the above table are components of one or more, but not all product grades.

As per paragraph (i) of 29 CFR 1910.1200, formulation is considered a trade secret and specific chemical identity and exact percentage (concentration) of composition may have been withheld. Specific chemical identity and exact percentage composition will be provided to health professionals, employees, or designated representatives in accordance with applicable provisions of paragraph (i).

### SECTION 4 FIRST AID MEASURES

#### INHALATION

At ambient/normal handling temperatures, no adverse effects due to inhalation of dust are expected. In case of adverse exposure to vapors and / or aerosols formed at elevated temperatures, immediately remove the affected victim from exposure. Administer artificial respiration if breathing is stopped. Keep at rest.

#### SKIN CONTACT

Wash contact areas with soap and water. For hot product: Immediately immerse in or flush affected area with

Product Name: SANTOPRENE™ TPV DEVELOPMENTAL GRADE (RESIN CURED)

Revision Date: 13 Oct 2021

Page 3 of 12

---

large amounts of cold water to dissipate heat. Cover with clean cotton sheeting or gauze and get prompt medical attention.

#### EYE CONTACT

Flush thoroughly with water for at least 15 minutes. Get medical assistance.

#### INGESTION

First aid is normally not required. Seek medical attention if discomfort occurs.

|                  |                               |
|------------------|-------------------------------|
| <b>SECTION 5</b> | <b>FIRE FIGHTING MEASURES</b> |
|------------------|-------------------------------|

#### EXTINGUISHING MEDIA

**Appropriate Extinguishing Media:** Use water fog, foam, dry chemical or carbon dioxide (CO<sub>2</sub>) to extinguish flames.

**Inappropriate Extinguishing Media:** Straight Streams of Water

#### FIRE FIGHTING

**Fire Fighting Instructions:** Assure an extended cooling down period to prevent re-ignition. Evacuate area. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply. Firefighters should use standard protective equipment and in enclosed spaces, self-contained breathing apparatus (SCBA). Use water spray to cool fire exposed surfaces and to protect personnel.

**Unusual Fire Hazards:** Explosion: Avoid generating dust; fine dust dispersed in air in sufficient concentration and in the presence of an ignition source is a potential dust explosion hazard.

**Hazardous Combustion Products:** Flammable hydrocarbons, Formaldehyde, Incomplete combustion products, Oxides of carbon, Smoke, Fume

#### FLAMMABILITY PROPERTIES

**Flash Point [Method]:** N/A

**Flammable Limits (Approximate volume % in air):** LEL: N/A UEL: N/A

**Autoignition Temperature:** N/A

|                  |                                    |
|------------------|------------------------------------|
| <b>SECTION 6</b> | <b>ACCIDENTAL RELEASE MEASURES</b> |
|------------------|------------------------------------|

#### NOTIFICATION PROCEDURES

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations. US regulations require reporting releases of this material to the environment which exceed the applicable reportable quantity or oil spills which could reach any waterway including intermittent dry creeks. The National Response Center can be reached at (800)424-8802.

#### PROTECTIVE MEASURES

Avoid contact with spilled material. Dust Deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration. Avoid dispersal of dust in the air (for example, clearing dust surfaces with compressed air). Prevent dust exposure to ignition sources. For example, use non-sparking tools and prohibit smoking, flares, sparks or flames in immediate area. See Section 5 for fire fighting information. See the Hazard Identification Section for Significant Hazards. See Section 4 for First Aid Advice. See Section 8 for advice on the minimum requirements for personal protective equipment. Additional protective measures may be necessary, depending on the specific

Product Name: SANTOPRENE™ TPV DEVELOPMENTAL GRADE (RESIN CURED)

Revision Date: 13 Oct 2021

Page 4 of 12

---

circumstances and/or the expert judgment of the emergency responders.

## **SPILL MANAGEMENT**

**Land Spill:** Spilled pellets present a slipping hazard on hard surfaces. Prevent dust cloud. Small Dry Spills: With clean shovel place material into clean, dry container and cover loosely; move containers from spill area.

**Water Spill:** Stop leak if you can do it without risk. Confine the spill immediately with booms. Warn other shipping. Skim from surface.

Water spill and land spill recommendations are based on the most likely spill scenario for this material; however, geographic conditions, wind, temperature, (and in the case of a water spill) wave and current direction and speed may greatly influence the appropriate action to be taken. For this reason, local experts should be consulted. Note: Local regulations may prescribe or limit action to be taken.

## **ENVIRONMENTAL PRECAUTIONS**

Prevent entry into waterways, sewers, basements or confined areas.

## **SECTION 7**

## **HANDLING AND STORAGE**

### **HANDLING**

Minimize dust generation and accumulation. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces. Dust from material can accumulate electrostatic charges due to friction from transfer and mixing operations and cause an electrical spark (ignition source). Provide adequate precautions to ignition sources, such as electrical grounding and bonding, inert atmosphere or non-sparking tools. However, bonding and grounds may not eliminate the hazard for static accumulation. Consult local applicable standards for guidance. Refer to NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids and EN 61241, Electrical Apparatus for Use in the Presence of Combustible Dust for safe handling. Avoid elevated temperatures for prolonged periods of time. Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area). Avoid vapors from heated materials to prevent exposure to potentially toxic/irritating fumes. Provide adequate ventilation if fumes or vapors are generated. Prevent small spills and leakage to avoid slip hazard. Care should be taken when storing and handling this product. Apart from the specific nature of the polymer product, conditions such as humidity, sunlight, and temperature have an influence on the way the product behaves during storage and handling. Special attention should be paid to avoid inappropriate stacking of palletized bags or other package units. Indeed, polymer products may be dimensionally unstable under certain conditions. Avoid conditions generating heat during transfer operations.

**Loading/Unloading Temperature:** [Ambient]

**Transport Temperature:** [Ambient]

**Transport Pressure:** [Ambient]

**Static Accumulator:** This material is not a static accumulator.

### **STORAGE**

Store in a cool, dry place. Do not store in open or unlabelled containers.

**Storage Temperature:** [Ambient]

**Storage Pressure:** [Ambient]

**Suitable Containers/Packing:** Bags (20/25kg); Boxes

Product Name: SANTOPRENE™ TPV DEVELOPMENTAL GRADE (RESIN CURED)

Revision Date: 13 Oct 2021

Page 5 of 12

**Suitable Materials and Coatings (Chemical Compatibility):** Polyethylene; Aluminum

## SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

### EXPOSURE LIMIT VALUES

Exposure limits/standards (Note: Exposure limits are not additive)

| Substance Name         | Form                  | Limit / Standard |           |  | NOTE | Source  |
|------------------------|-----------------------|------------------|-----------|--|------|---------|
| CARBON BLACK           |                       | TWA              | 3.5 mg/m3 |  | N/A  | OSHA Z1 |
| CARBON BLACK           | Inhalable fraction.   | TWA              | 3 mg/m3   |  | N/A  | ACGIH   |
| POLYMER DUST           | Respirable fraction.  | TWA              | 5 mg/m3   |  | N/A  | OSHA Z1 |
| POLYMER DUST           | Total dust.           | TWA              | 15 mg/m3  |  | N/A  | OSHA Z1 |
| POLYMER DUST           | Inhalable particles.  | TWA              | 10 mg/m3  |  | N/A  | ACGIH   |
| POLYMER DUST           | Respirable particles. | TWA              | 3 mg/m3   |  | N/A  | ACGIH   |
| TIN DICHLORIDE [as Sn] |                       | TWA              | 2 mg/m3   |  | N/A  | OSHA Z1 |
| TIN DICHLORIDE [as Sn] | Inhalable fraction.   | TWA              | 2 mg/m3   |  | N/A  | ACGIH   |
| ZINC OXIDE             | Fume.                 | TWA              | 5 mg/m3   |  | N/A  | OSHA Z1 |
| ZINC OXIDE             | Respirable fraction.  | TWA              | 5 mg/m3   |  | N/A  | OSHA Z1 |
| ZINC OXIDE             | Total dust.           | TWA              | 15 mg/m3  |  | N/A  | OSHA Z1 |
| ZINC OXIDE             | Respirable fraction.  | STEL             | 10 mg/m3  |  | N/A  | ACGIH   |
| ZINC OXIDE             | Respirable fraction.  | TWA              | 2 mg/m3   |  | N/A  | ACGIH   |

NOTE: Limits/standards shown for guidance only. Follow applicable regulations.

No biological limits allocated.

### ENGINEERING CONTROLS

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Control measures to consider:

Adequate ventilation should be provided so that exposure limits are not exceeded. **SPECIAL PRECAUTIONS:** Should significant vapors/fumes be generated during thermal processing of this product, it is recommended that work stations be monitored for the presence of thermal degradation by-products which may evolve at elevated temperatures (for example, oxygenated components). Processors of this product should assure that adequate ventilation or other controls are used to control exposure. It is recommended that the current ACGIH-TLVs for thermal degradation by-products be observed. Contact your local sales representative for further information. It is recommended that all dust control equipment such as local exhaust ventilation and material transport systems involved in handling of this product are designed and maintained to minimize dust generation and accumulation. Ensure that dust-handling systems (such as exhaust ducts, dusts collectors, vessels, and processing

Product Name: SANTOPRENE™ TPV DEVELOPMENTAL GRADE (RESIN CURED)

Revision Date: 13 Oct 2021

Page 6 of 12

equipment) are designed to minimize the potential for dust ignition and prevent explosion propagation. For example, use explosion relief vents, an explosion suppression system or inert equipment internals. Additional examples of proper equipment include using only appropriately classified electrical equipment and powered industrial trucks.

## PERSONAL PROTECTION

Personal protective equipment selections vary based on potential exposure conditions such as applications, handling practices, concentration and ventilation. Information on the selection of protective equipment for use with this material, as provided below, is based upon intended, normal usage.

**Respiratory Protection:** If engineering controls do not maintain airborne contaminant concentrations at a level which is adequate to protect worker health, an approved respirator may be appropriate. Respirator selection, use, and maintenance must be in accordance with regulatory requirements, if applicable. Types of respirators to be considered for this material include:

Particulate air-purifying respirator approved for dust / oil mist is recommended.

For high airborne concentrations, use an approved supplied-air respirator, operated in positive pressure mode. Supplied air respirators with an escape bottle may be appropriate when oxygen levels are inadequate, gas/vapor warning properties are poor, or if air purifying filter capacity/rating may be exceeded.

**Hand Protection:** Any specific glove information provided is based on published literature and glove manufacturer data. Glove suitability and breakthrough time will differ depending on the specific use conditions. Contact the glove manufacturer for specific advice on glove selection and breakthrough times for your use conditions. Inspect and replace worn or damaged gloves. The types of gloves to be considered for this material include:

If product is hot, thermally protective, chemical resistant gloves are recommended. If contact with forearms is likely, wear gauntlet style gloves.

**Eye Protection:** If contact is likely, safety glasses with side shields are recommended.

**Skin and Body Protection:** Any specific clothing information provided is based on published literature or manufacturer data. The types of clothing to be considered for this material include:

If product is hot, thermally protective, chemical resistant apron and long sleeves are recommended.

**Specific Hygiene Measures:** Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

## ENVIRONMENTAL CONTROLS

Comply with applicable environmental regulations limiting discharge to air, water and soil. Protect the environment by applying appropriate control measures to prevent or limit emissions.

|                  |                                         |
|------------------|-----------------------------------------|
| <b>SECTION 9</b> | <b>PHYSICAL AND CHEMICAL PROPERTIES</b> |
|------------------|-----------------------------------------|

**Note:** Physical and chemical properties are provided for safety, health and environmental considerations only and may not fully represent product specifications. Contact the Supplier for additional information.

## GENERAL INFORMATION

Product Name: SANTOPRENE™ TPV DEVELOPMENTAL GRADE (RESIN CURED)

Revision Date: 13 Oct 2021

Page 7 of 12

**Physical State:** Solid  
**Form:** Pellet  
**Color:** Natural or black (colorable)  
**Odor:** Rubberlike  
**Odor Threshold:** N/D

#### IMPORTANT HEALTH, SAFETY, AND ENVIRONMENTAL INFORMATION

**Relative Density (at 20 °C):** < 1 [In-house method]  
**Flammability (Solid, Gas):** N/A  
**Flash Point [Method]:** N/A  
**Flammable Limits (Approximate volume % in air):** LEL: N/A UEL: N/A  
**Autoignition Temperature:** N/A  
**Boiling Point / Range:** N/A  
**Decomposition Temperature:** N/D  
**Vapor Density (Air = 1):** N/A  
**Vapor Pressure:** N/A  
**Evaporation Rate (n-butyl acetate = 1):** N/A  
**pH:** N/A  
**Log Pow (n-Octanol/Water Partition Coefficient):** N/A  
**Solubility in Water:** Negligible  
**Viscosity:** N/A  
**Oxidizing Properties:** See Hazards Identification Section.

#### OTHER INFORMATION

**Freezing Point:** N/D  
**Melting Point:** N/D  
**Hygroscopic:** Yes  
**DMSO Extract (mineral oil only), IP-346:** < 3 %wt

|                   |                                 |
|-------------------|---------------------------------|
| <b>SECTION 10</b> | <b>STABILITY AND REACTIVITY</b> |
|-------------------|---------------------------------|

**REACTIVITY:** See sub-sections below.

**STABILITY:** Material is stable under normal conditions.

**CONDITIONS TO AVOID:** Avoid elevated temperatures for prolonged periods of time. Elevated temperatures. >260 °C (500 °F)

**MATERIALS TO AVOID:** Acetal resins, Halogenated compounds, Phenolic resins, Strong oxidizers

**HAZARDOUS DECOMPOSITION PRODUCTS:** Material does not decompose at ambient temperatures.

**POSSIBILITY OF HAZARDOUS REACTIONS:** Hazardous polymerization will not occur.

|                   |                                  |
|-------------------|----------------------------------|
| <b>SECTION 11</b> | <b>TOXICOLOGICAL INFORMATION</b> |
|-------------------|----------------------------------|

#### INFORMATION ON TOXICOLOGICAL EFFECTS

| Hazard Class                          | Conclusion / Remarks                                     |
|---------------------------------------|----------------------------------------------------------|
| Inhalation                            |                                                          |
| Acute Toxicity: No end point data for | Minimally Toxic. Based on chemical structure (polymers). |

Product Name: SANTOPRENE™ TPV DEVELOPMENTAL GRADE (RESIN CURED)

Revision Date: 13 Oct 2021

Page 8 of 12

|                                                                |                                                                                                                 |
|----------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------|
| material.                                                      |                                                                                                                 |
| Irritation: No end point data for material.                    | Negligible hazard at ambient/normal handling temperatures.                                                      |
| <b>Ingestion</b>                                               |                                                                                                                 |
| Acute Toxicity: No end point data for material.                | Minimally Toxic. Based on chemical structure (polymers).                                                        |
| <b>Skin</b>                                                    |                                                                                                                 |
| Acute Toxicity: No end point data for material.                | Minimally Toxic. Based on chemical structure (polymers).                                                        |
| Skin Corrosion/Irritation: No end point data for material.     | Negligible irritation to skin at ambient temperatures. Based on chemical structure (polymers).                  |
| <b>Eye</b>                                                     |                                                                                                                 |
| Serious Eye Damage/Irritation: No end point data for material. | May cause mild, short-lasting discomfort to eyes. Based on chemical structure (polymers).                       |
| <b>Sensitization</b>                                           |                                                                                                                 |
| Respiratory Sensitization: No end point data for material.     | Not expected to be a respiratory sensitizer.                                                                    |
| Skin Sensitization: No end point data for material.            | Not expected to be a skin sensitizer. Based on chemical structure (polymers).                                   |
| <b>Aspiration:</b> No end point data for material.             | Not expected to be an aspiration hazard. Based on physico-chemical properties of the material.                  |
| <b>Germ Cell Mutagenicity:</b> No end point data for material. | Not expected to be a germ cell mutagen. Based on chemical structure (polymers).                                 |
| <b>Carcinogenicity:</b> No end point data for material.        | Not expected to cause cancer. Based on chemical structure (polymers).                                           |
| <b>Reproductive Toxicity:</b> No end point data for material.  | Not expected to be a reproductive toxicant. Based on chemical structure (polymers).                             |
| <b>Lactation:</b> No end point data for material.              | Not expected to cause harm to breast-fed children.                                                              |
| <b>Specific Target Organ Toxicity (STOT)</b>                   |                                                                                                                 |
| Single Exposure: No end point data for material.               | Not expected to cause organ damage from a single exposure.                                                      |
| Repeated Exposure: No end point data for material.             | Not expected to cause organ damage from prolonged or repeated exposure. Based on chemical structure (polymers). |

## OTHER INFORMATION

### For the product itself:

Dust may be irritating to the eyes and respiratory tract.

Elevated temperatures or mechanical action may form vapors, mists or fumes which may be irritating to the eyes and respiratory tract.

The toxicological properties of this material have not been fully assessed. This material must be used by or under the supervision of a technically qualified person. Component concentrations in this formulation would not be expected to cause skin sensitization, based on tests of the components, this formulation, or similar formulations.

### Contains:

**Carbon black:** Certain carbon blacks have proved carcinogenic in animal studies. Inhalation animal studies of high concentrations resulted in chronic inflammation, lung fibrosis and lung tumors. Epidemiology studies of workers include findings of bronchitis, pneumonia, emphysema and excess cancer. Substances bound in a polymer or other matrix should present little or no hazard.

**Additives** that are encapsulated in the polymer. Under the normal conditions for processing and use of this polymer the encapsulated additives are not expected to pose any health hazard. However, grinding of the polymer is not recommended without the use of appropriate measures to control exposure (see Section 8 - Engineering Controls).

The following ingredients are cited on the lists below:



Product Name: SANTOPRENE™ TPV DEVELOPMENTAL GRADE (RESIN CURED)

Revision Date: 13 Oct 2021

Page 9 of 12

| Chemical Name | CAS Number | List Citations |
|---------------|------------|----------------|
| CARBON BLACK  | 1333-86-4  | 1, 3, 5        |

--REGULATORY LISTS SEARCHED--

1 = NTP CARC

3 = IARC 1

5 = IARC 2B

2 = NTP SUS

4 = IARC 2A

6 = OSHA CARC

Experimental research and development material. Health hazard data above is estimated based on best available information.

|                   |                               |
|-------------------|-------------------------------|
| <b>SECTION 12</b> | <b>ECOLOGICAL INFORMATION</b> |
|-------------------|-------------------------------|

The information given is based on data for the material, components of the material, or for similar materials, through the application of bridging principals.

**ECOTOXICITY**

Material -- Not expected to be harmful to aquatic organisms.

Material -- Not expected to demonstrate chronic toxicity to aquatic organisms.

**MOBILITY**

Material -- Low solubility and floats and is expected to migrate from water to the land. Expected to partition to sediment and wastewater solids.

**PERSISTENCE AND DEGRADABILITY**

**Biodegradation:**

Material -- Expected to be persistent.

NOTE: Material contains additives that are encapsulated in the polymer. Under normal conditions of processing and use the encapsulated additives are expected to have very limited solubility in water and, as a result, are not expected to cause adverse effects in the aquatic environment.

|                   |                                |
|-------------------|--------------------------------|
| <b>SECTION 13</b> | <b>DISPOSAL CONSIDERATIONS</b> |
|-------------------|--------------------------------|

Disposal recommendations based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.

**DISPOSAL RECOMMENDATIONS**

Suitable routes of disposal are supervised incineration, preferentially with energy recovery, or appropriate recycling methods in accordance with applicable regulations and material characteristics at the time of disposal.

**REGULATORY DISPOSAL INFORMATION**

RCRA Information: The unused product, in our opinion, is not specifically listed by the EPA as a hazardous waste (40 CFR, Part 261D), nor is it formulated to contain materials which are listed as hazardous wastes. It does not exhibit the hazardous characteristics of ignitability, corrosivity or reactivity and is not formulated with contaminants as determined by the Toxicity Characteristic Leaching Procedure (TCLP). However, used product may be regulated.

Product Name: SANTOPRENE™ TPV DEVELOPMENTAL GRADE (RESIN CURED)

Revision Date: 13 Oct 2021

Page 10 of 12

---

| SECTION 14 | TRANSPORT INFORMATION |
|------------|-----------------------|
|------------|-----------------------|

**LAND (DOT):** Not Regulated for Land Transport

**LAND (TDG):** Not Regulated for Land Transport

**SEA (IMDG):** Not Regulated for Sea Transport according to IMDG-Code

**Marine Pollutant:** No

**AIR (IATA):** Not Regulated for Air Transport

| SECTION 15 | REGULATORY INFORMATION |
|------------|------------------------|
|------------|------------------------|

**OSHA HAZARD COMMUNICATION STANDARD:** This material is considered hazardous in accordance with OSHA HazCom 2012, 29 CFR 1910.1200.

**Listed or exempt from listing/notification on the following chemical inventories: Please contact Customer Service (see Section 1 for supplier contact information).**

**SARA 302:** No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302

**CWA / OPA:** Plastic pellets are defined by the US EPA under the Clean Water Act (40CFR122.26) as a "significant material" which requires any industrial plant that may expose pellets to storm water to secure a storm water permit. Violations of the rule carry the same penalties as other Clean Water Act violations. Pellets found in storm water runoff are subject to EPA regulations with the potential for substantial fines and penalties.

**SARA (311/312) REPORTABLE GHS HAZARD CLASSES:** Combustible Dust

**SARA (313) TOXIC RELEASE INVENTORY:** This material contains no chemicals subject to the supplier notification requirements of the SARA 313 Toxic Release Program.

**The following ingredients are cited on the lists below:**

| Chemical Name                                     | CAS Number | List Citations       |
|---------------------------------------------------|------------|----------------------|
| CARBON BLACK                                      | 1333-86-4  | 1, 4, 10, 13, 17, 18 |
| DIATOMACEOUS EARTH                                | 68855-54-9 | 10                   |
| OCTADECANOIC ACID, ZINC SALT (ZINC STEARATE)      | 557-05-1   | 15                   |
| SEVERELY HYDROTREATED HEAVY PARAFFINIC DISTILLATE | 64742-54-7 | 17, 18, 19           |
| TALC                                              | 14807-96-6 | 17                   |

Product Name: SANTOPRENE™ TPV DEVELOPMENTAL GRADE (RESIN CURED)

Revision Date: 13 Oct 2021

Page 11 of 12

|                |           |          |
|----------------|-----------|----------|
| TIN DICHLORIDE | 7772-99-8 | 1, 4     |
| ZINC OXIDE     | 1314-13-2 | 1, 4, 15 |

--REGULATORY LISTS SEARCHED--

|               |                  |                   |             |
|---------------|------------------|-------------------|-------------|
| 1 = ACGIH ALL | 6 = TSCA 5a2     | 11 = CA P65 REPRO | 16 = MN RTK |
| 2 = ACGIH A1  | 7 = TSCA 5e      | 12 = CA RTK       | 17 = NJ RTK |
| 3 = ACGIH A2  | 8 = TSCA 6       | 13 = IL RTK       | 18 = PA RTK |
| 4 = OSHA Z    | 9 = TSCA 12b     | 14 = LA RTK       | 19 = RI RTK |
| 5 = TSCA 4    | 10 = CA P65 CARC | 15 = MI 293       |             |

Code key: CARC=Carcinogen; REPRO=Reproductive

**SECTION 16 OTHER INFORMATION**



This warning is given to comply with California Health and Safety Code 25249.6 and does not constitute an admission or a waiver of rights.

N/D = Not determined, N/A = Not applicable

**KEY TO THE H-CODES CONTAINED IN SECTION 3 OF THIS DOCUMENT (for information only):**

H290: May be corrosive to metals; Corrosive to Metals

H302: Harmful if swallowed; Acute Tox Oral, Cat 4

H314(1B): Causes severe skin burns and eye damage; Skin Corr/Irritation, Cat 1B

H317: May cause allergic skin reaction; Skin Sensitization, Cat 1

H332: Harmful if inhaled; Acute Tox Inh, Cat 4

H335: May cause respiratory irritation; Target Organ Single, Resp Irr

H373: May cause damage to organs through prolonged or repeated exposure; Target Organ, Repeated, Cat 2

H400: Very toxic to aquatic life; Acute Env Tox, Cat 1

H410: Very toxic to aquatic life with long lasting effects; Chronic Env Tox, Cat 1

H412: Harmful to aquatic life with long lasting effects; Chronic Env Tox, Cat 3

**THIS SAFETY DATA SHEET CONTAINS THE FOLLOWING REVISIONS:**

Company Contact Methods information was modified.

Composition: Component Table information was modified.

Section 01: Company Contact Methods information was modified.

Section 08: Exposure Limits Table information was modified.

Section 11: Tox List Cited Table information was modified.

Section 12: information was modified.

Section 15: List Citations Table information was modified.

Section 16: HCode Key information was modified.

**THIS MSDS COVERS THE FOLLOWING MATERIALS: SANTOPRENE (TPV) DEVELOPMENTAL GRADE**

The information and recommendations contained herein are, to the best of Celanese's knowledge and belief, accurate and reliable as of the date issued. You can contact Celanese to insure that this document is the most current available from Celanese. The information and recommendations are offered for the user's consideration and examination. It is the user's responsibility to satisfy itself that the product is suitable for the intended use. If buyer repackages this product, it is the user's responsibility to insure proper health, safety and other necessary information is included with

Product Name: SANTOPRENE™ TPV DEVELOPMENTAL GRADE (RESIN CURED)

Revision Date: 13 Oct 2021

Page 12 of 12

---

and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, re-publication or retransmission of this document, in whole or in part, is not permitted.

---

Internal Use Only

MHC: 0, 0, 0, 0, 0, 0

DGN: 4409119GUS (1021550)

---

Copyright 2002 Celanese Corporation, All rights reserved