

QS871 MICROMAX™ 电阻浆料

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04-12-2024

 8.0
 07-27-2025
 300000000897
 Date of first issue: 01-29-2024

SECTION 1. IDENTIFICATION

Product name : QS871 MICROMAX™ 电阻浆料

Product code : 00000000027045978

Manufacturer or supplier's details

Company name of supplier : Celanese Ltd. Irving Texas

Address : 222 West Las Colinas Boulevard Suite 900N

Irving TX 75039

Telephone : '+1 972-443-4000

Emergency telephone num- : DOMESTIC NORTH AMERICA: 800-424-9300

ber INTERNATIONAL, CALL +1 703-527-3887 (collect calls ac-

cepted)

Recommended use of the chemical and restrictions on use

Recommended use : For industrial use only.

Paste for electronic industry

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids : Category 4

Germ cell mutagenicity : Category 2

Carcinogenicity : Category 2

Reproductive toxicity : Category 1A

Specific target organ toxicity

- repeated exposure (Oral)

Category 1 (Blood)

Other hazards

None known.

GHS label elements

Hazard pictograms

Signal word : Danger

Hazard statements : H227 Combustible liquid.

H341 Suspected of causing genetic defects.

H351 Suspected of causing cancer.

H360 May damage fertility or the unborn child.

H372 Causes damage to organs (Blood) through prolonged or

repeated exposure if swallowed.

Precautionary statements : Prevention:



QS871 MICROMAX™ 电阻浆料

Version Revision Date: SDS Number: Date of last issue: 04-12-2024 8.0 07-27-2025 300000000897 Date of first issue: 01-29-2024

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read

and understood.

P210 Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking. P260 Do not breathe mist or vapours. P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P280 Wear protective gloves/ protective clothing/ eye protection/

face protection/ hearing protection.

P280 Wear protective gloves, protective clothing, eye protection

and face protection.

Response:

P308 + P313 IF exposed or concerned: Get medical advice/attention.

P370 + P378 In case of fire: Use dry sand, dry chemical or alco-

hol-resistant foam to extinguish.

Storage:

P403 Store in a well-ventilated place.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Terpineol	8000-41-7	>= 10 - < 30
Bis(2-butoxyethyl) ether	112-73-2	>= 5 - < 10
Silver Powder (particle diameter >100	7440-22-4	>= 5 - < 10
nm <1mm)		
Palladium	7440-05-3	>= 1 - < 5

Glass or Ceramic ingredient(s)	60 - 80%
Ruthenium, Lead, Silicon, Manganese,	
Aluminum	

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4. FIRST AID MEASURES

If inhaled : If inhaled, remove to fresh air.

If breathing is difficult, give oxygen.
If not breathing, give artificial respiration.

Get medical attention.



QS871 MICROMAX™ 电阻浆料

Version Date of last issue: 04-12-2024 **Revision Date:** SDS Number: 07-27-2025 30000000897 Date of first issue: 01-29-2024 8.0

In case of skin contact Wash off with soap and water.

Get medical attention if irritation develops and persists.

Wash contaminated clothing before re-use.

In case of eye contact Immediately flush eyes for at least 15 minutes. Get medical

attention.

If swallowed If swallowed

Rinse mouth with water.

Call a physician or poison control centre immediately.

DO NOT induce vomiting unless directed to do so by a physi-

cian or poison control center.

Most important symptoms

and effects, both acute and

delayed

Suspected of causing genetic defects. Suspected of causing cancer.

May damage fertility or the unborn child.

Causes damage to organs through prolonged or repeated

exposure if swallowed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Dry sand Dry chemical

Alcohol-resistant foam

Specific hazards during fire-

fighting

Hazardous decomposition products formed under fire condi-

(see also section 10)

Avoid breathing decomposition products.

Further information Evacuate personnel to safe areas.

Stop spill/release if it can be done with minimal risk.

Do not allow run-off from fire fighting to enter drains or water

courses.

Special protective equipment :

for firefighters

Exposure to decomposition products may be a hazard to

health.

Wear self-contained breathing apparatus for firefighting if nec-

essary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- :

tive equipment and emergency procedures

Avoid contact with skin, eyes and clothing.

Ensure adequate ventilation.

Wear suitable protective equipment.

Dispose of in accordance with local regulations.

Prevent further leakage or spillage if safe to do so. Environmental precautions

Prevent product from entering drains.

Clean contaminated floors and objects thoroughly while ob-

serving environmental regulations.

Methods and materials for

Contain spill.

containment and cleaning up Soak up with inert absorbent material.



QS871 MICROMAX™ 电阻浆料

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04-12-2024

 8.0
 07-27-2025
 300000000897
 Date of first issue: 01-29-2024

Collect and contain contaminated absorbent and dike material

for disposal.

Keep in suitable, closed containers for disposal.

Ventilate the area.

Clean contaminated surface thoroughly.

SECTION 7. HANDLING AND STORAGE

Advice on protection against :

fire and explosion

Avoid formation of dust and aerosols.

Keep away from heat and sources of ignition.

Advice on safe handling : Avoid inhalation, ingestion and contact with skin and eyes.

Use only with adequate ventilation/personal protection.

Keep container closed when not in use.

Take care to avoid waste and spillage when weighing, loading

and mixing the product.

Conditions for safe storage : Store in original container.

Keep containers tightly closed in a dry, cool and well-

ventilated place.

Keep away from sources of ignition - No smoking. Do not store or consume food, drink or tobacco in areas where they may become contaminated with this material.

Keep container closed when not in use.

Do not reuse empty container.

Further information on stor-

age stability

Stable under normal conditions.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Lead	7439-92-1	TWA	0.05 mg/m3 (Lead)	ACGIH
		PEL	0.05 mg/m3 (Lead)	OSHA CARC
		TWA	0.05 mg/m3 (Lead)	NIOSH REL
Silver Powder (particle diameter >100 nm <1mm)	7440-22-4	TWA (Dust and fume)	0.1 mg/m3	ACGIH
		TWA (Dust)	0.01 mg/m3	NIOSH REL
		TWA	0.01 mg/m3	OSHA P0
Silicon	7440-21-3	TWA (Respirable)	5 mg/m3	NIOSH REL
		TWA (total)	10 mg/m3	NIOSH REL
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA (respir-	5 mg/m3	OSHA P0



QS871 MICROMAX™ 电阻浆料

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04-12-2024

 8.0
 07-27-2025
 300000000897
 Date of first issue: 01-29-2024

		able dust fraction)		
Manganese	7439-96-5	TWA (Fumes)	1 mg/m3 (Manganese)	NIOSH REL
		ST (Fumes)	3 mg/m3 (Manganese)	NIOSH REL
		C (Fumes)	5 mg/m3	OSHA Z-1
		TWA (Inhal- able particu- late matter)	0.1 mg/m3 (Manganese)	ACGIH
		TWA (Respirable particulate matter)	0.02 mg/m3 (Manganese)	ACGIH
		TWA (Fumes)	1 mg/m3 (Manganese)	OSHA P0
		STEL (Fumes)	3 mg/m3 (Manganese)	OSHA P0
Aluminum	7429-90-5	TWA (Respirable)	5 mg/m3	NIOSH REL
		TWA (total)	10 mg/m3	NIOSH REL
		TWA (total dust)	15 mg/m3 (Aluminium)	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3 (Aluminium)	OSHA Z-1
		TWA (Total dust)	15 mg/m3 (Aluminium)	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3 (Aluminium)	OSHA P0

Biological occupational exposure limits

Components	CAS-No.	Control	Biological	Sam-	Permissible	Basis
		parameters	specimen	pling	concentra-	
				time	tion	
Lead	7439-92-1	Lead	In blood	Not criti-	200 μg/l	ACGIH
		(Lead)		cal		BEI

Engineering measures : Local exhaust or a laboratory hood should be used when

handling the materials.

Maintain air concentrations below occupational exposure

standards.

Personal protective equipment

Respiratory protection : Provide adequate ventilation.

No personal respiratory protective equipment normally re-

quired.

Where there is potential for airborne exposures in excess of applicable limits, wear approved respiratory protection with

dust/mist cartridge.

When workers are facing concentrations above the exposure

limit they must use appropriate certified respirators.

Consult the respirator manufacturer to determine the appropriate type of equipment for a given application. Observe respirator use limitations specified by the manufacturer. Persons performing maintenance or repairs on exhaust sys-



QS871 MICROMAX™ 电阻浆料

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04-12-2024

 8.0
 07-27-2025
 300000000897
 Date of first issue: 01-29-2024

tem equipment (e.g. ducts) may need to use respirators and protective clothing to prevent exposure to any accumulated

residues.

Hand protection

Material : Impervious gloves

Remarks : Gloves must be inspected prior to use. Gloves should be

discarded and replaced if there is any indication of degradation or chemical breakthrough. The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of

cuts, abrasion, and the contact time.

Eye protection : Wear safety glasses with side shields.

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Lightweight protective clothing

Safety shoes

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

Avoid contact with skin, eyes and clothing.

Contaminated work clothing should not be allowed out of the

workplace.

Remove contaminated clothing and protective equipment

before entering eating areas.

Remove and wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : viscous liquid

Colour : black

Odour : aromatic

pH : Substance/mixture is non-polar/aprotic.

Flash point : 198 °F / 92 °C

Method: closed cup

Density : 2.4 g/cm³ (68 °F / 20 °C)

Solubility(ies)

Water solubility : slightly soluble (68 °F / 20 °C)

Viscosity

Viscosity, dynamic : 145 - 210 Pa.s (77 °F / 25 °C)

Viscosity, kinematic : > 20.5 mm2/s (104 °F / 40 °C)



QS871 MICROMAX™ 电阻浆料

Version Revision Date: SDS Number: Date of last issue: 04-12-2024 8.0 07-27-2025 300000000897 Date of first issue: 01-29-2024

estimated

SECTION 10. STABILITY AND REACTIVITY

Possibility of hazardous reac-

tions

Polymerization will not occur.

Stable at normal temperatures and storage conditions.

Conditions to avoid Incompatible materials

Hazardous decomposition

products

None reasonably foreseeable.
Acids

No decomposition if stored and applied as directed.

Under fire conditions:

Carbon monoxide, carbon dioxide and unburned hydrocar-

bons (smoke). Metal oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified due to lack of data.

Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 46.83 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

Components:

Lead:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Remarks: Information given is based on data obtained from

similar substances.

Acute inhalation toxicity : LC50 (Rat): > 5.05 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Remarks: Information given is based on data obtained from

similar substances.

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 402

Remarks: Information given is based on data obtained from

similar substances.



QS871 MICROMAX™ 电阻浆料

Version Revision Date: SDS Number: Date of last issue: 04-12-2024 8.0 07-27-2025 300000000897 Date of first issue: 01-29-2024

Terpineol:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 401

Assessment: The substance or mixture has no acute oral tox-

icitv

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Silver Powder (particle diameter >100 nm <1mm):

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 401

Assessment: The substance or mixture has no acute oral tox-

icity

Acute inhalation toxicity : LC50 (Rat): > 5.16 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 436

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Silicon:

Acute oral toxicity : LD50 (Rat): 3,160 mg/kg

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : Remarks: No data available

Manganese:

Acute oral toxicity : LD50 (Rat): 9,000 mg/kg

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : Remarks: No data available

Aluminum:

Acute oral toxicity : Remarks: No data available

Acute inhalation toxicity : Remarks: Effects of breathing high concentration of respirable

particles may include: Respiratory tract damage

Lung damage

Acute dermal toxicity : Remarks: No data available



QS871 MICROMAX™ 电阻浆料

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04-12-2024

 8.0
 07-27-2025
 300000000897
 Date of first issue: 01-29-2024

Skin corrosion/irritation

Not classified due to lack of data.

Components:

Lead:

Species : Rabbit

Assessment : Not classified as irritant
Method : OECD Test Guideline 404

Result : No skin irritation

Remarks : Information given is based on data obtained from similar sub-

stances.

Terpineol:

Species : Rabbit

Assessment : Irritating to skin.

Method : OECD Test Guideline 404

Result : Skin irritation

Silver Powder (particle diameter >100 nm <1mm):

Species : Rabbit

Assessment : No skin irritation

Method : OECD Test Guideline 404
Result : Slight or no skin irritation

Remarks : Minimal effects that do not meet the threshold for classifica-

tion.

Silicon:

Remarks : No data available

Manganese:

Remarks : No data available

Aluminum:

Remarks : No data available

Serious eye damage/eye irritation

Not classified due to lack of data.

Components:

Lead:

Species : Rabbit

Result : No eye irritation

Assessment : Not classified as irritant
Method : OECD Test Guideline 405

Remarks : Information given is based on data obtained from similar sub-

stances.

Terpineol:

Species : animals (unspecified species)



QS871 MICROMAX™ 电阻浆料

Version Revision Date: SDS Number: Date of last issue: 04-12-2024 8.0 07-27-2025 300000000897 Date of first issue: 01-29-2024

Result : Eye irritation
Assessment : Irritating to eyes.

Method : OECD Test Guideline 405

Silver Powder (particle diameter >100 nm <1mm):

Species : Rabbit

Result : No eye irritation
Assessment : No eye irritation

Method : OECD Test Guideline 405

Silicon:

Species : Rabbit Remarks : slight irritation

Manganese:

Remarks : No data available

Aluminum:

Remarks : No data available

Respiratory or skin sensitisation

Skin sensitisation

Not classified due to lack of data.

Respiratory sensitisation

Not classified due to lack of data.

Components:

Lead:

Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

Result : Does not cause skin sensitisation.

Remarks : Information given is based on data obtained from similar sub-

stances.

Terpineol:

Test Type : Maximisation Test

Species : Guinea pig

Assessment : Not a skin sensitizer.

Method : OECD Test Guideline 406

Result : Did not cause sensitisation on laboratory animals.

Silver Powder (particle diameter >100 nm <1mm):

Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : US EPA Test Guideline OPPTS 870.2600

Result : Does not cause skin sensitisation.

Remarks : Information given is based on data obtained from similar sub-



QS871 MICROMAX™ 电阻浆料

Version **Revision Date:** SDS Number: Date of last issue: 04-12-2024 07-27-2025 300000000897 Date of first issue: 01-29-2024 8.0

stances.

Silicon:

No data available Remarks

Manganese:

Remarks No data available

Aluminum:

No data available Remarks

Germ cell mutagenicity

Suspected of causing genetic defects.

Components:

Lead:

Germ cell mutagenicity -

Assessment

In vitro tests showed mutagenic effects, Genetic damage in cultured mammalian cells was observed in some laboratory

tests but not in others.

Terpineol:

Germ cell mutagenicity -

Assessment

Tests on bacterial or mammalian cell cultures did not show mutagenic effects., Evidence suggests this substance does

not cause genetic damage in animals.

Carcinogenicity

Suspected of causing cancer.

Components:

Lead:

Carcinogenicity - Assess-

ment

Suspected human carcinogens, An increased incidence of

tumours was observed in laboratory animals., Information given is based on data obtained from similar substances.

Terpineol:

Carcinogenicity - Assess-

ment

Not classifiable as a human carcinogen., Overall weight of

evidence indicates that the substance is not carcinogenic.

IARC Group 2B: Possibly carcinogenic to humans

> Lead 7439-92-1

OSHA OSHA specifically regulated carcinogen

7439-92-1

(Lead and inorganic lead compounds)

NTP Reasonably anticipated to be a human carcinogen

> 7439-92-1 Lead



QS871 MICROMAX™ 电阻浆料

Version Revision Date: SDS Number: Date of last issue: 04-12-2024 8.0 07-27-2025 300000000897 Date of first issue: 01-29-2024

Reproductive toxicity

May damage fertility or the unborn child.

Components:

Lead:

Reproductive toxicity - As-

sessment

Known human reproductive toxicant, Reduced fertility, Infor-

mation given is based on data obtained from similar sub-

stances.

Delayed foetal development (variations), Information given is

based on data obtained from similar substances.

Terpineol:

Reproductive toxicity - As-

sessment

Animal testing showed effects on reproduction at levels equal

to or above those causing parental toxicity.

STOT - single exposure

Not classified due to lack of data.

Components:

Lead:

Assessment : The substance or mixture is not classified as specific target

organ toxicant, single exposure.

Terpineol:

Assessment : The substance or mixture is not classified as specific target

organ toxicant, single exposure.

STOT - repeated exposure

Causes damage to organs (Blood) through prolonged or repeated exposure if swallowed.

Components:

Terpineol:

Assessment : The substance or mixture is not classified as specific target

organ toxicant, repeated exposure.

Repeated dose toxicity

Components:

Lead:

Species : Rat LOAEL : 200 Application Route : Oral Target Organs : Blood

Assessment : The substance or mixture is classified as specific target organ

toxicant, repeated exposure, category 1.

Remarks : altered blood chemistry

Information given is based on data obtained from similar sub-

stances.



QS871 MICROMAX™ 电阻浆料

Version Revision Date: SDS Number: Date of last issue: 04-12-2024 8.0 07-27-2025 300000000897 Date of first issue: 01-29-2024

Terpineol:

Species : Rat Application Route : Oral

Remarks : No toxicologically significant effects were found.

Silicon:

Remarks : No data available

Manganese:

Species : Human

Remarks : central nervous system effects

Aluminum:

Species : Human Application Route : Inhalation

Remarks : Respiratory tract damage

Lung damage

Aspiration toxicity

Not classified due to lack of data.

Components:

Lead:

No aspiration toxicity classification

Silver Powder (particle diameter >100 nm <1mm):

No aspiration toxicity classification

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Lead:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0.107 mg/l

Exposure time: 96 h

Remarks: Information given is based on data obtained from

similar substances.

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Ceriodaphnia dubia (water flea)): 0.597 mg/l

Exposure time: 48 h

Remarks: Information given is based on data obtained from

similar substances.

Toxicity to algae/aquatic

plants

NOEC (algae): 0.0227 mg/l

Exposure time: 96 h

Remarks: Information given is based on data obtained from

similar substances.



QS871 MICROMAX™ 电阻浆料

Version Revision Date: SDS Number: Date of last issue: 04-12-2024 8.0 07-27-2025 300000000897 Date of first issue: 01-29-2024

Toxicity to fish (Chronic tox-

icity)

NOEC (Pimephales promelas (fathead minnow)): 0.02 mg/l

Exposure time: 30 d

Remarks: Information given is based on data obtained from

similar substances.

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

Terpineol:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 62 - 80 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

LC50 (Daphnia magna (Water flea)): 73 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

ErC50 (Pseudokirchneriella subcapitata (green algae)): 68

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

EbC50 (Pseudokirchneriella subcapitata (green algae)): 17

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Silver Powder (particle diameter >100 nm <1mm):

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 0.016 mg/l

Exposure time: 96 h

Remarks: Information given is based on data obtained from

similar substances.

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 0.0125 mg/l

Exposure time: 48 h

Remarks: Information given is based on data obtained from

similar substances.

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 0.19

mg/l

Exposure time: 96 h

Remarks: Information given is based on data obtained from

similar substances.

EC10 (Pseudokirchneriella subcapitata (green algae)):

0.03462 mg/l

Exposure time: 72 h

Remarks: Information given is based on data obtained from

similar substances.

Toxicity to fish (Chronic tox-

icity)

NOEC (Oncorhynchus mykiss (rainbow trout)): 0.0012 mg/l

Exposure time: 32 d



QS871 MICROMAX™ 电阻浆料

Version Date of last issue: 04-12-2024 **Revision Date:** SDS Number: 07-27-2025 300000000897 Date of first issue: 01-29-2024 8.0

Remarks: Information given is based on data obtained from

similar substances.

Toxicity to daphnia and other

aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): 0.00327 mg/l

Exposure time: 21 d

Remarks: Information given is based on data obtained from

similar substances.

Ecotoxicology Assessment

Acute aquatic toxicity Very toxic to aquatic life.

Chronic aquatic toxicity Very toxic to aquatic life with long lasting effects.

Silicon:

Toxicity to fish Remarks: No data available

Toxicity to daphnia and other :

aquatic invertebrates

Toxicity to algae/aquatic

plants

Remarks: No data available

Remarks: No data available

Manganese:

Toxicity to fish LC50 (Pimephales promelas (fathead minnow)): 30.6 mg/l

Toxicity to daphnia and other :

aquatic invertebrates

LC50 (Daphnia magna (Water flea)): 19.2 mg/l

Remarks: No data available

Toxicity to algae/aquatic

plants

Remarks: No data available

Aluminum:

NOEC (Salmo trutta (brown trout)): > 100 mg/l Toxicity to fish

Exposure time: 96 h Test Type: semi-static test

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

NOEC (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

NOEC (Scenedesmus capricornutum (fresh water algae)): >

100 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Persistence and degradability

Components:

Terpineol:

Biodegradability Biodegradation: 80 %

Exposure time: 28 d

Method: OECD Test Guideline 301 Remarks: Readily biodegradable.



QS871 MICROMAX™ 电阻浆料

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04-12-2024

 8.0
 07-27-2025
 300000000897
 Date of first issue: 01-29-2024

Bioaccumulative potential

Components:

Terpineol:

Bioaccumulation : Bioconcentration factor (BCF): 24.13

Remarks: Bioaccumulation is unlikely.

Silver Powder (particle diameter >100 nm <1mm):

Bioaccumulation : Remarks: Bioaccumulation is unlikely.

Information given is based on data obtained from similar sub-

stances.

Partition coefficient: n-

octanol/water

Remarks: Not applicable

Mobility in soil
No data available

Other adverse effects

Product:

Additional ecological infor-

mation

: No data is available on the product itself.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : If recycling is not practicable, dispose of in compliance with

local regulations.

Do not reuse empty container. Never place unused product

down any indoor or out door drain.

Contaminated/not cleaned containers should be treated/handled like product waste. Dispose of container properly. Refer to applicable Local, State/Provincial, and Federal

Regulations, as well as industry Standards.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(Ceramic, Silver)

Class : 9
Packing group : III
Labels : 9
Environmentally hazardous : no

IATA-DGR

UN/ID No. : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,



QS871 MICROMAX™ 电阻浆料

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04-12-2024

 8.0
 07-27-2025
 300000000897
 Date of first issue: 01-29-2024

N.O.S.

(Ceramic, Silver)

Class : 9 Packing group : III

Labels : Miscellaneous

Packing instruction (cargo

aircraft)

Packing instruction (passen-

ger aircraft)

964

964

IMDG-Code

UN number : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(Ceramic, Silver)

Class : 9
Packing group : III
Labels : 9
EmS Code : F-A, S-F
Marine pollutant : no

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

National Regulations

49 CFR

Not regulated as a dangerous good

Special precautions for user

Remarks : Regulated by DOT/49CFR as Combustible Liquid when trans-

ported in a bulk package (>=119 gallons(450 litres))., Not reg-

ulated by DOT in non-bulk package.

Marine Pollutants assigned UN number 3077 and 3082 in single or combination packaging containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 KG or less for solids may be transported as non-dangerous goods as provided in section 2.10.2.7 of IMDG code, IATA special provi-

sion A197, and ADR/RID special provision 375.

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)

Germ cell mutagenicity Carcinogenicity

Reproductive toxicity

Specific target organ toxicity (single or repeated exposure)



QS871 MICROMAX™ 电阻浆料

Version Revision Date: SDS Number: Date of last issue: 04-12-2024 8.0 07-27-2025 300000000897 Date of first issue: 01-29-2024

SARA 313 : The following components are subject to reporting levels es-

tablished by SARA Title III, Section 313:

Lead 7439-92-1

Silver Powder 7440-22-4

(particle diameter >100 nm <1mm)

Manganese 7439-96-5

California Prop. 65

WARNING: This product can expose you to chemicals including Lead, 2,2'-Iminodiethanol, which is/are known to the State of California to cause cancer, and

Lead, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California Regulated Carcinogens

Lead 7439-92-1

TSCA list

In compliance with TSCA-active Inventory requirements for commercial purposes.

The following substance(s) is/are subject to a Significant New Use Rule:

Bis(2-butoxyethyl) ether 112-73-2 See 40 CFR § 721.10229; Final

Rule

See 40 CFR § 721.10229; Proposed

Rule

The following substance(s) is/are subject to TSCA 12(b) export notification requirements:

Bis(2-butoxyethyl) ether 112-73-2 Lead 7439-92-1

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA CARC : OSHA Specifically Regulated Chemicals/Carcinogens
OSHA P0 : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated

values)

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

ACGIH / TWA : 8-hour, time-weighted average

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded

at any time during a workday

OSHA CARC / PEL : Permissible exposure limit (PEL)
OSHA P0 / TWA : 8-hour time weighted average
OSHA P0 / STEL : Short-term exposure limit



QS871 MICROMAX™ 电阻浆料

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04-12-2024

 8.0
 07-27-2025
 300000000897
 Date of first issue: 01-29-2024

OSHA Z-1 / TWA : 8-hour time weighted average

OSHA Z-1 / C : Ceiling

AIIC - Australian Inventory of Industrial Chemicals: ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System: IARC - International Agency for Research on Cancer; IATA - International Air Transport Association: IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ -Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 07-27-2025

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN

