

Product name	EXCEED™ XP PERFORMANCE POLYMERS (PPA) (LLDPE)		
Date of revision	16 August 2024	SDS Number:	P000001215_13635281
First issue date	30 October 2023	Version	5.08

SAFETY DATA SHEET



EXCEED™ XP PERFORMANCE POLYMERS (PPA) (LLDPE)

Section 1. Identification

Product name	: EXCEED™ XP PERFORMANCE POLYMERS (PPA) (LLDPE) see Section 16 for Synonyms
Product description	: LLDPE with polymer processing aid (PPA)
<u>Relevant identified uses of the substance or mixture and uses advised against</u>	
Identified uses	: Coatings, Extrusion and moulding, Film
Uses advised against	: This product is not recommended for any industrial, professional or consumer use other than the Identified Uses above.
Supplier	: EXXONMOBIL CHEMICAL SERVICES (SHANGHAI) CO., LTD Correspondence address: 1099 Zixing Road Minhang District SHANGHAI China
24 Hour Emergency Telephone	: (+86)0532-83889090 (NRCC)
Supplier General Contact	: (+86) 021-23515000
E-Mail	: sds-CN.SM@exxonmobil.com
FAX	: 86-21-23500826
Supplier	: ExxonMobil Chemical Asia Pacific (Regn. No. 52893724C) (A Division Of ExxonMobil Asia Pacific Pte Ltd - Regn. No. 196800312N) 1 HarbourFront Place #06-00 HarbourFront Tower One 098633 Singapore
Supplier General Contact	: +65 6885 8000
SDS Internet Address	: www.sds.exxonmobil.com

Section 2. Hazards identification

Classification of the substance or mixture according to GB 13690-2009 and GB 30000-2013	
<u>Emergency overview</u>	
Physical state	: Solid. [pellet, Granule, powder]
Colour	: Clear to Opaque, White to Off-White
Odour	: None to Mild
May form explosible dust-air mixture if small particles are generated during further processing, handling, or by other means.	
Classification of the substance or mixture	: Not classified.

<u>Precautionary statements</u>	
Physical and chemical hazards	: No known significant effects or critical hazards.

Date of issue/Date of revision	: 16 August 2024	Date of previous issue	: 16 August 2024	Version	: 5.08	1/10
---------------------------------------	------------------	-------------------------------	------------------	----------------	--------	------

Product name	EXCEED™ XP PERFORMANCE POLYMERS (PPA) (LLDPE)		
Date of revision	16 August 2024	SDS Number:	P000001215_13635281
First issue date	30 October 2023	Version	5.08

Section 2. Hazards identification

Health hazards : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.

Inhalation : No specific data.

Skin contact : No specific data.

Ingestion : No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Environmental hazards : No known significant effects or critical hazards.

Other hazards which do not result in classification : May form explosible dust-air mixture if small particles are generated during further processing, handling, or by other means.

Nota : This material should not be used for any other purpose than the intended use in Section 1 without expert advice. Health studies have shown that chemical exposure may cause potential human health risks which may vary from person to person.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Nota :

The product may contain varying levels of additives such as slip and anti-blocking agents, anti-oxidants, stabilizers and processing aids.

Section 4. First-aid measures

First aid

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur.

Skin contact : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. If burned by contact with hot material, molten material adhering to skin should be cooled as quickly as possible with water, and see a physician for removal of adhering material and treatment of burn.

Product name	EXCEED™ XP PERFORMANCE POLYMERS (PPA) (LLDPE)		
Date of revision	16 August 2024	SDS Number:	P000001215_13635281
First issue date	30 October 2023	Version	5.08

Section 4. First-aid measures

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
Ingestion	: Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Eye contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.

Over-exposure signs/symptoms

Inhalation	: No specific data.
Skin contact	: No specific data.
Eye contact	: No specific data.
Ingestion	: No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training.
Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

See toxicological information (Section 11)

Section 5. Firefighting measures

Extinguishing media

Suitable extinguishing media	: Use dry chemical, CO ₂ , water spray (fog) or foam.
Unsuitable extinguishing media	: Do not use water jet.

Specific hazards arising from the chemical

Hazardous combustion products	: Flammable hydrocarbons, hydrogen fluoride, Incomplete combustion products, Oxides of carbon, Smoke, Fume
-------------------------------	--

Special protective actions for fire-fighters

Special protective actions for fire-fighters	: Use standard firefighting procedures and consider the hazards of other involved materials. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. Assure an extended cooling down period to prevent re-ignition. Prevent run-off from fire control or dilution from entering streams, sewers or drinking water supply. No action shall be taken involving any personal risk or without suitable training.
--	---

Special protective equipment for fire-fighters

Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
--	---

Date of issue/Date of revision	: 16 August 2024	Date of previous issue	: 16 August 2024	Version	: 5.08	3/10
--------------------------------	------------------	------------------------	------------------	---------	--------	------

Product name	EXCEED™ XP PERFORMANCE POLYMERS (PPA) (LLDPE)		
Date of revision	16 August 2024	SDS Number:	P000001215_13635281
First issue date	30 October 2023	Version	5.08

Section 6. Accidental release measures

NOTIFICATION PROCEDURES

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

- Environmental precautions** : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and material for containment and cleaning up

- Small spill** : Move containers from spill area. Vacuum or sweep up material and place in a designated, labelled waste container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labelled waste container. Dispose of via a licensed waste disposal contractor. Confine the spill immediately with booms. Skim from surface Warn other shipping. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

- Precautionary measures to prevent the occurrence of secondary disasters** : Prevent entry into sewers, water courses, basements or confined areas.

Water spill and land spill recommendations are based on the most likely spill scenario for this material; however, geographic conditions, wind, temperature, (and in the case of a water spill) wave and current direction and speed may greatly influence the appropriate action to be taken. For this reason, local experts should be consulted. Note: Local regulations may prescribe or limit action to be taken.

Section 7. Handling and storage

Precautions for safe handling

- Precautions for operating** : Thermal burn hazard - contact with hot material may cause thermal burns. Put on appropriate personal protective equipment (see Section 8). Prevent small spills and leakage to avoid slip hazard. Care should be taken when storing and handling this product. Apart from the specific nature of the polymer product, conditions such as humidity, sunlight and temperature have an influence on the way the product behaves during storage and handling. Special attention should be paid to avoid inappropriate stacking of palletised bags or other package units. Indeed, polymer products may be dimensionally unstable under certain conditions. Avoid conditions generating heat during transfer operations.

- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

- Static Accumulator** : This material is a static accumulator.
- Loading/Unloading Temperature** : Ambient
- Transport Temperature** : Ambient

Product name	EXCEED™ XP PERFORMANCE POLYMERS (PPA) (LLDPE)		
Date of revision	16 August 2024	SDS Number:	P000001215_13635281
First issue date	30 October 2023	Version	5.08

Section 7. Handling and storage

Transport Pressure : Ambient

Conditions for safe storage : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Storage Temperature : Ambient

Storage Pressure : Ambient

Suitable Containers/Packing : Silos, Octatainer, Bags, Drums, Bulk Containers, Hopper Cars, Boxes

Suitable Materials and Coatings : aluminium, polyethylene

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

None.

NOTE: Limits/standards shown for guidance only. Follow applicable regulations.

For dusty conditions, ACGIH recommends for insoluble and poorly soluble particles not otherwise specified an 8-hour TWA of 10 mg/m³ (inhalable particles), 3 mg/m³ (respirable particles).

Appropriate engineering controls : SPECIAL PRECAUTIONS: Should significant vapors/fumes be generated during the thermal processing (rotomolding) of this product, it is recommended that work stations be monitored for the presence of thermal degradation by-products, such as aldehydes (formaldehyde, acetaldehyde, etc) and organic acids (formic acid, acetic acid, etc), which may evolve at elevated temperatures. Processors of this product should assure that adequate ventilation or other controls are used to control exposure. It is recommended that the current ACGIH-TLVs for the thermal degradation by-products be observed. Contact your local sales representative for further information.

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields. Face shield.

Skin protection

Product name	EXCEED™ XP PERFORMANCE POLYMERS (PPA) (LLDPE)		
Date of revision	16 August 2024	SDS Number:	P000001215_13635281
First issue date	30 October 2023	Version	5.08

Section 8. Exposure controls/personal protection

Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. If product is hot, thermally protective, chemical resistant gloves are recommended. If contact with forearms is likely, wear gauntlet style gloves.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. If product is hot, thermally protective, chemical resistant apron and long sleeves are recommended.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Note: Physical and chemical properties are provided for safety, health and environmental considerations only and may not fully represent product specifications. Contact the Supplier for additional information.

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance and physical state

Physical state	: Solid. [pellet, Granule, powder]
Colour	: Clear to Opaque, White to Off-White
Odour	: None to Mild
Odour threshold	: Not applicable.
pH	: Not applicable.
Melting point/freezing point	: 115 to 130°C (239 to 266°F) [In-house method]
Boiling point or initial boiling point and boiling range	: Not applicable.
Flash point	: Closed cup: Not applicable.
Evaporation rate	: Not applicable.
Flammability	: Ignitable
Lower and upper explosion limit/flammability limit	: Not applicable.
Vapour pressure	: Not applicable.
Relative vapour density	: Not applicable.
Relative density	: 0.9 to 0.95 [In-house method]
Bulk density	: 0.4 to 1 g/cm³ [In-house method]
Solubility in water	: Negligible
Partition coefficient: n-octanol/water	: Not applicable.
Auto-ignition temperature	: Not applicable.
Decomposition temperature	: Not available.
Viscosity	: Not applicable.
Molecular weight	: >25000

Particle characteristics

Median particle size	: Not available.
Hygroscopic	: No

Date of issue/Date of revision	: 16 August 2024	Date of previous issue	: 16 August 2024	Version	: 5.08	6/10
--------------------------------	------------------	------------------------	------------------	---------	--------	------

Product name	EXCEED™ XP PERFORMANCE POLYMERS (PPA) (LLDPE)		
Date of revision	16 August 2024	SDS Number:	P000001215_13635281
First issue date	30 October 2023	Version	5.08

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: Avoid elevated temperatures for prolonged periods of time.
Incompatible materials	: Strong oxidisers
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Conclusion/Summary

Inhalation	: Minimally Toxic. No end point data for material. Based on chemical structure (polymers).
Dermal	: Minimally Toxic. No end point data for material. Based on chemical structure (polymers).
Oral	: Minimally Toxic. No end point data for material. Based on chemical structure (polymers).

Irritation/Corrosion

Conclusion/Summary

Skin	: Negligible irritation to skin at ambient temperatures. No end point data for material. Based on chemical structure (polymers).
Eyes	: May cause mild, short-lasting discomfort to eyes. No end point data for material. Based on chemical structure (polymers).
Respiratory	: Negligible hazard at ambient/normal handling temperatures. No end point data for material.

Respiratory or skin sensitization

Conclusion/Summary

Skin	: Not expected to be a skin sensitizer. No end point data for material. Based on chemical structure (polymers).
Respiratory	: Not expected to be a respiratory sensitizer. No end point data for material.

Germ Cell Mutagenicity

Conclusion/Summary	: Not expected to be a germ cell mutagen. No end point data for material. Based on chemical structure (polymers).
---------------------------	---

Carcinogenicity

Conclusion/Summary	: Not expected to cause cancer. No end point data for material. Based on chemical structure (polymers).
---------------------------	---

Reproductive toxicity

Conclusion/Summary	: Not expected to be a reproductive toxicant. No end point data for material. Based on chemical structure (polymers).
---------------------------	---

Specific target organ toxicity (single exposure)

Conclusion/Summary	: Not expected to cause organ damage from a single exposure. No end point data for material.
---------------------------	--

Product name	EXCEED™ XP PERFORMANCE POLYMERS (PPA) (LLDPE)		
Date of revision	16 August 2024	SDS Number:	P000001215_13635281
First issue date	30 October 2023	Version	5.08

Section 11. Toxicological information

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Target organs
EXCEED™ XP PERFORMANCE POLYMERS (PPA) (LLDPE)	Not applicable.	-

Conclusion/Summary : Not expected to cause organ damage from prolonged or repeated exposure. No end point data for material. Based on chemical structure (polymers).

Aspiration hazard

Conclusion/Summary : Not expected to be an aspiration hazard. Based on physico-chemical properties of the material. No end point data for material.

Other information

- Contains** : Additives that are encapsulated in the polymer. Under the normal conditions for processing and use of this polymer the encapsulated additives are not expected to pose any health hazard. However, grinding of the polymer is not recommended without the use of appropriate measures to control exposure (see Section 8 - Engineering Controls).
- Product** : Elevated temperatures or mechanical action may form vapours, mists or fumes which may be irritating to the eyes and respiratory tract.

Section 12. Ecological information

The information given is based on data for the material, components of the material, or for similar materials, through the application of bridging principals.

Toxicity

Conclusion/Summary

- Acute toxicity** : Not expected to be harmful to aquatic organisms.
- Chronic toxicity** : Not expected to demonstrate chronic toxicity to aquatic organisms

Persistence and degradability

- Biodegradability** : Material -- Expected to be persistent.
- Hydrolysis** : Material -- Transformation due to hydrolysis not expected to be significant.
- Photolysis** : Material -- Transformation due to photolysis not expected to be significant.
- Atmospheric Oxidation** : Material -- Transformation due to atmospheric oxidation not expected to be significant.

Bioaccumulation/Accumulation

Conclusion/Summary : Material -- Potential to bioaccumulate is low.

Mobility in soil

Mobility : Material -- Expected to partition to sediment and wastewater solids. Low solubility and floats and is expected to migrate from water to the land.

Other ecological information

- Other adverse effects** : No known significant effects or critical hazards.
- Nota** :

Product name	EXCEED™ XP PERFORMANCE POLYMERS (PPA) (LLDPE)		
Date of revision	16 August 2024	SDS Number:	P000001215_13635281
First issue date	30 October 2023	Version	5.08

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Empty Container Warning (where applicable): Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Empty drums should be completely drained and safely stored until appropriately reconditioned or disposed. Empty containers should be taken for recycling, recovery, or disposal through suitably qualified or licensed contractor and in accordance with governmental regulations. DO NOT PRESSURISE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

Section 14. Transport information

	JT/T617-2018	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.

Special precautions for user

: **Transport within user’s premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Incompatible materials

: Strong oxidisers

Transport in bulk according to IMO instruments

: Not applicable.

Section 15. Regulatory information

[The General Rules for preparation of precautionary label for Chemicals \(GB 15258-2009\) :](#)

Not regulated.

This material is not considered hazardous according to The General Rule for Classification and Hazard Communication of Chemicals (GB 13690-2009).

[Law of the People's Republic of China on Prevention and Control of Environmental Pollution by Solid Waste :](#)

See Disposal Considerations section.

[Inventory list](#)

Please contact your supplier for information on the inventory status of this material.

Product name	EXCEED™ XP PERFORMANCE POLYMERS (PPA) (LLDPE)		
Date of revision	16 August 2024	SDS Number:	P000001215_13635281
First issue date	30 October 2023	Version	5.08

Section 16. Other information

History

- Date of issue/Date of revision : 16 August 2024
- Date of previous issue : 16 August 2024
- Version : 5.08

- Key to abbreviations :
 - ATE = Acute Toxicity Estimate
 - BCF = Bioconcentration Factor
 - GHS = Globally Harmonized System of Classification and Labelling of Chemicals
 - IATA = International Air Transport Association
 - IBC = Intermediate Bulk Container
 - IMDG = International Maritime Dangerous Goods
 - LogPow = logarithm of the octanol/water partition coefficient
 - MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
 - N/A = Not available
 - SGG = Segregation Group
 - UN = United Nations

- References : Not available.

 Indicates information that has changed from previously issued version.

THIS SDS COVERS THE FOLLOWING MATERIALS :

Exceed™ XP Performance Polymers;; EXC 112; EXP 606; EXP 607; EXT 318A; EXT 616A; EXT 656A; EXT 686; EXT 784; EXT 812A; EXT 828A; Exceed XP 6026ML; Exceed XP 6056ML; Exceed XP 7021ML; Exceed XP 7052ML; Exceed XP 8318ML; Exceed XP 8358ML; Exceed XP 8656ML; Exceed XP 8784ML; Exceed XP 8784MP

- Product code : P000001215_13635281

Notice to reader

"The information and recommendations contained herein are, to the best of ExxonMobil's knowledge and belief, accurate and reliable as of the date issued. You can contact ExxonMobil to insure that this document is the most current available from ExxonMobil. The information and recommendations are offered for the user's consideration and examination. It is the user's responsibility to satisfy itself that the product is suitable for the intended use. If buyer repackages this product, it is the user's responsibility to insure proper health, safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, re-publication or retransmission of this document, in whole or in part, is not permitted. The term, ""ExxonMobil"" is used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliates in which they directly or indirectly hold any interest."