## SAFETY DATA SHEET

EXXSOL™ D140



### Section 1. Identification

Product name : EXXSOL™ D140

Product description : Dearomatised Hydrocarbons

Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Printing ink solvent, Solvent

**Uses advised against**: This product is not recommended for any industrial, professional or consumer use

other than the Identified Uses above.

Supplier : ExxonMobil Petroleum & Chemical BV

**POLDERDIJKWEG** 

Antwerpen B-2030 Belgium

24 Hour Emergency

**Telephone** 

: +44 20 3885 0382 / +1-703-527-3887 (CHEMTREC)

Supplier General Contact : + 32 2 239 3111

E-Mail : SDS-CC@exxonmobil.com

### Section 2. Hazard identification

Classification of the substance or mixture

: Asp. Tox. 1, H304

**GHS label elements** 

Hazard pictograms :



Signal word : Danger

**Hazard statements** : H304 - May be fatal if swallowed and enters airways.

**Precautionary statements** 

Response : P301 + P331, P310 - IF SWALLOWED: Do NOT induce vomiting. Immediately call

a POISON CENTER or doctor.

**Storage** : P405 - Store locked up.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional,

national and international regulations.

Contains : Hydrocarbons, C16-C20, n-alkanes, isoalkanes, cyclics, <2% aromatics

Supplemental label

elements

: EUH066 - Repeated exposure may cause skin dryness or cracking.

Other hazards which do not

result in classification

: None known.

result in classification

Nota

: This material should not be used for any other purpose than the intended use in Section 1 without expert advice. Health studies have shown that chemical exposure may cause potential human health risks which may vary from person to person.

Date of issue/Date of revision: 20 AugustDate of previous issue: 8/20/2025Version: 6.041/102025

## Section 3. Composition/information on ingredients

Substance/mixture

: Substance

**Chemical name** 

: distillates (petroleum), hydrotreated middle

Ingredient name	% by weight	Identifiers
Hydrocarbons, C16-C20, n-alkanes, isoalkanes, cyclics, <2% aromatics		REACH #: 01-2119457735-29 EC: 919-029-3 CAS: -

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First-aid measures

### Description of necessary first aid measures

**Eye contact** 

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.

Inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact

: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

### Most important symptoms/effects, acute and delayed

### Potential acute health effects

Eye contact
 Inhalation
 No known significant effects or critical hazards.
 Skin contact
 Ingestion
 No known significant effects or critical hazards.
 Ingestion
 Way be fatal if swallowed and enters airways.

### **Over-exposure signs/symptoms**

Eye contact : No specific data.
Inhalation : No specific data.
Skin contact : No specific data.

**Ingestion** : Adverse symptoms may include the following:

nausea or vomiting

### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : If ingested, material n

: If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately.

Date of issue/Date of revision : 20 August Date of previous issue : 8/20/2025 Version : 6.04 2/10 2025

### Section 4. First-aid measures

**Specific treatments** 

- : No specific treatment.
- **Protection of first-aiders**
- : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

## Section 5. Firefighting measures

### **Extinguishing media**

Suitable extinguishing media

: Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

Unsuitable extinguishing media

: Do not use water jet.

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous combustion products

: Incomplete combustion products, Oxides of carbon, Smoke, Fume

Special protective actions for fire-fighters

: Use standard firefighting procedures and consider the hazards of other involved materials. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. Assure an extended cooling down period to prevent reignition. Prevent run-off from fire control or dilution from entering streams, sewers or drinking water supply. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### Section 6. Accidental release measures

### **NOTIFICATION PROCEDURES**

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate.

For emergency responders:

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** 

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and material for containment and cleaning up

**Small spill** 

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Date of issue/Date of revision : 20 August Date of previous issue : 8/20/2025 Version : 6.04 3/10 2025

## Section 6. Accidental release measures

### Large spill

: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Confine the spill immediately with booms. Remove from the surface by skimming or with suitable absorbents. Seek the advice of a specialist before using dispersants. Warn other shipping. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Water spill and land spill recommendations are based on the most likely spill scenario for this material; however, geographic conditions, wind, temperature, (and in the case of a water spill) wave and current direction and speed may greatly influence the appropriate action to be taken. For this reason, local experts should be consulted. Note: Local regulations may prescribe or limit action to be taken.

## Section 7. Handling and storage

### Precautions for safe handling

**Protective measures** 

: Put on appropriate personal protective equipment (see Section 8). Do not swallow. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

**Static Accumulator** 

: This material is a static accumulator. A liquid is typically considered a nonconductive, static accumulator if its conductivity is below 100 pS/m (100x10E-12 Siemens per meter) and is considered a semiconductive, static accumulator if its conductivity is below 10,000 pS/m. Whether a liquid is nonconductive or semiconductive, the precautions are the same. A number of factors, for example liquid temperature, presence of contaminants, anti-static additives and filtration can greatly influence the conductivity of a liquid.

Loading/Unloading **Temperature** 

: Ambient

**Transport Temperature Transport Pressure** 

: Ambient : Ambient

Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Storage Temperature **Storage Pressure** 

: Ambient Ambient

Suitable Containers/Packing: Tank Trucks, Railcars, Barges, Drums, Tank Cars

**Suitable Materials and** Coatings

: polyethylene, Polyester, Teflon, Carbon Steel, Stainless Steel, polypropylene

**Unsuitable Materials and** 

: butyl rubber, Natural Rubber, Ethylene-proplyene-diene monomer (EPDM), Polystyrene

Coatings

Date of issue/Date of revision Version: 6.04 : 20 August Date of previous issue : 8/20/2025 4/10 2025

## Section 8. Exposure controls/personal protection

### **Control parameters**

### **Occupational exposure limits**

No exposure limit value known.

## Appropriate engineering controls

## **Environmental exposure** controls

- : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
- : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### Individual protection measures

### **Hygiene measures**

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

### **Eye/face protection**

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

### **Skin protection**

**Hand protection** 

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. > 8 hours (breakthrough time): Nitrile, minimum 0.38 mm thickness or comparable protective barrier material

### **Body protection**

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

#### Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

### **Respiratory protection**

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: particulate filter

# Section 9. Physical and chemical properties and safety characteristics

Note: Physical and chemical properties are provided for safety, health and environmental considerations only and may not fully represent product specifications. Contact the Supplier for additional information.

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### **Appearance**

Physical state : Liquid. [Clear]
Colour : Colourless
Odour : Faint

Odour threshold : Not available.

Date of issue/Date of revision : 20 August Date of previous issue : 8/20/2025 Version : 6.04 5/10

# Section 9. Physical and chemical properties and safety characteristics

pH : Not applicable.

Melting point/freezing point : Not available.

Boiling point or initial : 279 to 311°C (534.2 to 591.8°F) [ASTM D86]

Boiling point or initial boiling point and boiling

range

Flash point : Closed cup: 137°C (278.6°F) [ASTM D-93]

Evaporation rate : <0.01 (butyl acetate = 1) [In-house method,]

Flammability : Ignitable

Lower and upper explosion limit/flammability limit

: Lower: 0.5% [Extrapolated]

Upper: 4%

Vapour pressure: <0.01 mm Hg [20 °C] [Calculated]</th>Relative vapour density: 8 [Air = 1] [In-house method ,]

Relative density : 0.83 [Calculated]

**Density** : 0.83 g/cm³ [15°C (59°F)] [ASTM D4052]

Solubility in water
Partition coefficient: n-

: Negligible

octanol/water

: >4 [Estimated]

Auto-ignition temperature

: 239°C (462.2°F) [ASTM E659]

**Decomposition temperature** 

: Not available.

**Viscosity** 

: 4.3 cSt [40 °C] [Calculated]

7.4 cSt [20 °C]

Molecular weight : 233

**Particle characteristics** 

Median particle size : Not applicable.

Pour point : -10.5°C [ASTM D5950]

Hygroscopic : No

**Coefficient of Thermal** 

**Expansion** 

: 0.0007 per Deg C

## Section 10. Stability and reactivity

**Reactivity**: No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability**: The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : Excessive heat.

Incompatible materials : Strong oxidisers

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

Date of issue/Date of revision: 20 AugustDate of previous issue: 8/20/2025Version: 6.046/102025

## **Section 11. Toxicological information**

### Information on toxicological effects

### **Acute toxicity**

Product/ingredient name	Result
Hydrocarbons, C16-C20, n-alkanes, isoalkanes, cyclics, <2% aromatics	<b>Rat - Oral - LD50</b> >5000 mg/kg
	Rabbit - Dermal - LD50 >3160 mg/kg
	Rat - Inhalation - LC50 Dusts and mists >5000 mg/m³ [4 hours]

### **Conclusion/Summary**

**Inhalation** : Minimally Toxic. Data available. Based on test data for structurally similar materials.

Test(s) equivalent or similar to OECD Guideline 403

**Dermal** : Minimally Toxic. Data available. Based on test data for structurally similar materials.

Test(s) equivalent or similar to OECD Guideline 402

Oral : Minimally Toxic. Data available. Based on test data for structurally similar materials.

Test(s) equivalent or similar to OECD Guideline 401

### **Irritation/Corrosion**

**Conclusion/Summary** 

Skin
 May dry the skin leading to discomfort and dermatitis. Data available. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline

404

**Eyes** : May cause mild, short-lasting discomfort to eyes. Data available. Based on test data

for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 405

**Respiratory**: Negligible hazard at ambient/normal handling temperatures. No end point data for

material.

### Respiratory or skin sensitization

### **Conclusion/Summary**

Skin : Not expected to be a skin sensitizer. Data available. Based on test data for

structurally similar materials. Test(s) equivalent or similar to OECD Guideline 406

**Respiratory**: Not expected to be a respiratory sensitizer. No end point data for material.

**Mutagenicity** 

**Conclusion/Summary**: Not expected to be a germ cell mutagen. Data available.

**Carcinogenicity** 

**Conclusion/Summary**: Not expected to cause cancer. No end point data for material.

Reproductive toxicity

**Conclusion/Summary**: Not expected to be a reproductive toxicant. Data available. Based on test data for the

material. Test(s) equivalent or similar to OECD Guideline 414

### Specific target organ toxicity (single exposure)

**Conclusion/Summary**: Not expected to cause organ damage from a single exposure. No end point data for

material.

### Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Target organs
distillates (petroleum), hydrotreated middle	Not applicable.	-

### **Conclusion/Summary**

: Not expected to cause organ damage from prolonged or repeated exposure. Data available. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 408 411 413

### **Aspiration hazard**

Product/ingredient name	Result
distillates (petroleum), hydrotreated middle	Category 1

Date of issue/Date of revision	: 20 August	Date of previous issue	: 8/20/2025	Version: 6.04	7/10
	2025				

## **Section 11. Toxicological information**

**Conclusion/Summary** 

: May be fatal if swallowed and enters airways. Based on physico-chemical properties of the material. Data available.

### Other information

**Product** 

: Prolonged and/or repeated skin contact with low viscosity materials may defat the skin resulting in possible irritation and dermatitis. Vapour concentrations above recommended exposure levels are irritating to the eyes and the respiratory tract, may cause headaches and dizziness, are anaesthetic and may have other central nervous system effects. Small amounts of liquid aspirated into the lungs during ingestion or from vomiting may cause chemical pneumonitis or pulmonary edema.

## **Section 12. Ecological information**

The information given is based on data for the material, components of the material, or for similar materials, through the application of bridging principals.

### **Toxicity**

Product/ingredient name

Hydrocarbons, C16-C20, n-alkanes, isoalkanes, cyclics, <2% aromatics

Result

Acute - LL0 Fish - Fish

1028 mg/l - data for similar materials [96 hours]

Acute - LL50

Invertebrate - Invertebrate

>3000 mg/l - data for similar materials [48 hours]

Acute - EL0

Algae - Skeletonema costatum

3198 mg/l - data for similar materials [72 hours]

Acute - NOEL

Algae - Skeletonema costatum

3198 mg/l - data for similar materials [72 hours]

**Conclusion/Summary** 

**Acute toxicity** 

: Not expected to be harmful to aquatic organisms.

**Chronic toxicity** 

: Not expected to demonstrate chronic toxicity to aquatic organisms

### Persistence and degradability

Product/ingredient name

Result

Hydrocarbons, C16-C20, n-alkanes, isoalkanes, cyclics, <2% aromatics

Ready Biodegradability 74% [28 days]

**Biodegradability** 

: Material -- Available OECD 301F biodegradation data indicate that material is readily biodegradable (=60% in 28 days).

Hydrolysis Photolysis

: Material -- Transformation due to hydrolysis not expected to be significant.
: Material -- Transformation due to photolysis not expected to be significant.

**Atmospheric Oxidation** 

: Material -- Expected to degrade rapidly in air

### **Bioaccumulative potential**

Not determined.

### **Mobility in soil**

**Mobility** 

: Material -- Expected to partition to sediment and wastewater solids. Low solubility and floats and is expected to migrate from water to the land.

Date of issue/Date of revision : 20 August Date of previous issue : 8/20/2025 Version : 6.04 8/10 2025

## **Section 12. Ecological information**

Other ecological information

Other adverse effects : No known significant effects or critical hazards.

## Section 13. Disposal considerations

**Disposal methods** 

: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

## **Section 14. Transport information**

	ADR	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according: Not applicable. to IMO instruments

## Section 15. Regulatory information

### International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

### **Montreal Protocol**

Not listed.

**Stockholm Convention on Persistent Organic Pollutants** 

Not listed.

**Rotterdam Convention on Prior Informed Consent (PIC)** 

Not listed.

**UNECE Aarhus Protocol on POPs and Heavy Metals** 

Not listed.

### **Inventory list**

**Australia inventory (AIIC)** : All components are listed or exempted. Canada inventory (DSL-NDSL) : All components are listed or exempted.

Date of issue/Date of revision Version: 6.04 : 20 August Date of previous issue : 8/20/2025 2025

## Section 15. Regulatory information

China inventory (IECSC) : All components are listed or exempted.

Japan inventory (CSCL) : All components are listed or exempted.

Japan inventory (Industrial Safety and : Not determined.

**Health Act)** 

**New Zealand Inventory of Chemicals** 

(NZIoC)

: All components are listed or exempted.

Philippines inventory (PICCS) : All components are listed or exempted.

Korea inventory (KECI) : All components are listed or exempted.

Taiwan Chemical Substances Inventory

**United States inventory (TSCA 8b)** 

: All components are listed or exempted.

(TCSI)

: All components are active or exempted.

The national inventory listings are based on the CAS number or numbers listed below.

64742-46-7

## Section 16. Other information

**History** 

Date of issue/Date of : 8/20/2025

revision

Date of previous issue : 20 August 2025

Version : 6.04

**Key to abbreviations** : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available SGG = Segregation Group UN = United Nations

Procedure used to derive the classification

Asp. Tox. 1, H304 Calculation method

References : Not available.

Indicates information that has changed from previously issued version.

Product code : 1161538

**Notice to reader** 

"The information and recommendations contained herein are, to the best of ExxonMobil's knowledge and belief, accurate and reliable as of the date issued. You can contact ExxonMobil to insure that this document is the most current available from ExxonMobil. The information and recommendations are offered for the user's consideration and examination. It is the user's responsibility to satisfy itself that the product is suitable for the intended use. If buyer repackages this product, it is the user's responsibility to insure proper health, safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, re-publication or retransmission of this document, in whole or in part, is not permitted. The term, ""ExxonMobil" is used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliates in which they directly or indirectly hold any interest."

Date of issue/Date of revision : 20 August Date of previous issue : 8/20/2025 Version : 6.04 10/10

2025