

| | | | |
|-------------------------|-------------------|--------------------|------------------|
| Product name | EXXSOL™ HEXANE SP | SDS Number: | 1201284_13510286 |
| Date of revision | 30 July 2025 | Version | 4 |
| First issue date | 13 February 2024 | | |

SAFETY DATA SHEET



EXXSOL™ HEXANE SP

Section 1. Identification

| | |
|---|--|
| Product name | : EXXSOL™ HEXANE SP |
| Product description | : Hexane |
| <u>Relevant identified uses of the substance or mixture and uses advised against</u> | |
| Identified uses | : Polymerization fluid |
| Uses advised against | : This product is not recommended for any industrial, professional or consumer use other than the Identified Uses above. |
| Supplier | : EXXONMOBIL CHEMICAL SERVICES (SHANGHAI) CO., LTD Correspondence address: 1099 Zixing Road Minhang District SHANGHAI China |
| 24 Hour Emergency Telephone | : (+86)0532-83889090 (NRCC) |
| Supplier General Contact | : (+86) 021-23515000 |
| E-Mail | : sds-CN.SM@exxonmobil.com |
| FAX | : 86-21-23500826 |
| Supplier | : ExxonMobil Chemical Asia Pacific (Regn. No. 52893724C) (A Division Of ExxonMobil Asia Pacific Pte Ltd - Regn. No. 196800312N) 1 HarbourFront Place #06-00 HarbourFront Tower One 098633 Singapore |
| Supplier General Contact | : +65 6885 8000 |
| SDS Internet Address | : www.sds.exxonmobil.com |

Section 2. Hazards identification

| | |
|---|-------------------|
| Classification of the substance or mixture is in accordance with national standard GB30000 series of Specification/Rules for classification and labeling of chemicals | |
| <u>Emergency overview</u> | |
| Physical state | : Liquid. [Clear] |
| Colour | : Colourless |
| Odour | : Slight |
| Highly flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure. (peripheral nervous system) Toxic to aquatic life with long lasting effects. IF SWALLOWED: Get emergency medical help immediately. IF exposed or concerned, get medical advice. Get medical help if you feel unwell. If skin irritation occurs: Get medical help. | |





| | | | |
|-------------------------|-------------------|--------------------|------------------|
| Product name | EXXSOL™ HEXANE SP | SDS Number: | 1201284_13510286 |
| Date of revision | 30 July 2025 | Version | 4 |
| First issue date | 13 February 2024 | | |

Section 2. Hazards identification

Classification of the substance or mixture
: FLAMMABLE LIQUIDS - Category 2
SKIN CORROSION/IRRITATION - Category 2
REPRODUCTIVE TOXICITY - Category 2
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (Narcotic effects) - Category 3
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
ASPIRATION HAZARD - Category 1
SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 2
LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2

GHS label elements

Hazard pictograms
:

Signal word
: Danger

Hazard statements
: H225 - Highly flammable liquid and vapour.
H304 - May be fatal if swallowed and enters airways.
H315 - Causes skin irritation.
H336 - May cause drowsiness or dizziness.
H361 - Suspected of damaging fertility or the unborn child.
H373 - May cause damage to organs through prolonged or repeated exposure. (peripheral nervous system)
H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention
: P203 - Obtain, read and follow all safety instructions before use.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240 - Ground and bond container and receiving equipment.
P241 - Use explosion-proof electrical, ventilating or lighting equipment.
P242 - Use non-sparking tools.
P243 - Take action to prevent static discharges.
P260 - Do not breathe vapour.
P264 - Wash thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P273 - Avoid release to the environment.
P280 - Wear protective gloves, protective clothing, eye protection, face protection, or hearing protection.

Response
: P301 + P331, P316 - IF SWALLOWED: Do NOT induce vomiting. Get emergency medical help immediately.
P302 + P352 - IF ON SKIN: Wash with plenty of water.
P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse affected areas with water or shower.
P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P318 - IF exposed or concerned, get medical advice.
P319 - Get medical help if you feel unwell.
P332 + P317 - If skin irritation occurs: Get medical help.
P362 + P364 - Take off contaminated clothing and wash it before reuse.
P370 + P378 - In case of fire: Use water fog, foam, dry chemical or carbon dioxide (CO2) to extinguish flames.
P391 - Collect spillage.

Storage
: P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 - Keep cool.
P405 - Store locked up.

Date of issue

Date of revision

Date of previous issue

Version

4

2/14

| | | | |
|-------------------------|-------------------|--------------------|------------------|
| Product name | EXXSOL™ HEXANE SP | SDS Number: | 1201284_13510286 |
| Date of revision | 30 July 2025 | Version | 4 |
| First issue date | 13 February 2024 | | |

Section 2. Hazards identification

| | |
|--------------------------------------|---|
| Disposal | : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations. |
| Physical and chemical hazards | : Highly flammable liquid and vapour. |
| Health hazards | : May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness. Suspected of damaging fertility or the unborn child. |

Symptoms related to the physical, chemical and toxicological characteristics

| | |
|---------------------|---|
| Eye contact | : Adverse symptoms may include the following: pain or irritation watering redness |
| Inhalation | : Adverse symptoms may include the following: nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness Numbness, muscle cramps, weakness and paralysis that may be delayed. |
| Skin contact | : Adverse symptoms may include the following: irritation redness |
| Ingestion | : Adverse symptoms may include the following: nausea or vomiting |

Delayed and immediate effects as well as chronic effects from short and long-term exposure

| | |
|------------------------------------|------------------|
| Short term exposure | |
| Potential immediate effects | : Not available. |
| Potential delayed effects | : Not available. |
| Long term exposure | |
| Potential immediate effects | : Not available. |
| Potential delayed effects | : Not available. |

| | |
|--|--|
| Environmental hazards | : Toxic to aquatic life with long lasting effects. |
| Contains | : naphtha (petroleum), hydrotreated light |
| Other hazards which do not result in classification | : None known. |
| Nota | : This material should not be used for any other purpose than the intended use in Section 1 without expert advice. Health studies have shown that chemical exposure may cause potential human health risks which may vary from person to person. |

| | | | |
|-------------------------|-------------------|--------------------|------------------|
| Product name | EXXSOL™ HEXANE SP | SDS Number: | 1201284_13510286 |
| Date of revision | 30 July 2025 | Version | 4 |
| First issue date | 13 February 2024 | | |

Section 3. Composition/information on ingredients

Substance/mixture : Substance

Chemical name : naphtha (petroleum), hydrotreated light

| Ingredient name | % (w/w) | Identifiers |
|---|---------|-----------------|
| naphtha (petroleum), hydrotreated light | 100 | CAS: 64742-49-0 |
| n-hexane | 40 - 60 | CAS: 110-54-3 |
| hexane (mixtures of isomers) | 30 - 45 | Proprietary |
| methylcyclopentane | 10 - 20 | CAS: 96-37-7 |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-aid measures

First aid

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Continue to rinse for at least 10 minutes. Get medical attention.

Eye contact : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Ingestion : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Inhalation : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.

Skin contact : Causes skin irritation.

Eye contact : No known significant effects or critical hazards.

Ingestion : Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.

Over-exposure signs/symptoms

| | | | |
|-------------------------|-------------------|--------------------|------------------|
| Product name | EXXSOL™ HEXANE SP | SDS Number: | 1201284_13510286 |
| Date of revision | 30 July 2025 | Version | 4 |
| First issue date | 13 February 2024 | | |

Section 4. First-aid measures

- Inhalation** : Adverse symptoms may include the following:
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
Numbness, muscle cramps, weakness and paralysis that may be delayed.
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Ingestion** : Adverse symptoms may include the following:
nausea or vomiting

Indication of immediate medical attention and special treatment needed, if necessary

- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.
- Notes to physician** : If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately. This material, or a component, may be associated with cardiac sensitization following very high exposures (well above occupational exposure limits) or with concurrent exposure to high stress levels or heart-stimulating substances like epinephrine. Administration of such substances should be avoided.

See toxicological information (Section 11)

Section 5. Firefighting measures

Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO₂, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

- Specific hazards arising from the chemical** : Highly flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapour/gas is heavier than air and will spread along the ground. Vapours may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous combustion products** : Incomplete combustion products, Oxides of carbon, Smoke, Fume

| | | | |
|-------------------------|-------------------|--------------------|------------------|
| Product name | EXXSOL™ HEXANE SP | | |
| Date of revision | 30 July 2025 | SDS Number: | 1201284_13510286 |
| First issue date | 13 February 2024 | Version | 4 |

Section 5. Firefighting measures

Special protective actions for fire-fighters
: Use standard firefighting procedures and consider the hazards of other involved materials. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool. Assure an extended cooling down period to prevent re-ignition. Prevent run-off from fire control or dilution from entering streams, sewers or drinking water supply. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters
: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

NOTIFICATION PROCEDURES

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

For emergency responders

Environmental precautions

Methods and material for containment and cleaning up

Small spill

Large spill

Precautionary measures to prevent the occurrence of secondary disasters

| | | | | | | |
|--|----------------|-------------------------------|----------------|----------------|-----|------|
| Date of issue / Date of revision | : 30 July 2025 | Date of previous issue | : 30 July 2025 | Version | : 4 | 6/14 |
|--|----------------|-------------------------------|----------------|----------------|-----|------|

| | | | |
|-------------------------|-------------------|--------------------|------------------|
| Product name | EXXSOL™ HEXANE SP | SDS Number: | 1201284_13510286 |
| Date of revision | 30 July 2025 | Version | 4 |
| First issue date | 13 February 2024 | | |

Section 6. Accidental release measures

Water spill and land spill recommendations are based on the most likely spill scenario for this material; however, geographic conditions, wind, temperature, (and in the case of a water spill) wave and current direction and speed may greatly influence the appropriate action to be taken. For this reason, local experts should be consulted. Note: Local regulations may prescribe or limit action to be taken.

Section 7. Handling and storage

Precautions for safe handling

Precautions for operating

Advice on general occupational hygiene

Static Accumulator

Loading/Unloading Temperature

Transport Temperature

Transport Pressure

Conditions for safe storage

Storage Temperature

Storage Pressure

Suitable Containers/Packing

Suitable Materials and Coatings

Unsuitable Materials and Coatings

Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not swallow. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

This material is a static accumulator. A liquid is typically considered a nonconductive, static accumulator if its conductivity is below 100 pS/m (100x10E-12 Siemens per meter) and is considered a semiconductive, static accumulator if its conductivity is below 10,000 pS/m. Whether a liquid is nonconductive or semiconductive, the precautions are the same. A number of factors, for example liquid temperature, presence of contaminants, anti-static additives and filtration can greatly influence the conductivity of a liquid.

Ambient

Ambient

Ambient

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Ambient

Ambient

Tank Trucks, Railcars, Barges, Drums

Carbon Steel, Stainless Steel, polyethylene, polypropylene, Polyester, Teflon

Natural Rubber, butyl rubber, Ethylene-propylene-diene monomer (EPDM), Polystyrene

Date of issue

Date of revision

Date of previous issue

Version

4

7/14

| | | | |
|-------------------------|-------------------|--------------------|------------------|
| Product name | EXXSOL™ HEXANE SP | SDS Number: | 1201284_13510286 |
| Date of revision | 30 July 2025 | Version | 4 |
| First issue date | 13 February 2024 | | |

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

| Ingredient name | Exposure limits |
|---|--|
| naphtha (petroleum), hydrotreated light | ExxonMobil (COMPANY) RCP - TWA: 85 ppm (Total Hydrocarbons). Form: Vapour.. RCP - TWA: 300 mg/m³ (Total Hydrocarbons). Form: Vapour.. |
| naphtha (petroleum), hydrotreated light | ACGIH TLV (United States, 1/2024) [branched hexane isomers] TWA 8 hours: 200 ppm. ACGIH TLV (United States, 1/2024) [hexane] Absorbed through skin. TWA 8 hours: 100 ppm. |
| n-hexane | GBZ 2.1 (China, 7/2024) Absorbed through skin. PC-TWA 8 hours: 100 mg/m³. PC-STEL 15 minutes: 180 mg/m³. ACGIH TLV (United States, 1/2024) Absorbed through skin. TWA 8 hours: 50 ppm. |
| cyclohexane | GBZ 2.1 (China, 7/2024) PC-TWA 8 hours: 250 mg/m³. ACGIH TLV (United States, 1/2024) TWA 8 hours: 100 ppm. |

NOTE: Limits/standards shown for guidance only. Follow applicable regulations.

Biological exposure indices

| Ingredient name | Exposure indices |
|-----------------|--|
| n-hexane | GBZ 2.1 (China, 11/2022) BEI: 4 mg/L, 2,5-hexanedione [in urine]. Sampling time: after work shift. BEI: 35 µmol/L, 2,5-hexanedione [in urine]. Sampling time: after work shift. |

Appropriate engineering controls

- : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls

- : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

- : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

- : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

| | | | |
|-------------------------|-------------------|--------------------|------------------|
| Product name | EXXSOL™ HEXANE SP | SDS Number: | 1201284_13510286 |
| Date of revision | 30 July 2025 | Version | 4 |
| First issue date | 13 February 2024 | | |

Section 8. Exposure controls/personal protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. < 1 hour (breakthrough time): Nitrile, minimum 0.38 mm thickness or comparable protective barrier material

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: organic vapour filter (Type A)

Section 9. Physical and chemical properties

Note: Physical and chemical properties are provided for safety, health and environmental considerations only and may not fully represent product specifications. Contact the Supplier for additional information.

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance and physical state

Physical state : Liquid. [Clear]

Colour : Colourless

Odour : Slight

Odour threshold : Not available.

pH : Not applicable.

Melting point/freezing point : Not available.

Boiling point or initial boiling point and boiling range : 65 to 68°C (149 to 154.4°F) [ASTM D86]

Flash point : Closed cup: <0°C (<32°F) [ASTM D-56]

Evaporation rate : 14 (butyl acetate = 1) [Calculated]

Flammability : Flammable liquids - Category 2

Lower and upper explosion limit/flammability limit : Lower: 1.2%
Upper: 8%

Vapour pressure : 135.01 mm Hg [20 °C] [Calculated]

Relative vapour density : 3 [Air = 1] [Calculated]

Relative density : 0.68 [Calculated]

Density : 0.68 g/cm³ [15°C (59°F)] [ASTM D4052]

Solubility in water : Negligible

Partition coefficient: n-octanol/water : >4 [Estimated]

Auto-ignition temperature : 267°C (512.6°F) [Extrapolated]

Decomposition temperature : Not available.

Viscosity : 0.4 cSt [40 °C] [Calculated]

| | | | | | | |
|--|----------------|-------------------------------|----------------|----------------|-----|------|
| Date of issue / Date of revision | : 30 July 2025 | Date of previous issue | : 30 July 2025 | Version | : 4 | 9/14 |
|--|----------------|-------------------------------|----------------|----------------|-----|------|

| | | | |
|-------------------------|-------------------|--------------------|------------------|
| Product name | EXXSOL™ HEXANE SP | SDS Number: | 1201284_13510286 |
| Date of revision | 30 July 2025 | Version | 4 |
| First issue date | 13 February 2024 | | |

Section 9. Physical and chemical properties

| | |
|---|-----------------------|
| Molecular weight | : 86 |
| Particle characteristics | |
| Median particle size | : Not applicable. |
| Pour point | : -108°C [ASTM D5950] |
| Hygroscopic | : No |
| Coefficient of Thermal Expansion | : 0.00135 per Deg C |

Section 10. Stability and reactivity

| | |
|---|---|
| Reactivity | : No specific test data related to reactivity available for this product or its ingredients. |
| Chemical stability | : The product is stable. |
| Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur. |
| Conditions to avoid | : Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapour to accumulate in low or confined areas. |
| Incompatible materials | : Reactive or incompatible with the following materials:;oxidising materials,Strong oxidisers |
| Hazardous decomposition products | : Under normal conditions of storage and use, hazardous decomposition products should not be produced. |

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

| Product/ingredient name | Result |
|---|--|
| naphtha (petroleum), hydrotreated light | Rabbit - Dermal - LD50 >3350 mg/kg Rat - Oral - LD50 >5000 mg/kg Rat - Inhalation - LC50 Vapour >20 mg/l [4 hours] |

| | |
|---------------------------|---|
| Conclusion/Summary | |
| Inhalation | : Minimally Toxic. Data available. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 403 |
| Dermal | : Minimally Toxic. Data available. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 402 |
| Oral | : Minimally Toxic. Data available. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 401 |

Irritation/Corrosion

| | |
|---------------------------|--|
| Conclusion/Summary | |
| Skin | : Irritating to the skin. Data available. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 404 |
| Eyes | : May cause mild, short-lasting discomfort to eyes. Data available. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 405 |

| | | | |
|-------------------------|-------------------|--------------------|------------------|
| Product name | EXXSOL™ HEXANE SP | SDS Number: | 1201284_13510286 |
| Date of revision | 30 July 2025 | Version | 4 |
| First issue date | 13 February 2024 | | |

Section 11. Toxicological information

Respiratory

: Negligible hazard at ambient/normal handling temperatures. No end point data for material.

Respiratory or skin sensitization

Conclusion/Summary

Skin

: Not expected to be a skin sensitizer. Data available. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 429

Respiratory

: Not expected to be a respiratory sensitizer. No end point data for material.

Germ Cell Mutagenicity

Conclusion/Summary

: Not expected to be a germ cell mutagen. Data available. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 471 473 475 476

Carcinogenicity

Conclusion/Summary

: Not expected to cause cancer. Data available. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 451

Reproductive toxicity

Conclusion/Summary

: May damage fertility. Data available. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 414 416

Specific target organ toxicity (single exposure)

Conclusion/Summary

: May cause drowsiness or dizziness. No end point data for material.

Specific target organ toxicity (repeated exposure)

| Product/ingredient name | Category | Target organs |
|---|-----------------|---------------------------|
| naphtha (petroleum), hydrotreated light | Not applicable. | peripheral nervous system |

Conclusion/Summary

: May cause damage to organs through prolonged or repeated exposure. Data available. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 408 413

Aspiration hazard

Conclusion/Summary

: May be fatal if swallowed and enters airways. Based on physico-chemical properties of the material. Data available.

Other information

Contains

: N-HEXANE: Prolonged and/or repeated exposures to n-Hexane can cause progressive and potentially irreversible damage to the peripheral nervous system (e.g. fingers, feet, arms, legs, etc.). Simultaneous exposure to Methyl Ethyl Ketone (MEK) or Methyl Isobutyl Ketone (MIBK) and n-Hexane can potentiate the risk of adverse effects from n-Hexane on the peripheral nervous system. n-Hexane has been shown to cause testicular damage at high doses in male rats. The relevance of this effect for humans is unknown. Contains hexane; individuals with pre-existing neurological disease should avoid exposure. Trixylenyl Phosphate (TXP): Exposure to large amounts over a prolonged time may cause neurological effects. The potential for delayed peripheral neuropathy is very low and will be dependent on the level of ortho isomer.

Product

: Vapour concentrations above recommended exposure levels are irritating to the eyes and the respiratory tract, may cause headaches and dizziness, are anaesthetic and may have other central nervous system effects. COMMERCIAL HEXANE: In a two-generation reproduction study conducted on commercial hexane in animals, reduced body weights were seen in offspring of both generations at the highest concentration (9000 ppm). No effects on reproductive performance were noted. Effects were seen only at many times the concentration level of the TLV. Normal hexane (n-hexane) causes peripheral nerve damage in laboratory animals and humans. Exposure to this material, or one of its components, in situations where there is the potential for high levels, such as in confined spaces or with abuse, may result in abnormal heart rhythm (arrhythmia). High-level exposure to hydrocarbons (above occupational exposure limits) may initiate arrhythmia in a worker that is undergoing stress or is taking a heart

| | | | |
|-------------------------|-------------------|--------------------|------------------|
| Product name | EXXSOL™ HEXANE SP | SDS Number: | 1201284_13510286 |
| Date of revision | 30 July 2025 | Version | 4 |
| First issue date | 13 February 2024 | | |

Section 11. Toxicological information

stimulating substance such as epinephrine, a nasal decongestant, or an asthma or cardiovascular drug. Small amounts of liquid aspirated into the lungs during ingestion or from vomiting may cause chemical pneumonitis or pulmonary edema.

Section 12. Ecological information

The information given is based on data for the material, components of the material, or for similar materials, through the application of bridging principals.

Toxicity

Conclusion/Summary

- Acute toxicity** : Toxic to aquatic life.
Chronic toxicity : Toxic to aquatic life with long lasting effects.

Persistence and degradability

- Biodegradability** : Material -- Expected to be readily biodegradable.
Atmospheric Oxidation : Material -- Expected to degrade rapidly in air

Bioaccumulation/Accumulation

Not determined.

Mobility in soil

- Mobility** : Material -- Highly volatile, will partition rapidly to air. Not expected to partition to sediment and wastewater solids.

Other ecological information

- Other adverse effects** : No known significant effects or critical hazards.




Section 13. Disposal considerations

- Disposal methods** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Empty Container Warning (where applicable): Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Empty drums should be completely drained and safely stored until appropriately reconditioned or disposed. Empty containers should be taken for recycling, recovery, or disposal through suitably qualified or licensed contractor and in accordance with governmental regulations. DO NOT PRESSURISE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

| | | | |
|-------------------------|-------------------|--------------------|------------------|
| Product name | EXXSOL™ HEXANE SP | SDS Number: | 1201284_13510286 |
| Date of revision | 30 July 2025 | Version | 4 |
| First issue date | 13 February 2024 | | |

Section 14. Transport information

| | JT/T617 | IMDG | IATA |
|----------------------------|---|---|---|
| UN number | UN1208 | UN1208 | UN1208 |
| UN proper shipping name | HEXANES | HEXANES (naphtha (petroleum), hydrotreated light, n-hexane) | Hexanes (naphtha (petroleum), hydrotreated light, n-hexane) |
| Transport hazard class(es) | 3 | 3 | 3 |
| Label(s) / Mark(s) |  |  |  |
| Packing group | II | II | II |
| Environmental hazards | Yes. | Yes. | Yes. The environmentally hazardous substance mark is not required. |

| | |
|-------------------------------|--|
| <u>Additional information</u> | |
| China - JT/T617 | : The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg. |
| IMDG | : The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg. Emergency schedules F-E, _S-D_ |
| IATA | : The environmentally hazardous substance mark may appear if required by other transportation regulations. Quantity limitation Passenger and Cargo Aircraft: 5 L. Packaging instructions: 353. Cargo Aircraft Only: 60 L. Packaging instructions: 364. Limited Quantities - Passenger Aircraft: 1 L. Packaging instructions: Y341. |

Special precautions for user : **Transport within user’s premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

| | |
|--|--|
| <u>Extinguishing media</u> | |
| Suitable extinguishing media | : Use dry chemical, CO ₂ , water spray (fog) or foam. |
| Unsuitable extinguishing media | : Do not use water jet. |
| Incompatible materials | : Reactive or incompatible with the following materials: ,oxidising materials,Strong oxidisers |
| Transport in bulk according to IMO instruments | : Not available. |

Section 15. Regulatory information

The hazard classification for this material is in accordance with national standard GB30000 series of Specification/Rules for classification and labeling of chemicals

[Refer to below China regulations \(if applicable\):](#)

The General Rules for preparation of precautionary label for Chemicals (GB 15258-2009)
Regulations on the Safe Management of Hazardous Chemicals
Measures for the Environmental Management Registration of New Chemical Substances

[Inventory list](#)

| | | | |
|-------------------------|-------------------|--------------------|------------------|
| Product name | EXXSOL™ HEXANE SP | SDS Number: | 1201284_13510286 |
| Date of revision | 30 July 2025 | Version | 4 |
| First issue date | 13 February 2024 | | |

Section 15. Regulatory information

| | |
|---|--|
| Australia inventory (AIC) | : All components are listed or exempted. |
| Canada inventory (DSL-NDSL) | : All components are listed or exempted. |
| China inventory (IECSC) | : All components are listed or exempted. |
| Japan inventory (CSCL) | : All components are listed or exempted. |
| Japan inventory (Industrial Safety and Health Act) | : Not determined. |
| New Zealand Inventory of Chemicals (NZIoC) | : Not determined. |
| Philippines inventory (PICCS) | : All components are listed or exempted. |
| Korea inventory (KECI) | : All components are listed or exempted. |
| Taiwan Chemical Substances Inventory (TCSI) | : All components are listed or exempted. |
| United States inventory (TSCA 8b) | : All components are active or exempted. |

Section 16. Other information

History

| | |
|---------------------------------------|--|
| Date of issue/Date of revision | : 30 July 2025 |
| Date of previous issue | : 30 July 2025 |
| Version | : 4 |
| Key to abbreviations | : ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Intermediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations |

References : Not available.

Indicates information that has changed from previously issued version.

Product code : 1201284_13510286

Notice to reader

"The information and recommendations contained herein are, to the best of ExxonMobil's knowledge and belief, accurate and reliable as of the date issued. You can contact ExxonMobil to insure that this document is the most current available from ExxonMobil. The information and recommendations are offered for the user's consideration and examination. It is the user's responsibility to satisfy itself that the product is suitable for the intended use. If buyer repackages this product, it is the user's responsibility to insure proper health, safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, re-publication or retransmission of this document, in whole or in part, is not permitted. The term, "ExxonMobil" is used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliates in which they directly or indirectly hold any interest."