

Product Name: FUEL OIL BIO - BMF.5™
Revision Date: 08 Feb 2023
Page 1 of 15

SAFETY DATA SHEET

(SOLAS regulation VI/5-1 format)

SECTION 1 PRODUCT AND COMPANY IDENTIFICATION

PRODUCT

Product Name: FUEL OIL BIO - BMF.5™
Product Description: Hydrocarbons and Additives
Product Code: 709783-60
Intended Use: Fuel oil
MARPOL Annex I Category: Fuel and residual oils, including ship's bunkers
See Section 14 for transportation information related to the Bill of Lading, other shipping documents

Trade Names	Trade Names
Bio VLSFO	BIO-VLSFO B30

COMPANY IDENTIFICATION

Country	Company	Emergency Telephone Number
International Sales	ExxonMobil Marine Fuels Ermyn House MP 31 Ermyn Way Leatherhead, KT22 8UX UK	(UK) (+44) (0) 23 8089 1558
Australia	MOBIL OIL AUSTRALIA PTY LTD A.B.N. 88 004 052 984 664 Collins St Docklands Victoria 3008 Australia	+1 609 737 4411
Belgium	ExxonMobil Petroleum & Chemical BV Polderdijkweg Haven 447 - 2030 Antwerpen, Belgium	+32 (0) 487 545 780
Canada	Imperial Oil 505 Quarry Park Boulevard SE Calgary, AB T2C 5N1 Canada	1-866-232-9563
Fiji	Mobil Oil Australia Pty Ltd - t/a Mobil Oil Fiji Level 6, ANZ House, 25 Victoria Parade, Suva, Fiji Islands	+1 609 737 4411
France	Esso SAF Tour Manhattan La Defense 2 5/6 Place de l'Iris 92400 Courbevoie France	+33 08 1000 3353
Hong Kong	ExxonMobil Hong Kong Limited: 2201, 22/F, Central Plaza 18 Harbour Road, Wanchai, Hong Kong	+1 609 737 4411
Italy	Esso Italiana SRL Viale Castello della Magliana 25 Rome 00148 Italy	+39 0382 24444
New Zealand	Mobil Oil New Zealand Limited Vero Centre	National Poison Center +64 3 479 7248 Freephone 0800 764 766

Product Name: FUEL OIL BIO - BMF.5™

Revision Date: 08 Feb 2023

Page 2 of 15

	48 Shortland Street Auckland 1140 New Zealand	
Norway	Esso Norge AS Drammensveien 149 Skøyen N-0213 Oslo, Norway	Emergency: (NO) +47 33 37 73 00 Poison: (NO) +47 22 59 13 00
Singapore	ExxonMobil Asia Pacific Pte Limited 1 HarbourFront Place #06-00 HarbourFront Tower One Singapore 098633	01-609-737-4411
Thailand	Esso (Thailand) Public Company Limited 3195/17-29 Rama 4 Road, Klong Ton, Klong Toey District Bangkok, Thailand 10110	+1-609-737-4411
United Kingdom	Esso Petroleum Company Limited Ermyn House MP 31 Ermyn Way Leatherhead, KT22 8UX UK	+32 (0) 487 545 780
United States	ExxonMobil Oil Corporation 22777 Springwoods Village Parkway Spring, TX 77389 USA	+1 609 737 4411

This (M)SDS is a document with no country specific information included.

SECTION 2 HAZARDS IDENTIFICATION

This material is hazardous according to UN GHS Criteria. Classification includes all GHS hazard classes. For hazard categories with two cut-off/concentration limits, classification was based on the higher limit.

GHS CLASSIFICATION:

Flammable liquid: Category 4.
Acute inhalation toxicant: Category 4.
Skin irritation: Category 2.
Germ Cell Mutagen: Category 1B.
Carcinogen: Category 1B.
Reproductive toxicant (developmental): Category 2.
Specific target organ toxicant (repeated exposure): Category 2.
Aspiration toxicant: Category 1.
Acute aquatic toxicant: Category 1.
Chronic aquatic toxicant: Category 1.

GHS Label Elements:

Pictogram:



Signal Word: Danger

Hazard Statements:

Physical: H227: Combustible liquid.

Product Name: FUEL OIL BIO - BMF.5™

Revision Date: 08 Feb 2023

Page 3 of 15

Health: H304: May be fatal if swallowed and enters airways. H315: Causes skin irritation. H332: Harmful if inhaled. H340: May cause genetic defects. H350: May cause cancer. H361: Suspected of damaging the unborn child. H373: May cause damage to organs through prolonged or repeated exposure.
Environmental: H410: Very toxic to aquatic life with long lasting effects.

Precautionary Statements:

Prevention: P201: Obtain special instructions before use. P202: Do not handle until all safety precautions have been read and understood. P210: Keep away from flames and hot surfaces. No smoking. P260: Do not breathe mist / vapours. P264: Wash skin thoroughly after handling. P271: Use only outdoors or in a well-ventilated area. P273: Avoid release to the environment. P280: Wear protective gloves/protective clothing/eye protection/face protection.

Response: P301 + P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. P302 + P352: IF ON SKIN: Wash with plenty of soap and water. P304 + P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing. P308 + P313: IF exposed or concerned: Get medical advice/attention. P312: Call a POISON CENTER or doctor/physician if you feel unwell. P331: Do NOT induce vomiting. P332 + P313: If skin irritation occurs: Get medical advice/attention. P362 + P364: Take off contaminated clothing and wash it before reuse. P370 + P378: In case of fire: Use water fog, foam, dry chemical or carbon dioxide (CO₂) to extinguish. P391: Collect spillage.

Storage: P403 + P235: Store in a well-ventilated place. Keep cool. P405: Store locked up.

Disposal: P501: Dispose of contents and container in accordance with local regulations.

Contains: Residues (petroleum), atmospheric; Residues (petroleum), catalytic reformer fractionator; Fuels, diesel; DISTILLATES (PETROLEUM), FULL-RANGE STRAIGHT-RUN MIDDLE; Gas oils (petroleum), hydrodesulfurized heavy vacuum; Distillates (petroleum), heavy thermal cracked; Gas oils (petroleum), heavy vacuum; Distillates (petroleum), hydrodesulfurized middle; Distillates (petroleum), light catalytic cracked; Distillates (petroleum), light thermal cracked; Residues (petroleum), catalytic cracking; Fuel oil, residual; Residues (petroleum), hydrocracked; Residues (petroleum), steam-cracked light; Residues (petroleum), thermal cracked

Other hazard information:

PHYSICAL / CHEMICAL HAZARDS

Material can accumulate static charges which may cause an ignition. Material can release vapours that readily form flammable mixtures. Vapour accumulation could flash and/or explode if ignited. Combustible.

HEALTH HAZARDS

High-pressure injection under skin may cause serious damage. Hydrogen sulphide, a highly toxic gas, is expected to be present. Signs and symptoms of overexposure to hydrogen sulphide include respiratory and eye irritation, dizziness, nausea, coughing, a sensation of dryness and pain in the nose, and loss of consciousness. Odour does not provide a reliable indicator of the presence of hazardous levels in the atmosphere. May be irritating to the eyes, nose, throat, and lungs.

ENVIRONMENTAL HAZARDS

No additional hazards.

NOTE: This material should not be used for any other purpose than the intended use in Section 1 without expert advice. Health studies have shown that chemical exposure may cause potential human health risks which may vary from person to person.

Product Name: FUEL OIL BIO - BMF.5™

Revision Date: 08 Feb 2023

Page 4 of 15

This material is defined as a mixture.

Hazardous Substance(s) or Complex Substance(s) required for disclosure

Name	CAS#	Concentration*	GHS Hazard Codes
Residues (petroleum), atmospheric	68333-22-2	0 - 20%	H332, H350(1B), H361(D), H373, H400(M factor 1), H410(M factor 1)
Residues (petroleum), catalytic reformer fractionator	64741-67-9	0 - 8.25%	H227, H304, H332, H350(1B), H361(D), H373, H400(M factor 1), H410(M factor 1)
Fuels, diesel	68334-30-5	0 - 10%	H226, H304, H332, H351, H315, H373, H401, H411
DISTILLATES (PETROLEUM), FULL-RANGE STRAIGHT-RUN MIDDLE	68814-87-9	0 - 8.25%	H304, H332, H373, H401, H411
Gas oils (petroleum), hydrodesulfurized heavy vacuum	64742-86-5	0 - 10%	H332, H350(1B), H361(D), H373, H400(M factor 1), H410(M factor 1)
Distillates (petroleum), heavy thermal cracked	64741-81-7	0 - 8.25%	H227, H332, H350(1B), H361(D), H373, H400(M factor 1), H410(M factor 1)
Gas oils (petroleum), heavy vacuum	64741-57-7	0 10%	H304, H332, H350(1B), H361(D), H373, H400(M factor 1), H410(M factor 1)
Distillates (petroleum), hydrodesulfurized middle	64742-80-9	0 - 8.25%	H304, H332, H350(1B), H315, H373, H401, H411
Distillates (petroleum), light catalytic cracked	64741-59-9	0 - 10%	H226, H304, H332, H350(1B), H315, H373, H400(M factor 1), H410(M factor 1)
Distillates (petroleum), light thermal cracked	64741-82-8	0 - 8.25%	H227, H332, H350(1B), H315, H373, H400(M factor 1), H410(M factor 1)
OXYGENATED HYDROCARBONS, MIXTURE	98072-31-2	0 - 10%	H227, H305
Residues (petroleum), catalytic cracking	92061-97-7	0 - 20%	H332, H350(1B), H361(D), H373, H400(M factor 1), H410(M factor 1)
Fuel oil, residual	68476-33-5	0 - 99.5%	H332, H350(1B), H361(D), H373, H400(M factor 1), H410(M factor 1)
Residues (petroleum), hydrocracked	64741-75-9	0 - 10%	H332, H350(1B), H361(D), H373, H400(M factor 1), H410(M factor 1)
Residues (petroleum), steam-cracked light	68513-69-9	0 - 10%	H227, H340(1B), H350(1B), H315, H401, H411
Residues (petroleum), thermal cracked	64741-80-6	0 - 10%	H332, H350(1B), H361(D), H373, H400(M factor 1), H410(M factor 1)
VACUUM RESIDUUM (PETROLEUM)	64741-56-6	0 - 10%	None

Hazardous Constituent(s) Contained in Complex Substance(s) required for disclosure

Name	CAS#	Concentration*	GHS Hazard Codes
ethylbenzene	100-41-4	< 1%	H225, H304, H332, H373, H401, H412
hydrogen sulphide	7783-06-4	< 0.1%	H220, H280, H330(2), H400(M factor 1)
naphthalene	91-20-3	< 1%	H228(2), H302, H351, H400(M factor 1), H410(M factor 1)

Product Name: FUEL OIL BIO - BMF.5™

Revision Date: 08 Feb 2023

Page 5 of 15

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

NOTE: Carbon monoxide (CO) may be present in the material in trace quantities and, when present, may accumulate to toxic or flammable concentrations in enclosed spaces such as tanks or tanker/railcar headspaces.

SECTION 4 FIRST AID MEASURES

INHALATION

Immediately remove from further exposure. Get immediate medical assistance. For those providing assistance, avoid exposure to yourself or others. Use adequate respiratory protection. Give supplemental oxygen, if available. If breathing has stopped, assist ventilation with a mechanical device.

SKIN CONTACT

Remove contaminated clothing. Dry wipe exposed skin and cleanse with waterless hand cleaner and follow by washing thoroughly with soap and water. For those providing assistance, avoid further skin contact to yourself or others. Wear impervious gloves. Launder contaminated clothing separately before reuse. Discard contaminated articles that cannot be laundered. If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury.

EYE CONTACT

Flush thoroughly with water. If irritation occurs, get medical assistance.

INGESTION

Seek immediate medical attention. Do not induce vomiting.

ACUTE AND DELAYED SYMPTOMS/EFFECTS

See Toxicological Section

NOTE TO PHYSICIAN

If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately.

SECTION 5 FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

Appropriate Extinguishing Media: Use water fog, foam, dry chemical or carbon dioxide (CO₂) to extinguish flames.

Inappropriate Extinguishing Media: Straight streams of water

FIRE FIGHTING

Fire Fighting Instructions: Evacuate area. Prevent run-off from fire control or dilution from entering streams, sewers or drinking water supply. Fire-fighters should use standard protective equipment and in enclosed spaces, self-contained breathing apparatus (SCBA). Use water spray to cool fire exposed surfaces and to protect personnel.

Unusual Fire Hazards: Combustible. The product may form flammable mixtures and can burn only when

Product Name: FUEL OIL BIO - BMF.5™

Revision Date: 08 Feb 2023

Page 6 of 15

heated above the flash point. Hazardous material. Firefighters should consider protective equipment indicated in Section 8.

Hazardous Combustion Products: Aldehydes, Hydrogen sulphide, Incomplete combustion products, Oxides of carbon, Smoke, Fume, Sulphur oxides

FLAMMABILITY PROPERTIES

Flash Point [Method]: >60°C (140°F) [ASTM D-93]

Flammable Limits (Approximate volume % in air): LEL: N/D UEL: N/D

Autoignition Temperature: >250°C (482°F) [ASTM E659]

SECTION 6

ACCIDENTAL RELEASE MEASURES

NOTIFICATION PROCEDURES

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

PROTECTIVE MEASURES

Avoid contact with spilled material. Warn or evacuate occupants in surrounding and downwind areas if required, due to toxicity or flammability of the material. See Section 5 for fire fighting information. See the Hazard Identification Section for Significant Hazards. See Section 4 for First Aid Advice. See Section 8 for advice on the minimum requirements for personal protective equipment. Additional protective measures may be necessary, depending on the specific circumstances and/or the expert judgment of the emergency responders.

For emergency responders: Respiratory protection: half-face or full-face respirator with filter(s) for organic vapor and, when applicable, H₂S, or Self Contained Breathing Apparatus (SCBA) can be used depending on the size of spill and potential level of exposure. If the exposure cannot be completely characterized or an oxygen deficient atmosphere is possible or anticipated, SCBA is recommended. Work gloves that are resistant to aromatic hydrocarbons are recommended. Note: gloves made of polyvinyl acetate (PVA) are not water-resistant and are not suitable for emergency use. Chemical goggles are recommended if splashes or contact with eyes is possible. Small spills: normal antistatic work clothes are usually adequate. Large spills: full body suit of chemical resistant, antistatic material is recommended.

SPILL MANAGEMENT

Land Spill: Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do so without risk. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Prevent entry into waterways, sewer, basements or confined areas. A vapour-suppressing foam may be used to reduce vapour. Use clean non-sparking tools to collect absorbed material. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Large Spills: Water spray may reduce vapour, but may not prevent ignition in enclosed spaces.

Water Spill: Stop leak if you can do so without risk. Confine the spill immediately with booms. Warn other shipping. Remove from the surface by skimming or with suitable absorbents. Seek the advice of a specialist before using dispersants.

Water spill and land spill recommendations are based on the most likely spill scenario for this material; however, geographic conditions, wind, temperature, (and in the case of a water spill) wave and current direction and speed may greatly influence the appropriate action to be taken. For this reason, local experts should be consulted. Note: Local regulations may prescribe or limit action to be taken.

ENVIRONMENTAL PRECAUTIONS

Large Spills: Dyke far ahead of liquid spill for later recovery and disposal. Prevent entry into waterways,

Product Name: FUEL OIL BIO - BMF.5™

Revision Date: 08 Feb 2023

Page 7 of 15

sewers, basements or confined areas.

SECTION 7 HANDLING AND STORAGE

HANDLING

Avoid all personal contact. Potentially toxic/irritating fumes/vapour may be evolved from heated or agitated material. Harmful amounts of H₂S may be present. The toxic and olfactory (sense of smell) fatigue properties of hydrogen sulfide require that air monitoring alarms and respiratory protection be used where the concentration might be expected to reach a harmful level, such as in an enclosed space, heated transport vessel, or in a spill or leak situation.

Do not use electronic devices (including but not limited to cellular phones, computers, calculators, pagers or other electronic devices, etc.) during safety critical tasks, such as bulk fuel loading or unloading operations, or in storage areas where vapours may be present, unless the devices are certified intrinsically safe by an approved national testing agency and to the safety standards required by national and/or local laws and regulations. Prevent small spills and leakage to avoid slip hazard. Do not siphon by mouth. Material can accumulate static charges which may cause an electrical spark (ignition source). Use proper bonding and/or ground procedures. However, bonding and grounds may not eliminate the hazard from static accumulation. Consult local applicable standards for guidance. Additional references include American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practice on Static Electricity) or CENELEC CLC/TR 50404 (Electrostatics - Code of practice for the avoidance of hazards due to static electricity).

Static Accumulator: This material is a static accumulator. A liquid is typically considered a nonconductive, static accumulator if its conductivity is below 100 pS/m (100x10E-12 Siemens per meter) and is considered a semiconductive, static accumulator if its conductivity is below 10,000 pS/m. Whether a liquid is nonconductive or semiconductive, the precautions are the same. A number of factors, for example liquid temperature, presence of contaminants, anti-static additives and filtration can greatly influence the conductivity of a liquid.

STORAGE

The type of container used to store the material may affect static accumulation and dissipation. Keep container closed. Handle containers with care. Open slowly in order to control possible pressure release. Store in a cool, well-ventilated area. Storage containers should be earthed and bonded. Fixed storage containers, transfer containers and associated equipment should be earthed and bonded to prevent accumulation of static charge.

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE LIMIT VALUES

Exposure limits/standards (Note: Exposure limits are not additive)

Substance Name	Form	Limit/Standard			Note	Source	Year
ATMOSPHERIC TOWER BOTTOMS..C13 [benzene solubles]	Total oil mist	TWA	0.1 mg/m ³		Skin	ExxonMobil	2021
CATALYTIC REFORMER FRACTIONATOR RESIDUE (PETROLEUM) [benzene solubles]	Total oil mist	TWA	0.1 mg/m ³		Skin	ExxonMobil	2021
Fuels, diesel	Stable Aerosol.	TWA	5 mg/m ³		Skin	ExxonMobil	2021
Fuels, diesel	Vapour.	TWA	200 mg/m ³		Skin	ExxonMobil	2021
DIESEL OIL..C9-20 [total		TWA	100		Skin	ACGIH	2020

Product Name: FUEL OIL BIO - BMF.5™

Revision Date: 08 Feb 2023

Page 8 of 15

hydrocarb, vapour&aerosol]	Inhalable fraction and vapour		mg/m3				
ethylbenzene		TWA	20 ppm			ACGIH	2020
GAS OILS (PETROLEUM), HYDRODESULFURIZED HEAVY VACUUM [benzene solubles]	Total oil mist	TWA	0.1 mg/m3		Skin	ExxonMobil	2021
HEAVY THERMAL CRACKED DISTILLATE [benzene solubles]	Total oil mist	TWA	0.1 mg/m3		Skin	ExxonMobil	2021
HEAVY VACUUM GAS OIL (PETROLEUM) [benzene solubles]	Total oil mist	TWA	0.1 mg/m3		Skin	ExxonMobil	2021
Distillates (petroleum), hydrodesulfurized middle	Stable Aerosol.	TWA	5 mg/m3			ExxonMobil	2021
Distillates (petroleum), hydrodesulfurized middle	Vapour.	TWA	200 mg/m3		Skin	ExxonMobil	2021
Distillates (petroleum), hydrodesulfurized middle	Inhalable fraction.	TWA	5 mg/m3			ACGIH	2020
hydrogen sulphide		STEL	14 mg/m3	10 ppm		ExxonMobil	2021
hydrogen sulphide		TWA	7 mg/m3	5 ppm		ExxonMobil	2021
Distillates (petroleum), light thermal cracked	Stable Aerosol.	TWA	5 mg/m3			ExxonMobil	2021
Distillates (petroleum), light thermal cracked	Vapour.	TWA	200 mg/m3			ExxonMobil	2021
naphthalene		TWA	10 ppm		Skin	ACGIH	2020
PETROLEUM CATALYTIC CRACKING RESIDUES [benzene solubles]	Total oil mist	TWA	0.1 mg/m3		Skin	ExxonMobil	2021
RESIDUAL FUEL OIL [benzene solubles]	Total oil mist	TWA	0.1 mg/m3		Skin	ExxonMobil	2021
RESIDUES (PETROLEUM), HYDROCRACKED [benzene solubles]	Total oil mist	TWA	0.1 mg/m3		Skin	ExxonMobil	2021
RESIDUES (PETROLEUM), THERMAL CRACKED [benzene solubles]	Total oil mist	TWA	0.1 mg/m3		Skin	ExxonMobil	2021
VACUUM RESIDUUM (PETROLEUM) [benzene solubles]	Fume, inhalable	TWA	0.5 mg/m3			ACGIH	2020
Carbon monoxide		TWA	25 ppm			ACGIH	2020

Biological limits

Substance Name	Specimen	Sampling Time	Limit	Determinant	Source
ethylbenzene	Creatinine in urine	End of shift	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	ACGIH BELs (BELs)
naphthalene	No Biological Specimen provided	End of shift		1-Naphthol, with hydrolysis + 2-Naphthol, with hydrolysis	ACGIH BELs (BELs)

NOTE: Limits/standards shown for guidance only. Follow applicable regulations.

Product Name: FUEL OIL BIO - BMF.5™

Revision Date: 08 Feb 2023

Page 9 of 15

ENGINEERING CONTROLS

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Control measures to consider:

Use explosion-proof ventilation equipment to stay below exposure limits.

PERSONAL PROTECTION

Personal protective equipment selections vary based on potential exposure conditions such as applications, handling practices, concentration and ventilation. Information on the selection of protective equipment for use with this material, as provided below, is based upon intended, normal usage.

Respiratory Protection: If engineering controls do not maintain airborne contaminant concentrations at a level which is adequate to protect worker health, an approved respirator may be appropriate. Respirator selection, use, and maintenance must be in accordance with regulatory requirements, if applicable. Types of respirators to be considered for this material include:

Positive-pressure, air-supplied respirator in areas where H₂S vapours may accumulate is recommended.

For high airborne concentrations, use an approved supplied-air respirator, operated in positive pressure mode. Supplied air respirators with an escape bottle may be appropriate when oxygen levels are inadequate, gas/vapour warning properties are poor, or if air purifying filter capacity/rating may be exceeded.

Hand Protection: Any specific glove information provided is based on published literature and glove manufacturer data. Glove suitability and breakthrough time will differ depending on the specific use conditions. Contact the glove manufacturer for specific advice on glove selection and breakthrough times for your use conditions. Inspect and replace worn or damaged gloves. The types of gloves to be considered for this material include:

Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style gloves. Nitrile, Viton

Eye Protection: If contact is likely, safety glasses with side shields are recommended.

Skin and Body Protection: Any specific clothing information provided is based on published literature or manufacturer data. The types of clothing to be considered for this material include:

Chemical/oil resistant clothing is recommended.

Specific Hygiene Measures: Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

ENVIRONMENTAL CONTROLS

Comply with applicable environmental regulations limiting discharge to air, water and soil. Protect the environment by applying appropriate control measures to prevent or limit emissions.

Product Name: FUEL OIL BIO - BMF.5™

Revision Date: 08 Feb 2023

Page 10 of 15

Note: Physical and chemical properties are provided for safety, health and environmental considerations only and may not fully represent product specifications. Contact the Supplier for additional information.

GENERAL INFORMATION

Physical State: Liquid
Form: Viscous
Colour: Dark Brown
Odour: Petroleum/Solvent
Odour Threshold: N/D

IMPORTANT HEALTH, SAFETY, AND ENVIRONMENTAL INFORMATION

Relative Density (at 15 °C): < 1
Density (at 15 °C): 800 kg/m³ (6.68 lbs/gal, 0.8 kg/dm³) - 991 kg/m³ (8.27 lbs/gal, 0.99 kg/dm³) [ISO 12185]
Flammability (Solid, Gas): N/A
Flash Point [Method]: >60°C (140°F) [ASTM D-93]
Flammable Limits (Approximate volume % in air): LEL: N/D UEL: N/D
Autoignition Temperature: >250°C (482°F) [ASTM E659]
Boiling Point / Range: > 35°C (95°F) [ASTM D86]
Decomposition Temperature: N/D
Vapour Density (Air = 1): N/D
Vapour Pressure: < 0.133 kPa (1 mm Hg) at 20 °C | 0.02 kPa (0.15 mm Hg) at 120 °C - 0.791 kPa (5.93 mm Hg) at 120°C [ASTM D2878]
Evaporation Rate (n-butyl acetate = 1): N/D
pH: N/A
Log Pow (n-Octanol/Water Partition Coefficient): N/D
Solubility in Water: Negligible
Viscosity: >7 cSt (7 mm²/sec) at 40°C [ISO 3104]
Oxidizing Properties: See Hazards Identification Section.

OTHER INFORMATION

Freezing Point: N/D
Melting Point: N/A
Pour Point: 0°C (32°F) - 30°C (86°F)

SECTION 10

STABILITY AND REACTIVITY

STABILITY: Material is stable under normal conditions.

CONDITIONS TO AVOID: Excessive heat. Open flames and high energy ignition sources.

MATERIALS TO AVOID: Alkalies, Halogens, Strong Acids, Strong oxidisers

HAZARDOUS DECOMPOSITION PRODUCTS: Material does not decompose at ambient temperatures.

POSSIBILITY OF HAZARDOUS REACTIONS: Hazardous polymerization will not occur.

SECTION 11

TOXICOLOGICAL INFORMATION

INFORMATION ON TOXICOLOGICAL EFFECTS

Product Name: FUEL OIL BIO - BMF.5™

Revision Date: 08 Feb 2023

Page 11 of 15

Hazard Class	Conclusion / Remarks
Inhalation	
Acute Toxicity: No end point data for material.	Moderately toxic. Based on assessment of the components.
Irritation: No end point data for material.	Elevated temperatures or mechanical action may form vapours, mist, or fumes which may be irritating to the eyes, nose, throat, or lungs.
Ingestion	
Acute Toxicity: No end point data for material.	Minimally Toxic. Based on assessment of the components.
Skin	
Acute Toxicity: No end point data for material.	Minimally Toxic. Based on assessment of the components.
Skin Corrosion/Irritation: No end point data for material.	Irritating to the skin. Based on assessment of the components.
Eye	
Serious Eye Damage/Irritation: No end point data for material.	May cause mild, short-lasting discomfort to eyes. Based on assessment of the components.
Sensitisation	
Respiratory Sensitization: No end point data for material.	Not expected to be a respiratory sensitizer.
Skin Sensitization: No end point data for material.	Not expected to be a skin sensitizer. Based on assessment of the components.
Aspiration: Data available.	May be fatal if swallowed and enters airways. Based on physico-chemical properties of the material.
Germ Cell Mutagenicity: No end point data for material.	Caused genetic effects in laboratory animals, but the relevance to humans is uncertain. Based on assessment of the components.
Carcinogenicity: No end point data for material.	Caused cancer in laboratory animals. Based on assessment of the components.
Reproductive Toxicity: No end point data for material.	Caused damage to the fetus in laboratory animals, but the relevance to humans is uncertain. Based on assessment of the components.
Lactation: No end point data for material.	Not expected to cause harm to breast-fed children.
Specific Target Organ Toxicity (STOT)	
Single Exposure: No end point data for material.	Not expected to cause organ damage from a single exposure.
Repeated Exposure: No end point data for material.	Contains a substance that may cause damage to organs from prolonged or repeated exposure. Based on assessment of the components.

TOXICITY FOR SUBSTANCES

NAME	ACUTE TOXICITY
ethylbenzene	Inhalation Lethality: 4 hour(s) LC50 17.8 mg/l (Vapour) (Rat); Oral Lethality: LD 50 3.5 g/kg (Rat)
hydrogen sulphide	Inhalation Lethality: 4 hour(s) LC50 444 ppm (Gas) (Rat)
naphthalene	Inhalation Lethality: 4 hour(s) LC50 > 0.4 mg/l (Max attainable vapor conc.) (Rat); Oral Lethality: LD 50 533 mg/kg (Mouse)

OTHER INFORMATION

For the product itself:

Target Organs Repeated Exposure: Blood, Bone marrow, Liver, Thymus

Product Name: FUEL OIL BIO - BMF.5™

Revision Date: 08 Feb 2023

Page 12 of 15

Contains:

HYDROGEN SULPHIDE: Chronic health effects due to repeated exposures to low levels of H₂S have not been established. High level (700 ppm) acute exposure can result in sudden death. High concentrations will lead to cardiopulmonary arrest due to nervous system toxicity and pulmonary edema. Lower levels (150 ppm) may overwhelm sense of smell, eliminating warning of exposure. Symptoms of overexposure to H₂S include headache, fatigue, insomnia, irritability, and gastrointestinal problems. Repeated exposures to approximately 25 ppm will irritate mucous membranes and the respiratory system and have been implicated in some eye damage. Middle distillates with cracked stocks: Carcinogenic in animal tests. Caused mutations in-vitro. Repeated dermal exposures to high concentrations in test animals resulted in reduced litter size and litter weight, and increased fetal resorptions at maternally toxic doses. Dermal exposure to high concentrations resulted in severe skin irritation with weight loss and some mortality. Inhalation exposure to high concentrations resulted in respiratory tract irritation, lung changes/infiltration/accumulation, and reduction in lung function. Middle distillates: Carcinogenic in animal tests. Lifetime skin painting tests produced tumours, but the mechanism is due to repeated cycles of skin damage and restorative hyperplasia. This mechanism is considered unlikely in humans where such prolonged skin irritation would not be tolerated. Did not cause mutations in-vitro. Inhalation of vapours did not result in reproductive or developmental effects in laboratory animals. Inhalation of high concentrations in animals resulted in respiratory tract irritation, lung changes and some reduction in lung function. Non-sensitising in test animals. **NAPHTHALENE:** Exposure to high concentrations of naphthalene may cause destruction of red blood cells, anemia, and cataracts. Naphthalene caused cancer in laboratory animal studies, but the relevance of these findings to humans is uncertain.

Residual fuel oil: Carcinogenic in animal tests. Caused mutations in-vitro. Dermal exposure to high concentrations resulted in maternal toxicity, decreased fetal weight and fetal survival, and some external fetal malformations. Dermal studies in animals: increased mortality, skin irritation, liver, kidney, thymus, bone marrow, blood and lymphoid tissue toxic effects. Possible allergen and photoallergen. **ETHYLBENZENE:** Caused cancer in laboratory animal studies. The relevance of these findings to humans is uncertain.

IARC Classification:

The following ingredients are cited on the lists below:

Chemical Name	CAS Number	List Citations
Residues (petroleum), catalytic reformer fractionator	64741-67-9	3
ethylbenzene	100-41-4	3
Gas oils (petroleum), hydrodesulfurized heavy vacuum	64742-86-5	3
Distillates (petroleum), heavy thermal cracked	64741-81-7	3
Gas oils (petroleum), heavy vacuum	64741-57-7	1, 3
Distillates (petroleum), hydrodesulfurized middle	64742-80-9	1
Distillates (petroleum), light catalytic cracked	64741-59-9	1
Distillates (petroleum), light thermal cracked	64741-82-8	1
naphthalene	91-20-3	3
Residues (petroleum), catalytic cracking	92061-97-7	3
Fuel oil, residual	68476-33-5	3
Residues (petroleum),	64741-75-9	3

Product Name: FUEL OIL BIO - BMF.5™

Revision Date: 08 Feb 2023

Page 13 of 15

hydrocracked		
Residues (petroleum), thermal cracked	64741-80-6	3
VACUUM RESIDUUM (PETROLEUM)	64741-56-6	3

--REGULATORY LISTS SEARCHED--

1 = IARC 1

2 = IARC 2A

3 = IARC 2B

SECTION 12 ECOLOGICAL INFORMATION

The information given is based on data for the material, components of the material, or for similar materials, through the application of bridging principals.

ECOTOXICITY

Material -- Expected to be very toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment.

MOBILITY

Majority of components -- Low solubility and floats and is expected to migrate from water to the land.
Expected to partition to sediment and wastewater solids.
Majority of components -- Low potential to migrate through soil.

PERSISTENCE AND DEGRADABILITY

Biodegradation:

Material -- Expected to be inherently biodegradable

BIOACCUMULATION POTENTIAL

Majority of components -- Has the potential to bioaccumulate, however metabolism or physical properties may reduce the bioconcentration or limit bioavailability.

INTERNATIONAL OIL POLLUTION COMPENSATION (IOPC)

Material is considered a persistent oil.

SECTION 13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Disposal recommendations based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.

MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides technical aspects at controlling pollutions from ships.

DISPOSAL RECOMMENDATIONS

Product is suitable for burning in an enclosed controlled burner for fuel value or disposal by supervised incineration at very high temperatures to prevent formation of undesirable combustion products.

Empty Container Warning Empty Container Warning (where applicable): Empty containers may contain residue

Product Name: FUEL OIL BIO - BMF.5™

Revision Date: 08 Feb 2023

Page 14 of 15

and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Empty drums should be completely drained and safely stored until appropriately reconditioned or disposed. Empty containers should be taken for recycling, recovery, or disposal through suitably qualified or licensed contractor and in accordance with governmental regulations. DO NOT PRESSURISE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

SECTION 14	TRANSPORT INFORMATION
-------------------	------------------------------

SEA (IMDG)

Proper Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (HEAVY HEATING OIL)

Hazard Class & Division: 9

EMS Number: F-A, S-F

UN Number: 3082

Packing Group: III

Marine Pollutant: Yes

Label(s): 9

Transport Document Name: UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (HEAVY HEATING OIL), 9, PG III, MARINE POLLUTANT

Note - this material is being carried under the scope of MARPOL Annex I

SECTION 15	REGULATORY INFORMATION
-------------------	-------------------------------

REGULATORY STATUS AND APPLICABLE LAWS AND REGULATIONS

Listed or exempt from listing/notification on the following chemical inventories : NDSL

SECTION 16	OTHER INFORMATION
-------------------	--------------------------

N/D = Not determined, N/A = Not applicable

KEY TO THE H-CODES CONTAINED IN SECTION 3 OF THIS DOCUMENT (for information only):

H220: Extremely flammable gas; Flammable Gas, Cat 1

H225: Highly flammable liquid and vapour; Flammable Liquid, Cat 2

H226: Flammable liquid and vapour; Flammable Liquid, Cat 3

H227: Combustible liquid; Flammable Liquid, Cat 4

H228(2): Flammable solid; Flammable Solid, Cat 2

H280: Contains gas under pressure; may explode if heated; Pressurized Gas

H302: Harmful if swallowed; Acute Tox Oral, Cat 4

H304: May be fatal if swallowed and enters airways; Aspiration, Cat 1

H305: May be harmful if swallowed and enters airways; Aspiration, Cat 2

H315: Causes skin irritation; Skin Corr/Irritation, Cat 2

H330(2): Fatal if inhaled; Acute Tox Inh, Cat 2

H332: Harmful if inhaled; Acute Tox Inh, Cat 4

H340(1B): May cause genetic defects; Germ Cell Mutagenicity, Cat 1B

H350(1B): May cause cancer; Carcinogenicity, Cat 1B

H351: Suspected of causing cancer; GHS Carcinogenicity, Cat 2

H361(D): Suspected of damaging the unborn child; Repro Tox, Cat 2 (Develop)

H373: May cause damage to organs through prolonged or repeated exposure; Target Organ, Repeated, Cat 2

Product Name: FUEL OIL BIO - BMF.5™

Revision Date: 08 Feb 2023

Page 15 of 15

H400: Very toxic to aquatic life; Acute Env Tox, Cat 1
H401: Toxic to aquatic life; Acute Env Tox, Cat 2
H410: Very toxic to aquatic life with long lasting effects; Chronic Env Tox, Cat 1
H411: Toxic to aquatic life with long lasting effects; Chronic Env Tox, Cat 2
H412: Harmful to aquatic life with long lasting effects; Chronic Env Tox, Cat 3

THIS MATERIAL SAFETY DATA SHEET CONTAINS THE FOLLOWING REVISIONS:

Composition: Component Table information was modified.
GHS Physical Hazards information was added.
GHS Physical/Chemical Classification information was added.
GHS Physical/Chemical Symbol information was modified.
GHS Precautionary Statements - Prevention information was modified.
GHS Precautionary Statements - Response information was modified.
GHS Precautionary Statements - Storage information was modified.
Hazard Identification: Physical/Chemical Hazard information was added.
Hazard Identification: Physical/Chemical Hazard information was deleted.
Section 01: Alternate Product Names Table information was added.
Section 01: Product Description information was modified.
Section 04: First Aid Notes information was added.
Section 05: Fire Fighting Measures - Unusual Fire Hazards information was modified.
Section 07: Handling and Storage - Handling information was modified.
Section 07: Handling and Storage - Storage Phrases information was modified.
Section 09: Boiling Point °C(°F) information was modified.
Section 09: Flash Point °C(°F) information was modified.
Section 09: Pour Point °C(°F) information was added.
Section 09: Viscosity information was modified.
Section 10: Conditions to Avoid information was deleted.
Section 10: Conditions to Avoid information was modified.
Section 11: Tox List Cited Table information was modified.
Revision Date: 08 Feb 2023

The information and recommendations contained herein are, to the best of ExxonMobil's knowledge and belief, accurate and reliable as of the date issued. You can contact ExxonMobil to insure that this document is the most current available from ExxonMobil. The information and recommendations are offered for the user's consideration and examination. It is the user's responsibility to satisfy itself that the product is suitable for the intended use. If buyer repackages this product, it is the user's responsibility to insure proper health, safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, re-publication or retransmission of this document, in whole or in part, is not permitted. The term, "ExxonMobil" is used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliates in which they directly or indirectly hold any interest.

DGN: 72068471 (1030594)
