

Product Name: KEROSENE  
Revision Date: 30 Sep 2021  
Page 1 of 13

## SAFETY DATA SHEET

### SECTION 1 PRODUCT AND COMPANY IDENTIFICATION

#### PRODUCT

**Product Name:** KEROSENE  
**Product Description:** Petroleum Hydrocarbons  
**Product Code:** 7033158-60  
**Intended Use:** Fuel

#### COMPANY IDENTIFICATION

**Supplier:** EXXONMOBIL EGYPT (SAE)  
1097 CORNISH EL NIL STREET  
GARDEN CITY  
11511 CAIRO  
Egypt

**Product Technical Information**

+20 2 279 16 360 / +20 2 279 16 390

**Supplier General Contact**

+20 2 279 16 200

**National Poison Control Centre:** +20226840902

### SECTION 2 HAZARDS IDENTIFICATION

This material is hazardous according to regulatory guidelines (see (M)SDS Section 15).

#### CLASSIFICATION OF SUBSTANCE OR MIXTURE:

Flammable liquid: Category 3.  
Aspiration toxicant: Category 1.  
Skin irritation: Category 2.  
Specific target organ toxicant (central nervous system): Category 3.  
Chronic aquatic toxicant: Category 2.

#### LABEL ELEMENTS:

##### Pictograms:



**Signal Word:** Danger

Product Name: KEROSENE

Revision Date: 30 Sep 2021

Page 2 of 13

---

### **Hazard Statements:**

#### Physical:

H226: Flammable liquid and vapour.

#### Health:

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H336: May cause drowsiness or dizziness.

#### Environment:

H411: Toxic to aquatic life with long lasting effects.

### **Precautionary Statements:**

#### Prevention:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233: Keep container tightly closed.

P240: Ground and bond container and receiving equipment.

P241: Use explosion-proof electrical, ventilating, and lighting equipment.

P242: Use non-sparking tools.

P243: Take action to prevent static discharges.

P261: Avoid breathing mist / vapours.

P264: Wash skin thoroughly after handling.

P271: Use only outdoors or in a well-ventilated area.

P273: Avoid release to the environment.

P280: Wear protective gloves and eye / face protection.

#### Response:

P301 + P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P303 + P361 + P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P304 + P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312: Call a POISON CENTRE or doctor/physician if you feel unwell.

P331: Do NOT induce vomiting.

P332 + P313: If skin irritation occurs: Get medical advice/ attention.

P362 + P364: Take off contaminated clothing and wash it before reuse.

P370 + P378: In case of fire: Use water fog, foam, dry chemical or carbon dioxide (CO2) to extinguish.

P391: Collect spillage.

#### Storage:

P403 + P235: Store in a well-ventilated place. Keep cool.

P405: Store locked up.

#### Disposal:

P501: Dispose of contents and container in accordance with local regulations.

**Contains:** Kerosine (petroleum)

### **Other hazard information:**

### **Physical / Chemical Hazards:**

Material can accumulate static charges which may cause an ignition. Material can release vapours that readily

Product Name: KEROSENE

Revision Date: 30 Sep 2021

Page 3 of 13

form flammable mixtures. Vapour accumulation could flash and/or explode if ignited.

#### Health Hazards:

High-pressure injection under skin may cause serious damage. May be irritating to the eyes, nose, throat, and lungs. Breathing of high vapour concentrations may cause dizziness, light-headedness, headache, nausea and loss of co-ordination. Continued inhalation may result in unconsciousness.

#### Environmental Hazards:

No additional hazards.

**NOTE:** This material should not be used for any other purpose than the intended use in Section 1 without expert advice. Health studies have shown that chemical exposure may cause potential human health risks which may vary from person to person.

### SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

This material is defined as a complex substance.

#### Reportable Hazardous Substance(s) or Complex Substance(s)

| Name                 | CAS#      | Concentration* | GHS Hazard Codes                   |
|----------------------|-----------|----------------|------------------------------------|
| Kerosine (petroleum) | 8008-20-6 | > 99 %         | H226, H304, H336, H315, H401, H411 |

#### Hazardous Constituent(s) Contained in Complex Substance(s) required for disclosure

| Name         | CAS#     | Concentration* | GHS Hazard Codes  |
|--------------|----------|----------------|---|
| ethylbenzene | 100-41-4 | 0.1 - 1%       | H225, H304, H332, H373, H401, H412                      |
| naphthalene  | 91-20-3  | < 1%           | H228(2), H302, H351, H400(M factor 1), H410(M factor 1) |

\* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

### SECTION 4 FIRST AID MEASURES

#### INHALATION

Remove from further exposure. For those providing assistance, avoid exposure to yourself or others. Use adequate respiratory protection. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance. If breathing has stopped, assist ventilation with a mechanical device or use mouth-to-mouth resuscitation.

#### SKIN CONTACT

Wash contact areas with soap and water. Remove contaminated clothing. Launder contaminated clothing before reuse. If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury.

#### EYE CONTACT

Flush thoroughly with water. If irritation occurs, get medical assistance.

Product Name: KEROSENE

Revision Date: 30 Sep 2021

Page 4 of 13

## INGESTION

Seek immediate medical attention. Do not induce vomiting.

## NOTE TO PHYSICIAN

If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately.

## PRE-EXISTING MEDICAL CONDITIONS WHICH MAY BE AGGRAVATED BY EXPOSURE

Contains hydrocarbon solvent/petroleum hydrocarbons; skin contact may aggravate an existing dermatitis.

## SECTION 5 FIRE FIGHTING MEASURES

### EXTINGUISHING MEDIA

**Appropriate Extinguishing Media:** Use water fog, foam, dry chemical or carbon dioxide (CO<sub>2</sub>) to extinguish flames.

**Inappropriate Extinguishing Media:** Straight streams of water

### FIRE FIGHTING

**Fire Fighting Instructions:** Evacuate area. Prevent run-off from fire control or dilution from entering streams, sewers or drinking water supply. Fire-fighters should use standard protective equipment and in enclosed spaces, self-contained breathing apparatus (SCBA). Use water spray to cool fire exposed surfaces and to protect personnel.

**Unusual Fire Hazards:** FLAMMABLE. Hazardous material. Firefighters should consider protective equipment indicated in Section 8. Vapour is flammable and heavier than air. Vapour may travel across the ground and reach remote ignition sources, causing a flashback fire danger.

**Hazardous Combustion Products:** Aldehydes, Incomplete combustion products, Oxides of carbon, Smoke, Fume, Sulphur oxides

### FLAMMABILITY PROPERTIES

**Flash Point [Method]:** >38°C (100°F) [ASTM D-93]

**Flammable Limits (Approximate volume % in air):** LEL: 0.7 UEL: 5.0

**Autoignition Temperature:** 250°C (482°F)

## SECTION 6 ACCIDENTAL RELEASE MEASURES

### NOTIFICATION PROCEDURES

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

### PROTECTIVE MEASURES

Avoid contact with spilled material. Warn or evacuate occupants in surrounding and downwind areas if required, due to toxicity or flammability of the material. See Section 5 for fire fighting information. See the Hazard Identification Section for Significant Hazards. See Section 4 for First Aid Advice. See Section 8 for advice on the minimum requirements for personal protective equipment. Additional protective measures may be necessary, depending on the specific circumstances and/or the expert judgment of the emergency responders.

For emergency responders: Respiratory protection: half-face or full-face respirator with filter(s) for organic vapor and, when applicable, H<sub>2</sub>S, or Self Contained Breathing Apparatus (SCBA) can be used depending on the size of spill and potential level of exposure. If the exposure cannot be completely characterized or an

Product Name: KEROSENE

Revision Date: 30 Sep 2021

Page 5 of 13

oxygen deficient atmosphere is possible or anticipated, SCBA is recommended. Work gloves that are resistant to aromatic hydrocarbons are recommended. Note: gloves made of polyvinyl acetate (PVA) are not water-resistant and are not suitable for emergency use. Chemical goggles are recommended if splashes or contact with eyes is possible. Small spills: normal antistatic work clothes are usually adequate. Large spills: full body suit of chemical resistant, antistatic material is recommended.

## SPILL MANAGEMENT

**Land Spill:** Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do so without risk. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Prevent entry into waterways, sewer, basements or confined areas. A vapour-suppressing foam may be used to reduce vapour. Use clean non-sparking tools to collect absorbed material. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Large Spills: Water spray may reduce vapour, but may not prevent ignition in enclosed spaces.

**Water Spill:** Stop leak if you can do so without risk. Eliminate sources of ignition. Warn other shipping. If the Flash Point exceeds the Ambient Temperature by 10 deg C or more, use containment booms and remove from the surface by skimming or with suitable absorbents when conditions permit. If the Flash Point does not exceed the Ambient Air Temperature by at least 10C, use booms as a barrier to protect shorelines and allow material to evaporate. Seek the advice of a specialist before using dispersants.

Water spill and land spill recommendations are based on the most likely spill scenario for this material; however, geographic conditions, wind, temperature, (and in the case of a water spill) wave and current direction and speed may greatly influence the appropriate action to be taken. For this reason, local experts should be consulted. Note: Local regulations may prescribe or limit action to be taken.

## ENVIRONMENTAL PRECAUTIONS

Large Spills: Dyke far ahead of liquid spill for later recovery and disposal. Prevent entry into waterways, sewers, basements or confined areas.

|                  |                             |
|------------------|-----------------------------|
| <b>SECTION 7</b> | <b>HANDLING AND STORAGE</b> |
|------------------|-----------------------------|

## HANDLING

Avoid breathing mists or vapour. Avoid contact with skin. Do not siphon by mouth. Do not use electronic devices (including but not limited to cellular phones, computers, calculators, pagers or other electronic devices, etc.) during safety critical tasks, such as bulk fuel loading or unloading operations, or in storage areas where vapours may be present, unless the devices are certified intrinsically safe by an approved national testing agency and to the safety standards required by national and/or local laws and regulations. Prevent small spills and leakage to avoid slip hazard. Material can accumulate static charges which may cause an electrical spark (ignition source). Use proper bonding and/or ground procedures. However, bonding and grounds may not eliminate the hazard from static accumulation. Consult local applicable standards for guidance. Additional references include American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practice on Static Electricity) or CENELEC CLC/TR 50404 (Electrostatics - Code of practice for the avoidance of hazards due to static electricity).

**Static Accumulator:** This material is a static accumulator. A liquid is typically considered a nonconductive, static accumulator if its conductivity is below 100 pS/m (100x10E-12 Siemens per meter) and is considered a semiconductive, static accumulator if its conductivity is below 10,000 pS/m. Whether a liquid is nonconductive or semiconductive, the precautions are the same. A number of factors, for example liquid temperature, presence of contaminants, anti-static additives and filtration can greatly influence the conductivity of a liquid.

## STORAGE

Product Name: KEROSENE

Revision Date: 30 Sep 2021

Page 6 of 13

The type of container used to store the material may affect static accumulation and dissipation. Keep container closed. Handle containers with care. Open slowly in order to control possible pressure release. Store in a cool, well-ventilated area. Storage containers should be earthed and bonded. Fixed storage containers, transfer containers and associated equipment should be earthed and bonded to prevent accumulation of static charge.

## SECTION 8

## EXPOSURE CONTROLS / PERSONAL PROTECTION

### EXPOSURE LIMIT VALUES

Exposure limits/standards (Note: Exposure limits are not additive):

| Substance Name                        | Form            | Limit/Standard |           |         | Note | Source     |
|---------------------------------------|-----------------|----------------|-----------|---------|------|------------|
| ethylbenzene                          |                 | STEL           | 543 mg/m3 | 125 ppm |      | Egypt OELs |
| ethylbenzene                          |                 | TWA            | 434 mg/m3 | 100 ppm |      | Egypt OELs |
| ethylbenzene                          |                 | TWA            | 20 ppm    |         |      | ACGIH      |
| Kerosine (petroleum)                  | Stable Aerosol. | TWA            | 5 mg/m3   |         | Skin | ExxonMobil |
| Kerosine (petroleum)                  | Vapour.         | TWA            | 200 mg/m3 |         | Skin | ExxonMobil |
| KEROSENE [as total hydrocarbon vapor] | Non-Aerosol     | TWA            | 200 mg/m3 |         | Skin | ACGIH      |
| naphthalene                           |                 | STEL           | 79 mg/m3  | 15 ppm  | Skin | Egypt OELs |
| naphthalene                           |                 | TWA            | 52 mg/m3  | 10 ppm  | Skin | Egypt OELs |
| naphthalene                           |                 | TWA            | 10 ppm    |         | Skin | ACGIH      |

Note: Information about recommended monitoring procedures can be obtained from the relevant agency(ies)/institute(s):

### ENGINEERING CONTROLS

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Control measures to consider:

Use explosion-proof ventilation equipment to stay below exposure limits.

### PERSONAL PROTECTION

Personal protective equipment selections vary based on potential exposure conditions such as applications, handling practices, concentration and ventilation. Information on the selection of protective equipment for use with this material, as provided below, is based upon intended, normal usage.

**Respiratory Protection:** If engineering controls do not maintain airborne contaminant concentrations at a level which is adequate to protect worker health, an approved respirator may be appropriate. Respirator selection, use, and maintenance must be in accordance with regulatory requirements, if applicable. Types of respirators to be considered for this material include:

Half-face filter respirator Type AP filter material.

For high airborne concentrations, use an approved supplied-air respirator, operated in positive pressure mode. Supplied air respirators with an escape bottle may be appropriate when oxygen levels are inadequate,

Product Name: KEROSENE

Revision Date: 30 Sep 2021

Page 7 of 13

---

gas/vapour warning properties are poor, or if air purifying filter capacity/rating may be exceeded.

**Hand Protection:** Any specific glove information provided is based on published literature and glove manufacturer data. Glove suitability and breakthrough time will differ depending on the specific use conditions. Contact the glove manufacturer for specific advice on glove selection and breakthrough times for your use conditions. Inspect and replace worn or damaged gloves. The types of gloves to be considered for this material include:

Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style gloves. Nitrile, minimum 0.38 mm thickness or comparable protective barrier material with a high performance level for continuous contact use conditions, permeation breakthrough minimum 480 minutes in accordance with CEN standards EN 420 and EN 374.

**Eye Protection:** If contact is likely, safety glasses with side shields are recommended.

**Skin and Body Protection:** Any specific clothing information provided is based on published literature or manufacturer data. The types of clothing to be considered for this material include:

Chemical/oil resistant clothing is recommended.

**Specific Hygiene Measures:** Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

## ENVIRONMENTAL CONTROLS

Comply with applicable environmental regulations limiting discharge to air, water and soil. Protect the environment by applying appropriate control measures to prevent or limit emissions.

|                  |   |
|------------------|---|
| <b>SECTION 9</b> | <b>PHYSICAL AND CHEMICAL PROPERTIES</b> |
|------------------|---|

**Note:** Physical and chemical properties are provided for safety, health and environmental considerations only and may not fully represent product specifications. Contact the Supplier for additional information.

## GENERAL INFORMATION

**Physical State:** Liquid  
**Colour:** Pale Yellow  
**Odour:** Petroleum/Solvent  
**Odour Threshold:** N/D

## IMPORTANT HEALTH, SAFETY, AND ENVIRONMENTAL INFORMATION

**Relative Density (at 15 °C):** 0.775 - 0.83  
**Flammability (Solid, Gas):** N/A  
**Flash Point [Method]:** >38°C (100°F) [ASTM D-93]  
**Flammable Limits (Approximate volume % in air):** LEL: 0.7 UEL: 5.0  
**Autoignition Temperature:** 250°C (482°F)  
**Boiling Point / Range:** > 200°C (392°F)  
**Decomposition Temperature:** N/D  
**Vapour Density (Air = 1):** N/D  
**Vapour Pressure:** < 0.133 kPa (1 mm Hg) at 20 °C  
**Evaporation Rate (n-butyl acetate = 1):** N/D  
**pH:** N/A



Product Name: KEROSENE

Revision Date: 30 Sep 2021

Page 8 of 13

**Log Pow (n-Octanol/Water Partition Coefficient):** > 3.5

**Solubility in Water:** Negligible

**Viscosity:** 1.1 cSt (1.1 mm<sup>2</sup>/sec) at 40°C

**Oxidizing Properties:** See Hazards Identification Section.

#### OTHER INFORMATION

**Freezing Point:** -47°C (-53°F)

**Melting Point:** N/A

### SECTION 10 STABILITY AND REACTIVITY

**STABILITY:** Material is stable under normal conditions.

**CONDITIONS TO AVOID:** Avoid heat, sparks, open flames and other ignition sources.

**MATERIALS TO AVOID:** Alkalies, Halogens, Strong Acids, Strong oxidisers

**HAZARDOUS DECOMPOSITION PRODUCTS:** Material does not decompose at ambient temperatures.

**POSSIBILITY OF HAZARDOUS REACTIONS:** Hazardous polymerization will not occur.

### SECTION 11 TOXICOLOGICAL INFORMATION

#### INFORMATION ON TOXICOLOGICAL EFFECTS

| Hazard Class   | Conclusion / Remarks   |
|--|--|
| <b>Inhalation</b>  |  |
| Acute Toxicity: (Rat) 4 hour(s) LC50 > 5000 mg/m <sup>3</sup> (Vapour) | Minimally Toxic. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 403                                  |
| Irritation: No end point data for material.                            | Elevated temperatures or mechanical action may form vapours, mist, or fumes which may be irritating to the eyes, nose, throat, or lungs.                     |
| <b>Ingestion</b>   |  |
| Acute Toxicity (Rat): LD50 > 5000 mg/kg                                | Minimally Toxic. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 420                                  |
| <b>Skin</b>  |  |
| Acute Toxicity (Rabbit): LD50 > 2000 mg/kg                             | Minimally Toxic. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 402                                  |
| Skin Corrosion/Irritation (Rabbit): Data available.                    | Irritating to the skin. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 404                           |
| <b>Eye</b>   |  |
| Serious Eye Damage/Irritation (Rabbit): Data available.                | May cause mild, short-lasting discomfort to eyes. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 405 |
| <b>Sensitisation</b>   |  |
| Respiratory Sensitization: No end point data for material.             | Not expected to be a respiratory sensitizer.   |
| Skin Sensitization: Data available.                                    | Not expected to be a skin sensitizer. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 406             |
| <b>Aspiration:</b> Data available.                                     | May be fatal if swallowed and enters airways. Based on physico-chemical properties of the material.  |



Product Name: KEROSENE

Revision Date: 30 Sep 2021

Page 9 of 13

|   |  |
|---|--|
| <b>Germ Cell Mutagenicity:</b> Data available.    | Not expected to be a germ cell mutagen. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 471 475 476 478 479                     |
| <b>Carcinogenicity:</b> Data available.           | Not expected to cause cancer. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 451   |
| <b>Reproductive Toxicity:</b> Data available.     | Not expected to be a reproductive toxicant. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 414 421                             |
| <b>Lactation:</b> No end point data for material. | Not expected to cause harm to breast-fed children.   |
| <b>Specific Target Organ Toxicity (STOT)</b>      |  |
| Single Exposure: No end point data for material.  | May cause drowsiness or dizziness.   |
| Repeated Exposure: Data available.                | Not expected to cause organ damage from prolonged or repeated exposure. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 410 412 |

## TOXICITY FOR SUBSTANCES

| NAME         | ACUTE TOXICITY  |
|--------------|---|
| ethylbenzene | Inhalation Lethality: 4 hour(s) LC50 17.8 mg/l (Vapour) (Rat); Oral Lethality: LD 50 3.5 g/kg (Rat)                         |
| naphthalene  | Inhalation Lethality: 4 hour(s) LC50 > 0.4 mg/l (Max attainable vapor conc.) (Rat); Oral Lethality: LD 50 533 mg/kg (Mouse) |

## OTHER INFORMATION

### For the product itself:

Vapour/aerosol concentrations above recommended exposure levels are irritating to the eyes and respiratory tract, may cause headaches, dizziness, anaesthesia, drowsiness, unconsciousness and other central nervous system effects including death. Small amounts of liquid aspirated into the lungs during ingestion or from vomiting may cause chemical pneumonitis or pulmonary edema.

Kerosene: Carcinogenic in animal tests. Lifetime skin painting tests produced tumours, but the mechanism is due to repeated cycles of skin damage and restorative hyperplasia. This mechanism is considered unlikely in humans where such prolonged skin irritation would not be tolerated. Did not cause mutations in-vitro. Inhalation of vapours did not result in reproductive or developmental effects in laboratory animals. Inhalation of high concentrations in animals resulted in respiratory tract irritation, lung changes and some reduction in lung function. Non-sensitizing in animal tests.

### Contains:

NAPHTHALENE: Exposure to high concentrations of naphthalene may cause destruction of red blood cells, anemia, and cataracts. Naphthalene caused cancer in laboratory animal studies, but the relevance of these findings to humans is uncertain.

ETHYLBENZENE: Caused cancer in laboratory animal studies. The relevance of these findings to humans is uncertain.

## SECTION 12 ECOLOGICAL INFORMATION

The information given is based on data for the material, components of the material, or for similar materials, through the application of bridging principals.

### ECOTOXICITY

Material -- Expected to be toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment.

Product Name: KEROSENE

Revision Date: 30 Sep 2021

Page 10 of 13

## MOBILITY

Majority of components -- Highly volatile, will partition rapidly to air. Not expected to partition to sediment and wastewater solids.

Majority of components -- Low potential to migrate through soil.

## PERSISTENCE AND DEGRADABILITY

### Biodegradation:

Material -- Expected to be inherently biodegradable

### Atmospheric Oxidation:

Majority of components -- Expected to degrade rapidly in air

## BIOACCUMULATION POTENTIAL

Majority of components -- Has the potential to bioaccumulate, however metabolism or physical properties may reduce the bioconcentration or limit bioavailability.

## ECOLOGICAL DATA

### Ecotoxicity

| Test                       | Duration   | Organism Type                   | Test Results                                  |
|----------------------------|------------|---------------------------------|---|
| Aquatic - Acute Toxicity   | 48 hour(s) | Daphnia magna                   | EL50 1 - 100 mg/l: data for similar materials |
| Aquatic - Acute Toxicity   | 96 hour(s) | Oncorhynchus mykiss             | LL50 1 - 100 mg/l: data for similar materials |
| Aquatic - Acute Toxicity   | 72 hour(s) | Pseudokirchneriella subcapitata | EL50 1 - 100 mg/l: data for similar materials |
| Aquatic - Chronic Toxicity | 21 day(s)  | Daphnia magna                   | NOELR 0.48 mg/l: data for similar materials   |
| Aquatic - Chronic Toxicity | 72 hour(s) | Pseudokirchneriella subcapitata | NOELR 1 - 10 mg/l: data for similar materials |

### Persistence, Degradability and Bioaccumulation Potential

| Media | Test Type              | Duration  | Test Results                             |
|-------|------------------------|-----------|--|
| Water | Ready Biodegradability | 28 day(s) | Percent Degraded < 60 : similar material |

## SECTION 13

## DISPOSAL CONSIDERATIONS

Disposal recommendations based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.

## DISPOSAL RECOMMENDATIONS

Product is suitable for burning in an enclosed controlled burner for fuel value or disposal by supervised incineration at very high temperatures to prevent formation of undesirable combustion products.

**Empty Container Warning** Empty Container Warning (where applicable): Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Empty drums should be completely drained and safely stored until appropriately reconditioned or disposed. Empty containers should be taken for recycling, recovery, or disposal through suitably qualified or licensed contractor and in accordance with governmental regulations. DO NOT PRESSURISE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE

Product Name: KEROSENE

Revision Date: 30 Sep 2021

Page 11 of 13

SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

|                   |                              |
|-------------------|------------------------------|
| <b>SECTION 14</b> | <b>TRANSPORT INFORMATION</b> |
|-------------------|------------------------------|

**LAND (ADR/RID)**

**Proper Shipping Name:** Kerosine (petroleum)  
**Proper Shipping Name Suffix:** Special Provision 363  
**Hazard Class:** 3  
**Classification Code:** F1  
**UN Number:** 1223  
**Packing Group:** III  
**Label(s) / Mark(s):** 3, EHS  
**Hazard ID Number:** 30  
**Hazchem EAC:** 3Y

**SEA (IMDG)**

**Proper Shipping Name:** Kerosine (petroleum)  
**Hazard Class & Division:** 3  
**EMS Number:** F-E, S-E  
**UN Number:** 1223  
**Packing Group:** III  
**Marine Pollutant:** Yes  
**Label(s):** 3  
**Transport Document Name:** UN1223, KEROSENE, 3, PG III, (38°C c.c.), MARINE POLLUTANT

**AIR (IATA)**

**Proper Shipping Name:** Kerosine (petroleum)  
**Hazard Class & Division:** 3  
**UN Number:** 1223  
**Packing Group:** III  
**Label(s) / Mark(s):** 3  
**Transport Document Name:** UN1223, KEROSENE, 3, PG III

|                   |                               |
|-------------------|-------------------------------|
| <b>SECTION 15</b> | <b>REGULATORY INFORMATION</b> |
|-------------------|-------------------------------|

This material is considered hazardous according to the Classification of Chemicals based on Globally Harmonized System of Classification and Labelling of Chemicals (GHS).

**REGULATORY STATUS AND APPLICABLE LAWS AND REGULATIONS**

**Listed or exempt from listing/notification on the following chemical inventories :** AIIC, DSL, ENCS, IECSC, KECI, PICCS, TCSI, TSCA

|                   |                          |
|-------------------|--------------------------|
| <b>SECTION 16</b> | <b>OTHER INFORMATION</b> |
|-------------------|--------------------------|

N/D = Not determined, N/A = Not applicable

**KEY TO THE H-CODES CONTAINED IN SECTION 3 OF THIS DOCUMENT (for information only):**

H225: Highly flammable liquid and vapour; Flammable Liquid, Cat 2

H226: Flammable liquid and vapour; Flammable Liquid, Cat 3

Product Name: KEROSENE

Revision Date: 30 Sep 2021

Page 12 of 13

---

H302: Harmful if swallowed; Acute Tox Oral, Cat 4  
H304: May be fatal if swallowed and enters airways; Aspiration, Cat 1  
H315: Causes skin irritation; Skin Corr/Irritation, Cat 2  
H332: Harmful if inhaled; Acute Tox Inh, Cat 4  
H336: May cause drowsiness or dizziness; Target Organ Single, Narcotic  
H351: Suspected of causing cancer; GHS Carcinogenicity, Cat 2  
H373: May cause damage to organs through prolonged or repeated exposure; Target Organ, Repeated, Cat 2  
H400: Very toxic to aquatic life; Acute Env Tox, Cat 1  
H401: Toxic to aquatic life; Acute Env Tox, Cat 2  
H410: Very toxic to aquatic life with long lasting effects; Chronic Env Tox, Cat 1  
H411: Toxic to aquatic life with long lasting effects; Chronic Env Tox, Cat 2  
H412: Harmful to aquatic life with long lasting effects; Chronic Env Tox, Cat 3

**THIS SAFETY DATA SHEET CONTAINS THE FOLLOWING REVISIONS:**

CLP Classification information was added.  
Composition: Component Table information was modified.  
GHS Environmental Classification information was deleted.  
GHS Environmental Hazards information was added.  
GHS Environmental Hazards information was deleted.  
GHS Environmental Symbol information was deleted.  
GHS Health Classification information was deleted.  
GHS Health Hazards information was added.  
GHS Health Hazards information was deleted.  
GHS Health Symbol information was deleted.  
GHS Physical Hazards information was added.  
GHS Physical Hazards information was deleted.  
GHS Physical/Chemical Classification information was deleted.  
GHS Physical/Chemical Symbol information was deleted.  
GHS Precautionary Statements - Disposal information was added.  
GHS Precautionary Statements - Disposal information was deleted.  
GHS Precautionary Statements - Prevention information was added.  
GHS Precautionary Statements - Prevention information was deleted.  
GHS Precautionary Statements - Response information was added.  
GHS Precautionary Statements - Response information was deleted.  
GHS Precautionary Statements - Storage information was added.  
GHS Precautionary Statements - Storage information was deleted.  
GHS Signal Word information was added.  
GHS Signal Word information was deleted.  
GHS Symbol information was added.  
GHS Target Organ Phrase information was deleted.  
Hazard Identification: EU - Hazards Statement - GHS information was deleted.  
Section 02: GHS Contains for LABEL\_GHS codes information was modified.  
Section 08: Exposure Limits Table information was modified.  
Section 11 Substance Toxicology table information was modified.  
Section 14: Proper Shipping Name information was modified.  
Section 15: National Chemical Inventory Listing information was modified.  
Section 16: HCode Key information was modified.

---

The information and recommendations contained herein are, to the best of ExxonMobil's knowledge and belief, accurate and reliable as of the date issued. You can contact ExxonMobil to insure that this document is the most current

Product Name: KEROSENE

Revision Date: 30 Sep 2021

Page 13 of 13

---

available from ExxonMobil. The information and recommendations are offered for the user's consideration and examination. It is the user's responsibility to satisfy itself that the product is suitable for the intended use. If buyer repackages this product, it is the user's responsibility to insure proper health, safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, republication or retransmission of this document, in whole or in part, is not permitted. The term, "ExxonMobil" is used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliates in which they directly or indirectly hold any interest.

---

Internal Use Only

MHC: 1A, 0B, 0, 0, 4, 1

PPEC: C

DGN: 2028424XEG (1013454)

---