

SAFETY DATA SHEET

ExxonMobil

MOBIL HEAVY DUTY SCA PRECHARGED COOLANT/ANTIFREEZE

Section 1. Identification

Product name : MOBIL HEAVY DUTY SCA PRECHARGED COOLANT/ANTIFREEZE

Product description : Glycol

Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Antifreeze/coolant

Uses advised against : This product is not recommended for any industrial, professional or consumer use other than the identified uses above.

Supplier : EXXON MOBIL CORPORATION
22777 Springwoods Village Parkway
Spring, TX 77389 USA

24-Hour emergency telephone number : 1-800-424-9300 / +1 703-741-5970 / +1-703-527-3887 (CHEMTREC)

Product Technical Information : 800-662-4525

SDS Internet Address : www.sds.exxonmobil.com

Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : ACUTE TOXICITY (oral) - Category 4
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2

GHS label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : H302 - Harmful if swallowed.
H373 - May cause damage to organs through prolonged or repeated exposure. (kidneys)

Precautionary statements

P101 - If medical advice is needed, have product container or label at hand.
P102 - Keep out of reach of children.
P103 - Read label before use.

Prevention : P260 - Do not breathe vapor.
P264 - Wash thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.

Response : P301 + P330, P312 - IF SWALLOWED: Rinse mouth. Call a POISON CENTER or doctor if you feel unwell.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

Contains : ETHANE-1,2-DIOL

Hazards not otherwise classified : None known.

Note : This material should not be used for any other purpose than the intended use in Section 1 without expert advice. Health studies have shown that chemical exposure may cause potential human health risks which may vary from person to person.

Section 2. Hazards identification

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	% by weight	Identifiers
ETHANE-1,2-DIOL	≥90	CAS: 107-21-1
ethanol, 2,2-oxybis-	≤10	CAS: 111-46-6

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs. Get medical attention following exposure or if feeling unwell.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention following exposure or if feeling unwell. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury. Wash clothing before reuse. Clean shoes thoroughly before reuse. Continue to rinse for at least 10 minutes. Get medical attention following exposure or if feeling unwell.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : No known significant effects or critical hazards.
- Ingestion** : Harmful if swallowed.

Over-exposure signs/symptoms

- Eye contact** : No specific data.
- Inhalation** : No specific data.

Section 4. First aid measures

- Skin contact** : Local necrosis as evidenced by delayed onset of pain and tissue damage a few hours after injection.
- Ingestion** : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO₂, alcohol-resistant foam or water spray (fog).
- Unsuitable extinguishing media** : Do not use water jet.

- Specific hazards arising from the chemical** : In a fire or if heated, a pressure increase will occur and the container may burst.

- Hazardous combustion products** : Aldehydes, Incomplete combustion products, Oxides of carbon, Smoke, Fume

- Special protective actions for fire-fighters** : Use standard firefighting procedures and consider the hazards of other involved materials. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. Assure an extended cooling down period to prevent re-ignition. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply. No action shall be taken involving any personal risk or without suitable training.

- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

NOTIFICATION PROCEDURES

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations. US regulations require reporting releases of this material to the environment which exceed the applicable reportable quantity or oil spills which could reach any waterway including intermittent dry creeks. The National Response Center can be reached at (800)424-8802.

Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

<p>Small spill</p>	<p>: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.</p>
<p>Large spill</p>	<p>: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Material will sink. Remove material, as much as possible, using mechanical equipment. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.</p>

Section 7. Handling and storage

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Do not breathe vapor or mist. Do not ingest. Avoid contact with eyes, skin and clothing. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Static Accumulator	: This material is not a static accumulator.
Conditions for safe storage, including any incompatibilities	: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Occupational exposure limits

Ingredient name	Exposure limits
ETHANE-1,2-DIOL	<p>CAL OSHA PEL (United States, 5/2018) C: 100 mg/m³. Form: vapor. C: 40 ppm. Form: vapor.</p> <p>OSHA PEL 1989 (United States, 3/1989) CEIL: 50 ppm. CEIL: 125 mg/m³.</p> <p>ACGIH TLV (United States, 1/2024) STEL 15 minutes: 10 mg/m³. Form: Inhalable fraction. Aerosol only.. STEL 15 minutes: 50 ppm. Form: Vapor fraction. TWA 8 hours: 25 ppm. Form: Vapor fraction.</p>
ethanol, 2,2-oxybis-	<p>OARS WEEL (United States, 4/2022) TWA 8 hours: 10 mg/m³.</p>

Section 8. Exposure controls/personal protection

NOTE: Limits/standards shown for guidance only. Follow applicable regulations.

Appropriate engineering controls	: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
<u>Individual protection measures</u>	
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
<u>Skin protection</u>	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. < 1 hour (breakthrough time): Nitrile, minimum 0.38 mm thickness or comparable protective barrier material
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties and safety characteristics

Note: Physical and chemical properties are provided for safety, health and environmental considerations only and may not fully represent product specifications. Contact the Supplier for additional information.

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state	: Liquid.
Color	: Pink
Odor	: Characteristic
Odor threshold	: Not available.
pH	: 6
Melting point/freezing point	: -18°C (-0.4°F)

Section 9. Physical and chemical properties and safety characteristics

Boiling point or initial boiling point and boiling range	: 171 to 175°C (339.8 to 347°F)
Flash point	: Closed cup: 119°C (246.2°F) [Setaflash Closed Cup]
Evaporation rate	: Not available.
Flammability	: Ignitable
Lower and upper explosion limit/flammability limit	: Lower: 3.2% Upper: 15.3%
Vapor pressure	: <0.1 mm Hg [20 °C]
Relative vapor density	: 2.1 [Air = 1]
Relative density	: 1.115
Solubility in water	: Complete
Partition coefficient: n-octanol/water	: <2
Auto-ignition temperature	: >371.11°C (>700°F)
Decomposition temperature	: Not available.
Viscosity	: <15.6 cSt [40 °C]
Particle characteristics	
Median particle size	: Not applicable.

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: High energy sources of ignition. Excessive heat.
Incompatible materials	: strong acids, Strong oxidizers
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Test	Species	Result	Duration
MOBIL HEAVY DUTY SCA PRECHARGED COOLANT/ANTIFREEZE ethanol, 2,2-oxybis-	LDLo Oral	Human	1560 mg/kg	-
	LC50 Inhalation Dusts and mists	Rat	>4.6 mg/l	4 hours
	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LDLo Oral	Human	500 mg/kg	-

Conclusion/Summary

Inhalation	: Minimally Toxic. No end point data for material. Based on assessment of the components.
Dermal	: Minimally Toxic. No end point data for material. Based on assessment of the components.
Oral	: Moderately toxic Data available. Based on assessment of the components.

Section 11. Toxicological information

Irritation/Corrosion

Conclusion/Summary

- Skin** : Negligible irritation to skin at ambient temperatures. No end point data for material. Based on assessment of the components.
- Eyes** : May cause mild, short-lasting discomfort to eyes. No end point data for material. Based on assessment of the components.
- Respiratory** : Negligible hazard at ambient/normal handling temperatures. No end point data for material.

Respiratory or skin sensitization

Conclusion/Summary

- Skin** : Not expected to be a skin sensitizer. No end point data for material. Based on assessment of the components.
- Respiratory** : Not expected to be a respiratory sensitizer. No end point data for material.

Mutagenicity

Conclusion/Summary

- : Not expected to be a germ cell mutagen. No end point data for material. Based on assessment of the components.

Carcinogenicity

Conclusion/Summary

- : Not expected to cause cancer. No end point data for material. Based on assessment of the components.

Reproductive toxicity

Conclusion/Summary

- : Not expected to be a reproductive toxicant. No end point data for material. Based on assessment of the components.

Specific target organ toxicity (single exposure)

Conclusion/Summary

- : Not expected to cause organ damage from a single exposure. No end point data for material.

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Target organs
MOBIL HEAVY DUTY SCA PRECHARGED COOLANT/ANTIFREEZE	Category 2	kidneys

Conclusion/Summary

- : May cause damage to organs through prolonged or repeated exposure. No end point data for material. Based on assessment of the components.

Aspiration hazard

Conclusion/Summary

- : Not expected to be an aspiration hazard. Based on physico-chemical properties of the material. No end point data for material.

Other information

Contains

- : ETHYLENE GLYCOL (EG): Repeated high oral exposure has caused kidney damage, neurological effects, degeneration of the liver and changes in blood chemistry and circulating blood cells in laboratory animals. Repeated overexposure has the potential to cause similar toxic effects in humans. EG causes developmental and reproductive effects at high dose levels in laboratory animals. The relevance of these findings to humans is uncertain. DIETHYLENE GLYCOL (DEG): Orally, DEG is more toxic to humans than animal test data indicate. Probable lethal dose for an adult is about 50 ml (2 oz.), or 2 -3 swallows. Smaller amounts may cause kidney degeneration and failure. Benign urinary bladder tumors were observed in rats, no tumors were observed in mice.

Section 12. Ecological information

The information given is based on data for the material, components of the material, or for similar materials, through the application of bridging principals.

Toxicity

Conclusion/Summary

- Acute toxicity** : Not expected to be harmful to aquatic organisms.
- Chronic toxicity** : Not expected to demonstrate chronic toxicity to aquatic organisms.

Section 12. Ecological information

Persistence and degradability

Biodegradability : Material -- Expected to be readily biodegradable.

Atmospheric Oxidation : Material -- Expected to degrade rapidly in air

Bioaccumulative potential

Conclusion/Summary : Material -- Potential to bioaccumulate is low.

Mobility in soil

Mobility : Material -- Expected to remain in water or migrate through soil.

Other ecological information



Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty Container Warning (where applicable): Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Empty drums should be completely drained and safely stored until appropriately reconditioned or disposed. Empty containers should be taken for recycling, recovery, or disposal through suitably qualified or licensed contractor and in accordance with governmental regulations. **DO NOT PRESSURISE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.**

Section 14. Transport information

	DOT Classification	TDG Classification	IMDG	IATA
UN number	UN3082	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	Environmentally hazardous substance, liquid, n.o.s. (ETHANE-1,2-DIOL)	-	-	-
Transport hazard class(es)	9	-	-	-
Label(s) / Marks	 			
Packing group	III	-	-	-
Environmental hazards	Yes.	No.	No.	No.

Additional information

Section 14. Transport information

- DOT Classification** : Non-bulk packages of this product are not regulated as hazardous materials in package sizes less than the product reportable quantity, unless transported by inland waterway. The marine pollutant mark is not required when transported on inland waterways in sizes of ≤ 5 L or ≤ 5 kg.
Reportable quantity 5263.2 lbs / 2389.5 kg [566.13 gal / 2143 L]. Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements.
Limited quantity Yes.
Packaging instruction Exceptions: 155. Non-bulk: 203. Bulk: 241.
Special provisions 8, 146, 173, 335, 441, IB3, T4, TP1, TP29
- IATA** : The environmentally hazardous substance mark may appear if required by other transportation regulations.
- Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to IMO instruments : Not applicable.

Section 15. Regulatory information

U.S. Federal regulations : TSCA 8(a) CDR Exempt/Partial exemption: Not determined

TSCA 12(b) - Chemical export notification

Not applicable.

Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs) : Listed

Clean Air Act Section 602 Class I Substances : Not listed

Clean Air Act Section 602 Class II Substances : Not listed

DEA List I Chemicals (Precursor Chemicals) : Not listed

DEA List II Chemicals (Essential Chemicals) : Not listed

SARA 302/304

Composition/information on ingredients

No products were found.

SARA 304 RQ : Not applicable.

SARA 311/312

Classification : ACUTE TOXICITY (oral) - Category 4
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2

SARA 313

	Product name	CAS number	%
Form R - Reporting requirements	ETHANE-1,2-DIOL	107-21-1	≥ 90
Supplier notification	ETHANE-1,2-DIOL	107-21-1	≥ 90

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Section 15. Regulatory information

- Massachusetts** : The following components are listed: ETHYLENE GLYCOL
- New York** : The following components are listed: Ethylene glycol
- New Jersey** : The following components are listed: ETHYLENE GLYCOL
- Pennsylvania** : The following components are listed: 1,2-ETHANEDIOL; ETHANOL, 2,2'-OXYBIS-
- Illinois** : None of the components are listed.

California Prop. 65

 **WARNING:** Reproductive Harm - www.P65Warnings.ca.gov.

Inventory list

- Australia inventory (AIC)** : All components are listed or exempted.
- Canada inventory (DSL-NDSL)** : All components are listed or exempted.
- China inventory (IECSC)** : Not determined.
- Japan inventory (CSCL)** : All components are listed or exempted.
- Japan inventory (Industrial Safety and Health Act)** : Not determined.
- New Zealand Inventory of Chemicals (NZIoC)** : Not determined.
- Philippines inventory (PICCS)** : All components are listed or exempted.
- Korea inventory (KECI)** : All components are listed or exempted.
- Taiwan Chemical Substances Inventory (TCSI)** : Not determined.
- United States inventory (TSCA 8b)** : All components are active or exempted.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	*	2
Flammability		1
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.)



Procedure used to derive the classification

Classification	Justification
ACUTE TOXICITY (oral) - Category 4	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2	Calculation method

New Jersey Right to Know Disclosure

Section 16. Other information

Name	CAS #
ETHANE-1,2-DIOL ethanol, 2,2-oxybis-	107-21-1 111-46-6

History

Date of issue/Date of revision : 16 July 2024

Date of previous issue : 4 December 2023

Version : 0.02

Key to abbreviations :

- ATE = Acute Toxicity Estimate
- BCF = Bioconcentration Factor
- GHS = Globally Harmonized System of Classification and Labelling of Chemicals
- IATA = International Air Transport Association
- IBC = Intermediate Bulk Container
- IMDG = International Maritime Dangerous Goods
- LogPow = logarithm of the octanol/water partition coefficient
- MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
- N/A = Not available
- SGG = Segregation Group
- UN = United Nations

References : Not available.

Indicates information that has changed from previously issued version.

Product code : 351010101594_13488811

Notice to reader

The information and recommendations contained herein are, to the best of ExxonMobil's knowledge and belief, accurate and reliable as of the date issued. You can contact ExxonMobil to insure that this document is the most current available from ExxonMobil. The information and recommendations are offered for the user's consideration and examination. It is the user's responsibility to satisfy itself that the product is suitable for the intended use. If buyer repackages this product, it is the user's responsibility to insure proper health, safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, re-publication or retransmission of this document, in whole or in part, is not permitted. The term, "ExxonMobil" is used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliates in which they directly or indirectly hold any interest.