



Dow Corning® MB 25-502 Masterbatch

Dow Corning Corporation - Slip Agent / Lubricant / Mold Release / Processing Aid Masterbatch

Sunday, November 3, 2019

General Information

Product Description

Dow Corning® MB25-502 Masterbatch is a pelletized formulation containing 25% of a high molecular weight (HMW) siloxane polymer dispersed in low density polyethylene (LDPE). It is designed to be used as an additive in polyethylene compatible systems to provide benefits such as processing improvements.

Liquid siloxane plastic additives have been used for several years to improve the lubricity and flow of thermoplastics. They are effective in this role although some difficulties have been experienced in the incorporation of liquids into thermoplastic melts without the use of specialized equipment. It has also been difficult to produce masterbatches with greater than 20% liquid siloxane because of processing difficulty and bleed problems.

The Dow Corning® brand MB Series Masterbatches address these problems by supplying a high concentration of a high molecular weight (HMW) siloxane as a dispersion in a dry pellet form in a variety of thermoplastics.

APPLICATIONS

- Additive in polyethylene compatible systems, high mineral filled polyethylene formulation (like HFFR-PE compounds), and extrusion process.

General

Material Status	• Commercial: Active		
Availability	• Africa & Middle East • Asia Pacific	• Europe • Latin America	• North America

ASTM & ISO Properties ¹

Additives General	Nominal Value	Unit
Additives Category	Masterbatch -- Slip Agent / Lubricant / Mold Release / Processing Aid -- Silicone-based	
Carrier Resin	Polyethylene or ethylene-olefin copolymer (PE)	
Recommended for Use In	Polyethylene or ethylene-olefin copolymer (PE)	
Forms	Pellets / Granules	
Additives Physical	Nominal Value	Unit
Density	0.928	g/cm ³
Additive Concentration	25	%
State at Room Temperature	Solid	
Chemical Description	Siloxane	

Notes

¹ Typical properties: these are not to be construed as specifications.