



Ultradur® B 4560 BK10089

BASF Corporation - Polybutylene Terephthalate

Monday, November 4, 2019

General Information

Product Description

Ultradur B 4560 BK10089 is an injection molding, pigmented black, PBT grade.

Applications

Typical applications include industrial parts in the automotive field, such as head lamp bezels

General

Material Status	• Commercial: Active
Availability	• North America
Uses	• Automotive Applications • Industrial Parts
Agency Ratings	• EC 1907/2006 (REACH)
RoHS Compliance	• RoHS Compliant
Automotive Specifications	• GM GMP.PBT.037 • GM GMP.PBT.037 Color: 10089 • GM QK 006511 Color: 10089 Black
Appearance	• Black
Forms	• Pellets
Processing Method	• Injection Molding

ASTM & ISO Properties ¹

Physical	Nominal Value	Unit	Test Method
Density	1.30	g/cm ³	ISO 1183
Melt Volume-Flow Rate (MVR) (250°C/2.16 kg)	33	cm ³ /10min	ISO 1133
Molding Shrinkage			ISO 294-4
Across Flow	2.0	%	
Flow	1.5	%	
Viscosity Number (Reduced Viscosity)	112.0	ml/g	ISO 1628
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus (73°F)	377000	psi	ISO 527-2
Tensile Stress (Yield, 73°F)	8700	psi	ISO 527-2
Tensile Strain (Yield, 73°F)	4.0	%	ISO 527-2
Nominal Tensile Strain at Break (73°F)	35	%	ISO 527-2
Impact	Nominal Value	Unit	Test Method
Charpy Notched Impact Strength (73°F)	1.7	ft-lb/in ²	ISO 179
Charpy Unnotched Impact Strength			ISO 179
-22°F	40	ft-lb/in ²	
73°F	67	ft-lb/in ²	
Thermal	Nominal Value	Unit	Test Method
Heat Deflection Temperature (66 psi, Unannealed)	275	°F	ISO 75-2/B
Heat Deflection Temperature (264 psi, Unannealed)	140	°F	ISO 75-2/A
Melting Temperature (DSC)	433	°F	ISO 3146

Ultradur® B 4560 BK10089

BASF Corporation - Polybutylene Terephthalate

Processing Information

Injection	Nominal Value	Unit
Drying Temperature	212 to 248	°F
Drying Time	4.0	hr
Suggested Max Moisture	0.040	%
Processing (Melt) Temp	482 to 518	°F
Mold Temperature	104 to 176	°F
Injection Pressure	508 to 1810	psi
Injection Rate	Fast	
Back Pressure	< 145	psi

Notes

¹ Typical properties: these are not to be construed as specifications.